

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELIII HEADQUARTERS: DELIII FIRE SERVICE: NEW DELIII- 1100010



No. F6/DFS/MS/GH/SZ/2025/ 284

Dated: 29/04/2025

FIRE SAFETY CERTIFICATE

Certified that the Amby Inn Guest House located at M-13, Lajpat Nagar-II, New Delhi - 110024, building comprised of Basement, Ground plus three upper floors, Basement (Storage), Ground floor (Reception + 05 guest rooms), 1st floor to 3rd floor (06 guest rooms at each floor), total 23 guest rooms only, owned / occupied by Amby Inn Guest House was granted FSC by this department vide letter No. F6/DFS/MS/GH/SZ/2022/385 dated 17/08/2022. The premise was re-inspected by the officer concerned of this department on 21/04/2025 in the presence of Mr. Rajesh Anand (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Group - A "Residential Building" Sub Division-A-1, Basement (Storage), Ground floor (Reception + 05 guest rooms), 1st floor to 3rd floor (06 guest rooms at each floor), total 23 guest rooms only with effect from 3rd floor (06 guest rooms at each floor), total 23 guest rooms only with effect from 40 guest rooms at each floor), total 23 guest rooms only with effect from 6 guest rooms at each floor), total 23 guest rooms only with effect from 6 guest rooms only rooms only with effect from 6 guest rooms only rooms on

Issued 29 04 2025 at New Delhi by.

DIRECTOR
OCDELHI FIRE SERVICE

Copy to: -

1. The Commissioner, MCD, Civic Center, J.L.N. Marg New Delhi - 110002: with a request to ensure the occupancy as detailed above and deviation if any.

2. The Joint Commissioner of Police (Lic.), Ist Floor, P.S Defence Colony, New Delhi-24 w.r.t.- MCD portal ID - 2025032904896 dated 07/04/2025.

3. The Manager, Amby Inn Guest House located at M-13, Lajpat Nagar-II, New Delhi – 110024

Conditions for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

 5. This fire safety certificate may not be a second building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J'[sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

			<u>INSPE</u>	CTION REPOR	RT			
1	Name & address of the building Building is comprised of				Amby Inn Guest House located at M-13, Lajpat			
				Nagar-II, New Delhi - 110024.				
2				Basement + Ground + 03 upper floors,				
				Name of the Control o	Basement – Storage, Ground floor (Reception + 05			
				guest rooms),	-		-	
						*	-	
				at each floor), (Total 23 guest rooms only). Terrace floor – temporary construction pota cabin				
				(closed).	- tempe	nary constructi	on pota caon	
3	Type of occupancy			Residential Building 'Group – A'(Guest House)				
4	Type of occupancy Type of case			Renewal				
5								
6	Details of previous FSC			N/A	F6/DFS/MS/GH/SZ/2022/385 dated 17/08/2022			
7	Fire safety directives letter no.							
	Date of inspection			21.04.2025	1.)(4 D O / I av	i Nagar	
8	-		of the inspecting officers	Yashwant Sing			mi Nagar	
9			of the designation of	Mr. Rajesh An	and (O	wner)		
			r from the building side					
10	Yea	ar c	of construction	2009			201021	
11	Applicant's letter no. MCD Application I.D No. 2025032904890 07/04/2025			904896 dated				
]	Mi	nimum standard of fire	Old NOC	P	Provided at	Remarks	
S.N	pr	ev	ention and fire safety U/R	Requirement	t	site	MR/NMR	
0	_		33					
	Acc	ces	s to Building:			•		
	A		oad width	6.0 meters	7.0) meters	MR	
	В	G	ate width	N/A		N/A	N/A	
	C	V	Vidth of internal road	N/A		N/A	N/A	
?	Number, Width, Type and Arran		oer, Width, Type and Arran	gement of Exits:				
	A	N	lumber of staircases					
		a	Upper floor	01 no.		01 no.	MR	
		С	Basement	02 no.		02 no.	MR	
	В	V	Vidth of staircases					
			Y I G				1	
		a	Upper floor	1.2 meter	1.	25 meters	MR (Old	
		a	Upper floor	1.2 meter	1.	25 meters	MR (Old case)	
		a b	Basement	1.2 meter		neters & 1.17	MR (Old case)	
	C	b	• •				case)	
	С	b	Basement			neters & 1.17	case) MR	
	C	b Pr a b	Basement rotection of exits Fire check door Pressurization	1.2 meter		meters & 1.17 meters	case)	
	C	b Pra b No	Basement rotection of exits Fire check door Pressurization o. of continuous staircases	1.2 meter N/A		meters & 1.17 meters N/A	case) MR	
	C D	b Pra b Note to	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace	1.2 meter N/A N/A 01 no.		meters & 1.17 meters N/A N/A	case) MR N/A N/A	
	C D E	Pra b Note to W	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor	N/A N/A 01 no. Old case	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters	N/A N/A	
	C D	Pra b Note to W	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace	1.2 meter N/A N/A 01 no.	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final	N/A N/A MR	
	C D E F	Pra b No to W Do	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor oor size	N/A N/A 01 no. Old case	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters	N/A N/A MR MR	
	C D E F	Pra b No to W Do	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor oor size artmentation:	N/A N/A 01 no. Old case 1.0 meter	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final exits)	N/A N/A N/A MR MR MR	
	C D E F Com	Pra b No to W Do	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor oor size artmentation: re check door	N/A N/A 01 no. Old case 1.0 meter	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final exits) N/A	N/A N/A MR MR N/A N/A	
	C D E F Con A B	Pra b No to W Do	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor oor size artmentation: re check door ealing of electrical shafts	N/A N/A 01 no. Old case 1.0 meter	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final exits)	N/A N/A N/A MR MR MR	
	C D E F Con A B C	Pra b No to W Do Fi See Fi	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor oor size artmentation: re check door caling of electrical shafts re rating of shaft door	N/A N/A 01 no. Old case 1.0 meter N/A N/A N/A N/A	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final exits) N/A	N/A N/A MR MR N/A N/A	
	C D E F Con A B C D	Pra b No to W Do Fi See Fi W	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace rotection of exits recall for corridor roor size artmentation: re check door realing of electrical shafts re rating of shaft door rater curtain	N/A N/A 01 no. Old case 1.0 meter N/A N/A N/A N/A N/A	1.20 r	N/A N/A 01 no. 1.20 meters meter (final exits) N/A N/A N/A N/A N/A N/A	N/A N/A MR MR N/A N/A N/A N/A N/A	
-	C D E F Con A B C D E	Pra a b No to W Do Fi Se Fi W Fi	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace rotection of corridor oor size artmentation: re check door caling of electrical shafts re rating of shaft door rater curtain re dampers	N/A N/A 01 no. Old case 1.0 meter N/A N/A N/A N/A	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final exits) N/A N/A N/A N/A	N/A N/A MR N/A MR N/A N/A N/A N/A N/A	
-	C D E F Com A B C D E Smc	Pra b No to W Do Fi See Fi W Fi oke	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor oor size artmentation: re check door realing of electrical shafts re rating of shaft door rater curtain re dampers Management System:	N/A N/A 01 no. Old case 1.0 meter N/A N/A N/A N/A N/A N/A N/A	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final exits) N/A N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A N/A N/A	
-	C D E F Con A B C D E	Pra b No to W Do Fi See Fi W Fi oke	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace rotection of corridor oor size artmentation: re check door caling of electrical shafts re rating of shaft door rater curtain re dampers	N/A N/A 01 no. Old case 1.0 meter N/A N/A N/A N/A N/A N/A N/A N/A N/A	1.20 r	N/A N/A 01 no. 1.20 meters meter (final exits) N/A N/A N/A N/A N/A N/A	N/A	
3	C D E F Com A B C D E Smc	b Pra a b No to W Do Fi See Fi W Fi Doke Ba	Basement rotection of exits Fire check door Pressurization o. of continuous staircases terrace ridth of corridor oor size artmentation: re check door realing of electrical shafts re rating of shaft door rater curtain re dampers Management System:	N/A N/A 01 no. Old case 1.0 meter N/A N/A N/A N/A N/A N/A N/A	1.20 r	neters & 1.17 meters N/A N/A 01 no. 1.20 meters meter (final exits) N/A N/A N/A N/A N/A N/A N/A N/A	N/A N/A N/A MR N/A N/A N/A N/A N/A N/A N/A N/A N/A N/	

Amb	N(2) $+$ by Inn Guest House located at M-13, Lajpat Nagar-II, New Delhi - 110024
	Fire Extinguisher:

5.	F	ire Extinguisher:			MR			
	A		06 nos.	06 nos.	MR			
	В	Types	CO ₂ & ABC	CO ₂ & ABC				
	C	ISI marking	ISI Marked	ISI Marked	MR			
6	F	irst-Aid-Hose Reel:						
	A	Total numbers of each floors	01 no.	01 no.	MR			
	В		30 mtrs	30 mtrs	MR			
	C		05 mm	05 mm	MR			
7	A	utomatic Fire Detection and	: (required as per c	lause				
	Automatic Fire Detection and Alarming System: (required as per clause 7.31.viii, UBBL 2016)							
	A		Required	Provided	MR			
	В	Location of main panel	At ground floor	Provided	MR			
			reception					
	C	Location of repeater panel	N/A	N/A	N/A			
	D	Alternate source of power	N/A	N/A	N/A			
	E	Hooters	Audible in entire building	Provided	MR			
8	_	OEFA:	Required	Provided	MR			
9	Pu	ıblic Address System:	Required	Provided	MR			
10	Aı	utomatic Sprinkler System:						
	A	Basement	Required	Provided	MR			
	В	Upper floor	N/A	N/A	N/A			
	C	Sprinkler above false	N/A	N/A	N/A			
		ceiling	1 1/12	IV/A	1 N /A			
1	In	ternal Hydrants:						
	A	Size of riser/down-	N/A	N/A	N/A			
		comer		1,771	11/11			
	В	Number of hydrants per Branch	N/A	N/A	N/A			
	C	Hose box	N/A	N/A	NI/A			
2	11/11							
	A	Total number of	N/A	N/A	271.			
		hydrants	11/21	IN/A	N/A			
	B	Hose box	N/A	N/A	N/A			
3	Pu	mping Arrangements:		10/11	N/A			
	Ground level							
	A	Discharge of main pump	N/A	NI/A				
ı	В	Head of main pump	N/A	N/A	N/A			
	C	Number of main pumps	N/A	N/A	N/A			
	D	Jockey pump out put	N/A	N/A	N/A			
	E	Jockey pump head	N/A	N/A	N/A			
	F	Standby pump out put	N/A	N/A	N/A			
-	G	Standby pump head		N/A	N/A			
-	H	Auto starting /manual	N/A N/A	N/A	N/A			
		stopping	IN/A	N/A	N/A			
	Terrace Level							
+	A	Discharge of pump	450+180 LPM	450				
-	B	Head of the pump	35 mtrs	450+180 LPM	MR			
_	$\frac{\mathbf{D}}{\mathbf{C}}$	Power supply	Required	35 mtrs	MR			
-	D	Auto starting of pump		Provided	MR			
	ע	Auto starting of pump	Required	Provided	MR			

Ca	ptive Water Storage for Fire I	Fighting:		
A	Underground tank capacity		N/A	NI/A
-	Draw-off connection			N/A
C	Fire service inlet			N/A
D	Access to tank			N/A N/A
E	Overhead tank capacity			MR
Exi	it Signage:			MR
Pro	ovision of Lifts:		Tiovided	IVIK
A	Pressurization of lift shaft	N/A	N/A	N/A
B	Pressurization of lift lobby	N/A		N/A
C	Communication in lift car	N/A		N/A
D	Firemen's grounding switch	N/A		N/A
E	Lift signage	N/A		N/A
Sta	andby Power Supply:		Provided(DG)	MR
		•		
A	Total area	N/A	N/A	N/A
B	Location	N/A	N/A	N/A
Fir	re Control Room:			
A	Detector system panel	N/A	N/A	N/A
В	Flow switch panel	N/A	N/A	N/A
C	PA system panel	N/A	N/A	N/A
D	Battery backup	N/A	N/A	N/A
E	Building floor plans	N/A	N/A	N/A
Special Fire Protection systems		N/A	N/A	N/A
for protection of special Risks,				
if a	fire protection system was			
	A B C D E Ext Pro A B C D E Sta Re A B Fin A B C D E Sp for	A Underground tank capacity B Draw-off connection C Fire service inlet D Access to tank E Overhead tank capacity Exit Signage: Provision of Lifts: A Pressurization of lift shaft B Pressurization of lift lobby C Communication in lift car D Firemen's grounding switch E Lift signage Standby Power Supply: Refuge Area: A Total area B Location Fire Control Room: A Detector system panel B Flow switch panel C PA system panel D Battery backup E Building floor plans Special Fire Protection systems	B Draw-off connection N/A C Fire service inlet N/A D Access to tank N/A E Overhead tank capacity 5,000 liters Exit Signage: Required Provision of Lifts: A Pressurization of lift shaft N/A B Pressurization of lift lobby N/A C Communication in lift car N/A D Firemen's grounding switch N/A E Lift signage N/A Standby Power Supply: Required Refuge Area: A Total area N/A B Location N/A Fire Control Room: A Detector system panel N/A B Flow switch panel N/A C PA system panel N/A D Battery backup N/A E Building floor plans N/A Special Fire Protection systems for protection of special Risks,	A Underground tank capacity N/A N/A B Draw-off connection N/A N/A C Fire service inlet N/A N/A D Access to tank N/A N/A E Overhead tank capacity 5,000 liters Provided Provided Provision of Lifts: A Pressurization of lift shaft N/A N/A B Pressurization of lift lobby N/A N/A C Communication in lift car N/A N/A D Firemen's grounding switch N/A N/A E Lift signage N/A N/A Standby Power Supply: Required Provided(DG) Refuge Area: A Total area N/A N/A B Location N/A N/A Fire Control Room: A Detector system panel N/A N/A B Flow switch panel N/A N/A C PA system panel N/A N/A D Battery backup N/A N/A Special Fire Protection systems for protection of special Risks,

The fire protection system was randomly checked and tested and was found functional at the time of inspection and terrace floor temporary construction pota cabin closed.

Keeping in view the compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. The FSC issued vide letter no. F6/DFS/MS/GH/SZ/2022/385 dated 17/08/2022 renewal under rule 35 (6) of the Delhi Fire Service rules 2010 is recommended for approval up to third floor.

Signature of the Inspecting Officer
Name: Yaswant Singh Meena

Designation: ADO /Laxmi Nagar

D.O/SD MWW n/L

24 41 2005

BOYEN

Six,

F.T/Letter is Putup for Sign. Alea

g stylen