

#### GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/EH/2025/SZ/ 108

Dated: 25/03/2025

#### FIRE SAFETY CERTIFICATE

Certified that the M/s Amritsar Haveli (a unit of Radha Enterprises), running at ground and first only in a building comprised of basement (Closed), ground plus three upper floors (2<sup>nd</sup> & 3<sup>rd</sup> floor are vacant) located at J-2/3, GF & FF, Rajouri Garden, New Delhi-110027, was issued Fire Safety Certificate vide Letter No. F.6/DFS/MS/EH/2018/SZ/939 dated 07.05.2018 (for GF, FF & SF). The Restaurant building was re-inspected by the officer concerned of this department on 19.03.2025 in the presence of Sh. Vinod (Manager) and found that the restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the restaurant building/premises (Ground & First Floor only) is fit for occupancy class Group "D" Assembly Building" w.e.f. 25 03 2025 for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 25/03/2025 at New Delhi.

Delhi Fire Service

## Online application Id 2025022502426 dated 26.02.2025

Copy to: - The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delm.
: -for information regarding use of basement.

## Conditions for validity of Fire Safety Certificate: -

1. This FSC is valid only for ground and first floor.

2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

3. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.

4. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

5. The trained staff should be available round the clock.

6. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

7. Basement strictly shall be kept vacant as seen during inspection/used as per BBL.

8. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

9. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

10. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

# INSPECTION REPORT

M/s Amritsar Haveli a unit of Radha Enterprises, J-2/3, GF, FF, 1. Name & address of the building :

Rajouri Garden, New Delhi-110027.

Group D (Assembly Building) Type of Occupancy 2.

Basement (Closed), Ground plus three upper floors but restaurant running at ground & first floor only (2<sup>nd</sup> & 3<sup>rd</sup> floor are vacant) Building Comprised of

Type of Case

F.6/DFS/MS/EH/2018/SZ/939 dated 07.05.2018 (for GF, FF & SF) Details of Previous NOC

N/A Fire Safety directives letter No 19.03.2025 Date of inspection

A.D.O. R.K. Yadav (JKP) Name of Inspecting Officers

Name and designation of officers

Sh. Vinod (Restaurant Manager) From the building side

Before 2009

	11. Applicant's letter No.		025022502426 dated 26.02.2  Provided at site	Remarks		
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Requirements as per FSC dt. 07.05.2018		MR/NMR		
1.	Access to building					
	Road width     Gate width	Accessible (09 mtrs) 4.5 mtrs N/A	12 mtrs Directly accessible from road N/A	MR MR N/A		
	Width of internal road			******		
2.	Number, Width, Type & Arrangement of Exits					
	a. Number of staircases	02 No.'s	02 No.'s	MR		
	Upper Floors	02 No.'s	02 No.'s	MR		
	Basements	02 No. S	021.0.0	-		
	b. Width of staircases	Trans Proite	1.25 & 1.02 m	MR, old case		
	Upper Floor     Basements	Two Exits Two Exits	1.25 & 1.02 m	MR, old case		
	c. Protection of exits	1 WO EXILS				
	Fire check door	Required	Provided	MR		
	Pressurization	N/A	N/A	N/A		
	d. No. of continuous staircases to	01 nos.	01 nos.	MR		
	terrace	1.5 m	Opening in hall	MR		
	e. Wighth of Corridor f. Door Size	02 Exits	Provided	MR		
	Compartmentation					
	Compartmentation					
	Fire check door	N/A	N/A	N/A		
	<ul> <li>Sealing of electrical shafts</li> </ul>	N/A	N/A	N/A		
	<ul> <li>Fire Rating of shaft door</li> </ul>	N/A	N/A	N/A		
	Water Curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
	Smoke Management System		V.			
	Basements	Required	Provided	MR		
T.	Upper floors	Required	Provided	MR		
	Fire Extinguishers					
	Total numbers	02 No.'s/floor	Provided	MR		
	• Types	ABC/CO <sub>2</sub>	Provided	MR		
	IS marking	ISI marked	ISI marked	MR		
	First-Aid Hose Reels					
	Total numbers on ground floor		Provided	MR		
	<ul> <li>Length of hose reel hose</li> </ul>	30 mtrs	Provided	MR		
	<ul> <li>Nozzle diameter</li> </ul>	5 mm	Provided	MR		

N	23

7.	Automatic fire detection and alarming	ayatem	Provided	MR
	Type of detectors	Smoke & Heat	Ground floor	MR
	Location of Main Panel	Required	N/A	N/A
	Location of Repeater Panel	N/A	Provided	MR
	Alternate source of power	Required	Near exit	MR
	ve ve veten	Required		MR
	2 3 W SNS	Required	Provided	
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System			
10.	Automatic Sprinkler System	Required	Provided	MR
	Basement	Required	Provided	MR
	<ul> <li>Ground Floor &amp; Upper floor</li> </ul>	N/A	N/A	N/A
	<ul> <li>Sprinkler above false ceiling</li> </ul>	N/A		
11.	Internal Hydrants			) (D
•••		100 mm	Provided	MR MR
	Size of riser/down-comer     Number of hydrants	One	Provided	MR
	Number of nyurants     Hose Box	One	Provided	IVIIX
12	Yard Hydrants		1	
12.		N/A	N/A	N/A
	Total number of hydrants	N/A	N/A	N/A
	Hose Box			
13.	Pumping Arrangements	-11   3-1-30-0-1		
	Ground Level	S*/A	N/A	N/A
	Discharge of main Pump	N/A N/A	N/A	N/A
	> Head of Main pump	N/A N/A	N/A	N/A
	Number of main pumps	N/A N/A	N/A	N/A
	> Jockey Pump out put	N/A	N/A	N/A
	> Jockey pump head	N/A	N/A	N/A
	> Standby Pump out put	N/A	N/A	N/A
	<ul> <li>Standby Pump Head</li> <li>Auto Starting/Manual Stopping</li> </ul>	N/A	N/A	N/A
	M STATE OF THE PARTY OF THE PAR	N/A	N/A	N/A
0	> Pump House Access	1474		
	<ul> <li>Terrace level</li> <li>Discharge of pump</li> </ul>	450 LPM & 180 LPM	450 LPM & 180 LPM	MR
	> Discharge of pump	40 m	40 m	MR
	> Power Supply	Required	Provided	MR
	> Auto Starting of pump	Required	Provided	MR
274	Captive Water Storage for fire fighting		C M - CM	
14.		N/A	N/A	N/A
	Underground tank capacity	N/A	N/A	N/A
	> Draw-off connection	N-1000-10	N/A	N/A
	> Fire service inlet	N/A	N/A	N/A
	Access to tank	N/A	Provided	MR, old case
	Overhead Tank capacity	5000 ltrs	46 - 20 - 20 - 20 - 10 - 10 - 10 - 10 - 10	MR
	- L. O.	Required	Provided	MIK
15.	Exit Signage.			MIC .
	Provision of Lifts.	2		
	Provision of Lifts.	N/A	N/A	N/A
	Provision of Lifts.  • Pressurization of Lift Shaft		50.000.00	N/A N/A
	Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby	N/A	N/A N/A Provided	
	Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car	N/A Required	N/A Provided	N/A MR
15. 16.	Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	N/A Required Required	N/A Provided Provided	N/A MR MR
	Provision of Lifts.  Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car	N/A Required	N/A Provided	N/A MR

63.

+	> Total Area	N/A		
	> Location	N/A	NA	
		N/A	N/A	N/A
Fi	e Control Room		1.00	N/A
-	Detector System Danel	NVA		
	Detector System Panel	N/A	N/A	
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A		N/A
	Battery backup		N/A	N/A
		N/A	N/A	
	Building Floor Plans	N/A	N/A	N/A
_		597.	2.55.	N/A
Sp	ecial Fire Protection System for otection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were test/checked at random and found functional at the time of inspection. The shortcomings issued by this department vide latter No. F.6/DFS/MS/EH/2020/SZ/285 dated 12.03.2020 have been rectified.

Note: - As per undertaking submitted by building management (placed at C-70) that the restaurant running at ground & first floor only in a building comprised of basement, ground plus three upper floors. Basement have closed with Gypsum board which fire proof and lift will not operate in the basement. 2<sup>nd</sup> & 3<sup>rd</sup> floor of the building is vacant at this time.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F.6/DFS/MS/EH/2018/SZ/939 dated 07.05.2018 (for GF, FF & SF), renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up for approval & signature please.

Signature of the Inspecting Officer Name- R.K. Yadav

Designation- ADO (JKP)

DO (SD)

2/14/5

21 mg 2025

Directo

ADKM