

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, NEW DELHI - 110001

No: F6/DFS/MS/Hospital/WZ/2025/ 378

Dated: 09/07/2025

FIRE SAFETY CERTIFICATE

Certified that the M/s. Apollo Cradle (A unit of Apollo Specialty Hospitals PVT. Ltd. Located at 15A, Shivaj Marg, Najafgarh Road, New Delhi-110015, comprised of 02 Basement + Ground + 03 Upper Floors. The premises was inspected by the officers concerned of this department on 01/07/2025, in the presence of Sh. Kamal Rathee and found that the premises have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class Group C (Institutional) with effect from 69.07. 2025.... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 9 07 2015. at New Delhi.

(Atul Garg) Director

Copy to:-

- 1. The Directorate General Health Service (DGEHS), Govt. of NCT of Delhi, F-17, Karkardooma, New Delhi- 110032.
- 2. The Medical Superintendent, Apollo Cradle (A unit of Apollo Specialty Hospitals PVT. Ltd. Located at 15A, Shivaj Marg, Najafgarh Road, New Delhi-110015.
- 3. The Executive Engineer (Building.) Municipal Corporation of Delhi, Office, Karol Bagh, Anand Parbat New Delhi.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The basement & upper floor shall be used as per building bye laws & sanctioned plan. If it used other than sanctioned plan, FSC will be automatically null & void strictly.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

4112 INSPECTION REPORT Name & address of the building Apollo Cradle (A unit of Apollo Speciality Hospitals PVT. Ltd. Located at 15A, Shivaj Marg, Najafgarh Road, New Delhi-110015. Type of Occupancy Institutional (Hospital) Type of Case New 3. Details of previous NOC Nil 4. Fire Safety directives letter No F.6/DFS/MA/BP/2022/02 dated 04.01.2023 5. Date of inspection 01/07/2025 6. Name of the Inspecting Officers M.K.Chattopadhyay Dy.CFO(WZ) & Sarabjeet Singh ADO (MN) 7. designation Sh. Kamal Rathee, Fire Officer Name and 8. officers from the building side Year of Construction 2023 9. Outdoor dairy No.2964 dated: 23/06/2025 Applicant's letter No. 10 The said hospital is comprised of 02 basement + ground + 03 upper floors. Minimum Standards on fire BBL /NBC Provided at site Remarks S. prevention and fire safety U/R 33 MR/NMR Requirement No Access to building MR Provided Road width 9 mts Provided MR 6 mts Gate width NA NA NA Width of internal road Number, Width, Type & Arrangement of Exits a. Number of staircases Provided Upper Floors 03 MR Provided **Basements** 02 MR b. Width of staircases 2X2m, 1X1.5m Upper Floors Provided MR 02 X 1.5m Provided **Basements** MR c. Protection of exits Fire check door Required Provided MR NA Provided in 01 staircase Pressurization NA d. No. of continuous staircases to terrace 02 Provided MR e. Width of Corridor 2.4 mts Provided MR f. Door Size 2 x 2 mts, 1 x 1.5 mts Provided MR Compartmentation. Fire check door Required Provided MR Sealing of electrical shafts Required Provided MR Fire Rating of shaft door Required Provided MR Water Curtain NA NA NA Fire Dampers Required Provided MR 4 Smoke Management System. Basements Required Provided MR Upper floors Required Provided MR Fire Extinguishers Total numbers 35 nos. Provided MR Types CO2, DCP, ABC type MR Provided IS marking ISI marked Provided MR First-Aid Hose Reels. 6 Total numbers on each floor MR 02 Provided Length of hose reel hose MR 30 m required Provided MR Nozzle diameter Provided

5 mm required

		8114		- b7	
	Automatic fire detection and alarming system				
	Type of detectors	Smoke	Provided	MR MR	
	Location of Main Panel	Ground floor	Provided	MR	
	1967	Required	Provided	MR	
	Location of Repeater Panel	Required	Provided	MR	
	Alternate source of power	Required	Provided	MR	
	Hooters' Location		Provided		
	MOEFA	Required	Provided	MR	
	Public Address System.	Required	Provided		
10	Automatic Sprinkler System.				
	Basement	Required	Provided	MR	
	Upper Floor	Required	Provided	NA	
	Sprinkler above false ceiling	NA	NA	A 10.5	
1	Internal Hydrants		Provided	MR	
	Size of riser/down-comer	150mm	Provided	MR	
	 Number of hydrants per floor 	02	Provided	MR	
	Hose Box	02	· A A A A A A A A A A A A A A A A A A A		
12	Vord Hydrants				
	Total number of hydrants	04	Provided	MR MR	
	Hose Box	04	Provided	MIK	
13	Pumping Arrangements.			T MD	
	Ground Level Ground Level Ground Level Ground Level	2 x 2280 LPM	Provided -	MR	
	Discharge of main Pump	40 m	Provided	MR MR	
	Head of Main pump	01	Provided	MR	
	Number of main pumps	180 LPM	Provided	MR	
	> Jockey Pump out put	40 m	Provided	MR	
	Jockey pump headStandby Pump out put	2280 LPM	Provided	MR	
	TI-od	40 m	Provided	MR	
	a : /Meanal ctonning	Required	Provided	MR	
	> Auto Starting/ Manual stopping > Pump House Access	Required	Provided	IVIK	
	/2			NIA	
	Terrace level Discharge of pump	NA	NA	NA NA	
	The AV Works Consumer	. NA	NA	NA NA	
	> Head of the pump > Power Supply	NA	NA		
	Auto Starting of pump	NA	NA	NA	
14	or or fire fightin	g.			
14	Underground tank capacity	1,50,000 ltrs	Provided	MR	
	> Draw-off connection	Required	Provided	MR	
	> Fire service inlet	Required	Provided	MR	
	> Access to tank	Required	Provided	MR	
	Overhead Tank capacity	10,000 ltrs	Provided	MR	
5	Exit Signage.	Required	Provided	MR	
6			NA	NA	
	Pressurization of Lift Shaft	NA	NA NA	NA NA	
	Pressurization of Lift lobby	NA D i.e.d	Provided	MR	
	Communication In lift Car	Required	Provided	MR	
	Fireman's Grounding Switch	Required Required	Provided	MR	
	Lift Signage		Provided	MR	
17	Standby power supply	Required	110 1100	17110	

_	Refuge Area. Total Area	NA	NA	NA
e.	Location	NA	NA	NA
19	Fire Control Room	NOT REQUIRED		
_	Detector System Panel	NA	Provided	NA
3	Flow Switch Panel	NA	NA	NA
	PA System Panel	NA	Provided	NA
	Batter backup	NA	Provided	NA
	Building Floor Plans	NA	Provided	NA
20	Special Fire Protection Systems for	Required LT & HT	Flooding system	MR
20	Protection of special Risks, if any:	Panel	Provided	

The Fire Protection system provided in the building found in good working condition at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

07/07/2025 Signature of the Inspecting Officer

Name: - M. K. Chattopadhyay Designation: - Dy.CFO (WZ)

Signature of the Inspecting Officer

Name: - Sarabjeet Singh Designation: - ADO (MN)

Sir, F. T is put up for your kind persuals

Aijnafus pls. 1 Sep.