

No: F6/DFS/MS/EH/WZ/2025/ 365

Dated: 29/ 10 /2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Aum Hospitality located at Shop No. 25, TF, NWA, Club Road, West Punjabi Bagh, New Delhi – 110026, in a building comprised of Basement, Stilt, Upper Ground + 03 upper floors but restaurant is running at 3rd floor onlywas earlier granted FSC by this department vide letter No. F6/DFS/MS/EH/WZ/2022/285 dated 12.10.2022. Now, the building/premises was reinspected by the officer concerned of this department on 15.10.2025 in presence of Mr. Sachin Joshi (Owner)and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Assembly Building" (Group-D), (restaurant at 3rd floor only), with effect from 29.1.1.0.../2025 for period of three yearsin accordance with Rule 36 unless renewed under Rule 37 or so ner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire Service Rules, 2 10 printed below.

Issued on 29/10/2025 at New Delhi by

(S. K. Dua)
Dy. Chief Fire Officer (WZ)
Delhi, Fire Service

Copy to:-

- 1. The Dy. Health Officer, SDMC, West Zone, Vishal Enclave, Rajouri Garden, New Delhi 110027. w.r.to ID No. 2025100914081 dated 09.10.2025.
- 2. The Licensee, Aum Hospitality at Shop No. 25, TF, NWA, Club Road, West Punjabi Bagh, New Delhi 110026.

Conditions for the validity of fire safety certificate

- 1. This FSC is valid fo 3rd floor only.
- 2. All the fire safety a rangements provided therein shall be maintained in good working condition at all times.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety cereficate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. Any flammable material for interior decoration shall strictly by prohibit.

•	301	, .		CTION REPORT				
1	Nar	ne d	& address of the building	M/s Aum Hospitality located at Shop No. 25, TF, NWA, Club Road, West Punjabi Bagh,				
2	Divi	14:.		New Delhi – 110026.				
-	Building is comprised of			Basement, Stilt, Upper ground +03 upper floors)				
3				(But restaurant is running at 3rd floor only)				
4	Type of occupancy			Assembly Building-"restaurant"				
-	Type of case			Renewal				
5	_	-	of previous FSC	F6/DFS/MS/EH/WZ/2022/285dated 12.10.2022				
6	Fire	Fire safety direction letter no. Nil						
7	Date of inspection			15.10.2025	15.10.2025			
8	Name of the inspecting officers			Suman Kumar, ADO				
9	1		of the designation of officer	Mr. Sachin Joshi	(Owner)			
			ne building side					
10	Year of construction			2018 (as per MHA Portal)				
11	Ap	olic	ant's letter no.	MCD Portal application ID No. 2025100914081				
				dated 09.10.2025				
S.N	Mi	nin	um Standards on fire	BBL/NBC	Provided at	Remark		
0	Prevention and fire safety requirements U/R 33		ntion and fire safety	Requirements/	Site	s MR/ NMR		
1	Access To Building:							
	Ro	ad v	vidth	12 m	Provided	MR		
			vidth	4.5 m	On Road	MIR		
	Width of internal road			NA	NA	NA		
2	Number, Width, Type and Arrangement of Exits:							
	A	-	umber of staircases		[k]	1 Non		
		-	Upper floor	02 nos.	Provided	MR		
	_	_	Basement	NA	NA	NA		
	B	_	idth of staircases	1,5 3 3 3	"TR	LMD		
			Upper floor Basement	1.5 m x 2 NA	Provided NA	MIR NA		
	C		rotection of exits	INA	INA	INA		
	-		Fire check door	Required	Provided	MR		
			Pressurization	NA	NA	NA		
	D	N	lo. of continuousstaircases terrace	01 no.	Provided	MR		
	E		Vidth of corridor	NA	ŇÁ	NA		
	F	-	Door size	1.5 mx 2	Provided	MR		
3	Compartmentation:				1101100	1		
	A Fire check door			NA	NA	NA		
	B Sealing of electrical shafts			NA	NA NA	NA NA		
	C Fire rating of shaft door			NA	NA NA	NA NA		
	D Water curtain			NA	NA NA			
	E Fire dampers			NA	NA NA	NA		
4	-	_	Management System:	1 - 14 -	INA	NA		
300	A Upper floors			Required	Net	71		
	B Basements			NA	Natural	MR		
	1 - 1			1 - 10 -	NA	NA		

5.	Fire Extinguisher:							
	A	maintour	05 nos.	08 nos.	MR			
	В	Types	ABC& Co2	ABC& Co2	MR			
	C	ISI marking	Required	Provided	MR			
6	First-Aid-Hose Reels:							
	A	Total numbers at each floor	01 no.	01 no.	MR			
	В	Length of hose reel hose	30 mtr.	30 mtr.	MR			
	C	Nozzle diameter	05 mm	05 mm	MR			
7	Automatic Fire Detection And Alarming System:							
	A	Type of detectors	Smoke & Heat	Provided	MR			
	В	Location of main panel	Required	Provided	MR			
	C	Location of repeater panel	NA	Provided	NA			
	D	Alternate source of power	Required	Provided	MR			
	E	Hooters Location	Required	Provided	MR			
8	-	OEFA:	Required	Provided	MR			
9	-	blic Address System:	NA	NA	NA			
10	-	tomatic Sprinkler System:		1224	- 11			
	A	Basement	NA	NA	NA			
	В	Upper floor	Required	Provided	MR			
	C	Sprinkler above false ceiling	NA	NA	NA			
11	Internal Hydrants:							
	A	size of riser/down-comer	100 mm	Provided	MR			
	В	Number of hydrants per floor	01 no.	Provided	MR			
	C	Hose box	01 no.	Provided	MR			
12	Ya	Yard Hydrants:						
	A	Total number of hydrants	NA	NA	NA			
	В	Hose box	NA	NA	NA			
13	1250	mping Arrangements:						
	A Ground level							
	2)	Discharge of main pump	2280 LPM	Provided	MR			
	a)	Head of main pump	70 m	Provided	MR			
	b)	To Control to the con	01	Provided	MR			
	c)	Number of main pumps	180 LPM	Provided	MR			
	d)	Jockey pump out put	70 m	Provided	MR			
	e)	Jockey pump head	2280 LPM	Provided	MR			
	f)	Standby pump out put	70 m	Provided	MR			
	g)	Standby pump head	Required	Provided	MR			
	h)	Auto starting /manual	Toquiro	September 1. Total Sold				
		Stopping Pump House Access	Required	Provided	MR			
	1 Pump House Needs							
	В	Terrace level	450 LPM	450 LPM	MR			
	a)	Discharge of pump	70 m	Provided	MR			
	b)	Head of the pump	Required	Provided	MR			
	c)	Power supply		Provided	MR			
	d)	Auto starting of pump	Required	1101100				

("	- 3	subscript of v		البائاص			
14	Captive Water Storage for Fire Fighting:						
A -	A	Underground tank capacity	1,00,000 ltrs	Provided	MR		
	B	Draw-off connection	Required	Provided	MR		
	C	Fire service inlet	Required	Provided	MR		
	D	Access to tank	Required	Provided	MR		
	E	Overhead tank capacity	10,000 ltrs.	Provided	MR		
15	Ex	Exit Signage: Required		Provided	MR		
16	Provision of Lifts:						
7	A	Pressurization of lift shaft	NA NA	l NA	NA NA		
	В	Pressurization of lift lobby	NA	NA	NA		
	C	Communication in lift car	Required	Provided	MR		
	D	Firemen's grounding switch	Required	Provided	MR		
	E	Lift signage	Required	Provided	MR		
17	Standby Power Supply:		Required	Provided	MR		
18	Refuge Area:						
	A	Total area	NA	NA	NA		
	В	Location	NA	NA	NA		
19	Fire Control Room:						
	A	Detector system panel	NA	NA	NA		
	В	Flow switch panel		NA	NA		
	Ć	Pa system panel		NA	NA		
	D	Battery backup		NA	NA		
	E	Building floor plans cial Fire Protection SystemsFor		NA NA	NA NA		

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standard of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No. F6/DFS/MS/EH/WZ/2022/285 dated 12.10.2022 is recommended to be renewed (restaurant at 3rd floor only), under Rule 35 of the Delhi Fire Service Rules 2010.

Accordingly, DFA is put for approval and signature please.

Signature of the Inspecting Officer Name Suman Kumar Designation ADO (SPM)