

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001



No. F.6/DFS/MS/2025/WZ/ 163

Dated: 04/04/2025

FIRE SAFETY CERTIFICATE

Certified that the Delhi Metro Rail Corporation Ltd at Badli Enclave Metro Station of Line 2 Ext. Delhi, comprised of Ground Level + Concourse Level + Platform Level owned/ occupied by Delhi Metro Rail Corporation Ltd has already been issued FSC by this department vide letter No. F.6/DFS/MS/2022/WZ/139 dated 31.03.2022. The premises was re-inspected by the officer concerned of this department on 27.03.2025 in the presence of Mr. Pushkar (AM/Fire) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class "D" Assembly Building less than 15 mtr with effect from for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 04/04/2025 at New Delhi by

(Atul Garg) DIRECTOR Ph; 011-23414000

Copy to :-

- Chy 1. Mr. Rajesh Agrawal, (GM/E&M) Metro Bhawan, 13, Fire Brigade Lane, Barakhamba Road, New Delhi-110001.
- 2. Mr. Pushkar (Fire Inspector) Delhi Metro Rail Corporation Ltd at Badli Enclave Metro Station of Line 2 Ext. Delhi.

Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. All the staff members must know the correct method of operation of firefighting system.
- 5. The owner/occupier shall submit a declaration every year in Form 'K'[sub rule (2) of Rule 38] provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on http://delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms
- 6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction (Clause 2.9.2 of UBBL-2016) or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of Rule 37] along with a copy of this Certificate, six months prior to its

1	٧Į	
	•	

1						
-			INSPEC	TION REPORT	190	
	Nome & ad	dress of the building			on Ltd at Badli Enclay	Motes Stat
1. 1	Name & ac	idicss of the building		2 Ext. Delhi	on Liu at badii Enclav	e Metro Stat
2.	Type of Oc	cupancy	Assemb			
	Type of Ca			•	Concourse Level + Pla	atform Level
4. 1	Details of	Previous NOC		S/MS/2022/WZ/139		
		directives letter No		S/MS/BP/2013/259		
	Date of ins		27.03.20			
0.70.0		specting Officer	Sh. Aja	y Kumar Sharma (A	DO Rohini)	
		designation of officers	Mr. Pus	shkar (AM/Fire)		
		uilding side				
9.	Year of Co	onstruction	2013			
10.	Applicant'	s letter No.	OD No.	.12831 dated 24.02.	2025.	
		Standards on fire prev	ention	NBC	Provided at site	Remarks
1		afety U/R 33		Requirement		MR/NMR
i.	Access to					1
-		ad width		Accessible	Accessible	'MR
		ite width		Accessible	5m	MR
		idth of internal road		-NA-	-NA-	-NA-
_		Width, Type & Arrang	ement of			
2.			ement of	Daits		
	a. Numbe	er of staircases		06nos. Concourse to	Provided	MR
		11 El		platform		
	•	Upper Floors		02nos. ground to Concourse		
		D		-NA-	-NA-	-NA-
		Basements				
	b. Width	of staircases		3.8 x 2nos.	Provided	
		Ba-		2.05 x 2nos.	Provided	MR
	•	Upper Floor		3.85 x 1 & 1.47 x	Provided	IVIX
				1 for future Extn.	-NA-	-NA-
	•	Basements		-NA-	11/4	
	c. Prote	ction of exits		2 1	Provided	MR
	•	Fire check door		Required	-NA-	-NA-
	•	Pressurization		-NA-	19-70-15-	MR
		continuous staircases to	o terrace	02nos.	Provided	-NA-
		of Corridor		-NA-	-NA-	-NA-
	f. Door			-NA-	-NA-	-IVA
3.		tmentation				MR
3.		ire check door		Required	Provided	MR
		ealing of electrical shafts	li e	Required	Provided	
	• 5	ire Rating of shaft door		Required	Provided	MR
		Water Curtain		-NA-	-NA-	-NA-
	- S-	Fire Dampers		-NA-	-NA-	-NA-
-		Management System				7 374
4.		Basements		-NA-	-NA-	-NA-
-		Upper floors		12 a/c per hour	Natural ventilated	MR
_		ctinguishers				1 1/0
		Total numbers		20nos.	Provided	MR MR
5.	1 -				ABC/CO2	MK
5.		Types		ABC/CO2	Yes	MR

Oby to

N/15

\top	Total numbers on each floor	06 on each platform	06 on each platform 3/4	MR			
	- IOMI IIMIIIOOID OIL WANT LIVE	3/4 on Concourse/Plat	on Concourse/ Plat				
		form	from Provided	MR			
	 Length of hose reel hose 	45mm					
	 Nozzle diameter 	5m	Provided	MR			
	Automatic fire detection and alarming system						
	a) Type of detectors	Smoke	Provided	MR			
t	b) Location of Main Panel	Required	Provided	MR			
	c) Location of Repeater Panel	-NA-	-NA-	-NA-			
Ì	d) Alternate source of power	Required	Provided	MR			
	e) Hooters' Location	Required	Provided	MR MR			
8.	MOEFA	Required	Provided				
9.	Public Address System	Required	Provided	MR			
10.	Automatic Sprinkler System		3.77	NTA			
	Basement	-NA-	-NA-	-NA-			
	Ground & Upper Floors	-NA-	-NA-	-NA-			
	Sprinkler above false ceiling	-NA-	-NA-	-NA-			
11.	Internal Hydrants						
	Size of riser/down-comer	150mm	Provided	MR			
	Number of hydrants per floor	Required	Provided	MR MR			
	Hose Box	Required	Provided				
12.	Yard Hydrants						
	Total number of hydrants	02nos.	Provided	MR			
	Hose Box	Required	Provided	MR			
13.	Pumping Arrangements						
	Ground Level						
	 Discharge of main Pump 	1800lpm	1800lpm	MR			
	➤ Head of Main pump	70m	70m	MR			
	Number of main pumps	01	01	MR			
	Jockey Pump out put	180lpm	180lpm	MR			
	Jockey pump head	70m	70m	MR			
	> Standby Pump out put	1800lpm	1800lpm 70m	MR MR			
	> Standby Pump Head	70m Required	Provided	MR			
	> Auto Starting/Manual Stopping	Required	Provided	MR			
_	> Pump House Access	Toquito	1101144				
	Terrace level	-NA-	-NA-	-NA-			
	> Discharge of pump	-NA-	-NA-	-NA-			
	> Head of the pump	-NA-	-NA-	-NA-			
	> Power Supply Auto Storting of pump	-NA-	-NA-	-NA-			
14	 Auto Starting of pump Captive Water Storage for fire fighting 		-11/1-	-11/7-			
14				MR			
	Underground tank capacity						
	> Draw-off connection	Required	Provided	MR			
	➤ Fire service inlet	Required	Provided	MR			
	> Access to tank	Required	Provided	MR			
15	Overhead Tank capacity	10,000ltr	Provided	MR			
		Required	Provided	MR			
16	Provision of Lifts.						
-	Pressurization of Lift Shaft	-NA-	-NA-	-NA-			
	Pressurization of Lift lobby	-NA-	-NA-	-NA-			

0

	• C	Communication In lift Car Required				
	• Fi	reman's Grounding Switch	Required	Provided	MR	
	• Li	ft Signage	Required	Provided	MR	
17.		power supply	Required	Provided		
			Required	Provided	MR	
18.	Refuge Area.					
	> To	tal Area	-NA-	NI.		
	➤ Lo	cation	-NA-	-NA-	-NA-	
19.	Fire Control Room -NANA-					
	• D	etector System Panel	Required	Provided	1.00	
	• Fl	ow Switch Panel	-NA-		MR	
	• P.	A System Panel	Required	-NA- Provided	-NA-	
	• B	attery backup	Required	Provided	MR MR	
	• B	uilding Floor Plans	-NA-	-NA-	-NA-	
20.		ire Protection System for on of special Risks, if any:	-NA-	-NA-	-NA-	

Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2022/WZ/139 dated 31.03.2022 is recommended for renewal under rule 37 of the Delhi Fire Service rules 2010.

> Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO(Rohini)

D.B Mukherjee

DO (NW)

for being perusal of sign for