





GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/CGHS/2025/SZ/ 237

Dated: 09/05/2025

FIRE SAFETY CERTIFICATE

Issued on 09 /05 /2025 at New Delhi by

(ATUL CARC)

Ph. 011-23414000

Copy to: -

- The Joint Director (L&I), Building Section, Delhi Development Authority. Vikash Sadan, INA, New Delhi–110023
- The President, M/s Bandhu Vihar CGHS Ltd. at Plot No. 11, Sector-10, Dwarka, New Delhi-110075

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangement provided therein shall be maintained in good working conditions
 at all time as seen during inspection. Any loss of life property due to non-functional fire safety
 measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire-fighting system.
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, prior to its expiry.
- The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

hilit

	INSPEC	TION REPORT			
1	Name & Address of the Building	Bandhu Vihar CGHS Ltd. at Plot No. 11,			
		Sector-10, De	warka New Date:	M No. 11,	
2	Type of Occupancy	Sector-10, Dwarka, New Delhi-110075 Residential Building 'A'			
3	Building Comprised of	02 High Rise Blocks, of G/Stilt + 06/07 UFs			
4	Type of Case	Renewal	blocks, of G/Still +	06/07 UFs	
5	Details of Previous NOC		GHS/2001/259 dated		
6	Fire Safety Directives Letter No	F6//DEC/AC	07/CCT16/075 Dated	12/02/2001	
7	Date of Inspection	29/04/2025	97/CGHS/875, Dt. 2	5/07/1997	
8	Name of the Inspecting Officers				
9	Name & Designation of Officers	ADO (DWK)			
	from the building side	Sh. Ravinder			
10	Year of construction	2000			
11	Applicant letter No.	No. NIL dated 11.04.2025 received through			
		Outdoor Diary !	rougn 125		
S.	Minimum standards on Fire	Requirement		Remark	
No.	Prevention and Fire Safety U/R 33	Rule 35(6)	TO THE CONTROL OF THE	MR/NM	
1	Access to Building.				
	 Road width 	12 mtr	Provided	MR	
	Gate width	06 mtr	Provided	MR	
	Width of internal road	06 mtr	Provided	MR	
2	Number, width, type & arrangem	ent of exits.			
	a) Number of Staircase				
	Upper floors.	02 Nos	Provided	MR	
	➤ Basements	-NA-	-NA-	-NA-	
	b) Width of Staircase		1 272	1.21	
	> Upper floors	1.25 mtr	Provided	MR	
	➤ Basement floor	-NA-	-NA-	-NA-	
	c) Protection of exits			101	
	➤ Fire check door	-NA-	-NA-	-NA-	
	➤ Pressurization	-NA-	-NA-	-NA-	
	d) No. of continuous staircase to terrace	02 Nos	Provided	MR	
	e) Width of corridor	-NA-	-NA-	-NA-	
	f) Door size	Required	Provided	MR	
3	Compartmentation.	required	Tioriaca	17111	
	Fire check door.	-NA-	-NA-	-NA-	
	Sealing of electrical shafts.	Required	Provided	MR	
	Fire rating of shaft door.	-NA-	-NA-	-NA-	
	Water curtain	-NA-	-NA-	-NA-	
	Fire dampers.	-NA-	-NA-	-NA-	
4	Smoke Management system.	TIA	-NA	-1474-	
	Basement	-NA-	-NA-	-NA-	
	Upper floors		Natural Ventilation	MR	
5	Fire Extinguishers.	required	vaturar ventriation	MIC	
	Total numbers		02/Floor (Each Blk)	MR	
	Types	ISI marked	CO ₂ & ABC	MR	
	ISI Marking		Provided	MR	
6	First Aid Hose Reels.				
_		01/Floor	Provided	MR	
	1 Otal numbers on each floor	UI/FIOOI	11011000		
	Total numbers on each floor. Length of hose-reel hose.	30m	30m	MR	

St

N-B

7	Automatic fire detection & alarming	system.		
	Type of detectors	-NA-	-NA-	-N
	 Location of Main Panel 	-NA-	-NA-	-N/
	 Location of Repeater Panel 	-NA-	-NA-	-NA
	Alternate source of power	-NA-	-NA-	-N/
	Hooter's location	-NA-		_
8	MOEFA		-NA-	-NA
9		Required	Provided	MF
10	Public Address System	-NA-	-NA-	-NA
10	Automatic Sprinkler System			-,
	Basement	-NA-	-NA-	-NA
	Upper floors	-NA-	-NA-	-NA
	 Sprinkler above false ceiling 	-NA-	-NA-	-NA
11	Internal Hydrants.			
	 Size of Riser/Down-comer 	100 mm	Provided	MR
	 Number of Hydrant per floor 	One each floor	Provided	MR
	Hose box.	Required	Provided	MR
12	Yard Hydrants.			
	Total number of hydrants.	Required	Provided	MR
	Hose box.	Required	Provided	MR
13	Pumping arrangements.	1	Tiorided	IVIIC
	Ground Level			
	 Discharge of main pump 	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head.Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump output. Standby Pump head.	-NA-	-NA-	-NA-
	Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	Pump house access.	-NA-	-NA-	-NA-
	Terrace Level	-11//-	-NA-	-NA-
	Discharge of pump.	450 LPM	450 LPM	100
	➤ Head of pump.	(Each Blk)	(Each Blk)	MR
	Power supply.	40m each	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14	Captive water storage for firefighting	Required	Provided	MR
	Underground tank capacity.	2,00,000 ltr	D	
	Draw-off connection.	Required	Provided	MR
	Fire Service Inlet.	Required	Provided Provided	MR
	Access to tank.	Required	Provided	MR
	 Overhead tank capacity. 	10,000 Ltr	Provided	MR
15	Exit Signage.		- C-17-17	MR
16	Provision of Lifts.	Required	Provided	MR
	 Pressurization of lift shaft. 	NI A		
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car	Required	-NA-	-NA-
	The state of the s		Provided	MR
	Fireman's switch.	Required		N ATS
1=	 Lift signage. 	Required Required	Provided	MR
17	Lift signage. Standby Power Supply	Required	Provided	MR
17 18	Lift signage. Standby Power Supply Refuge Area			
	Lift signage. Standby Power Supply	Required	Provided	MR





9.	Fire Control Room.			
7.	MOEFA System Panel.	-NA-	-NA-	-NA-
	 Flow switch panel. PA system panel. Battery backup. Building floor plan. 	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
		-NA-	-NA-	-NA
		-NA-	-NA-	-NA
20.	Special Fire Protection System for Protection of Special Risk, if any.	CO ₂ type fire extinguisher provided near electrical panel		MR

The fire protection systems provided in the building were test checked and found functional at the time of inspection. The shortcomings issued by this department vide letter No. F6/DFS/MS/CGHS/2025/SZ/123 dated 26/03/2025 have been rectified.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety as required under the rules, the fire safety certificate issued vide letter No. F6//MS/DFS/CGHS/2001/259 dated 12/02/2001, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (DWK)

Director Sir, Frettes is promp for your 8ing. Pl