

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No: F6/DFS/MS/EH/SZ/2025/ | 4 8

Dated: 24/04/2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Bikanervala International located at 7, Masjid Moth, Greater Kailash-II, New Delhi - 48, comprised of Basement, Ground + 02 upper floor only owned /occupied by M/s Bikanervala International was granted FSC by this department vide letter no. F.6/DFS/MS/EH/SZ/2022/136 dated 23.05.2022. Now, the restaurant premises was re-inspected by the officer concerned of this department on 15.04.2025 in presence of Mr. Ramesh Sharma (Manager) and observed that the premises /building has deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. Accordingly, the premises is fit for occupancy class (Group D) "Assembly Building", with effect from .24.../2025 and valid upto 31.03.2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire Service Rules, 2010 printed below.

Issued on 24 04 20.25 at New Delhi by

Director Delhi Fire Service

Tél: 011-23414000

Copy to:-

- 1. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2025040305394 dated 03.04.2025.
- 2. The Dy. Health Officer, Public Health Department, South Zone, Green Park, Delhi 16.
- 3. The Licensee, M/s Bikanervala International at 7, Masjid Moth, Greater Kailash-II, New Delhi -48.

Conditions for the validity of fire safety certificate

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the 3. management.
- All the staff members must know the correct method of operation of fire fighting system. 4.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if 5.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

| | | INSPE | ECTION REPORT | | |
|-----|---|---|--|--|------------------------------|
| 1 | Nam | e & address of the building | M/s Bikanerwa Masjid Moth, G | ala International lo reater Kailash-II, Nev | cated at 7, w Delhi - 48. |
| 2 | Buil | ding is comprised of | (Basement, Ground + 02 upper floor) | | |
| 3 | | e of occupancy | Group-D-4, Assembly | | |
| 4 | | e of case | Renewal | | |
| 5 | • • | ails of previous FSC | F.6/DFS/MS/EH/SZ/2022/136 dated 23.05.2022 | | |
| | | safety direction letter no. | F6/DFS/MS/EH/2005/718 dated 04.04.2005 | | |
| 6 | | | 15.04.2025 | | |
| 7 | | e of inspection | ADO (SPM) | | |
| 8 | | ne of the inspecting officers | | rma (Manager) | |
| 9 | | ne of the designation of officer | Wir. Kainesii Shai | ma (Transition) | |
| | from the building side | | 2005 | | |
| 10 | | r of construction | 2005 | ion no. 202504030 | 5394 dated |
| 11 | App | olicant's letter no. | Online application is | | |
| | | | 03.04.2025 | Provided at Site | Remarks |
| S.N | | nimum Standards on fire | Old NOC | 11001200 | MR/ |
| 0 | Pre | evention and fire safety | Requirements | | NMR |
| | | uirements U/R 33 | | | |
| 1 | 1 | cess To Building: | I Dinod | 09 mtrs. | MR |
| | Roa | ad width | Required | Approachable | MR |
| | Gate width | | Required NA | NA | NA |
| | Width of internal road Number, Width, Type and Arran | | goment of Exits: | | |
| 2 | Nu | mber, Width, Type and Arran | gement of Zaras | | |
| | A | Number of staircases | 02 nos. | Provided | MR |
| | | a Upper floor b Basement | 02 nos. | Provided | MR |
| | D | Width of staircases | | | NGD (-14 |
| | В | a Upper floor | 1.25 m | 0.92 m & 1.10 m | MR (old |
| | | a opper need | | 0.02 8-1.10 m | case) MR (old |
| | | b Basement | 1.25 m | 0.92 m & 1.10 m | case) |
| | | | | | case) |
| | C | Protection of exits | Required | Provided | MR |
| | | a Fire check door | NA | NA | NA |
| | | b Pressurization No. of continuous staircases | Required | Provided | MR |
| | D | to terrace | Roquirea | | |
| | E | Width of corridor | NA | NA | NA |
| | F | Door size | 02 exits | 1.70 m & 1.05 m | MR (old |
| | r | Door size | | | case) |
| 3 | Co | mpartmentation: | | | |
| | A | Fire check door | Required | Provided | MR |
| | В | Sealing of electrical shafts | NA | NA | NA |
| | C | Fire rating of shaft door | NA | NA | NA |
| | D | Water curtain | NA | NA | NA |
| | E | Fire dampers | NA | NA | NA |
| 4 | Sm | oke Management System: | 1 | | 1.60 |
| | A | Upper floors | 12 ACPH | Exhaust fan provided | |
| | В | Basements | 12 ACPH | Exhaust fan provided | MR |

| | Fine Ev | tinguisher: | 10 nos. | 10 nos. | MR | |
|----|------------------------------------|---|------------------------------|----------------|----------------------|--|
| 5. | | Total numbers | ABC& Co2 | Provided | MR | |
| | B | Types | | Provided | MR | |
| | C | ISI marking | Required | | | |
| | Einst-Ai | d-Hose Reels: | | Provided | MR | |
| 6 | A | Total numbers on each | 01 no. | 110,13 | | |
| | A | floor | 30 mtr. | Provided | MR | |
| | В | Length of hose reel hose | 05 mm | Provided | MR | |
| | C | Nozzle diameter | | | | |
| 7 | Automatic Fire Detection And Aları | | ning System. | Smoke & heat | MR | |
| | A | Type of detectors | Required | Ground floor | MR | |
| | В | Location of main panel | Required | NA | NA | |
| | C | Location of repeater panel | NA | | | |
| | D | Alternate source of power | Required | Battery backup | MR | |
| | E | Hooters Location | Required | Provided | MR | |
| 8 | MOEFA | λ: | Required | Provided | MR | |
| 9 | Public A | Address System: | NA | NA | NA | |
| 10 | Automa | tic Sprinkler System: | | | | |
| | A | Basement | Required | Provided | MR | |
| | В | Restaurant area | Required | Provided | MR | |
| | C | Sprinkler above false ceiling | NA | NA | NA | |
| 11 | Internal Hydrants: | | | | | |
| | A | size of riser/down-comer | 100 mm | Provided | MR | |
| | В | Number of hydrants per floor | 01 no. | Provided | MR | |
| | С | Hose box | 01 no. | Provided | MR | |
| 12 | Yard H | ydrants: | | Trovided | MIK | |
| | A | Total number of hydrants | NA | NA | NIA | |
| | В | Hose box | NA | NA | NA | |
| 13 | Pumping Arrangements: | | 141 | INA | NA | |
| | A | Ground level | - | 100 | | |
| | | | | | | |
| | a) | Discharge of main pump | NA | NA | NIA | |
| | b) | Head of main pump | NA | NA | NA | |
| | c) | Number of main pumps | NA | NA NA | NA | |
| | d) | Jockey pump out put | NA | NA NA | NA | |
| | e) | Jockey pump head | NA | NA NA | NA | |
| | f) | Standby pump out put | NA | NA NA | NA | |
| | | C4 11 | | 4.44.7 | NA | |
| | g) h) | Standby pump head | NA | NA | | |
| | g) h) | Standby pump head Auto starting /manual | NA NA | NA NA | NA | |
| | g) h) | Standby pump head Auto starting /manual stopping Pump House Access | NA | NA | | |
| | g) h) i B | Standby pump head Auto starting /manual stopping Pump House Access Terrace level | | | NA NA | |
| | g) h) | Standby pump head Auto starting /manual stopping Pump House Access | NA NA | NA NA | NA | |
| | g) h) i B | Standby pump head Auto starting /manual stopping Pump House Access Terrace level Discharge of pump | NA NA 450 LPM & 180 LPM | NA | NA NA | |
| | g) h) i B a) b) c) | Standby pump head Auto starting /manual stopping Pump House Access Terrace level Discharge of pump Head of the pump | NA NA 450 LPM & 180 LPM 35 m | NA NA Provided | NA NA NA MR | |
| | g) h) i B a) b) | Standby pump head Auto starting /manual stopping Pump House Access Terrace level Discharge of pump | NA NA 450 LPM & 180 LPM | NA NA | NA NA NA | |

| 4 | A | otive Water Storage For Fire F Underground tank capacity | NA | NA | NA | | | |
|----|-----|---|-------------|----------|--------------|--|--|--|
| - | B | Draw-off connection | NA | NA | NA | | | |
| | C | Fire service inlet | Required | Provided | MR | | | |
| | D | Access to tank | NA | NA | NA | | | |
| | E | Overhead tank capacity | 5,000 ltrs. | Provided | MR(old case) | | | |
| 5 | Exi | t Signage: | Required | Provided | MR | | | |
| _ | Dro | Provision of Lifts: | | | | | | |
| 16 | - | Pressurization of lift shaft | NA | NA | NA | | | |
| | A | Pressurization of lift lobby | NA | NA | NA | | | |
| | B | Communication in lift car | NA | NA | NA | | | |
| | _ | Firemen's grounding switch | NA | NA | NA | | | |
| | D | | NA | NA | NA | | | |
| | E | Lift signage | Required | Provided | MR | | | |
| 17 | | Standby Power Supply: | | | | | | |
| 18 | Re | fuge Area: | NA | NA | | | | |
| | A | Total area | NA | NA NA | NA | | | |
| | В | Location | NA | 1471 | | | | |
| 19 | Fi | re Control Room: | NA | NA | | | | |
| | A | Detector system panel | NA | NA NA | NA | | | |
| | В | Flow switch panel | NA- | NA NA | NA | | | |
| | C | Pa system panel | NA | NA NA | NA | | | |
| | D | Battery backup | NA NA | NA NA | NA | | | |
| | - | Duilding floor plans | NA | | NA | | | |
| 20 | Si | pecial Fire Protection Systems Forcial Risks, If Any: | 14/1 | ,Â | | | | |

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F.6/DFS/MS/EH/SZ/2022/136 dated 23.05.2022 is recommended to be renewed under Rule 37 of the Delhi Fire Service Rules 2010.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Sumit Kumar Name

ADO (SPM) Designation

Director (DFS)