GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/School/2025/SZ/664

FIRE SAFETY CERTIFICATE

Certified that the Birla Vidya Niketan School (Higher Secondary & Primary Block) located at Pushp Vihar, Sector-IV, New Delhi-110017 comprised of 02 Building Blocks (Basement, Ground plus Three Upper floors each) owned/occupied by Birla Academy of No. department vide letter this issued **FSC** by was Culture Art and F.6/MS/DFS/School/2022/SZ/408 dated 12-04-2022 for Higher Sec. Block F6/DFS/MS/School/2022/SZ/309 dated 23/03/2022 for primary Block. The premises was re-inspected by officer concerned by this department on 07/05/2025 in the presence of Mr. C.L. Mishra (Manager-Admin) of the school and observed that the school premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Educational" Group-B (School) as above with effect from under rule 37 or sooner cancelled under rule 40 and subject to compliance of conditions, mentioned below.

Issued 16 5./2025 at New Delhi by

DELHI FIRE SERVICE

Copy to: -

- 1. Mr. C.L. Mishra (Manager-Admin) Birla Vidya Niketan, Pushp Vihar-IV, New Delhi-110017
- 2. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

Conditions for the validity of Fire Safety Certificate: -

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire fighting system.
- 4. The basement shall be used as per the provisions of BBL-/NBC Part- IV.
- 5. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 7. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

	INSPECTION REPORT							
				3 . 01 10F1	. G to			
ì	Name & Address of the Building	Birla Vidya Niketan School (Higher Secondary School & Primary Block), Pushp Vihar, Sector-IV, New Delhi-110017						
2	Type of Occupancy	Educational, Group-B (School)						
3.	Building Comprised of	Both of Blocks are Basement, Ground + 03 upper floors						
4	Type of Case	Renewal						
5	Details of Previous NOC	F.6/MS/DFS/School/2022/SZ/408 dated 12-04-2022 for Higher Sec. Block F6/DFS/MS/School/2022/SZ/309 dated 23/03/2022 for primary Block						
6	Fire Safety Directives Letter No	F.6/DFS/MS/BP/2013/13 dated 21/03/2013						
7	Date of Inspection	07-05-2025						
8.	Name of the Inspecting Officers.	Sh. Rajesh Kumar, ADO (BCP).						
9	Name & Designation of Officers from the building side	Mr. C.L. Mishra (Manager-Admin)						
10	Year of construction	2015						
11 S. No	Applicant letter No. Minimum standards on Fire Prevention and Fire Safety U/R 33	Email dated 02- Requirements		4-2025 Provided at Site	Remarks MR/NMR			
1	Access to Building.	1	1					
	Road width	9 mtr		12 mtr	MR			
	Gate width	6 mtr/4.5 mtr		Provided	MR			
	Width of internal road	6 mtr		Provided	MR			
2	Number, width, type & arrangement of e	xits.						
	a) Number of Staircase	*						
	Upper floors.	05 Nos ea	ach blk	Provided	MR			
	Basement floor.	03 Nos each blk		Provided	MR			
	b) Width of Staircase							
	> Upper floors	1.5m each blk	1.58m GF to 2	m, 1.50m, 1.50m, 1.50 & 1.40m o 2 nd Floor– 2m (Canteen Block)				
	Basement floor c) Protection of exits	1.5m each blk 1.52m, 1.50m & 1.50m		MR				
	c) Protection of exits > Fire check door							
	> Pressurization	Require		Provided	MR			
		-NA-		-NA-	-NA-			
	d) No. of continuous staircase to terrace e) Width of corridor	Required		01 No	MR			
	e) Width of corridor f) Door size	-NA-		-NA-	-NA-			
3	Compartmentation.	1m		Provided	MR			
	Fire check door.		•		IVIIC			
		Required						
				Provided	MR			
	 Sealing of electrical shafts 	Require		Provided Provided	MR MR			
	 Sealing of electrical shafts. Fire rating of shaft door 	Require -NA-			MR			
	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers 	Require -NA- -NA-		Provided	MR -NA-			
4	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system	Require -NA-		Provided -NA-	MR -NA- -NA-			
4	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain 	Require -NA- -NA- -NA-	ed	Provided -NA- -NA- -NA-	MR -NA-			
	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors 	Require -NA- -NA- -NA-	H	Provided -NA- -NA- -NA-	MR -NA- -NA- -NA-			
5	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers.	Require -NA- -NA- -NA-	H	Provided -NA- -NA-	MR -NA- -NA-			
	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers 	Require -NA- -NA- -NA-	H	Provided -NANANA- Provided exhaust fan Natural Ventilation	MR -NANANA-			
	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers Types 	Require -NANANA- 30 ACP	H H	Provided -NANANA- Provided exhaust fan Natural Ventilation 40 Nos each blk	MR -NANANA-			
	 Sealing of electrical shafts. Fire rating of shaft door. Water curtain Fire dampers. Smoke Management system. Basement Upper floors Fire Extinguishers. Total numbers 	Require -NA- -NA- -NA-	H H	Provided -NANANA- Provided exhaust fan Natural Ventilation	MR -NANANA- MR MR			

N/29



		2,	1/29	आ	नादी क
	First A	Aid Hose Reels.	KI,	3	मृत मा
		The Hose Reels.			
	•	Fotal numbers on each floor.			
- 1	•	Length of hose-reel hose.		BF-03, UF-04 No	
	•	Nozzle Diameter	Hose-reel		os
7	Autor		t e	Join each	
	Autor	natic fire detection & alarming sy	stem Fortil	5mm each	
	•	- JPC OI delectors		er Secondary block	
	•	Location of Main Panel	Required	Smoke type	1
	•	Location of Repeater Panel	Required	Ground floor	N
	•	Alternate source of power	-NA-	-NA-	-1
	•	Hooter's location	Required	Provided	i i
8	MOE	CFA	Every floor	Provided	
9			Required	Provided	I N
10	Auto	c Address System	Required	Provided	M
10	Automatic Sprinkler System		For higher Se	econdary block	M
	•	Basement	Required	Provided	1
	•	Upper floors	-NA-	-NA-	M
	•	Sprinkler above false ceiling	-NA-	-NA-	-NA
11	Inte	rnal Hydrants.		condary block	-NA
		Size of Riser/Down-comer	150 mm	Provided Provided	MR
	١.	Number of Hydrant per floor	04 Nos	Provided	
		• Hose box.			MR
10	¥7		04 Nos	Provided	MR
12	Yar	d Hydrants.			
		Total number of hydrants.	-NA-	-NA-	-NA-
		Hose box.	-NA-	-NA-	-NA-
13	Pui	nping arrangements.			-
		 Ground Level Discharge of main pump.	-NA-	-NA-	-NA-
		Head of main pump.	-NA-	-NA-	-NA-
Ĭ	ł	Number of main pumps.	-NA-	-NA-	-NA-
-	V	> Jockey Pump output.	-NA-	-NA-	-NA-
		Jockey Pump head.	-NA-	-NA-	-NA-
		Standby Pump output.	-NA-	-NA-	-NA-
ł	ł	> Standby Pump head.	-NA-	-NA-	-NA-
		Auto Starting/Manual Stopping		-NA-	-NA-
1	1	Pump house access.	-NA-	-NA-	-NA-
		Terrace Level	1600.0.0	1600 0 0 450	A/D
	-	Discharge of pump.	1620 & 2 x 450 LPM	1620 & 2 x 450 LPM	MR
		➢ Head of pump.	450. LPM 40m & 35m	40m & 35m	MR
		Power supply.Auto starting of pump.		Provided	MR
	1	Auto starting of pump.	Required	Provided	MR
	1 =	aptive water storage for fire fighting.	2.5-1	- I	
1	14 C	Underground tank capacity.	-NA-	-NA-	-NA-
		> Draw-off connection.	-NA-	-NA-	-NA-
		Fire Service Inlet	-NA-	-NA-	-NA-
		Access to tank.	-NA-	-NA-	MR
		 Overhead tank capacity. 	25,000 Ltr &	25,000 Ltr & 25,000 ltrs	IVIK
			15,000 ltrs	Provided	MR
		xit Signage.	Required	1101100	
	16 P	rovision of Lifts.	-NA-	-NA-	-NA-
		Pressurization of lift shaft.	-NA-	-NA-	-NA-
		 Pressurization of lift lobby. 	-NA-		
		 Communication in lift car. 	-11/1-	-NA-	-NA-



Fireman's switch.	Required	Provided	MR		
Lift signage.	Required	Provided	MR		
Standby Power Supply	Required	Provided (DG set)	MR		
Standby 10.000	y				
Refuge Area	-NA-	-NA-	-NA-		
• Location	-NA-	-NA-	-NA-		
Eiro Control Room.	,				
Detector system panel.	-NA-	-NA-	-NA-		
Flow switch panel.	-NA-	-NA-	-NA-		
PA system panel.	-NA-	-NA-	-NA-		
The state of the s	-NA-	-NA-	-NA-		
Battery backup.Building floor plan.	-NA-	-NA-	-NA-		
C . LEine Ductaction System for the	Building floor plan. Special Fire Protection System for the Protection of special Risk, if any. -NA- Special Fire Protection System for the Protection of special Risk, if any. -NA- Special Fire Protection System for the Protection of special Risk, if any.				

The Fire protection systems provided in the building were checked, tested at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/MS/DFS/School/2022/SZ/408 dated 12-04-2022 for Higher Sec. Block & F6/DFS/MS/School/2022/SZ/309 dated 23/03/2022 for primary Block renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

DO(SD)

17

a

IC C t

ıt 3

t