DI INGI II - I - XL



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



43

No. F6/DFS/MS/Petrol/SZ/2025/ 571

Dated: 24 /1 0 /2025

## FIRE SAFETY CERTIFICATE

Certified that the M/s BP Vasant Vihar Service Station (Retail Outlet of B.P.C.L. Petroleum Class A & B) located at Palam Road, Vasant Vihar, New Delhi - 110057, comprised of ground floor owned / occupied by Bharat Petroleum Corporation Limited was issued FSC vide letter No. F6/DFS/MS/Petrol/2022/SZ/36 dated 24/01/2022. The premise was re- inspected by the officer concerned of this department on 11/10/2025 in the presence of Mr. Sachin & Tarun and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Storage" (Petrol Pump and Service Station) with effect from 24/10/2025 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rule 2010 & also conditions printed bellow.

at New Delhi by.

Dy. Chief Fire Officer

## Copy to: -

Issued on

- 1. The Administrative Officer, (Factory Licence Dep.) South Zone, MCD, Green Park, New Delhi-
- 2. The Authorized Signatory, M/s BP Vasant Vihar located at Palam Road, Vasant Vihar, New Delhi-110057.

## Conditions for the validity of Fire Safety Certificate

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipment's and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the firefighting equipment's shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 6. This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

Vasant Vihar, New Delhi-110057.  Building is comprised of Ground floor only Type of occupancy Storage occupancy (Petrol Pump) Type of case Renewal Details of previous FSC F6/DFS/MS/Petrol/2022/SZ/36 dated 24/01/2022 Fire safety directives letter no. Nil Date of inspection 10.10.2025. Name of the inspecting officers Yashwant Singh Meena ADO (BCP) Name of the designation of officer from the building side Year of construction Nil Applicant's letter no. Email dated 24/09/2025 Minimum standard of fire prevention and fire safety U/R 33 Requirement site MR/NMR  Access to Building: A Road width Required 30 mtrs. MR B Gate width N/A N/A N/A N/A N/A C Width of internal road N/A N/A N/A N/A N/A Number, Width, Type and Arrangement of Exits:  A Number of staircases a Upper floor N/A N/A N/A N/A N/A B Width of staircases a Upper floor N/A N/A N/A N/A N/A C Protection of exits a Fire check door N/A N/A N/A N/A N/A C Protection of exits  a Fire check door N/A			INSPEC	CTION REPORT			
Building is comprised of   Ground floor only	01.	Nan	ne & address of the building				
Type of occupancy   Storage occupancy (Petrol Pump)	02.	Bui	lding is comprised of				
Type of case	03.						
Details of previous FSC	04.	1,500,500					
24/01/2022  Fire safety directives letter no.  Date of inspecting officers Name of the inspecting officers Name of the designation of officer from the building side  Year of construction Nil Applicant's letter no.  Minimum standard of fire prevention and fire safety U/R 33  Requirement  A Road width B Gate width N/A N/A N/A N/A Number, Width, Type and Arrangement of Exits:  A Number of staircases a Upper floor N/A N/A N/A N/A  B Width of staircases a Upper floor C Basement N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  B Width of corridor N/A N/A N/A N/A  C Protection of exits  a Fire check door N/A N/A N/A N/A  D No. of continuous staircases of the continuous staircases to terrace E Width of corridor N/A N/A N/A N/A  C Protection of exits  A Fire check door N/A N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A N/A  C Fire rating of shaft door D Water curtain N/A N/A N/A N/A  B Smoke Management System:  A Basement N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Smoke Management System:  A Basement N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A  B Sexpection N/A  B Sexpection N/A  B Sexpection N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A N/A  B Sexpection N/A N/A N/A N/A N/A N/A B Sexpection N/A N/A N/A N/A N/A N/A B Sexpe	05.			F6/DFS/MS/Petr	ol/2022/SZ/36 date	d	
Date of inspection   10.10.2025.			7	24/01/2022			
Date of inspection	06.	Fire	safety directives letter no.	Nil			
Name of the inspecting officers   Yashwant Singh Meena ADO (BCP)	07.			(SEV) 3390			
Name of the designation of officer from the building side  New Year of construction  Nil  Applicant's letter no.  Minimum standard of fire prevention and fire safety U/R 33  A Road width Required 30 mtrs.  A Road width N/A	08.	_		A 040-040-040-040-040-040-040-040-040-040	Meena ADO (BCP	)	
Nil Applicant's letter no. Email dated 24/09/2025  Minimum standard of fire prevention and fire safety U/R 33  A ccess to Building: A Road width Required 30 mtrs. MR B Gate width N/A N/A N/A N/A  Number, Width, Type and Arrangement of Exits:  A Number of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  C Basement N/A N/A N/A N/A  C Basement N/A N/A N/A N/A  C Broection of exits  a Fire check door N/A N/A N/A N/A  D No. of continuous N/A N/A N/A N/A  E Width of corridor N/A N/A N/A N/A  Compartmentation:  A Fire check door N/A N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A N/A N/A  B Sealement N/A N/A N/A N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A N/A N/A N/A  B Sealement N/A	09.	Nar	me of the designation of	A CONTRACTOR OF THE PARTY OF TH			
Minimum standard of fire prevention and fire safety U/R 33 Requirement site MR/NMR  Access to Building:  A Road width Required 30 mtrs. MR  B Gate width N/A N/A N/A N/A  Number, Width, Type and Arrangement of Exits:  A Number of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  C Basement N/A N/A N/A N/A N/A  C Protection of exits  a Fire check door N/A N/A N/A N/A  D No. of continuous N/A N/A N/A N/A  E Width of corridor N/A N/A N/A N/A  C Protection of exits  A Fire check door N/A N/A N/A N/A N/A  C Protection of exits  A Fire check door N/A	10.			Nil			
Minimum standard of fire prevention and fire safety U/R 33   Requirement   Requirement	11.	Apı	plicant's letter no.	Email dated 24/0	09/2025		
Access to Building:  A Road width Required 30 mtrs. MR B Gate width N/A N/A N/A N/A C Width of internal road N/A N/A N/A N/A  Number, Width, Type and Arrangement of Exits:  A Number of staircases  a Upper floor N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  C Basement N/A N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A N/A  C Basement N/A N/A N/A N/A  C Protection of exits  a Fire check door N/A N/A N/A N/A  D No. of continuous N/A N/A N/A N/A  E Width of corridor N/A N/A N/A N/A  Compartmentation:  A Fire check door N/A N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A N/A  D Water curtain N/A N/A N/A N/A  B Smoke Management System:  A Basement N/A N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR				Old NOC	Provided at	Remarks	
A   Road width   Required   30 mtrs.   MR     B   Gate width   N/A   N/A   N/A   N/A     C   Width of internal road   N/A   N/A   N/A   N/A     Number, Width, Type and Arrangement of Exits:    A   Number of staircases     a   Upper floor   N/A   N/A   N/A   N/A     C   Basement   N/A   N/A   N/A   N/A     C   Basement   N/A   N/A   N/A   N/A     C   Basement   N/A   N/A   N/A   N/A     C   Protection of exits     a   Fire check door   N/A   N/A   N/A   N/A     b   Pressurization   N/A   N/A   N/A   N/A     D   No. of continuous   N/A   N/A   N/A   N/A     staircases to terrace     E   Width of corridor   N/A   N/A   N/A   N/A     F   Door size   1.0 mtr.   1.0 mtr.   MR      S   Compartmentation:     A   Fire check door   N/A   N/A   N/A   N/A     C   Fire rating of shaft door   N/A   N/A   N/A   N/A     D   Water curtain   N/A   N/A   N/A   N/A     E   Fire dampers   N/A   N/A   N/A   N/A     B   Seasement   N/A   N/A   N/A   N/A     B   Seasement   N/A   N/A   N/A   N/A     B   Seasement   N/A   N/A   N/A     B   Upper floor   12 ACPH   Exhaust fan provided   MR	S.No	pr	evention and fire safety U/R 33	Requirement	site	MR/NMR	
A Road width Required 30 mtrs. MR B Gate width N/A N/A N/A N/A C Width of internal road N/A N/A N/A Number, Width, Type and Arrangement of Exits:  A Number of staircases  a Upper floor N/A N/A N/A N/A B Width of staircases  a Upper floor N/A N/A N/A N/A C Basement N/A N/A N/A N/A C Basement N/A N/A N/A N/A C Basement N/A N/A N/A N/A C Protection of exits  a Fire check door N/A N/A N/A N/A D No. of continuous N/A N/A N/A N/A F Door size 1.0 mtr. 1.0 mtr. MR  C Compartmentation:  A Fire check door N/A N/A N/A N/A F Door size 1.0 mtr. 1.0 mtr. MR  C Fire rating of shaft door N/A N/A N/A N/A D Water curtain N/A N/A N/A N/A N/A F Fire dampers N/A N/A N/A N/A N/A  Smoke Management System: A Basement N/A N/A N/A N/A N/A B Upper floor 12 ACPH Exhaust fan provided MR	01.	Ac	cess to Building:				
B Gate width N/A N/A N/A N/A C Width of internal road N/A N/A N/A Number, Width, Type and Arrangement of Exits:  A Number of staircases  a Upper floor N/A N/A N/A N/A C Basement N/A N/A N/A N/A B Width of staircases  a Upper floor N/A N/A N/A N/A C Basement N/A N/A N/A N/A C Basement N/A N/A N/A N/A C Brotection of exits  a Fire check door N/A N/A N/A N/A D No. of continuous N/A N/A N/A N/A F Door size 1.0 mtr. 1.0 mtr. MR  C C Fire rating of shaft door N/A N/A N/A N/A D Water curtain N/A N/A N/A N/A E Fire dampers N/A N/A N/A N/A  Smoke Management System: A Basement N/A N/A N/A N/A N/A B Upper floor 12 ACPH Exhaust fan provided MR	V-1	200		Required	30 mtrs.	MR	
C   Width of internal road   N/A   N/A   N/A		J. E. S.	ACCORDANCE NO CONTRACTOR		N/A	N/A	
A Number of staircases  a Upper floor N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A  B Width of staircases  a Upper floor N/A N/A N/A  C Basement N/A N/A N/A N/A  C Brotection of exits  a Fire check door N/A N/A N/A N/A  b Pressurization N/A N/A N/A N/A  D No. of continuous N/A N/A N/A N/A  E Width of corridor N/A N/A N/A N/A  C Compartmentation:  A Fire check door N/A N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A N/A  B Smoke Management System:  A Basement N/A N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR				N/A	N/A	N/A	
A   Number of staircases	02.	C Wilding of Michigan Cond					
C   Basement   N/A   N/A   N/A     B   Width of staircases     a   Upper floor   N/A   N/A   N/A     C   Basement   N/A   N/A   N/A     C   Protection of exits     a   Fire check door   N/A   N/A   N/A     b   Pressurization   N/A   N/A   N/A     D   No. of continuous   N/A   N/A   N/A     staircases to terrace     E   Width of corridor   N/A   N/A   N/A     F   Door size   1.0 mtr.   1.0 mtr.   MR      3.   Compartmentation:     A   Fire check door   N/A   N/A   N/A     B   Sealing of electrical shafts   N/A   N/A   N/A     C   Fire rating of shaft door   N/A   N/A   N/A     D   Water curtain   N/A   N/A   N/A     E   Fire dampers   N/A   N/A   N/A     A   Smoke Management System:     A   Basement   N/A   N/A   N/A     B   Upper floor   12 ACPH   Exhaust fan provided   MR							
B Width of staircases  a Upper floor N/A N/A N/A  C Basement N/A N/A N/A  C Protection of exits  a Fire check door N/A N/A N/A  b Pressurization N/A N/A N/A  D No. of continuous staircases to terrace  E Width of corridor N/A N/A N/A  F Door size 1.0 mtr. 1.0 mtr. MR  C Compartmentation:  A Fire check door N/A N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A N/A  D Water curtain N/A N/A N/A N/A  E Fire dampers N/A N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR			a Upper floor	N/A	N/A	58.50 200145	
a Upper floor N/A N/A N/A C Basement N/A N/A N/A  C Protection of exits  a Fire check door N/A N/A N/A  b Pressurization N/A N/A N/A  D No. of continuous N/A N/A N/A  F Door size 1.0 mtr. 1.0 mtr. MR  C C Fire rating of shaft door N/A N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A  C Fire dampers N/A N/A N/A N/A  B Smoke Management System:  A Basement N/A N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR			C Basement	N/A	N/A	N/A	
C   Basement   N/A   N/A   N/A		В	Width of staircases	4			
C Protection of exits  a Fire check door N/A N/A N/A  b Pressurization N/A N/A N/A  D No. of continuous N/A N/A N/A  E Fire check door N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A  D Water curtain N/A N/A N/A  E Fire dampers N/A N/A N/A  B Basement N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR			a Upper floor	N/A		W. 1003-Col-80	
a   Fire check door			C Basement	N/A	N/A	N/A	
b   Pressurization   N/A   N/A   N/A     D   No. of continuous   staircases to terrace     E   Width of corridor   N/A   N/A     F   Door size   1.0 mtr.   1.0 mtr.   MR     Sealing of electrical shafts   N/A   N/A   N/A     C   Fire rating of shaft door   N/A   N/A   N/A     D   Water curtain   N/A   N/A   N/A     E   Fire dampers   N/A   N/A   N/A     A   Basement   System:     A   Basement   N/A   N/A   N/A     B   Upper floor   12 ACPH   Exhaust fan provided   MR     C   Fire rating of shaft   N/A   N/A   N/A     C   Fire rating of shaft door   N/A   N/A   N/A     D   Water curtain   N/A   N/A   N/A   N/A     D   Water curtain   N/A   N/A   N/A   N/A     E   Fire dampers   N/A   N/A   N/A   N/A     E   Fire dampers   N/A   N/A   N/A   N/A     E   Fire dampers   N/A   N/A   N/A   N/A   N/A     E   Fire dampers   N/A   N/A   N/A   N/A   N/A   N/A     E   Fire dampers   N/A		C				7.77	
D   No. of continuous staircases to terrace   E   Width of corridor   N/A			18.15.15.15.15.15.15.15.15.15.15.15.15.15.			Contract Con	
staircases to terrace  E Width of corridor N/A N/A N/A  F Door size 1.0 mtr. 1.0 mtr. MR  Compartmentation:  A Fire check door N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A  D Water curtain N/A N/A N/A  F Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR				7457(0)/\$0 CO			
E Width of corridor N/A N/A N/A F Door size 1.0 mtr. 1.0 mtr. MR  Compartmentation:  A Fire check door N/A N/A N/A B Sealing of electrical shafts N/A N/A N/A C Fire rating of shaft door N/A N/A N/A D Water curtain N/A N/A N/A N/A E Fire dampers N/A N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A N/A B Upper floor 12 ACPH Exhaust fan provided MR		D		N/A	N/A	N/A	
F Door size 1.0 mtr. 1.0 mtr. MR  Compartmentation:  A Fire check door N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A  D Water curtain N/A N/A N/A  F Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR		_	The state of the s	N/A	N/A	N/A	
3. Compartmentation:  A Fire check door N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A  D Water curtain N/A N/A N/A  F Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR		10000		Company of the Compan	COOLERCOCT (**)	250000000000000000000000000000000000000	
A Fire check door N/A N/A N/A  B Sealing of electrical shafts N/A N/A N/A  C Fire rating of shaft door N/A N/A N/A  D Water curtain N/A N/A N/A  E Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR	03.	2001		1.0 ma.	1.0 ma.		
B Sealing of electrical shafts N/A N/A N/A C Fire rating of shaft door N/A N/A N/A D Water curtain N/A N/A N/A E Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A B Upper floor 12 ACPH Exhaust fan provided MR				N/A	N/A	N/A	
C Fire rating of shaft door N/A N/A N/A  D Water curtain N/A N/A N/A  E Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR			ADDRESS STATE RODGE CONTROLS		5.5.5.5		
D Water curtain N/A N/A N/A E Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR				(A COMPA-42)	2 30000	The Walter	
E Fire dampers N/A N/A N/A  Smoke Management System:  A Basement N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR			(50)				
4. Smoke Management System:  A Basement N/A N/A N/A  B Upper floor 12 ACPH Exhaust fan provided MR	- 1		100,3003				
A Basement N/A N/A N/A B Upper floor 12 ACPH Exhaust fan provided MR	04.	0000011	The transfer of the contract o	1 1/2 1	1,1/1	11//1	
B Upper floor 12 ACPH Exhaust fan provided MR	04.			N/A	N/A	N/A	
- 11						N. 907900	
Fire Extinguisher:		1 , 3rd		12 ACI II	- In the second second	1	
The state of the s		Fire	Extinguisher:				

(5)	A	Total numbers	05 nos.	Provided	MR
	В	Types	ABC/CO <sub>2</sub> /DCP	Provided	MR
	C	ISI marking	ISI Marked	Provided	MR

06.	Fi	rst-Aid-Hose Reel:	H122		
	A Total numbers of each floor		N/A	N/A	N/A
	В	Length of hose reel hose	N/A	N/A	N/A
	C	Nozzle diameter	N/A	N/A	N/A
07.	Au	tomatic Fire Detection and Alarming		T 27/4 T	
	A	Type of detectors	N/A	N/A	N/A
	В	Location of main panel	N/A N/A	N/A	N/A
	C	Location of repeater panel	N/A	N/A	N/A
	D	Alternate source of power	N/A	N/A	N/A
	E	Hooters	N/A	N/A	N/A
08.		OEFA:	N/A	N/A	N/A
09		blic Address System:	N/A	N/A	N/A
10.	_	tomatic Sprinkler System:	NI/A		
	A	Basement	N/A	N/A	N/A
	B	Upper floor	N/A	N/A	N/A
	C	Sprinkler above false ceiling	N/A	N/A	N/A
11.		ternal Hydrants:	777.		
	A	Size of riser/down-comer	N/A	N/A	N/A
	B	Number of hydrants per floor	N/A	N/A	N/A
	C	Hose box	N/A	N/A	N/A
12.	_	rd Hydrants:	ADMINI III		
	A	Total number of hydrants	N/A	N/A	N/A
V-m	В	Hose box	N/A	N/A	N/A
13.		mping Arrangements:			
l	G	round level	E.		
	A	Discharge of main pump	N/A	N/A	N/A
	В	Head of main pump	N/A	N/A	N/A
	C	Number of main pumps	N/A	N/A	N/A
	D	Jockey pump out put	N/A	N/A	N/A
	E	Jockey pump head	N/A	N/A	N/A
	F	Standby pump out put	N/A	N/A	N/A
	G	Standby pump head	N/A	N/A	N/A
1	Н	Auto starting /manual stopping	N/A	N/A	N/A
ŀ	I	Pump house access	N/A	N/A	ACCESS-0000000
		race Level	1071	IN/A	N/A
	A	Discharge of pump	N/A	N/A	N/A
	В	Head of the pump	N/A	N/A	N/A N/A
	C	Power supply	N/A	N/A	N/A
	D	Auto starting of pump	N/A	N/A	N/A
1.	Car	ntive Water Starage for Fire File		- 1/ A/A	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	A	Underground tank capacity		27/4	NT/A
	В	Draw-off connection	N/A	N/A	N/A
-	C	Fire service inlet	N/A	N/A	N/A
-	D	Access to tank	N/A N/A	N/A N/A	N/A
-	E	Overhead tank capacity	N/A N/A	N/A N/A	N/A

H123

<i>M/s</i> 15.	No	Vasant Vihar located at Palam Road, Vasant Vi Smoking Signage (Hindi & English)	Required	Provided (Hindi & English)	MR
16.	Provision of Lifts:				
10.	A	Pressurization of lift shaft	N/A	N/A	N/A
	В	Pressurization of lift lobby	N/A	N/A	N/A N/A
	C	Communication in lift car	N/A	N/A	N/A
	D	Firemen's grounding switch	N/A	N/A	N/A
	100		N/A	N/A	
	E	Lift signage	NA	N/A	N/A
17.	. Standby Power Supply:				
18.	Re	fuge Area:	N/A	N/A	N/A
	A	Total area	N/A	N/A	N/A
	В	Location	14/21		
19.	Fir	e Control Room:	NI/A	N/A	N/A
	A	Detector system panel	N/A	N/A	N/A
	В	Flow switch panel	N/A	N/A	N/A
	C	PA system panel	N/A	N/A	N/A
	D	Battery backup	N/A	N/A	N/A
		Building floor plans	N/A		N/A
20	E	ecial Fire Protection systems for	NA	N/A	11/11
20.	Sp	otection of special Risks, if any:  The fire protection system was rando		1 and tosted and	was

The fire protection system was randomly checked and tested and

Keeping in view of the deemed compliance of minimum standards on fire functional at the time of inspection. prevention and fire safety measures as required under the Rules, renewal of the FSC issued vide letter No. F6/DFS/MS/Petrol/2022/SZ/36 dated 24/01/2022, under rules 37 of the Delhi

Fire Service Rules, 2010 is recommended.

Signature of the Inspecting Officer Name: - Yashwant Singh Meena

Designation: - ADO/BCP