GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No.F.6/DFS/MS/GH/2025/SZ/ 47-0

Dated: 08/08/2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Cabana Guest House at 2313, Laxmi Narayan Street, Chuna Mandi, Pahar Ganj, New Delhi, comprised of basement (storage), stilt (parking), ground floor (reception & 03 guest rooms), 1st & 2nd floor each having 05 guest rooms, 3rd floor having 04 guest rooms (total 17 guest rooms only), was issued FSC by this department vide letter No. F.6/DFS/MS/GH/2022/378 dated 04.08.2022. The premises was re-inspected by the officer concerned of this department on dated 29.07.2025 in the presence of Manager, and found that the guest house have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class "Residential" (Guest house) (17 guest rooms up-to 3rdfloor) w.e.f. 08 08 2025 for a period of three years, in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below. Issued on O8 08 2025 at New Delhi.

> (Virendra Singh) Chief Fire Officer Delhi Fire Service

Copy to: -

The Commissioner, MCD, Delhi: with a requestto ensure the occupancy as detailed above and deviation, fany. Online application Id 2025071411344 dated 15.07.2025.

The Executive Engineer (Bldg.), MCD, Civic Centre, New Delhi.

: - for information regarding use of basement.

Conditions for the validity of fire safety certificate: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

4. The trained staff should be available round the clock.

- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

7. Basement shall be used as per the BBL/UBBL. Presently basement used for storage only

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

M/s. Cabana Guest House at 2313, Laxmi Narayan Street,

Chauna Mandi, Pahar Ganj, New Delhi.

2. Building is comprised of

Basement (storage), stilt (parking) ground floor (reception & 03 guest rooms), 1st & 2nd floor (05 guest rooms at each floor) & 3rd

floor having 04 guest rooms (total 17 guest rooms only)

3. Type of Occupancy

Residential (Guest House)

4. Type of Case

Renewal

5. Details of Previous FSC letter

F.6/DFS/MS/GH/2022/378 dated 04.08.2022

6. Fire Safety direction letter No

N/A

:

:

7. Date of Inspection

29.07.2025

8. Name of the Inspecting officers

ADO R.K. Yadav (JKP)

9. Name and designation of officer

from the building side

Manager

10. Year of construction

2008

:

Sr.No.	Minimum Standards on Fire Prevention and Fire Safety U/R33	Requirementas per UBBL/NBC-2016	Provided at Site	Remarks MR/NMR		
1	Access to Building.	N	= =			
	 Road width 	N/A	6.0 m	N/A		
	 Gate width 	N/A	N/A	N/A		
	 Width of internal road 	N/A	N/A	N/A		
2	Number, Width, Type and Arrang	ement of Exits.				
	a. Number of Staircases					
	Upper floor	01 Nos.	01 Nos.	MR		
,	Basement	01 Nos.	01 Nos.	MR		
	B. Width of Staircases		7.7.100	IVIIC		
	Upper floor	0.80 m. old case	1.45 to 1.50 m	MR		
	Basement	1.0 m. old case	and a series of the series of			
	c. Protection of Exits	1.0 m. old case	1.45 to 1.50 m	MR		
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	d. No. of Continuous Staircases to	01 nos	Provided	MR		
	Terrace	3.100	Tiovided	MIK		
	e. Width of Corridor	N/A	N/A	N/A		
	f. Door Size	N/A	206 cms × 80 cms	N/A		
3	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	 Fire rating of shaft door 	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	Fire dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basement	30 ACPH	Exhaust fan provided) (D		
	Upper floor	12 ACPH	Natural Ventilation	MR MR		
5.	Fire Extinguishers.					
	Total numbers	12 nos.	Provided	MR		
	Types .	ABC /CO ₂	Provided	MR		
	 IS marking 	ISI marked	Provided	MR		

06	First-Aid-Hose Reels.				
	Total numbers on each floor				
	• Length of here	01 No	Provided		
	 Length of hose reel hose Nozzle diameter 	30 m	Provided	MR	
0.5		05 mm	Provided	MR	
07	Automatic Fire Detection, CO detec	ction and Alarmir	19 System	MR	
	 CO Type of detectors 				
	• Location of main panel	N/A N/A	N/A	N/A	
	• Location of repeater panel	N/A	N/A	N/A	
	Alternate source of power	N/A	N/A	N/A	
	Hooter's location	N/A	N/A	N/A	
08	MOEFA		N/A	N/A	
09		Required	Provided	MR	
10	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.		100.00	IVIK	
	Basement Stilt	N/A	N/A		
	• upper floor	N/A	N/A N/A	N/A	
	 sprinkler above false ceiling 	N/A	N/A	N/A	
11	Internal Hydrants			N/A	
	size of riser/down-comer				
	Number of hydrants per floor	N/A	N/A	N/A	
	Hose box	N/A	N/A	N/A	
12	Yard Hydrants.	N/A	N/A	N/A	
		Les d'Artes			
	Total number of hydrants	N/A	N/A	N/A	
	Hose box	N/A	N/A	N/A N/A	
13	Pumping Arrangements.				
	➢ Ground Level		An increased paint of the	/	
	Discharge of main pump		soul established		
	Head of main pump	N/A	N/A	NT/A	
	Number of main pumps	N/A	N/A	N/A N/A	
	Jockey pump out put	N/A	N/A	N/A	
	Jockey pump head	N/A	N/A	N/A	
	Standby pump out put	N/A	N/A	N/A	
	Standby pump headAuto starting /manual	N/A N/A	N/A	N/A	
	stopping	N/A	N/A N/A	N/A	
	Pump house access		IVA	N/A	
	> Terrace Level				
	Discharge of pump	450 LPM	450 LPM	MR	
	Head of the pump	40 m	40 m	MR	
	Power supply Auto Starting of pump	Required Required	Provided Provided	MR	
	Auto Starting of pump	Required	Provided	MR	
1	Captive Water Storage for Fire Fighting.				
	Underground tank capacity	N/A	N/A	N/A	
	Draw-off connection	N/A	N/A	N/A	
	Fire service inlet	N/A	Provided	N/A	
	Access to tank	N/A	N/A	N/A	
	Overhead Tank capacity	5,000 ltrs	5,000 ltrs	MR	

	sion of Lifts. Pressurization of Lift Shaft	N/A	N/A		
1.	Pressurization of Lift lobby Communication in lift car Firemen's grounding switch	N/A	N/A	N/A	
•		Required	Provided	N/A	
•		Required	Provided	MR	
•		Required	Provided	MR	
	Lift Signage		TOVICO	MR	
Stand	by power supply	Required	Provided	MR	
Refu	ge Area.		_ 11 11		
	Total area	N/A	N/A	N/A	
•	The second of th	N/A	N/A	N/A	
•	Location				
Fire	Fire Control Room				
	D. t. ster system nanel	N/A	N/A	N/A	
	Detector system panel	N/A	N/A	N/A	
	Flow switch panel	N/A	N/A	N/A	
•			N/A	N/A	
•	PA system panel	N/A		AT/A	
	D. II Lealon	N/A N/A	N/A	N/A	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: - As per affidavit submitted by guest house management (placed at C-101) that the building comprised of basement, stilt, ground plus three upper floors, using basement as storage, stilt as parking, ground floor (reception & 03 guest rooms), 1st & 2nd floor each having 05 guest rooms, 3rd floor having 04 guest rooms (total 17 guest rooms only).

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F.6/DFS/MS/GH/2022/378 dated 04.08.2022, renewal under rule 37, of the Delhi Fire Service Rules 2010, is recommended.

Signature of Inspecting Offi

Name: -R.K. Yadav

Designation: - ADO (JKP)