GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/NDZ/2025/35

Dated: 17./.91./2025

ire Service

FIRE SAFETY CERTIFICATE

Certified that the Capital Residency located at 22, Main Bazar, Pahar Ganj, New Delhi comprised of Ground + 02 Upper floors, Ground floor (Commercial shop), 1st floor (08 guest rooms + reception + 01 store), 2nd floor (04 guest rooms), total 12 guest rooms owned/occupied by by this department vide letter Hotel Capital Residency was earlier granted FSC No.F6/DFS/MS/GH/NDZ/2022/89 dated 09/02/2022. Now, the premises was re-inspected by the officer concerned of this department on 06/01/25 in the presence of Mr. Nagendar and found that the said guest house building has deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 1st floor (08 guest rooms + reception), 2nd floor (04 guest rooms) 12 guest rooms only up to Second floor, with effect from ...1.7.1 cal. 2025. and valid up to three year from the date of issue in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 17/01/2025 at New Delhi by.

Copy to:-

1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above.

2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID no. 2024122818484 dated 28.12.2024.

3. The Manager, Capital Residency at 22, Main Bazar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house ground to second floor only.

Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

 The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 9. Any flammable material for interior decoration is prohibited.

N. 26

INSPECTION REPORT

1. Name & address of the building:- Hotel Capital Residency at 22, Main Bazar,

Pahar Ganj, New Delhi 2. Type of occupancy:-

Residential, Sub Division-A-1 Gr. + 02 Upper floors (total 12 Guest rooms)

Ground floor (Commercial shop), 1st floor (08 guest rooms + reception + 01 store), 2nd floor (04 guest rooms)

3. Type of case:-Renewal

4. Details of previous FSC:-No.F6/DFS/MS/GH/NDZ/2022/89 dated

09/02/2022. 5. Fire safety directives No.-

N/A 6. Date of inspection:-06/01/25

7. Name of the inspecting officer:-Sh. Suman Kumar (ADO)

8. Name & designation of officer From the building side:-

Mr. Nagendar 9. Year of construction:-2007

10 Applicant's letter N

S.No.	Minimum Standard C	Decrisoment	Provided at site	Old Case Remarks	
	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing fire safety arrangements	Provided at site	MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arr	angement of E	exits		
	A. Number of staircases		_		
	1. Upper floors	01 No.	01 No.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase				
	1. Upper floors	0.80 mtr.	0.90 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1 mtr.	1 mtr.	MR	
3.	Compartmentation				
*	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System				
	1) Basements	N/A	N/A	N/A	
	2) Upper floors	12 ACPH	Natural/exhaust fan	MR	
5.	Fire Extinguishers	V2	S S S S S S S S S S S S S S S S S S S		

		I OC NICE	100
	7/3/2000 CO		MR
			MR
	Required	Provided	MR
1) Total number of eachfloor	01		MR
2) Length of hose reel hose	30 m	30 m	MR
3) Nozzle diameter	05 mm	05 mm	MR
Automatic Fire Detection &	l.		
1) Type of detectors CO	Required	Provided	MR
2) Location of main panel	Gr. floor	Provided	MR
3) Location of repeater panel	N/A	N/A	N/A
	Required	Provided	MR
5) Hooter's Location	Gr. floor	Provided	MR
MOEFA	N/A		N/A
Public Address System	THE STATE OF THE S	0.000,000,000,000	N/A
			1
1) Basement	N/A	N/A	N/A
2) Upper floors		Philipped Coupers	N/A
			N/A
ceiling		- 11.0	LNZA
	N/A	N/A	N/A
			N/A
floor	-3/-2	17/21	IVA
3) Hose box	N/A	N/A	N/A
Yard Hydrants		23/22	14/21
	N/A	N/A	N/A
2) Hose box			N/A
Pumping Arrangement		- 112	14/21
1) Ground level	N/A	N/A	N/A
a) Discharge of main		10 (A 14 (A 16 (A 17 (A 17 A 17 A 17 A 17 A 17 A 17 A	N/A
pump	5000 8100 1000		I'VA
b) Head of main pump	N/A	N/A	N/A
			N/A
d) Jockey pump out put	N/A	The state of the s	N/A
e) Jockey pump head	N/A		N/A
 f) Stand by pump output 	N/A		N/A
g) Stand by pump head	N/A	N/A	N/A
h) Auto starting/Manual	N/A	N/A	N/A
stopping		l l	-
	E		
	180 LPM	180 LPM /	MR
	30 mtr	30 mtr	MR
		Provided	MR
a) Auto starting of pump	Required .	Provided	MR
Captive Water Storage for Fi	re Fighting		
	((,		
	2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors CO 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Yard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	2) Types Required First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter 05 mm Automatic Fire Detection & Alarming Syst 1) Type of detectors CO 2) Location of main panel Gr. floor 3) Location of repeater panel N/A 4) Alternate source of power S Hooter's Location Gr. floor MOEFA N/A Public Address System N/A Automatic Sprinkler System 1) Basement N/A 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer N/A 2) Number of hydrants per floor 3) Hose box N/A Yard Hydrants 1) Total number of hydrants N/A 2) Hose box N/A Pumping Arrangement 1) Ground level N/A a) Discharge of main pump N/A b) Head of main pump N/A c) Number of main pump N/A d) Jockey pump head N/A f) Stand by pump output e) Jockey pump head f) Stand by pump head N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply Required	2) Types

		- 60		
	Under ground tank capacity	N/A	. N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2,500 ltr.	2,500 ltr. /	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
10.	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
15.	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	NA		

The fire protection systems provided in the guest house building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed we may renew the FSC issued vide letter No. No.F6/DFS/MS/GH/NDZ/2022/89 dated 09/02/2022, renewal under rule 35 of the Delhi Fire Service rules 2010, Accordingly, DFA is put up for kind perusal and signature please.

Signature of the Inspecting Officer

Name: - Suman Kumar Designation: - ADO