

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS : DELHI FIRE SERVICE, NEW DELHI – 110001

No: F6/DFS/MS/BNQT/WZ/2025/ 29

Dated: 02 /0 5 /2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Clay One Sapphire located at A-10, GF, Kailash Park, Moti Nagar, Delhi - 110015, comprised of Ground + 02 upper floors but restaurant is running at ground floor only was granted FSC by this department vide letter no. F6/DFS/MS/WZ/EH/2022/BNQT/31 dated 23.06.2022. Now, the building/premises was re-inspected by the officer concerned of this department on 24.04.2025 in presence of Mr. Ankit (Manager) and observed that the premises /building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010. Accordingly, the premises is fit for occupancy class (Group D) "Assembly Building", (ground floor only), with effect from .0.2 / 05 /2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire Service Rules, 2010 printed below.

Issued on ...02 05 2025 at New Delhi by

Delhi Fire Service Tel: 011-23414000

Copy to:-

- 1. The Joint Commissioner of Police (Licensing), 1st Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2025040906008 dated 09.04.2025.
- 2. The DHO, Karol Bagh Zone, MCD, Anand Parbat, New Delhi 110005.
- 3. The Licensee, M/s Clay One Sapphire at A-10, GF, Kailash Park, Moti Nagar, Delhi 110015.

Conditions for the validity of fire safety certificate

- This FSC is valid for ground floor only.
- All the fire safety arrangements provided therein shall be maintained in good working condition at all 1. 2.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the 3. management.
- The trained fire fighting staff should be available round the clock. 4.
- Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority. 5.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if 6.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of 7. Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

T		INSPE	ECTION REPORT			
1	N	Name & address of the building M/s Clay One Sapphire at A-10, GF, Kailash				
2	Bı	uilding is comprised of	Park, Moti Nagar	, New Delhi - 110015	•	
	Prised of		Ground + 02 upper floor			
3	Ty	pe of occupancy	(Restaurant is running at ground floor only)			
4	Ty	vpe of case	Assembly Renewal			
5		etails of previous FSC				
	or previous FSC		F6/DFS/MS/WZ/EH/2022/BNQT/31 dated			
6	Fi	re safety direction letter no.	23.06.2022			
7	Da	ate of inspection	Nil			
8	No	ame of the inspection of	24.04.2025			
9	Name of the inspecting officers		ADO (SPM)			
	fre	ame of the designation of officer	Mr. Ankit (Manager)			
10	from the building side Year of construction					
11	_		2015			
4.4	A	oplicant's letter no.	1	n ID No. 20250409	06008 date	
O Nr	-		09.04.2025			
S.N	M	inimum Standards on fire	Requirements as	Provided at Site	Remarks	
0	Pr	evention and fire safety	per Rule 35 (6)		MR/	
	-	quirements U/R 33	of DFS Act-2007		NMR	
1		ccess To Building:				
		oad width	09 mtrs.	Provided	MR	
		ate width	05 mtrs.	Directly accessible	MR	
		idth of internal road	NA	NA	NA	
2	Number, Width, Type and Arrang		gement of Exits:			
	A	Number of staircases				
		a Upper floor	NA	Running at GF	NA	
		b Basement	NA	NA	NA	
	В	Width of staircases				
		a Upper floor	NA	Running at GF	NA	
		b Basement	NA	NA	NA	
	C	Protection of exits	¥			
		a Fire check door	NA	NA	NA	
	D	b Pressurization No. of continuous staircases	NA	NA	NA	
	ע	to terrace	NA	NA	NA	
1	E	Width of corridor	NA			
ŀ	F	Door size		NA	NA	
	-	mpartmentation:	2.0 m & 1.0 m	Provided	MR	
\dashv						
-	A B	Fire check door	NA	NA	NA	
-		Sealing of electrical shafts	NA	NA	NA	
-	C	Fire rating of shaft door	NA	NA	NA	
-	D	Water curtain	NA	NA	NA	
ı	E	Fire dampers	NA	NA	NA	
	5m	oke Management System:			- 14 1	
	A B	Upper floors Basements	12 ACPH	Provided	MR	

5.	Fire	Extinguisher:		D '1-1	MR
	A	Total numbers	04 nos.	Provided Provided	MR
	В	Types	ABC& Co2	Provided	MR
	C	ISI marking	Required	Provided	MR
6	First-	Aid-Hose Reels:		Provided	MR
	A	Total numbers on each floor	01 no.		
	В	Length of hose reel hose	30 mtr.	Provided	MR
	C	Nozzle diameter	05 mm	Provided	MR
7	Autom	atic Fire Detection And Alan	rming System:	T N T A	NA
	A	Type of detectors	NA	NA	NA NA
1	В	Location of main panel	NA	NA NA	NA NA
t	C	Location of repeater	NA	NA	1474
		panel	NA	NA	NA
	D	Alternate source of power	NA NA	NA	NA
_	E	Hooters Location	Required	Provided	MR
- 1	MOEFA		NA	NA	NA
	Public A	Address System:	IVA		1
) .	Automa	tic Sprinkler System:	LNIA	NA	NA
1	A	Basement	NA	Provided	NA
]	В	Upper floors	NA		NA
	C	Sprinkler above false	NA	NA	
	-	ceiling			
I	nternal	Hydrants:		Provided	MR
	4	size of riser/down-comer	100 mm	Provided	MR
F		Number of hydrants per	01 no.	Provided	1,11
-		floor	0.1	Provided	MR
(C	Hose box	01 no.	Tiovided	
. 3	ard Hy	drants:		1274	NA
A		Total number of hydrants	NA	NA	
F		Hose box	NA	NA	NA
-		Arrangements:			
_		Ground level			
A	Y	Ground level			
a	ı)	Discharge of main pump	NA	NA	NA
))	Head of main pump	NA	NA	NA
-	;)	Number of main pumps	NA	NA	NA
_	i)	Jockey pump out put	NA	NA	NA
_	e)	Jockey pump head	NA	NA	NA
1	f)	Standby pump out put	NA	NA NA	NA
-	g)	Standby pump head	NA	NA	NA
i	h)	Auto starting /manual	NA	NA	NA
		stopping			
	i	Pump House Access	NA	NA	NA
H	В	Terrace level	,		
	a)	Discharge of pump	450 LPM	Provided	MR
-	b)	Head of the pump	40 m	Provided	MR
	c)	Power supply	Required	Provided	MR
-	d)	Auto starting of pump			

14	Ca	Captive Water Storage For Fire Fighting:					
	A	Underground tank capacity	NA	NIA	1		
	B	Draw-off connection	NA	NA NA	NA		
	C	Fire service inlet	Required	Provided	NA		
	D	Access to tank	NA	NA	MR		
	E	Overhead tank capacity	10,000 ltrs.	Provided	NA		
15	Ex	it Signage:	Required		MR		
16	Provision of Lifts:		Provided	MR			
	A	Pressurization of lift shaft	NA	T > 7.6			
	В	Pressurization of lift lobby	NA NA	NA	NA		
	C	Communication in lift car	NA	NA NA	NA		
	D	Firemen's grounding switch	NA NA		NA		
	E	Lift signage		NA	NA		
17		andby Power Supply:	NA	NA	NA		
18			Required	Provided	MR		
10	Refuge Area:						
	A	Total area	NA	NA	NA		
	B	Location	NA	NA	NA		
19	Fire Control Room:						
	A	Detector system panel	NA	NA	NA		
	В	Flow switch panel	NA-	NA	NA		
	C	Pa system panel	NA	NA	NA		
	D	Battery backup	NA	NA	NA		
	E	Building floor plans	NA	NA	NA		
20		ecial Fire Protection Systems F	ABC type fire	MR			
	Sp	ecial Risks, If Any:	extinguishers				
				provided near			
	Į		electric panel				

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter no. F6/DFS/MS/WZ/EH/2022/BNQT/31 dated 23.06.2022 is recommended to be renewed (ground floor only), under Rule 35 of the Delhi Fire Service Rules 2010.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name Sumit Kumar Designation ADO (SPM)

Dy. CFO (WZ)

28 Jul Bos

Director Milarla (

Aufsm