

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/School/2025/SZ/ 分子の

Dated: 20/03/2025

## **FIRE SAFETY CERTIFICATE**

Certified that the Delhi Public School located at East of Kailash, New Delhi -110065 comprised of 04 interconnected Blocks, A & C Blocks- Ground plus One upper Floors, B & D Blocks- Ground Plus Two Upper Floors owned/occupied by Delhi Public School was issued FSC by this department vide letter No. F6/DFS/MS/School/2022/SZ/395 dated 07/04/2022. The premises was re-inspected by officer concerned of this department on 12/03/2025 in presence of Mr. Sanjay Singh and observed that the said School building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "Educational Building" Group-B, (School) with effect from  $\frac{20}{03}/2025$  for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions, under rule 38 of the Delhi Fire Service Rules, 2010 

> (ATVL GARG) DIRECTOR DELHI FIRE SERVICE

Copy to: -

1. The Principal, Delhi Public School located at East of Kailash, New Delhi -110065

2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-54

## Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

 All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

- 4. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

NIG



1	INSPECTION REPORT					
•	Name & Address of the Building	Delhi Public School, East of Kailash, New Delhi-				
		110065				
2	Type of Occupancy	- Comp R (School)				
3	Building Comprised of	Calcal has Four Ruilding Blocks interconnected at 1				
	- Comprised of	Floor through corri	dor. Block A & C : G+	1, Block, B &		
	· · · · · · · · · · · · · · · · · · ·	D : G+2	contact compactor of			
4	Type of Case	Denewal				
5	Details of Previous NOC	F6/DFS/MS/School/2022/SZ/395 dated 07/04/2022				
6	Fire Safety Directives Letter No	Nil				
7	Date of Inspection	12/03/2025				
8	Name of the Inspecting Officers	Sh. Rajesh Kumar, ADO (BCP)				
9	Traile & Designation of Officers	Mr. Sanjay Singh				
	Hom the building side	Ivii. Gailay Gillga				
10	Year of construction	1980				
11	Applicant letter No.	DPSR/DFS/FF/NO	C/3-25 dated 19/02/202	25		
S. No.	Minimum standards on Fire Prevention	Old NOC Provided at Site Remarks				
	and Fire Safety U/R 33	Requirement		MR/NMR		
1	Access to Building.	Attequir carone	DATE TO THE			
1	Road width	Required	Approachable	MR		
	Gate width	Required	4.75m, 2.60m & 2.10m	MR		
	and a control of the	-NA-	-NA-	-NA-		
2	Width of internal road		-NA-	-14/4		
	Number, width, type & arrangement of	exits.				
	a) Number of Staircase		n le real I I I	2025 Remarks MR/NMR  MR -NA-		
	Upper floors.	01 Nos each	Total 04 Nos			
	➤ Basement floor.	-NA-	-NA-	-NA-		
	b) Width of Staircase			Y '		
	➤ Upper floors	1.5 mtr	1.44m, 1.35m, 1.30m	The second second second		
	➤ Basement floor	ille dire	& 0.80m	(old case)		
		-NA-	-NA-	-NA-		
	c) Protection of exits					
	➤ Fire check door	-NA-	-NA-	-NA-		
	> Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace	01 No	03 Provided			
	e) Width of corridor	1.5m	Provided			
	f) Door size	1 mtr	Provided			
3	Compartmentation.	ment of the Association	ATOTIGOG	IVIK		
	Fire check door.	-NA-	-NA-	NIA		
	Sealing of electrical shafts.	-NA-	-NA-			
	Fire rating of shaft door.	-NA-	-NA-			
	Water curtain	-NA-	-NA-			
	Fire dampers.	-NA-		U. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.		
4	Smoke Management system.	TIME	-NA-	-NA-		
18.0%	Basement	30 ACPH				
			-NA-	-NA-		
	Upper floors	12 ACPH	-NA-	-NA-		
				l second		
5	Fire Extinguishers.					
	Total numbers	Required 100 Nos MF				
	Types	ABC/CO2	ABC & Co			
	ISI Marking	ISI mark	Provided			
6	First Aid Hose Reels.		20311999	MK		
	Total numbers on each floor.	06 at GF & 04 at	Provided			

M/17



	Length of hose-reel hose.	30m	30m	MI
	Nozzle Diameter	5mm	5mm	MF
,	Automatic fire detection & alarming sy			
	Type of detectors	-NA-	-NA-	-NA
	Location of Main Panel	-NA-	-NA-	-NA
	Location of Repeater Panel	-NA-	-NA-	-NA
	Alternate source of power	-NA-	-NA-	-NA
	Hooter's location	-NA-	-NA-	-NA
8	MOEFA	-NA-	-NA-	-NA
9	Public Address System	-NA-	-NA-	-NA
0	Automatic Sprinkler System	-147	144	1
	Basement	-NA-	-NA-	-NA
	Upper floors	-NA-	-NA-	-NA
	Opper Hoors     Sprinkler above false ceiling	-NA-	-NA-	-NA-
11	Internal Hydrants.	TWE	-1411	-11/4
	Size of Riser/Down-comer	-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
12	Yard Hydrants.	-13/3	Land Branch	1111
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.			
	Ground Level	10441 104 104	- Alg since	
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	-NA-	-NA-	-NA-
	Jockey Pump output.	-NA-	-NA-	-NA-
	Jockey Pump head	-NA-	-NA-	-NA-
	Standby Pump output.	≛NA±	. €NA∈	≅NA=
	Standby Pump head.	-NA-	-NA-	-NA-
	> Auto Starting/Manual	-NA-	-NA-	-NA-
	Stopping.  > Pump house access.	-NA-	-NA-	-NA-
	Terrace Level			
	Discharge of pump.	450 & 180 LPM	Provided	MR
	➤ Head of pump.	40 m each	Provided	MR
	> Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14	Captive water storage for firefighting.			
	Underground tank capacity.	-NA-	-NA-	-NA-
	<ul> <li>Draw-off connection.</li> <li>Fire Service Inlet.</li> </ul>	-NA-	-NA-	-NA-
	> Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	10,000 ltrs	Provided	-NA- MR
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.	- required	. IOHGVU	MIK
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	<ul> <li>Pressurization of lift lobby.</li> </ul>	-NA-	-NA-	-NA-
	<ul> <li>Communication in lift car.</li> </ul>	-NA-	-NA-	-NA-
	Fireman's switch.	-NA-	-NA-	-NA-
	Lift signage.	-NA-	-NA-	-NA-
17	Standby Power Supply	-NA-	-NA-	-NA-
18	Refuge Area		5.4	
	Total area	-NA-	-NA-	-NA-
	Location	-NA-	-NA-	-NA-



Fire Control Room.	-NA-	-NA-	-NA
Detector system panel.	-NA-	-NA-	-NA
Flow switch panel.	-NA-	-NA-	-NA
PA system panel.     Battery backup.	-NA-	-NA-	-NA
		-NA-	-NA
Building floor plan.  Special Fire Protection System for the Protectio	-NA-	3.7.300	-NA

The fire protection system provided in the building / premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/School/2022/SZ/395 dated 07/04/2022, renewal under rule 37 of the Delhi Fire Service Rules 2010, is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: ADO (BCP)

F.t. Letter is pully for