



## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/School/2025/SZ/16

Dated: .1.0./.01/2025

## FIRE SAFETY CERTIFICATE

Certified that the **Delhi Public School International** located at P-37, Sector-VI, Pushp Vihar, M.B. Road Saket, New Delhi-110017 having three blocks, A-Blocks: B+G+3, B-Block: B+G+1 (Audi at 1st Floor of B-Block) and C-Block: B+G+2 (A & B blocks are interconnected upto 1st floor and C block interconnect with A block at first floor) was issued FSC by this department vide letter No. F6/DFS/MS/School/2022/SZ/45 dated 14/01/2022. The premises was re-inspected by officer concerned of this department on 03/01/2025 in presence of Mr. Sravani Rao (Principal) and observed that the said School building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "**Educational Building**" Group-B, with effect from 10/01/2025 for a period of **Three years** in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 10 01 /2025 at New Delhi by

(ATUL GARG) BIRECTOR DELHI FIRE SERVICE

## Copy to: -

 The Principal, DPS International, P-37, Sec-VI, Pushp Vihar, M.B. Road, Saket, New Delhi-110017

2. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-54

## Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

 All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

4. The basement shall be used as per the provisions of BBL-/NBC Part- IV.

5. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>

 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

9/12



1	Name & Address of the Building	DPS International, P-37, Sector-VI, Pushp Vihar, M.B. Road, Saket, New Delhi-110017					
2	Type of Occupancy	Educational, Group-B (School)					
3	Building Comprised of	School has three blocks. A-Bk: B+G+3, B-Bk: B+G+01 (Audi at FF of B-Bk) and C-Bk: B+G+02 (A&B Blocks are interconnected upto 1st Floor & C Bk interconnected with A Block at 1st floor)					
4	Type of Case	Renewal					
5	Details of Previous NOC	F6/DFS/MS/School/2022/SZ/45 dated 14/01/2022					
6	Fire Safety Directives Letter No	F.6/DFS/MS/BP/2002/1105 dated 09/07/2002					
7	Date of Inspection	03/01/2025					
8	Name of the Inspecting Officers	Sh. Rajesh Kumar, ADO (BCP)					
9	Name & Designation of Officers from the building side	Mr. Sravani Rao (Principal)					
10	Year of construction	2002					
11	Applicant letter No.	DPSI/Estate/2057/ dated 11/12/2024					
. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC Requiremen		Provided at Site		arks NMR	
1	Access to Building.	-		COURCE F			
	Road width	6 mtr		10 mtr	N	IR.	
= -	Gate width	5 mtr		Provided	N	AR :	
ox.	Width of internal road	-NA-		-NA-	-1	IA-	
2	Number, width, type & arrangement of	exits.					
10	a) Number of Staircase		-				
V.	<ul> <li>Upper floors.</li> <li>Basement floor.</li> </ul>	06 Nos (A&B Bk: 3 Nos GF to Terrace + 01 FF to Terrace & 02 in C Bk) A&B Bk: 06 Nos		A&B Block- 06 Nos		MR	
	7.0	C Bk: 02 Nos	154	C Block- 02 Nos	11.	_	
-	b) Width of Staircase			Bustli k			
	➤ Upper floors	1.5 mtr A&B Bk: 1.40m, 1.85m, 1.85m & 1m, C Block: 1.40m each		(old case)			
	➤ Basement floor 1.5 mtr		A&B Bk. 1.40m x 3, 1.20m, 1m			MR ld case)	
	c) Protection of exits	2199914	17.5	A la monard &			
	> Fire check door	Required		Provided		MR	
	> Pressurization	-NA-		diffuse con -NA-		-NA	
	d) No. of continuous staircase to terrace	04 No		Provided		MR	
-	e) Width of corridor	1.5m	S 1/11 }	Provided		MR	
,	f) Door size	Class rooms-1m Audi- 1.50m		Class room-1m Audi-1.60m, 2.05m & 2.05m		MR	
3	Compartmentation.						
	Fire check door.     Seeling of electrical shall.	Required	i	Provided		MR	
	Sealing of electrical shafts.  Fire retire of the 0.1.	-NA-		-NA-		-NA-	
	• Fire rating of shaft door.	-NA-		-NA-		-NA-	
y	Water curtain	-NA-		-NA-		-NA-	
	• Fire dampers.	-NA-	Yes.	-NA-	1	-NA-	
4	Smoke Management system.						
	Basement	30 ACPH		Exhaust Fan		MR	
	Upper floors	12 ACPH		-NA-		-NA-	

A





5	Fire Extinguishers.	TOTAL MINERAL CONTRACTOR	11437	MR
200	Total numbers	Required	114 Nos	MR
	Types	ABC/CO2	ABC & Co	MR
	ISI Marking	ISI mark	Provided	MIK
6	First Aid Hose Reels.	de la	00. 1 . 1 . 10	) (D
	Total numbers on each floor.	A&B Bk-04 nos. C Bk-02 nos. Audi-02 nos.	A&B Bk-04 nos. C block-02 nos. Audi-02 nos.	MR
	r at Channelberr	30m	30m	MR
	<ul> <li>Length of hose-reel hose.</li> <li>Nozzle Diameter</li> </ul>	5mm	5mm	MR
-	Automatic fire detection & alarming s	vstem.	mid this it does that	
7	Type of detectors	Regd. in basement	Smoke & Heat	MR
	Location of Main Panel	-NA-	-NA-	-NA-
		-NA-	Ground floor	-NA-
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power     Hooter's location	-NA-	-NA-	-NA-
			Provided	MR
8	MOEFA	Reqd. in Audi	Provided	-NA-
9	Public Address System	-NA-	riovided	
10	Automatic Sprinkler System		Descrided	MR
	Basement	Required	Provided	-NA-
	Upper floors	-NA-	-NA-	-NA-
	<ul> <li>Sprinkler above false ceiling</li> </ul>	-NA-	Provided	-IVA-
11	Internal Hydrants.		275 (21	) (D
	Size of Riser/Down-comer	100mm	Provided	MR
	Number of Hydrant per floor	A&B block-04 nos. C block-02 nos.	A&B block-04 nos. C block-02 nos. Auditorium-02 nos.	MR
	Hose box.	Auditorium-02 nos.  A&B block-04 nos.  C block-02 nos.	A&B block-04 nos. C block-02 nos.	MR
	Those box.	Auditorium-02 nos.	Auditorium-02 nos.	
12	Yard Hydrants.	10	04 17	-NA-
	<ul> <li>Total number of hydrants.</li> </ul>	-NA-	04 Nos	-NA-
	Hose box.	-NA-	04 Nos	-NA-
13	Pumping arrangements.		inferil has a 3	
	Ground Level		2200 I PM	MR
	Discharge of main pump.	1620 LPM	2280 LPM	
	Head of main pump.	50m	50m	MR
	Number of main pumps.	One	Provided	MR
	Jockey Pump output.	180 LPM	180 LPM	MR
	Jockey Pump head	50m	50m	MR
	Standby Pump output.	1620 LPM	2280 LPM	MR
	Standby Pump head.	50m	50m	MR
	> Auto Starting/Manual	Required	Provided	MR
	Stopping.  > Pump house access.	Required	Provided	MR
	Terrace Level			7
	Discharge of pump.	A&B & C Bk	540 LPM + 540 LPM	MR
	Head of pump.	40 mtr	43.5m each	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14	Captive water storage for firefighting.			
	<ul> <li>Underground tank capacity.</li> </ul>	50,000 Ltr	Provided	MR
	Draw-off connection.	-NA-	-NA-	-NA-
	> Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
		A&B Bk:40,000 Ltr	A&B Bk-40,000 Ltr	
	<ul> <li>Overhead tank capacity.</li> </ul>	C Block- 20,000 Ltr	C Bk- 20,000 Ltr	MR

	n la Clamaga	Required	Provided	MR		
5	Exit Signage.					
6	Provision of Lifts.  Pressurization of lift shaft. Pressurization of lift lobby. Communication in lift car. Fireman's switch. Lift signage.	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		Required	Provided	MR		
		-NA- Required	-NA- Provided	-NA- MR		
17	Standby Power Supply					
18	Refuge Area  Total area Location  Fire Control Room. Detector system panel. Flow switch panel. PA system panel.	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
19		-NA-	-NA-	-NA-		
17		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
	<ul> <li>Battery backup.</li> </ul>	-NA-	-NA-	-NA-		
	Building floor plan.  Special Fire Protection System for the Prot	otection of special Risk, if ne building / premises w	env.	-NA-		

The fire protection system provided in the building / premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/School/2022/SZ/45 dated 14/01/2022, renewal under rule 37 of the Delhi Fire Service Rules 2010, is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Design: ADO (BCP)

DO (\$D)

Mels 6/1/20

Dinition () 2085

As offmored

your Synat

fetter

PI

is pulled

9/1/2005

Di rector M

m