
Dated:03/12/2025



FIRE SAFETY CERTIFICATE

Certified that the Delhi Public School (International) Primary & Nursery School), Sector - 10, R.K Puram, New Delhi - 110022, Comprised of Basement (Storage only), Ground plus two upper floors owned/occupied by Delhi Public School was earlier issued Fire Safety Certificate vide letter No F6/DFS/MS/School/2022/SZ/1260 dated 24/11/2022. Now, the school building was re-inspected by officer concerned of this department on 21/11/2025 in presence of Mrs. Sravani Rao (Principal) of the school and found that the said school building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service, 2010 and that the school building is fit for occupancy class Group - B "Educational Building" with effect from 63/12/2025 for a period of three years in accordance with Rule 36 unless renewal under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the DFS Rules, 2010.

03 12 2025 at New Delhi by. Issued on

> Dy. Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Directorate of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi 110054.
- 2. The Principal, Delhi Public School (International) Primary & Nursery School), Sector 10, R.K. Puram, New Delhi - 110022.

Conditions for the validity of Fire Safety Certificate

- 1. The owner /occupier shall apply for renewal of this fire safety certificate to the Director in form J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry
- 2. All the means of escape shall be kept free of all the type of obstruction all the time.
- 3. All the employees shall be acquainted with the use and maintenance of all fire equipment's and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the firefighting equipment's shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc. may be got verified from the authorities concerned.
- 6. Basement shall be used as per UBBL 2016.
- 7. This Fire Safety Certificate cannot be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

				CTION REPO	PT	The Street			
		2							
01	building			Delhi Public School (International) Primary & Nursery School), Sector – 10, R. K Puram, New Delhi - 110022					
				Dellii - 110022					
02.				Basement (Storage only), Ground plus two upper floors					
		Company			Building, Group - B (Scho	ool)			
03.	T	ype of occupancy		Renewal Case					
04.	T	ype of case		F6/DFS/MS/	School/2022/SZ/1260 date	ed			
05.	D	etails of previous FSC		24/11/2022	×				
		" ' lotter	no	F6/DFS/MS/BP/2003/2192 dated 19/09/2					
06.	Fi	re safety directives letter	110.	21/11/2025					
07.	D	ate of inspection		Vashwant Si	ngh Meena, ADO/BCP				
08.	N	ame of the inspecting off	icers	Mrs Sravani	Rao (Principal)				
09.	N	ame of the designation	n 01	Mis. Stavani	VII.5. DIGITALIS				
122 1	of	ficer from the building si	de	2002					
10.	Y	ear of construction		Outdoor dairy no. 7472 dated 28/10/2025					
11.	A	policant's letter no.		Outdoor daily no. 7472 det		Accinion in			
11.	-	Minimum standard of fire	2	As per old		MR/NM			
S.No	, F	revention and fire safety U/I	R 33						
)1.	A	ccess to Building:		9.0 meter	9.0 meter	MR			
	A	Road width			2 11.1	MR			
	В			5.0 meter	N/A	N/A			
	C Width of internal road			N/A					
2.	Number, Width, Type and Arrangement of Exits:								
	A					MF			
		a Upper floor		02 nos.	03 Provided	MF			
	-	C Basement		02 nos.	03 Provided	1417			
	В				1 20 % Pr 1m	MR			
		a Upper floor		Required	1.37m, 1.30m & 1m	MR			
		C Basement		Required	1.38m, 1.37m & 1m	MIK			
	C	C Protection of exits a Fire check door			n '1.1	MR			
				Required	Provided	TO MAKE ST			
		b Pressurization		N/A	N/A	N/A			
	D	No. of continu	ious	Required	Provided	MR			
		staircases to terrace		100		MD			
	E	Width of corridor		1.5m	Provided	MR			
	F	- The control of the		1m Provided		MR			
3.	Co	mpartmentation:	Ø .) (D			
	A	Fire check door		Required	Provided	MR			
	В	Sealing of electrical sha	ıfts	N/A	N/A	N/A			
	C	Fire rating of shaft door		N/A	N/A	N/A			
	D	Water curtain		N/A	N/A	N/A			
	E	Fire dampers		N/A	N/A	N/A			
4.	Sm	Smoke Management System:							
	A	Basement		30 ACPH	Exhaust fan provided	MR			
	В	Upper floor		12 ACPH	Natural ventilation	MR			
5.		Extinguisher:			Appendix and appendix appendix and appendix appendix appendix appendix and appendix				
_		Total numbers		52 nos. 52 nos.		MR			
_		B Types ABO		C & W.CO ₂	ABC & W.CO ₂				
198	100			I Marked	Provided	MR MR			
110									

-N/12 -

0.	-	V 1300 W	_N 12 -					
06.	_	st-Aid-Hose Reel:		TIE ASMA	MR			
	A	Total numbers of each floor	UF - 03Nos Basement- 02Nos	UF - 03Nos Basement- 02Nos	IVIK			
	В	Length of hose reel hose	30m	30m	MR			
	C	Nozzle diameter	5mm	5mm	MR			
07.		tomatic Fire Detection and Al		-	(4)			
	A	Type of detectors	Smoke	Provided	MR			
	В	Location of main panel	Ground Floor	Provided	MR			
	C	Location of repeater panel	N/A	N/A	N/A			
	D	Alternate source of power	N/A	N/A N/A	N/A			
	E	Hooters	N/A	The second secon	N/A			
08.	M	OEFA:		N/A				
09		blic Address System:	Required	Provided	MR			
10.	Automatic Sprinkler System:		Required	Provided	MR			
	A	Basement	D1					
	В	Upper floor	Required	Provided	MR			
	C	Sprinkler above false ceiling	N/A	N/A	N/A			
11.	In	ternal Hydrants:	N/A	N/A	N/A			
	A	Size of riser/down-comer	100	¥ .				
	В	Number of hydrants per	100mm	100mm	MR			
		floor	UF - 03Nos Basement- 02Nos	UF - 03Nos	MR			
			- UZNOS	Basement- 02Nos				
	C	Hose box	UF - 03Nos	UF - 03Nos	MD			
			Basement- 02Nos	Basement-	MR			
12.	V	and III 1	Þ	02Nos				
14.	A	ard Hydrants:						
	B	Total number of hydrants Hose box	N/A	Provided	N/A			
13.	1767		N/A	Provided	N/A			
1	Pumping Arrangements: Ground level							
•	A							
	B	Discharge of main pump	1260 LPM	2280 LPM	MR			
	C	Head of main pump	70 m	70 m	MR			
	D	Number of main pumps	01	01	MR			
	E	Jockey pump out put Jockey pump head	180 LPM	180 LPM	MR			
	F	Standby pump out put	70 m	70 m	MR			
	G	Standby pump head	1620 LPM	2280 LPM	MR			
	H	Auto starting /manual	70 m	70 m	MR			
		stopping	Required	Provided	MR			
	I	Pump house access	Required	Provided	100			
2	Terrace Level Required Provided MR							
	A	Discharge of pump	900 LPM	900 LPM	1.00			
	В	Head of the pump	40 meter	Provided	MR			
	C	Power supply	Required		MR			
	D	Auto starting of pump	Required	Provided	MR			
4.	(100)			Provided	MR			
7.	Captive Water Storage for Fire Fighting:							
-	A	Underground tank capacity	50,000 liters	Provided	MR			
	В	Draw-off connection	N/A	N/A	N/A			
	C	Fire service inlet	N/A	N/A	N/A			
	D	Access to tank	N/A	N/A	N/A			
1	E	Overhead tank capacity	10,000 liters	20,000	MR			
	-	- · · · · · · · · · · · · · · · · · · ·	20,000 11010	liters				
			li .	HIGIS	1			

Pressurization of lift shaft Pressurization of lift shaft Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: efuge Area:	N/A N/A N/A Required Required Required	N/A N/A N/A Provided Provided Provided	N/A N/A N/A MR MR MR				
Pressurization of lift lobby Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: efuge Area:	N/A N/A Required Required Required	N/A N/A Provided Provided	N/A N/A MR MR				
Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: efuge Area:	N/A Required Required Required	N/A Provided Provided	N/A MR MR				
Communication in lift car Firemen's grounding switch Lift signage andby Power Supply: efuge Area:	Required Required Required	Provided Provided	MR MR				
Firemen's grounding switch Lift signage andby Power Supply: efuge Area:	Required Required	Provided	MR				
Lift signage andby Power Supply: efuge Area:	Required		NEW TOTAL				
andby Power Supply: efuge Area:		Provided	MR				
efuge Area:							
	4.000						
T 1	N/A	N/A	N/A				
Total area	N/A	N/A	N/A				
B Location							
re Control Room:	N/A	N/A	N/A				
Detector system panel	17/	N/A	N/A				
Flow switch panel			N/A				
DA gyistem nanel		23 1000 1000	N/A				
PA system paner	N/A	C1_ X2AA 51-61	N/.				
Battery backup	N/A	St. SouthEnglish.	77. 2003				
Building floor plans	NA	N/A	N/.				
pecial Fire Protection systems for cotection of special Risks, if any:		and tested a	nd was				
	Period Room: Detector system panel Flow switch panel PA system panel Battery backup Building floor plans Period Fire Protection systems for	Perfection of special Risks, if any: Detector system panel N/A N/A	Perfection of special Risks, if any: Detector system panel				

Keeping in view of the deemed compliance of minimum standards on 1 prevention and fire safety measures as required under the Rules the Fire Safety Certific issued vide letter no. F6/DFS/MS/School/2022/SZ/1260 dated 24/11/2022, under the r 37 of the Delhi Fire Service Rules, 2010 is **recommended**.

Signature of the Inspecting Officer
Name: - Yashwant Singh Meena
Designation: - ADO/BCP

DO/SD

Mayinder Singh

geolog

K. MALIK

Eineisel Bustin

m. cr

So to

26/11/

Miles A.K. MANIK

Ravinder Singh

NTO