



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No.F.6/DFS/MS/School/2025/SZ/1115

Dated: .09 69/2025

FIRE SAFETY CERTIFICATE

Certified that the **Delhi Public School**, located at Sector-C Pocket-5, Vasant Kunj, New Delhi 110070 comprised of Block-C, Ground plus 03 Floors & Block-G, 02 Basement, Ground plus 02 Floors owner/occupied by Delhi Public School was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/20222/SZ/966 Dt. 06/09/2022. The premises was re-inspected by officer concerned of this department on 25/08/2025 in presence of Mr. Indradhanush Chowdhary (Estate) and observed that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy **class "Educational Building" Group-B** with effect from <u>09/69/2025</u> for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 69/09/2025 at New Delhi by

(VIRENDRA SINGH) CHIEF FIRE OFFICER PELHI FIRE SERVICE

Copy to: -

1. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi 110054.

2. Delhi Public School, located at Sector-C Pocket-5, Vasant Kunj, New Delhi 110070 Conditions for the validity of Fire Safety Certificate:

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

4. The basement shall be used as per the provisions of UBBL-2016 /NBC Part- IV.

5. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

 This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry.

•	Name & Address of the Building	TION REPORT				
2	Type of Occupancy	Delhi Public School, Sector-C Pocket-5, Vasant Kunj, New Delhi 110070				
3	Building Comprised of	New Delhi 110070 Educational, Group-B (School)				
,	Daniang Comprised of	Block C. C	up-B (School)			
4	Type of Case	Block-C, Ground plus 03 floors & Block-G, (Basement, Ground plus 02 floors				
5	Details of Previous NOC	Renewal	d plus 02 floors	-100K O, 02		
6	Fire Safety Directives Letter No		1/0.0			
7	Date of Inspection	F6/DFS/MS/3016	ool/20222/SZ/966 Dt. 06/0	09/2022		
8	Name of the Inspecting Officers	F6/DFS/MS/2018/BP/159 Dated 17/05/2018 25-08-2025				
9	Name & Designation of Officers	ADO (BCP) Mr. Indradhanush Chowdhary (Estate)				
	from the building side					
10	Year of construction		(Estate)			
11	Applicant letter No.	1996, 2002 & 202	20			
S. No	Minimum standards on Fire Prevention	DFS Outdoor diary no 4787dated 12/08/2025				
	and Fire Safety U/R 33	NBC/UBBL	Provided at Site	Remarks		
1	Access to Building.	requirements	a so state at Site	MR/NMR		
	Road width			MINIMI		
	Gate width	Required	6 mtr	MR		
	Width of internal road	Required	4 mtr	MR		
2	Number, width, type & arrangement of exits.	-NA-	-NA-	-NA-		
	a) Number of Staircase			- 100		
	> Upper floors.					
	- FF-27 10013.	02 No's	02 Nos	MR		
	➤ Basement floor.	Blk G- 05	05 Nos			
	b) Width of Staircase	Blk G- 04	04 Nos	MR		
	> Upper floors					
	- PPO MOOIS	1.50 & 2m	1.50m, 2.17m ramp	MR		
	> Basement floor	Blk G-(1.50 & 4 x 2m		MR		
	c) Protection of exits	2m & 1.50	Provided	MR		
	Fire check door	NIA				
	Pressurization	-NA-	-NA-	-NA-		
ı	d) No. of continuous staircase to terrace	-NA-	-NA-	-NA-		
t	e) Width of corridor	One each block	Provided	MR		
t	f) Door size	-NA-	-NA-	-NA-		
3	Compartmentation.	1 mtr	1 mtr	MR		
	Fire check door.	N/A				
	 Sealing of electrical shafts. 	-NA-	-NA-	-NA-		
	• Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
		-NA-	-NA-	-NA-		
4.	• Fire dampers.	-NA-	-NA-	-NA-		
	Smoke Management system.					
	Daschielli	12 ACPH	Exhaust fan provided	MR		
5.	• Upper floors	-NA-	-NA-	-NA-		
	Fire Extinguishers.					
	rotal numbers	Required	25 Nos	MR		
	• Types	ABC	ABC Type	MR		
	ISI Marking			IVIIX		
		ISI mark	Provided	MR		
6.	First Aid Use D					
6.	First Aid Hose Reels.					
6.	Total numbers on each floor	02 in each blocks				
6.	 First Aid Hose Reels. Total numbers on each floor. Length of hose-reel hose. 	02 in each blocks 30 m	Provided	MR		

आज़ादी_{का} अमृत महोत्स

	1410			
	Nozzle Diameter	5 mm	Provided	MR
7	Automatic fire detection & alarming system	n		
		Required	l Provided	MR
	Type of detectorsLocation of Main Panel	Required	Provided	MR
	Location of Main Failer Spangeter Panel	-NA-	-NA-	-NA-
	Location of Repeater Panel	Required	Provided	MR
	Alternate source of power	Required		MR
	Hooter's location	Required	1 200 - 100 -	MR
8.	MOEFA	-NA-	-NA-	-NA-
9.	Public Address System	-11/1	177	
10.	Automatic Sprinkler System	Paguired	Provided	MR
	Basement	Required	-NA-	-NA-
	Upper floors	-NA-	- Contract	-NA-
	 Sprinkler above false ceiling 	-NA-	-NA-	
11.	Internal Hydrants.		2 11 1	MR
11.	Size of Riser/Down-comer	Required	Provided	MR
	N. Land Hudrant per floor	Required	Provided	MR
	vv t	Required	Provided	IVIK
2040				MR
12.	Yard Hydrants.	Required	Provided	
	Total number of hydrants.	Required	Provided	MR
	Hose box.			
13.	Pumping arrangements.			- · · ·
	Ground Level	2280 LPM	Provided	MR
	Discharge of main pump.	70m	Provided	MR
	➤ Head of main pump.	01	Provided	MR
	> Number of main pumps.	180 LPM	Provided	MR
	> Jockey Pump output.	70m	Provided	MR
	> Jockey Pump head.	2280 LPM	Provided	MR
	Standby Pump output.Standby Pump head.	70m	Provided	MR
	 Standby Pullip Read. Auto Starting / Manual Stopping. 	Required	Provided	MR
	> Pump house access.	Required	Provided	MR
		Acceptance of the control of the con		
	Terrace Level	900 PM for G		
	Discharge of pump.	Block	Provided	MR
		450 LPM for C		100
	1 - fmn	40 mtr	Provided	MR
	> Head of pump.	Required	Provided	MR
	Power supply.Auto starting of pump.	Required	Provided	MR
	Captive water storage for fire fighting.			
14.	Underground tank capacity.	1,00,000 ltrs	Provided	MR
	> Draw-off connection.	Required	Provided	MR
	Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
	Overhead tank capacity.	20,000 ltrs for G Block & 10,000 ltrs	Provided & 10,000 ltrs	MR
		Required	Provided	MR
15.	Exit Signage.			
16.	Provision of Lifts. Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
			-14/4-	-INA-
			TARRED OF THE PARTY OF THE PART	
	 Fireman's switch. 	-NA-	-NA-	-NA-
		-NA- -NA- Required	-NA- -NA- Provided (DG Set)	-NA- -NA- MR

Mr



1			
Total area	-NA-	-NA-	-NA-
Location	-NA-	-NA-	-NA-
Fire Control Room.			
Detector system panel. Flow switch panel.	-NA-	-NA-	-NA-
PA system panel.	-NA-	-NA-	-NA-
 Battery backup. 	-NA-	-NA-	-NA-
Building floor plan.	-NA-	-NA-	-NA-
	-NA-	-NA-	-NA-
Special Fire Protection System for the Protection of special Risk, if any.	-NA-	-NA-	-NA-
	Location Fire Control Room. Detector system panel. Flow switch panel. PA system panel. Battery backup. Building floor plan. Special Fire Protection System for the	Location -NA- Fire Control Room. Detector system panel. Flow switch panel. PA system panel. Battery backup. Building floor planNANANANANANANANA	Location

The Fire protection systems provided in the premises were test checked at random and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and safety measures as required under the rules, the FSC issued vide letter no fire Sales, the FSC issued vide letter no F6/DFS/MS/School/20222/SZ/966 Dt. 06/09/2022, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer
Name: Sh. Rajesh Kum
Design: ADO

DO (South)

F.T. Letter in South