GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

No. F.6/DFS/MS/EH/2025/SZ/264

Dated: 09 | 07 | 2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Delia My Bar Headquarters A unit of KBPS Hospitality LLP at Plot No. 11, 3rd floor, Pusa Road, Karol Bagh, New Delhi- 110005, running at third floor only in a building comprised of basement, ground plus three upper floors, owned/occupied by M/s A unit of KBPS Hospitality LLP, was issued FSC by this department vide Letter No. F.6/DFS/MS/EH/SZ/2022/333 dated 24.11.2022. The Restaurant building was re-inspected by the officer concerned of this department on dated 02.07.2025 in the presence of Manager, and found that the restaurant have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the restaurant building/premises (Third floor only) is fit for occupancy class Group "D" Assembly Building" w.e.f. D9 0 7 2025 for a period of three years, accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on D9 0 7 2025 at New Delhi.

Delhi Fire Service

Online application Id 2025053109399 dated 02.06.2025

Copy to: - The Executive Engineer (Building), MCD, Civic Centre, Minto Road, New Delhi.
:-for information regarding use of basement.

Conditions for validity of Fire Safety Certificate:-

- 1. This FSC is valid only for third floor.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 5. The trained staff should be available round the clock.
- Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 7. Basement strictly shall be used as per BBL. Presently basement used for storage purpose only.
- The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 10. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.
- During inspection terrace was being used for dinning /serving of food as per MCD policy. You
 may take necessary action as deemed fit.

		INSPECTION REPO	DT			
	1. Name & address of the buildi			Inneliable, E.I.I		
		- Seria iviy Dai 1	leadquarters (a unit of KBPS I	Hospitality LLI		
	Building is comprised of	Pasterna	, Pusa Road, Karol Bagh, New	d of basement		
		ground plus three upr	third floor of a building comprise per floors, using, basement (storag	e), ground floor		
	l l	(Haldiram Restaurant). 1st floor (Jewellery Shop), 2st f	loor (Path Lab),		
	Type of Occupancy	3 rd floor (Delia My B	ar restaurant & Dinning/Service a	rea at terrace.		
	4. Type of Case	The second secon	: Group D (Assembly) Restaurant & Bar : Renewal			
	5. Details of Previous NOC					
	6. Fire Safety directives letter N	: F.6/DFS/MS/EH/SZ/2022/333 dated 24.11.2022				
	7. Date of inspection	7. Date of inspection : 02.07.2025 8. Name of Inspecting Officers : A D O R K Vaday (IKP)				
	8. Name of Inspecting Oct					
	9. Name and designation of office					
	From the building side					
	10. Year of Construction		: Manager : 2011 : MHA Portal ID 2025053109399 dated 02.06.2025			
	11. Applicant's letter No.					
	Minimum Standards on fire	Requirements	Provided at site	Remarks		
lo.	prevention and fire safety U/R 33			MR/NMR		
	Access to building					
	- P -1 -161	06 m	Provided	M/R		
	Road width Gate width	Required	Directly assessable from road	N/A		
	Width of internal road	N/A	N/A	N/A		
	Number, Width, Type & Arrange					
•	Number, Width, Type & Arrange	intent of Exits	(Restaurant running at o	nly third floo		
	a. Number of staircases		04	MR		
	Upper Floors	02 nos.	04 nos.	N/A		
	Basements	N/A	N/A	18/23		
	b. Width of staircases • Upper Floor		1" - 1.25 m, 2"t - 2.07 m & 3"t -	N/A		
	• Opper Floor	2.0 & 1.50 m	1.50 m (iron made) & 4th - 1.02 to	N/A		
		21/4	1.20 m (3 rd floor to terrace) N/A	N/A		
	Basements	N/A	IN/A	1471		
	c. Protection of exits	Required	Provided in kitchen	MR		
	Fire check door Pressurization	N/A	N/A	N/A		
	c et alimana et alimana et al	N/A	IN/O	10/1		
	d. No. of continuous staircases to	02	03	MR		
	ng to Comider	N/A	N/A	N/A		
	f. Door Size	2.0 &1.50 m	2.0 &1.50 m	MR		
	Compartmentation					
3.						
		Required	Provided	MR		
	Fire check door Sealing of electrical shafts	Required Required	Provided Sealed	No. Control of		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door	Required	Sealed	MR		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain		Sealed N/A	MR N/A		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door	Required N/A	Sealed	MR N/A N/A		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain	Required N/A N/A	Sealed N/A N/A	MR N/A N/A N/A		
4.	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements	Required N/A N/A N/A N/A	Sealed N/A N/A N/A (Restaurant running at on	MR N/A N/A N/A		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System	Required N/A N/A N/A	Sealed N/A N/A N/A N/A (Restaurant running at on	MR N/A N/A N/A N/A ly third floor		
ı.	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements Upper floors Fire Extinguishers	Required N/A N/A N/A N/A N/A 12 ACPH	Sealed N/A N/A N/A (Restaurant running at on N/A Exhaust Fan Provided	MR N/A N/A N/A ly third floor		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements Upper floors Fire Extinguishers Total numbers in restaurant	Required N/A N/A N/A N/A N/A 12 ACPH	Sealed N/A N/A N/A (Restaurant running at on N/A Exhaust Fan Provided	MR N/A N/A N/A ly third floor		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements Upper floors Fire Extinguishers Total numbers in restaurant Types	Required N/A N/A N/A N/A N/A 12 ACPH 10 no.'s ABC/CO ₂	Sealed N/A N/A N/A (Restaurant running at on N/A Exhaust Fan Provided	MR N/A N/A N/A ly third floor N/A MR		
i.	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements Upper floors Fire Extinguishers Total numbers in restaurant Types IS marking	Required N/A N/A N/A N/A N/A 12 ACPH	Sealed N/A N/A N/A (Restaurant running at on N/A Exhaust Fan Provided	MR N/A N/A N/A ly third floor N/A MR		
5.	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements Upper floors Fire Extinguishers Total numbers in restaurant Types IS marking First-Ald Hose Reels	Required N/A N/A N/A N/A N/A 12 ACPH 10 no.'s ABC/CO ₂ ISI marked	Sealed N/A N/A N/A (Restaurant running at on N/A Exhaust Fan Provided Provided Provided	MR N/A N/A N/A ly third floor N/A MR M/R		
5.	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements Upper floors Fire Extinguishers Total numbers in restaurant Types IS marking First-Ald Hose Reels Total numbers at each floor	Required N/A N/A N/A N/A N/A 12 ACPH 10 no.'s ABC/CO ₂ ISI marked	Sealed N/A N/A N/A (Restaurant running at on N/A Exhaust Fan Provided Provided Provided	MR N/A N/A N/A ly third floor N/A MR M/R M/R M/R		
	Fire check door Sealing of electrical shafts Fire Rating of shaft door Water Curtain Fire Dampers Smoke Management System Basements Upper floors Fire Extinguishers Total numbers in restaurant Types IS marking First-Ald Hose Reels	Required N/A N/A N/A N/A N/A 12 ACPH 10 no.'s ABC/CO ₂ ISI marked	Sealed N/A N/A N/A (Restaurant running at on N/A Exhaust Fan Provided Provided Provided Provided Provided	MR N/A N/A N/A ly third floor N/A MR M/R		

1	12
N	112

7.	Automatic fire detection and alarming	system in restaurant		
	Type of detectors Smoke/Heat	Required	Provided	
	Location of Main Panel Location of Repeater Panel	Required		MR
		N/A	Provided near reception N/A	MR
	 Alternate source of power 	Required	Provided	N/A
	 Hooters' Location 	Required	Provided	MR
3.	MOEFA	Required	Provided	MR
).).	Public Address System	N/A	N/A	M/R
				N/A
10.	Automatic Sprinkler System		(Restaurant at third	floor only
	Basement	N/A	Provided	N/A
	Upper floors/Restaurant Sprinkler above false ceiling	N/A	Provided	N/A
		N/A	N/A	N/A
11.	Internal Hydrants			
	Size of riser/down-comer	100 MM	100 MM	MR
	Number of hydrants	02 no's	02 no's	MR
	Hose Box	02 no's	02 no's	MR
12.	Yard Hydrants			
	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13.	A	****		(8/30/8/8)
	Pumping Arrangements			
MR	Ground Level	2280 LPM	2280 LPM	MR
	 Discharge of main Pump Head of Main pump Number of main pumps 		70 m	MR
		70 m	01	MR
	> Jockey Pump out put	180 LPM	180 LPM	MR
	 Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual Stopping Pump House Access 	70 m	70 m	MR
		2280 LPM	2280 LPM	MR
		70 m	70 m	MR
		Required	Provided	M/R
		Required	Provided	M/R
		•		
	Terrace level	450 LPM	450 LPM	M/R
	 Discharge of pump Head of the pump Power Supply Auto Starting of pump 	40 m	40 m	M/R
		Required	Provided	M/R
		Required	Provided	M/R
14.	Captive Water Storage for fire-fighting			
- 7.5	TOM THOSE PROPERTY OF THE PROP	1000001	1.00.000 h	MR
	 Underground tank capacity Draw-off connection 	1,00,000 ltrs	1,00,000 ltrs Provided	M/R
	Fire service inlet	Required	Provided	M/R
	Access to tank Overhead Tank capacity	Required Required	Provided	M/R
		20,000 ltrs	20,000 ltrs	M/R
15.	Exit Signage.	Required	Provided	M/R
16.	Provision of Lifts	Acquired	Tiorida	WO MANUFACTA
		****	504	N/A
	Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car	N/A	N/A	
		N/A	N/A	N/A N/A
	Fireman's Grounding Switch	N/A N/A	N/A N/A	N/A
	Lift Signage	N/A N/A	N/A N/A	N/A
-			PARTITION .	1

14						
17.	Standby power supply	Required	Provided	M/R		
18.	Refuge Area.					
	> Total Area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19.	Fire Control Room					
-	Detector System Panel Flow Switch Panel	N/A	N/A	N/A		
		N/A	N/A	N/A		
	PA System Panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20.	Special Fire Protection System for Protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F.6/DFS/MS/EH/SZ/2022/333 dated 24.11.2022, renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note: - The Management of the restaurant use terrace for dinning/serving of food as per the MCD permission letter No. DHO/KBZ/2025/307 dated 29.05.2025 (placed at C- 54).

Signature of the Inspecting O

Name- R.K. Yadav

Designation- ADO (JKP)

Resubmitted as directed please