## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001 Dated. 03/06/2025

No.F.6/DFS/MS/EH/2025/SZ/R22

## FIRE SAFETY CERTIFICATE

Certified that M/s Drums of Heaven located at S-14, Green Park Extension, New Delhi 110016 comprised of Basement (Storage), Ground, Mezzanine + 02 upper floors but restaurant running on ground and Mezzanine floor only owned/occupied by Karamjit Singh Puri was issued Fire Safety Certificate by this department vide letter no. F6/DFS/MS/EH/SZ/2022/52 Dt. 28/02/2022. The restaurant premise was reinspected by the officer concerned of this department on 24/05/2025 in the presence of Mr. Ajit Sharma (Manager) and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class D "Assembly Building" (Restaurant at Ground & Mezzanine) and Validity upto 31/03/2028 in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on <u>03</u>/<u>06</u>/2025 at New Delhi by

CHIEF FIRE OFFICER DELHI FIRE SERVICE

Copy to: -

1. The Addl. Commissioner of Police, (Lic/Branch) 1st Floor PS Defence Colony, New Delhi 110049 (Ref. MCD Portal ID 2025050507868 dated 05/05/2025)

## Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. This fire safety certificate may not in any way be treated as regularization (Clause UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of 2.8 of

UBBL-2016), if any. 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

	INSPECTIO		eaven at S-14 Green	Park		
	Name & Address of the Building	M/s Drums of Heaven at S-14, Green Park Extension, New Delhi 110016 Group-D-4 Assembly				
1						
1	Type of Occupancy	(Restaurant at GF & Mezz. Floor)  Basement, Ground, mezzanine + 02 upper floor Renewal  F6/DFS/MS/EH/SZ/2022/52 Dt. 28/02/2022  Nil  24/05/2025  Sh. Suman Kumar, ADO  Mr. Ajit Sharma (Manager)				
12	Building Comprised of					
3	Building Comprised of					
4	Type of Case  Details of Previous NOC					
5	Fire Safety Directives Letter No					
6						
7	Date of Inspection					
3	Name of the Inspecting Officers					
)	Name & Designation of Officers					
	from the building side Year of construction					
0		MCD Portal ID 2025050507868 dated 05/05/2025				
1	Applicant letter No.					
S.	Minimum standards on Fire Prevention	Old NOC	Provided at Site	Remarks		
9. No.	and Fire Safety U/R 33	Requirements		MR/NM		
<u>NO.</u> [	Access to Building.					
,	Road width	4.5 mtr	Provided	MR		
	Gate width	N/A	N/A	N/A		
	Width of internal road	N/A	N/A	N/A		
	Number, width, type & arrangement of e					
2						
	a. Number of Staircase	02.11-2-	02 Nos	MR		
	Upper floors.	02 No's	02 Nos	MR		
	Basement floor.	02 No's	02 1103	1111		
	b. Width of Staircase	1.05	1.20m & 1.0 m	MR(old cas		
	Upper floors	1.25 mtr each	1.0 & 0.90 mtr	MR(old cas		
	c. Basement floor	1.25 mtr each	1.0 & 0.90 mu	MICOR Cas		
	d. Protection of exits	1.711	N/A	N/A		
	Fire check door	N/A		N/A		
	e. Pressurization	N/A	N/A	MR		
	f. No. of continuous staircase to	Required	01 Provided	IVIIC		
	terrace	N/A	N/A	N/A		
	g. Width of corridor	2 exits	02 exit provided	MR		
	h. Door size	2 exits	02 CAR provided	1,121		
3	Compartmentation.			T		
	Fire check door.	N/A	N/A	N/A		
	Sealing of electrical shafts.	N/A	N/A	N/A		
	Fire rating of shaft door.	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	Fire dampers.	N/A	N/A	N/A		
4	Smoke Management system.					
4		30 ACPH	Exhaust fan	MR		
	Basement	12 ACPH	Exhaust fan	MR		
	Upper floors	12 /10111				
5	Fire Extinguishers.	00 17	10 Nos	MR		
	Total numbers	08 Nos	ABC & CO <sub>2</sub>	MR		
	Types	ABC/CO <sub>2</sub>	Provided	MR		
	ISI Marking	ISI marked	Tiovided	4		
6	First Aid Hose Reels.	One	Provided	MR		
	Total numbers on each floor.	30m	Provided	MR		
	Length of hose-reel hose.	5mm	Provided	MR		
	Nozzle Diameter					
7	Automatic fire detection & alarming sys	N/A	N/A	N/A		
	Type of detectors	N/A	N/A	N/A		
	Location of Main Panel	N/A	N/A	N/A		
	Location of Repeater Panel	1				

		Mao					
1	Alternate source of power	N/A		N/A		N/A	
	Hooter's location	N/A		N/A		N/A	
8	MOEFA	Requir	ed	Provided		MR	
9	Public Address System	N/A		N/A		N/A	
10			_	15			
	Basement	Require	ed	Provided		MR	
	Restaurant area	N/A		N/A		N/A	
11	Sprinkler above false ceiling	N/A		N/A	1	N/A	
11	Internal Hydrants. Size of Riser/Down-comer	100 mm		D ::::			
	Number of Hydrant per floor	One	1	Provided		MR	
	Hose box.	One		Provided		MR.	
12	Yard Hydrants.	One		Provided	IN	ИR	
12	Total number of hydrants.	N/A		NI/A		T / A	
	Hose box.	N/A N/A		N/A		J/A	
13	Pumping arrangements.	IN/A		N/A	I N	J/A	
13	Ground Level						
	Discharge of main pump.	NI/A		DT/A	121	r / A	
	Head of main pump.	N/A		N/A		/A	
	Number of main pumps.	N/A		N/A		/A	
	Jockey Pump output.		N/A N/A			N/A	
1	Jockey Pump head.	N/A	_	N/A	N/	/A	
	Standby Pump output.	N/A		N/A	N/	/ <b>A</b>	
	Standby Pump head.	N/A	9	N/A	N/	Ά	
	Auto Starting/Manual Stopping.		N/A N/A		N/	Ά	
	Pump house access.	N/A		N/A	N/.	Α	
L		N/A		N/A	N/.	A	
<u> </u>	Terrace Level						
	Discharge of pump.	450 & 180	450 & 180 LPM		MF	?	
	Head of pump.	35m					
	Power supply.			Provided	MF		
I A	Auto starting of pump.	Required		Provided	MR		
4 (	Continue water storage for fire fighting	Required		Provided	MR		
	Captive water storage for fire fighting.			T/A	1221		
	Inderground tank capacity.  Oraw-off connection.	N/A		V/A	N/A		
	raw-on connection.		1 1	V/A			
120	ina Camuina Inlat	N/A			N/A		
1	ire Service Inlet.	Required		Provided	MR		
A	ccess to tank.	Required N/A	N	Provided J/A	MR N/A		
A O	ccess to tank. verhead tank capacity.	Required N/A 5,000 Ltrs	N P	Provided V/A Provided	MR		
A O 5 Ex	ccess to tank. verhead tank capacity. xit Signage.	Required N/A	N P	Provided J/A	MR N/A		
A O Ex	ccess to tank. verhead tank capacity. xit Signage. rovision of Lifts.	Required N/A 5,000 Ltrs Required	N P	Provided N/A Provided Provided	MR N/A MR MR		
A O E 2 Pr Pr	ccess to tank. verhead tank capacity. xit Signage. ovision of Lifts. essurization of lift shaft,	Required N/A 5,000 Ltrs Required N/A	N N	Provided J/A Provided Provided	MR N/A MR MR N/A		
A O Ex	ccess to tank. verhead tank capacity. xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby.	Required N/A 5,000 Ltrs Required N/A N/A	N.	Provided N/A Provided Provided //A	MR N/A MR MR N/A N/A		
A O E E E E E E E E E E E E E E E E E E	ccess to tank. verhead tank capacity. xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car.	Required N/A 5,000 Ltrs Required N/A N/A N/A	N. N. N.	Provided J/A Provided Provided //A //A	MR N/A MR MR N/A N/A N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch.	Required N/A 5,000 Ltrs Required N/A N/A N/A N/A	N. N. N. N. N.	Provided  Provided  Provided  /A /A /A /A	MR N/A MR MR N/A N/A N/A N/A N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage.	Required N/A 5,000 Ltrs Required N/A N/A N/A N/A N/A N/A	N   N   N   N   N   N   N   N   N   N	Provided  J/A Provided Provided  /A /A /A /A /A	MR N/A MR MR N/A N/A N/A N/A N/A N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage. andby Power Supply	Required N/A 5,000 Ltrs Required N/A N/A N/A N/A	N   N   N   N   N   N   N   N   N   N	Provided  Provided  Provided  /A /A /A /A	MR N/A MR MR N/A N/A N/A N/A N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. covision of Lifts. essurization of lift shaft, essurization of lift lobby. communication in lift car. reman's switch. ft signage. andby Power Supply fuge Area	Required N/A 5,000 Ltrs Required N/A N/A N/A N/A N/A N/A Required	N   N   N   N   N   N   N   Pro	Provided J/A Provided Provided /A /A /A /A A Dvided	MR N/A MR MR N/A N/A N/A N/A N/A N/A N/A N/A N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage. andby Power Supply fuge Area tal area	Required N/A 5,000 Ltrs Required N/A	N   P   N   N   N   N   N   P   P   N   P   P	Provided J/A Provided Provided //A //A //A //A //A //A //A //A //A //	MR N/A MR MR N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage. andby Power Supply fuge Area tal area cation	Required N/A 5,000 Ltrs Required N/A N/A N/A N/A N/A N/A Required	N   N   N   N   N   N   N   Pro	Provided J/A Provided Provided //A //A //A //A //A //A //A //A //A //	MR N/A MR MR N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. vovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage. andby Power Supply fuge Area tal area cation e Control Room.	Required N/A 5,000 Ltrs Required N/A N/A N/A N/A N/A N/A N/A N/A N/A Required	N   N   N   N   N   N   N   Pro	Provided  J/A Provided Provided  /A /A /A /A /A /A A  Ovided	MR N/A MR MR N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  kit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage. andby Power Supply fuge Area tal area cation e Control Room. tector system panel.	Required N/A 5,000 Ltrs Required N/A	N/A   N/A	Provided J/A Provided Provided /A /A /A A Divided	MR N/A MR MR N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  xit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage. andby Power Supply fuge Area tal area cation e Control Room. tector system panel. ow switch panel.	Required N/A 5,000 Ltrs Required N/A	N	Provided J/A Provided Provided /A /A /A A Ovided	MR N/A MR N/A		
A O O O O O O O O O O O O O O O O O O O	ccess to tank. verhead tank capacity.  kit Signage. ovision of Lifts. essurization of lift shaft, essurization of lift lobby. ommunication in lift car. reman's switch. ft signage. andby Power Supply fuge Area tal area cation e Control Room. tector system panel.	Required N/A 5,000 Ltrs Required N/A	N/A   N/A	Provided J/A Provided Provided /A /A /A A Ovided	MR N/A MR MR N/A		