

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001

No. F.6/DFS/MS/Hospital/2025/SZ/ 4G7

Dated: .0.8./.0.9../2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Fortis C-Doc Hospital, located at B-16, Chirag Enclave, New Delhi 110048 comprised of Basement, Ground plus Three Upper Floors owned/occupied by M/s Fortis C-Doc Hospital was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/Hospital/2022/SZ/484 dated 01/11/2022. The Hospital was re-inspected by officers concerned of this department on 04/09/2025 in the presence of Mr. Sourabh Bhardwaj and observed that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of Delhi Fire Service Rules, 2010 and that the building is fit for occupancy class "Institutional building" Group-C (Hospital) with effect from __Og_ / _og_ /2025 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(VIRENDRA SINGH)
CHIEF FIRE OFFICER
DELHI FIRE SERVICE

Copy to: -

1. M/s Fortis C-Doc Hospital, located at B-16, Chirag Enclave, New Delhi 110048

2. The Directorate General of Health Service, (Nursing Home Cell) 3rd Floor, Delhi Govt. Dispensary Building, S-1, School Block, Shakarpur Delhi 110092.

Conditions for the validity of Fire Safety Certificate:

1. All the means of escape/entry/exit shall be kept free from any obstruction.

 All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting system.

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. The basement shall be used strictly as per the provisions of UBBL /NBC Part- IV.

6. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry.


8. The temporary structure erected at part portion of terrace shall be removed on or before six months from the date of issuance of this FSC and compliance.





		ON REPORT				
TT.	Name & Address of the Building	M/s Fortis C-Doc Hospital, B-16, Chirag Enclave New Delhi 110048				
-	Type of Occupancy		ding, "Group-C" (Hospit	ai)		
_	Building Comprised of	Basement, Ground + 03 upper floors.				
	Type of Case	Renewal				
	Details of Previous NOC	F6/DFS/MS/Hospital/2022/SZ/484 dated 01/11/2022				
	Fire Safety Directives Letter No	F6/DFS/MS/202	2/BP/Hospital/456 dated	25.02.2022		
6	Fire Safety Directives 2	04/09/2025				
7	Date of Inspection Name of the Inspecting Officers	Sh. Rajesh Kumar (DO)				
9	Name & Designation of Officers	Mr. Sourabh Bhardwaj				
	from the building side	2018		outle tee		
10	Year of construction	DES outdoor diary No 4981 dated 18/08/2025				
11	Applicant letter No.	requirements	Provided at Site	Remarks		
No.	Minimum standards on Fire Prevention and Fire Safety U/R 33	MR/NMI				
1	Access to Building.	9 mtr	30 mtr	MR		
•	Road width	SSX 33100,000	Directly accessible	MR		
	Gate width	6 mtr	NA NA	-NA-		
	width of internal road	-NA-	IVA			
	Number, width, type & arrangement of exits.					
2	- Ctoircase	W. II	s red	MR		
		03 Nos	Provided	MR		
8	Upper floors.Basement floor.	02 Nos	Provided	300000		
- 1	b) Width of Staircase	2 mtr & 1.50mtr	2 mtr,1.50 mtr & 1.3m	MR		
	> Upper floors > Basement floor	1.50 m & 1.50m	1.5m & 1.50 m	MR		
	c) Protection of exits	B 1 1	Provided	MR		
- 1	> Fire check door	Required	-NA-	-NA-		
	> Pressurization	-NA-	02 Provided	MR		
	a di ensignasse to terrace	Required	Provided	MR		
		Required		MR		
A		1.50 & 2m	Provided	IVIIC		
				MR		
3	Compartmentation. • Fire check door.	Required	Provided	MR		
	Fire check door. Sealing of electrical shafts.	Required	Provided	MR		
	Sealing of electrical shares.	Required	Provided	MR		
	Fire rating of shaft door.	Required	Provided			
	Water curtain	Required	Provided	MR		
	Fire dampers.			1 m		
4.	Smoke Management system.	12 ACPH	Exhaust fan Provided	MR		
	Basement	12 ACPH	Exhaust fan Provided	MR		
	Upper floors					
5.	Fire Extinguishers.	Required	55 Nos	MR		
	Total numbers	ISI marked	ABC & Co2	MR		
	Types ISI Marking	Required	Provided	MR		
	ISI Marking		Targette - mpt.			
6.	First Aid Hose Reels.	02 Nos at each	Provided	MR		
	Total numbers on each floor.	30m	Provided	MR		
	 Length of hose-reel hose. 	700-700-700	Provided	MR		
		5mm	Tiovidod			
	Nozzle Diameter	Jimi				
7	Nozzle Diameter Automatic fire detection & alarming system. Type of detectors	Required	Smoke / Heat	MR		

14/15



				गमृत महा
	 Location of Repeater Panel 	-NA-	-NA-	-N/
	 Alternate source of power 	Required	Provided	MI
0	Hooter's location	Required	All floor	MI
8.	MOEFA	Required	Provided	MF
9. 10.	Public Address System	-NA-	-NA-	-NA
10.	Automatic Sprinkler System			-INA
	Basement	Required	Provided	MR
	 Upper floors 	Required	Provided	MR
11	Sprinkler above false ceiling	Required	Provided	
11.	Internal Hydrants.			MR.
	Size of Riser/Down-comer	100 mm	Provided	100
	 Number of Hydrant per floor 	02 Nos	Provided	MR
12.	• Hose box.	02 Nos	Provided	MR
14.	Yard Hydrants.		7.071404	MR
	 Total number of hydrants. 	02 Nos	Provided	
	 Hose box. 	02 Nos		MR
13.	Pumping arrangements.	02 1103	Provided	MR
	Ground Level			
	Discharge of main nump	1600 (D) (
	▶ Head of main pump	1620 LPM	Provided	MR
	Number of main pumps	70 mtr	Provided	MR
	> Jockey Pump output.	01 No	Provided	MR
	➤ Jockey Pump head.	180 LPM	Provided	MR
	Standby Pump output.	70 mtr	Provided	MR
	Standby Pump head.	1620 LPM	Provided	
	Auto Starting/Manual Stopping.	70 mtr	Provided	MR
	 ▶ Pump house access. 	Required	Provided	MR
	Tarroca I	Required	Provided	MR
	• Terrace Level		Tiovided	MR
	Discharge of pump.Head of pump.	-NA-	-NA-	
	Power supply.	-NA-	-NA-	-NA-
-	> Auto starting of pump.	-NA-	-NA-	-NA-
14.	Captive water storage for fire fighting.	-NA-	-NA-	-NA-
	Underground tank capacity.		and the first of the first	-NA-
	Draw-off connection.	75,000 Ltrs	Provided	MD
	Fire Service Inlet.	Required	Provided	MR
	Access to tank.	Required	Provided	MR
16	Overhead tank canacity	Required	Provided	MR MR
15.	Exit Signage.	10,000 Ltrs	Provided	MR
16.	Provision of Lifts.	Required	Provided	MR
	Pressurization of lift shaft.	Demonstrate	A TOP IN THE RESERVE OF THE PERSON OF THE PE	IVII
	• Pressurization of lift lobby	Required	Provided	MR
	Communication in lift cor	Required	Provided	MR
	• Fireman's switch.	Required	Provided	MR
17.	• Lift signage	Required	Provided	MR
8.	Standby Power Supply	Required	Required	MR
18.	Refuge Area	Required	Provided (DG Set)	MR
	Total area	-NA-	20100	
0	• Location	3	-NA-	-NA-
19.	Fire Control Room.	-NA-	-NA-	-NA-
	Detector system panel.	NIA		
	Flow switch panel.	-NA-	-NA-	-NA-
	Pariot.			-1VA-
	PA system panel.	-NA-	-NA-	-NA-

-NA--NA-Battery backup. -NA--NA-Building floor plan. -NA--NA-Special Fire Protection System for the LT, HT & Required MR Protection of special Risk, if any. Transformers provided with Co2 flooding

The fire protection system provided in the building were randomly checked and found some observations at the time of inspection. As per the FSG issued by this department the 2 staircases observations at the third width of 1.5 mtr each which are available on site and meeting the were recommended having width of 1.5 mtr each which are available on site and meeting the were recommended in the management has given affidavit (endorsed at C-80-79) that they will remove the requirement. The management has given affidavit (endorsed at C-80-79) that they will remove the requirement. The interest at part portion of terrace within six months and intimate this department temporary structure erected at part portion of terrace within six months and intimate this department for compliance. The existing firefighting arrangement has also been found extended to the terrace

Keeping in view of the compliances of the minimum standards of fire prevention and fire safety measures as required under the rules, it is recommending for renewal of Fire Safety

Certificate under Rule 37 of Delhi Fire Service Rules 2010.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar

Design: Divisional Officer