

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No. F6/DFS/MS/NDZ/2025/ 109

Dated:-07.103./2025

FIRE SAFETY CERTIFICATE

Issued on 07 03 2025 at New Delhi by.

DIRECTOR Delhi Fire Service

Copy to:-

1) The Chief Architect, NDMC, Palika Kendra, New Delhi.

2) The Executive Engineer, (E) Parliament Library building, CPWD Library Building, Pt. Pant Marg, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained firefighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7 The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry.
- 9. Any flammable material for interior decoration is prohibited. And use of basement shall be strictly as per BBL concerned.

INSPECTION REPORT

 Name & address of the building:- GMC Balayogi Auditorium, Parliament Library

Parliament House Compley Name 2: 11 Parliament House Complex, New Delhi.

2. Type of occupancy:-Assembly occupancy

B+ Gr.+01 upper floor

3. Type of case:-

Renewal

4. Details of previous FSC:-5. Fire safety directives No.- F6/DFS/MS/NDZ/2022/209 dated 12/05/2022.

F6/DFS/MS/1993/1007 dated 04/06/1993

6. Date of inspection:-

20/02/2025

7. Name of the inspecting officer:-

Sh. Rajinder Atwal (DO/CD) & Sh. Ravinder Singh (ADO/CC)

8. Name & designation of officer From the building side:-

Sh. Akhilesh Meena, JE Savidhan Sadan & Sh. IR Choud

9. Year of construction:-

1993

10. Applicant's letter No:-

mail id no. deleeepwed1.cpwd@nic.in dated 06.02.2025

S.No.	Minimum Standards on fire	Requirements /	Provided at site	Renewa	
4	Prevention and fire safety U/R 33	Existing arrangements	Trovided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	06 mtr.	Provided	MR	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arrang	ement of Exits		1,772	
	A. Number of staircases				
-	1. Upper floors	02 nos	02 nos	MR	
3	2. Basements	02 nos	02 nos	MR	
	B. Width of staircase	02 nos	02 nos	MR	
	1. Upper floors	2.0 mtr. each	2.0 mtr. each	MR	
	2. Basements	N/A	N/A	N/A	
-	C. Protection of exits				
1	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size (Audi)	6x1.50 mtr. & 4x1.5mt (UL)	6x1.50 mtr. & 4x1.5mt (UL)	MR	
3.	Compartmentation				
	1) Fire check door	Required	Provided	MR	
-	2) Sealing of electrical shafts	Required	Provided	MR	
	3) Fire rating of shaft door	Required	Provided	MR	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System			MR	
	1) Basements	Required	Provided	MR	
	2) Upper floors	12 ACPH	Provided	IVIK	

	1) 77 . 1			MR	
	1) Total numbers	08nos	10 nos	MR	
	2) Types	ABC, CO2 &	ABC, CO2 &		
	3) ISI marking	W. CO2	W. CO2 Yes	MR	
6.	First-Aid Hose Reel	ISI	165		
				MR	
	1) Total number of each floor	02 Nos	02nos	MR	
	2) Length of hose reel hose3) Nozzle diameter	30 m	30 m	MR	
7.		5 mm	5 mm	IVII	
7.	Automatic Fire Detection & Alarming System				
	Type of detectors Location of main panel	Smoke/beam	Provided	MR MR	
	3) Location of repeater panel	Ground floor	Provided	1000000	
	4) Alternate source of power	N/A	N/A	N/A	
	5) Hooter's Location	Required	Provided	MR	
8.	MOEFA	Ground floor	Ground floor	MR	
9.	Public Address System	Required	Provided	MR	
10.	Automatic Sprinkler System	Required	Provided	MR	
	1) Basement	T		1.00	
	2) Upper floors	Required	Provided	MR	
	3) Sprinkler above false ceiling	Required	Provided	MR	
11.	Internal Hydrants	N/A	N/A	N/A	
	1) Size of riser/down-comer	100 mm.	100		
	2) Number of hydrants per floor		100 mm.	MR	
	3) Hose box at each floor	02nos Nos.	02 nos	MR MR	
12.	Yard Hydrants 02 Nos. 02 Nos.				
	1) Total number of hydrants	02Nos.	02 Nos.) m	
	2) Hose box	02Nos.	02 Nos.	MR	
		021103.	UZ NOS.	MR	
13.	Pumping Arrangement common pump house of complex				
	Ground level	1			
	 a) Discharge of main pump 	AOCO T DO C			
		2850 LPM	2850 LPM	MR	
	b) Head of main pump	55 mtr.	2850 LPM 55 mtr.	MR MR	
	b) Head of main pumpc) Number of main pump		55 mtr.	MR	
	b) Head of main pumpc) Number of main pumpd) Jockey pump out put	55 mtr.	55 mtr. 2 Nos.	MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head	55 mtr. 2 Nos.	55 mtr. 2 Nos. 280 LPM	MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output	55 mtr. 2 Nos. 280 LPM	55 mtr. 2 Nos.	MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head	55 mtr. 2 Nos. 280 LPM 55 mtr.	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM	MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM	55 mtr. 2 Nos. 280 LPM 55 mtr.	MR MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr.	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr.	MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr.	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr.	MR MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided	MR MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr.	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr.	MR MR MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump b) Head of pump	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided	MR MR MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump b) Head of pump c) Power supply	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required 900 lpm 25mt Required	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided 900 lpm 25mt	MR MR MR MR MR MR MR MR	
	b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required 900 lpm 25mt Required Required	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided 900 lpm 25mt Provided Provided	MR	
. (b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire F	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required 900 lpm 25mt Required Required Required ighting Existin	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided 900 lpm 25mt Provided Provided	MR M	
. (b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire F 1) Under ground tank capacity	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required 900 lpm 25mt Required Required ighting Existin 2,00,000 ltrs.	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided 900 lpm 25mt Provided Provided 2,00,000 ltrs.	MR M	
. (b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire F 1) Under ground tank capacity a) Draw-off connection	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required 900 lpm 25mt Required Required Required ighting Existin 2,00,000 ltrs. Required	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided 900 lpm 25mt Provided Provided Provided 2,00,000 ltrs. Provided	MR M	
. (b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 4) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fire F 1) Under ground tank capacity	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Required 900 lpm 25mt Required Required ighting Existin 2,00,000 ltrs.	55 mtr. 2 Nos. 280 LPM 55 mtr. 4500 LPM 55 mtr. Provided 900 lpm 25mt Provided Provided 2,00,000 ltrs.	MR M	

Fire Extinguishers

N/112

_	d) Over head tank capacity	50,000 ltrs. Required	50,000 ltrs.	MR
5.	Exit Signage.	Required	provided	MR
	Provision of Lifts.			
16.	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area			
	Total area location	N/A	N/A	N/A
10	Fire Control Room	Required	Provided	MR
20.	a) Detector system panel	Required	Provided	MR
	b) Flow switch panel	Required	Provided	MR
		Required	Provided	MR
	d) Battery backup	Required	Provided	MR
	e) Building floor plan	Required	Provided	MR
	Special Fire Protection System for	27	pecial Risk,	MR

The fire protection systems provided in the auditorium building were randomly tested, checked and found functional at the time of inspection..

In view of the compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, if agreed, we may renew the FSC issued vide letter No. F6/DFS/MS/NDZ/2022/209 dated 12/05/2022. Accordingly, FSC letter is prepared and put up for kind perusal, approval and signature please.

Signature of the Inspecting Officer

Name :- Rajinder Atwal

Designation :- DO (CD)

Signature of the Inspecting Officer

Name :- Ravinder Singh Designation :- ADO (CC)

phico (2025)

ug - C

1 20 Joss

C(03/19

Anill

sent upfor keen porment

to appoint, per pert

- 13/N