

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2025/ 1159

Dated:-

18/09/2025

FIRE SAFETY CERTIFICATE

Certified that the Govt. Co-Ed. Sarvodaya Vidyalaya (School ID-1413003), Located at Ghevra, Delhi-110081, comprised of Ground + 03 Upper Floors & M.P. Hall, owned/occupied by Govt. Co-Ed. Sarvodaya Vidyalaya (School ID-1413003), was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/School/WZ/2022/1169 dated 20/10/2022. The said premise was re-inspected by the officer concerned of this department on 28/08/2025 in the presence of Sh. Jasbir Singh (Estate Manager) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 18/09/2025 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 18 09 2025 at New Delhi by.

Virendra Singh Chief Fire Officer

Ch

Copy to:-

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054

 The Principal, Govt. Co-Ed. Sarvodaya Vidyalaya (School ID-1413003), Ghevra, Delhi-110081.

Conditions for validity of fire safety certificate:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building : Govt. Co-ed. Sarvodaya Vidyalaya (School ID-

1413003) Located at Ghevra, Delhi-110081

: Educational, 2. Type of Occupancy

: Renewal, (G + 03 Upper Floor & M.P. Hall) Type of Case

: F6/DFS/MS/School/WZ/2022/1169 dated 20/10/2022 4. Details of previous NOC

: as per NBC Part-IV 5. Fire Safety directives Letter No.

: 28/08/2025 6. Date of inspection

: Aman Kumar Lathar, ADO (JWP) 7. Name of the Inspecting Officer

8. Name and designation of Officer

: Sh. Jasbir Singh (Estate Manager) from the building side

: 2021-22 9. Year of Construction

: SVG/2025/520 dated 22/07/2025 10. Applicant's letter No.

| S No | Minimum standards on fire prevention and fire safety U/R 33 | NBC Requirement/as per earlier FSC issued dated 20/10/2022 | | Provided at site | Remarks MR/NMR | | | |
|---------|---|--|--|------------------|-------------------|--|--|--|
| 1. | Access of building | | | | | | | |
| | Road width | 06 m | Provided | | MR | | | |
| | Gate width | | | Provided | MR | | | |
| | Width of internal road | NA | | NA | NA | | | |
| 2. | Number, width, Type & Arrangements of exits | | | | | | | |
| | a. Number of staircases | | | | | | | |
| - 1 | Upper floors | 04 | 04 & 01 ramp | | MR | | | |
| - 1 | Basements | NA | | NA | NA | | | |
| | b. Width of staircases | | | | | | | |
| | Upper floors | 1.5 m each | each 1.70 m x 3, 1.64 m x 1 & 2 m to 1.64 m x 1 ramp | | | | | |
| - 11 | Basements | NA | | | NA | | | |
| | c. Protection of exits | | | | | | | |
| | Fire check door | NA | | NA | NA | | | |
| | Pressurization | NA | | NA | NA | | | |
| 1 | d. No of continuous staircase to terrace | 02 | | 04 | | | | |
| | e. Width Of Corridor | 1.5 mtrs. | | Provided | MR | | | |
| | f. Door Size | | | Provided | MR | | | |
| 3. | Compartmentation | | | | | | | |
| | Fire check door | NA | NA | | NA | | | |
| | Sealing of electrical shafts | NA | | NA | NA | | | |
| | • Fire Rating of shaft door | NA | | NA | NA | | | |
| Ш | • Water Curtain | NA NA | | NA | | | | |
| 1 | • Fire Dampers | NA NA | | NA | | | | |
| 1. | Smoke managements System | | | | | | | |
| | Basements | NA | | NA | NA | | | |
| | • Upper floors | | | NA | NA NA | | | |
| | Fire Extinguishers | | | • • • • | INA | | | |
| | Total numbers | 34 nos. | | Provided | | | | |
| | Types | 1 | | MR | | | | |
| | ISI marking | ISI Marked. | | Provided | MR | | | |
| | and a second second | isi waiked. | | Provided | MR | | | |

| 5. | First – Aid Hose Reels | | | - | | | | |
|-----------|--|-------------|-----------------|----------|--|--|--|--|
| | Total numbers on each floor | 02 | 05 | M | | | | |
| - 1 | Length of hose reel hose | 30m | Provided | M | | | | |
| | Nozzle diameter | 5mm | Provided | M | | | | |
| 7. | Automatic fire detection and alarming system | | | | | | | |
| • | Type of detectors | NA | NA | N/ | | | | |
| | Location of Main Panel | NA | NA | NA | | | | |
| | Location of Repeater Panel | NA | NA | NA | | | | |
| | Alternate source of power | NA | NA | NA | | | | |
| | Hooters' Location | NA | NA | NA | | | | |
| 8. | MOEFA | NA | NA | NA | | | | |
| 9. | Public Address System | NA | NA | NA | | | | |
| 10. | Automatic Sprinkler System | | | 1 | | | | |
| 10. | Basements | NA | NA | NA | | | | |
| | Upper Floor | NA | NA | NA | | | | |
| | Sprinkler above false ceiling | NA | NA | NA | | | | |
| 11. | Internal Hydrants: | 14/1 | 1474 | INZ | | | | |
| | Size of riser/down- comer | NA | NA | NA | | | | |
| | | NA NA | NA NA | NA NA | | | | |
| | Number of hydrants per floor Hose Box | NA NA | NA NA | NA NA | | | | |
| 12. | Yard Hydrants | 11// | I IVA | INA | | | | |
| | Total number of hydrants | NA | NA | NA | | | | |
| | Hose Box | NA NA | NA NA | NA NA | | | | |
| 13. | Pumping Arrangements: | INA | IVA | INA | | | | |
| | Ground Level | | | | | | | |
| | Discharge of main pump | NA | NA | NA | | | | |
| | ➤ Head of main pump | NA | NA NA | NA NA | | | | |
| | Number of main pumps | NA | NA NA | NA NA | | | | |
| | Jockey pump out put | NA | NA NA | NA NA | | | | |
| | Jockey pump head | NA | NA NA | NA | | | | |
| | Standby Pump out put | NA | NA | . NA | | | | |
| | > Standby Pump Head | NA | NA | NA | | | | |
| | Auto Staring/Manual stopping | NA | NA | NA | | | | |
| | > Pump House Access | NA | NA | NA | | | | |
| | Terrace level Discharge of nump | | | | | | | |
| | Discharge of pumpHead of the pump | 450 lpm | 450 lpm x 2 | MR | | | | |
| | > Power supply | 40Mtr | Provided | MR | | | | |
| | Auto starting of pump | Required | Provided | MR | | | | |
| 14. | | Required | Provided | MR | | | | |
| | Under ground tank conscient | | | | | | | |
| | Draw off connection | NA NA | NA | NA | | | | |
| | Fire service inlet | NA NA | NA NA | NA NA | | | | |
| | Access to tank | NA NA | NA NA | NA NA | | | | |
| 15 | Overhead Tank capacity | 10,000Ltrs. | NA Provided. | NA | | | | |
| 16. | - Shage | Required | Provided. | MR | | | | |
| 10. | The control of Lifts | | | MR | | | | |
| | Pressurization of Lift Shaft Pressurization of lift lobby | NA | NA | NA | | | | |
| | Communication in lift Car | NA | NA . | NA | | | | |
| | Fireman's Grounding Switch | NA NA | NA | NA | | | | |
| | Lift Signage | NA NA | NA | NA | | | | |
| 17 | - I Supply | NA NA | NA | NA | | | | |
| 18 | . Refuge Area | NA | NA | NA | | | | |
| | Total areaLocation | NA | NA | | | | | |
| 19 | D. Fire control room | NA | NA NA | NA NA | | | | |
| | Detector system panel | | | | | | | |
| | Flow Switch Panel | NA | NA | NA | | | | |
| | PA System Panel | NA | NA | NA NA | | | | |
| | ▶ Battery backup | NA NA | NA | NA | | | | |
| | ➤ Building Floor Plans | INA | NA | N'A | | | | |

Special Fire Protection Systems for Required ABC type fire ext. for electrical panel Protection of special Risks, if any; The fire protection systems provided in the building were checked and found functional at the time of inspection. Note: - Management has constructed a separate M. P. Hall, have provided 06 nos. exit doors (2 m x 1, 1.5 m x 1 & 1.25 m x 3 wide) & protected with 02 nos. hose reels & hydrant. In view of the deemed compliance of the minimum standards of fire prevention and fire safety requirements under the rules, renewal of Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/WZ/2022/1169 dated 20/10/2022 is recommended under Rule 37 of the Delhi Fire Service Rules, 2010 under DFS Act 2007. Accordingly DFA is put up for approval please. ADO (JWP) Si, F.S. letter is put-up for your vignature bl.

[15] 41 a...

Sii, F.S. letter is put-up for your vignature bl.

[1] [1] [1]

[6] [0] [25]

And [w]