

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001 No F 6 / DFS / MS / 2025/ School/WZ/207 Dated: 0

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Bal Vidyalaya No. 1 (ID- 1411002) located at Shakurpur, Delhi-110034 comprised of 03 Blocks (Block 1- Ground plus three upper floors, Block 2 & 3 Ground plus first floor) was issued FSC by this department vide letter No F6/DFS/MS/School/WZ/2022/535 dated 17.05.2022. The premises was re-inspected by the officer concerned of this department on 25.02.2025 in the presence of Md. Imran Akthar (PGT, Chemistry), and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have deemed complied with fire prevention & fire safety requirements in accordance with circular issued by Director of Education letter no 3298-3398 dated 01.03.2011 and the building/ premise is fit for occupancy Group B Educational with effect from ...04/03/2025... for a period of three years, in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40, subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on .04/03/2025 at New Delhi, by

Copy to: -

- 1. The Principal, Govt. Sarvodaya Bal Vidyalaya No. 1 (ID- 1411002) located at Shakurpur, Delhi-
- The Director, Education, Government of NCT of Delhi. Old Sect. Delhi-110054.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building: Govt. Sarvodaya Bal Vidyalaya, No. 1 located at Shakurpur, Delhi- 110034.

Educational 2. Type of Occupancy

: 03 Blocks (Block 1 = G+3 & Block 2 & 3 = G+1) 3. Building Comprised of

4. Type of Case F6/DFS/MS/School/WZ/2022/535 Dated- 17/05/2022 5. Details of Previous NOC

DOE Circular Dated 01/03/2011 6. Fire Safety directives letter No :

25/02/2025 7. Date of inspection

R.K.Sinha, ADO (BW) 8. Name of Inspecting Officer

9. Name and designation of officers

: Md. Imran Akthar (PGT Chemistry) From the building side

S. No.	11. Applicant's letter No. Minimum Standards on fire prevention and fire safety U/R 3	DOE/ Inspection dated 21/04/		Provided at site	Remarks MR/NMR		
1.	Access to building			2 11 1	MR		
_	Road width	Accessible		Provided	MR(old case)		
	Gate width	5 m		3.96 m	NA NA		
	 Width of internal road 	NA		NA	IVA		
	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases		. 1=.	1 1 21 Pl 1 2 01 (da	o MR		
	Upper Floors	1 in each blo	con	ock 1= 01, Block 2= 01 (als nnected with stair of block Block 3= 02	1)		
	Basements	NA		NA	NA		
	b. Width of staircases						
	Upper Floor	1.50 m each	& conn	1 × 2.10 m, BL-2= 1.40 m nected with 2.10 m wide Bl-1 & BL-3= 2 × 1.45 m	MR(old case)		
	Basements	NA		NA	NA		
	c. Protection of exits						
	Fire check door	NA		NA	NA		
	Pressurization	NA		NA	NA		
	d. No. of continuous staircases to terrace	01 in each blo	ock	Provided	MR		
	e. Width of Corridor	1.5 m		Provided	MR		
×	f. Door Size	1 m		Provided	MR		
	Compartmentation						
	Fire check door	NA		NA	NA		
	Sealing of electrical shafts	NA NA		NA	NA		
	 Fire Rating of shaft door 	NA		NA NA	NA		
	Water Curtain	NA		NA	NA		
	Fire Dampers	NA		NA	NA		
	Smoke Management System						
	Basements	NA		NA	NA		
	Upper floors	Required		Naturally Ventilated	MR		
5.	Fire Extinguishers						
	Total numbers	20 Nos.		42 Nos.	MR		
	• Types	ABC/ Co2 Ty	ре	Provided	MR		
	IS marking	Required		Provided	MR		
_	First-Aid Hose Reels	9					
	 Total numbers on each flo 	and the second second		02 Provided	MR		
	 Length of hose reel hose 	30 m		Provided	MR		
	Nozzle diameter	5 mm		Provided	MR		
	Automatic fire detection and ala	rming system					
	Type of detectors	NA		NA	NA		
	Location of Main Panel	NA		NA	2-902/20		
	 Location of Repeater Pane 	e ecessis		NA NA	NA		
		1111		IVA	NA		

	N-19						
		NA	NA NA				
Alternate source of power	NA		NA				
Alternate source of power	NA	NA	NA				
Hooters' Location	ŇA	NA	MR				
MOEFA	Required	Provided					
Public Address System	Requires	NA	NA				
0. Automatic Sprinkler System	NA	NA NA	, NA				
Basement	NA		NA				
Ground Floor	NA	NA					
Sprinkler above false ceiling			MR				
1 Internal Hydrants	Required	Provided	MR				
Size of riser/down-comer	Required	Provided	MR				
Number of hydrants per floor	Required	Provided	** AND				
Hose Box		-	NA				
2. Yard Hydrants	NA	NA	NA				
Total number of hydrants	NA	NA					
Hose Box	1800 (42)						
3. Pumping Arrangements • Ground Level		2.23	NA				
Ground Level Discharge of main Pump	NA	NA NA	NA				
	NA	NA					
> Head of Main pump		NA	NA				
> Number of main pumps	NA	NA NA	NA				
> Jockey Pump out put	NA NA	NA NA	NA				
> Jockey pump head	NA	NA NA	NA -				
Standby Pump out put	NA NA	NA	NA				
> Standby Pump Head	NA NA	NA	NA				
➤ Auto Starting/Manual	NA	1 30.90.0					
Stopping > Pump House Access	NA	NA	NA				
Terrace level							
	450 lpm	2 × 450 lpm	MR				
> Discharge of pump	40 m	Provided	MR				
> Head of the pump	1.2 000						
> Power Supply	Required	Provided	MR				
> Auto Starting of pump	Required	Provided	MR				
14. Captive Water Storage for fire fightin	Captive Water Storage for fire fighting						
Underground tank capacity	NA	· NA	, NA				
> Draw-off connection	NA .	NA	NA NA				
> Fire service inlet	NA	NA	NA				
> Access to tank	NA	NA	NA				
Overhead Tank capacity	10,000 ltrs	Provided	MR				
15. Exit Signage.	Required	Provided	MR				
16. Provision of Lifts.	Provision of Lifts.						
Pressurization of Lift Shaft	NA	NA	NA				
	****		NA				
	NA	NA					
Pressurization of Lift lobby	NA NA	NA NA	NA				
Pressurization of Lift lobby Communication In lift Car	NA ,	NA	NA				
Pressurization of Lift lobby	NA NA	NA NA	NA NA				
Pressurization of Lift lobby Communication In lift Car	NA NA NA	NA NA NA	NA NA NA				
 Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch 	NA NA	NA NA	NA NA				
 Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 	NA NA NA	NA NA NA	NA NA NA				
Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 17. Standby power supply 18. Refuge Area.	NA NA NA NA	NA NA NA	NA NA NA				
Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage 17. Standby power supply 18. Refuge Area.	NA NA NA	NA NA NA NA	NA NA NA NA				
 Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area 	NA NA NA NA	NA NA NA NA	NA NA NA NA				
Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location	NA NA NA NA	NA NA NA NA	NA NA NA NA				

<i>k</i> = 2				
A System Panel	NA	NA	NA	
attery backup	NA	NA	NA	
uilding Floor Plans	NA	NA	NA	
ire Protection System for n of special Risks, if any:	NA	NA	NA	
	attery backup uilding Floor Plans ire Protection System for	A System Panel NA attery backup NA uilding Floor Plans NA ire Protection System for NA	A System Panel NA NA attery backup NA NA uilding Floor Plans NA NA ire Protection System for NA NA	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of deemed compliance of the minimum standards of fire prevention and fire safety measures as required under DOE Circular No. 3298-3398 dated 01/03/2011, it is recommended to renew the Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/WZ/2022/535 dated 17/05/2022.

> Signature of Inspecting Officer Name: Rajeev Kumar Sinha Designation: ADO/B.W.

Dycfolo

8m, F.T Letter in proto for again plus