GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI** 

No. F6/DFS/MS/School/WZ/2025/894

Dated: 14 07 2025

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Co-ed Vidyalaya, located at H-Block, Karampura, New Delhi-110015. (School ID-1516104), comprised of total 04 blocks, 03 blocks (ground + 01 & 1 block ground floor only) A, C & D block (ground + 01 upper floor & b block (ground floor only), owned/Occupied by Govt. Sarvodaya Co-ed Vidyalaya, was issued FSC vide letter No F6/DFS/MS/School/WZ/2022/761 dated 15/07/2022. The premises was reinspected by the officer concerned by this department on 02/07/2025, in the presence of Dr. Jawahar Lal Sharma (H.O.S) and observed that all the fire prevention & fire safety arrangements provided in the premises found in good working condition. That the building/premises have deemed complied with fire prevention and fire safety requirements in accordance with the Circular No.F.16/Estate/CC/Fire Safety/2011/3298 to 3398 dated 01/03/2011 and found that the building / premises is fit for the occupancy class "Educational" Group B with effect from 14.0.7.20.25.. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. Condition mentioned below.

Issued on ... 14 07 2025 at New Delhi.

Copy to:

1. Director of Education, GNCT of NCT of Delhi, Old Secretariat.

2. The Principal, Govt. Sarvodaya Co-ed Vidyalaya, located at H-Block, Karampura, New Delhi-110015. (School ID-1516104). Email ID:-1516104zone16@gmail.com.

## Conditions for the validity of FSC:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. Fire fighting system which is provided in the building should be working condition for children safety.

| A. C. | Nome & add Col   | NoreC'  | TION REPOR                           | <u>RT</u>  |                    |          |
|-------|--|---|--------------------------------------|--|--------------------|----------|
| 1.    | Name & address of the building   | Govt. Sarvodaya Co-ed Vidyalaya, located at H-Blo |                                      |  |                    |          |
| 200   |  | Karamp  | ura, New Delhi                       | i-110015.(School ID-15   | 16104)             |          |
| 2.    | Type of Occupancy  | Educational                                       |                                      |  |                    |          |
| 3.    |  | Renewal   |                                      |  |                    |          |
| 4.    | Details of previous NOC  | F6/DFS/   | MS/School/W                          | Z/2022/761 dated 15/07/  | 2022.              |          |
| 5.    | Fire Safety directives letter No   | 3298-33   | 98 dated 01/03/                      | /2011  |                    |          |
| 6.    | D at   | 02/07/20  | )25                                  |  |                    |          |
| 7.    | Name of the Inspecting Officers  | Sarabjee  | t Singh ADO (I                       | MN)  |                    |          |
| 8.    |  |   | har Lal Sharma                       |  |                    |          |
|       | officer of the building of the   |   |                                      |  | 100/06/2           | 102      |
| 9.    | Year of Construction   | 1960, D-b   | olock in 2013 (A                     | s per prev. Insp. Report da  | ted 29/06/2        | .022     |
| 10    |  | 26 05 W   |                                      | Joseph 04/06/2025  |                    |          |
| flaa  | Applicant's letter No.  e said school building comprised of or only) A, C & D block (ground + C vide letter no. F6/DFS/MS/School | 01 uppo<br>/WZ/202                                | 22/761 dated 1                       | lock (B.   | Rema               | ırk      |
| S.    | Minimum Standards on fire  |   | Rule 35 (6)<br>Rule 2010             | Tiovidea   | MR/N               | [M]      |
| No    | prevention and fire safety U/R 33  | DFS   | Rule 2010                            |  |                    | _        |
| 1     | Access to building   |   | 6 m                                  | Provided   | MI                 |          |
|       | Road width   |   | 4.5 m                                | Provided   | MI                 | _        |
|       | • Gate width   |   | NA NA                                | NA   | N/                 | 1        |
|       | Width of internal road     Number, Width, Type & Arranger  | ment of   | 100-1000 000                         |  |                    |          |
| 2     | Number, Width, Type & Arranges  a. Number of staircases  | ement of Exits                                    |                                      | 900  | Provided MR old ca |          |
|       | Number of starcases     Upper Floors   | Required  |                                      | Provided   | MR old cas         |          |
|       | Basements  | NA  |                                      | NA   | IVA                |          |
|       | b. Width of staircases   |   |                                      | A-BLK=2 x 1.63 m,  |                    | N        |
|       | Upper Floors   | 1.5<br>m  |                                      | C-BLK=1 x 1.45 m, D-BLK=1 x 1.54 m, K are connected with each through corridor | other              | o<br>ca  |
|       | Basements  | NA  |                                      | NA   |                    | -1       |
|       | c. Protection of exits   |   |                                      | NA   | N/                 | 4        |
|       | <ul> <li>Fire check door</li> </ul>  |   | NA                                   | NA<br>NA   | N/                 |          |
|       | Pressurization   |   | NA<br>NA                             | One  | N.                 | -        |
|       | d. No. of continuous staircases to terra   |   | 1.5 m                                | Provided   | M                  | 0.00     |
|       | e. Width of Corridor   |   | 1.0 m                                | Provided   | M                  | R        |
|       | f. Door Size   |   | 110 111                              |  |                    |          |
| 3     | Compartmentation.  • Fire check door   |   | NA                                   | NA   | N.                 | A        |
|       | • Fire check door  Sealing of electrical shafts  |   | NA                                   | NA   | N.                 | A        |
|       | Fire Rating of shaft door  |   | NA                                   | NA   | N.                 | A        |
|       | Water Curtain  | 500.00  |                                      | NA   | N.                 | A        |
|       | Fire Dampers   | NA  |                                      | NA   | N.                 | A        |
| 4     | Smoke Management System.   | N:  |                                      | -  |                    |          |
| 4     | Basements  |   | NA                                   | NA   | N                  | A        |
|       |  |   | NA                                   | NA   |                    | A        |
|       | • Upper floors   |   |                                      |  |                    | _        |
| 5     | Fire Extinguishers   |   | 22 = 22                              | 20.7   |                    |          |
| 5     | • Upper floors  Fire Extinguishers • Total numbers   |   | 22 nos.                              | 29 Provided  | M                  | IR       |
| 5     | Fire Extinguishers   |   | 22 nos.<br>D <sub>2</sub> , ABC type | 29 Provided Provided Provided  |                    | IR<br>IR |

| M | u | 1 |
|---|---|---|
| 1 | 4 |   |

|     | T  |           |                      | 100      |  |  |
|-----|--|-----------|----------------------|----------|--|--|
| 6   | First-Aid Hose Reels.  |           |                      | 1        |  |  |
|     | Total numbers on each floo                                   |           | Provided             | N        |  |  |
|     | <ul> <li>Length of hose reel hose</li> </ul>                 | NA        | Provided             | N.       |  |  |
|     | Nozzle diameter  | NA        | Provided             | N.       |  |  |
| 7   | Automatic fire detection and alar                            |           |                      |          |  |  |
|     | <ul> <li>Type of detectors</li> </ul>                        | NA        | NA                   | N/       |  |  |
|     | <ul> <li>Location of Main Panel</li> </ul>                   | NA        | NA                   | NA.      |  |  |
|     | <ul> <li>Location of Repeater Panel</li> </ul>               | NA        | NA                   | N.A      |  |  |
|     | <ul> <li>Alternate source of power</li> </ul>                | NA        | NA                   | NA       |  |  |
| 200 | Hooters' Location  | NA        | NA                   | NA       |  |  |
| 8   | MOEFA  | NA        | NA                   | NA       |  |  |
| 9   | Public Address System.                                       | NA        | NA                   | NA       |  |  |
| 10  | Automatic Sprinkler System.                                  |           |                      | -        |  |  |
|     | Basement   | NA        | NA                   | NA       |  |  |
|     | Upper Floor  | NA        | NA                   | NA NA    |  |  |
|     | Sprinkler above false ceiling                                | 100000000 | NA                   | NA NA    |  |  |
| 11  | Internal Hydrants  |           |                      | IVA      |  |  |
|     | Size of riser/down-comer                                     | NA        | NA                   | NT4      |  |  |
|     |  |           | NA<br>NA             | NA NA    |  |  |
|     | Number of hydrants per floor     Hose Box                    | NA NA     | NA<br>NA             | NA<br>NA |  |  |
| 10  |  | INA       | NA NA                | NA       |  |  |
| 12  | Yard Hydrants.   |           |                      |          |  |  |
|     | Total number of hydrants                                     | NA        | NA                   | NA       |  |  |
|     | Hose Box   | NA        | NA                   | NA       |  |  |
| 13  | Pumping Arrangements.  |           |                      |          |  |  |
|     | Ground Level   |           |                      |          |  |  |
|     | <ul> <li>Discharge of main Pump</li> </ul>                   | NA        | NA                   | NA       |  |  |
|     | Head of Main pump  | NA        | NA                   | NA       |  |  |
|     | Number of main pumps   | NA        | NA NA                | NA<br>NA |  |  |
|     | Jockey Pump out put  | NA        | NA<br>NA             | NA<br>NA |  |  |
|     | Jockey pump head   | NA        | NA<br>NA             | NA<br>NA |  |  |
|     | Standby Pump out put   | NA<br>NA  | NA<br>NA             | NA<br>NA |  |  |
|     | Standby Pump Head  | NA<br>NA  | NA<br>NA             | NA<br>NA |  |  |
|     | > Auto Starting/ Manual stopping                             | NA<br>NA  | NA<br>NA             | NA<br>NA |  |  |
|     | > Pump House Access  | INA       | AMA                  |          |  |  |
|     | Terrace level     Discharge of nump                          | NA        | 2 x 450 LPM Provided | NA       |  |  |
|     | <ul><li>Discharge of pump</li><li>Head of the pump</li></ul> | NA<br>NA  | 40 m Provided        | NA<br>NA |  |  |
|     | <ul><li>Head of the pump</li><li>Power Supply</li></ul>      | NA<br>NA  | Provided             | NA       |  |  |
|     | > Auto Starting of pump                                      | NA NA     | Provided             | NA       |  |  |
| 14  | Captive Water Storage for fire fighti                        |           |                      |          |  |  |
| 14  | Underground tank capacity                                    | NA        | NA                   | NA       |  |  |
|     | > Draw-off connection  | NA        | NA                   | NA       |  |  |
|     | > Fire service inlet   | NA        | NA                   | NA       |  |  |
|     | > Access to tank   | NA        | NA                   | NA       |  |  |
|     | <ul> <li>Overhead Tank capacity</li> </ul>                   |           | 10,000 ltrs Provided | MR       |  |  |
| 5   | Exit Signage.  | ,NA       | NA NA                | NA       |  |  |
| 7   |  |           | 1                    |          |  |  |

|    | 1            |   | MLB   |     |       |  |  |
|----|--------------|---|-------|-----|-------|--|--|
|    |              | on of Lifts   |       |     |       |  |  |
| 1  |              | Pressurization of Lift Shaft                              | NA    | NA  | NA    |  |  |
|    |              | Pressurization of Lift lobby                              | NA    | NA  | NA    |  |  |
|    | •            | Communication In lift Car                                 | NA    | NA  | NA    |  |  |
|    | •            | Fireman's Grounding Switch                                | NA    | NA  | NA    |  |  |
| 1  | •            | Lift Signage  | NA    | NA  | NA    |  |  |
| 17 | Standb       | y power supply  | NA    | NA  | NA    |  |  |
| 18 | Refuge Area. |   |       |     |       |  |  |
|    | >            | Total Area  | NA    | NA  | NA    |  |  |
|    | >            | Location  | NA    | NA  | NA    |  |  |
| 19 | Fire Co      | ntrol Room  |       |     | NA    |  |  |
|    | •            | Detector System Panel                                     | NA    | NA  | NA NA |  |  |
|    | 350          | Flow Switch Panel   | NA    | NA  |       |  |  |
|    |              |   | NA    | NA  | NA    |  |  |
|    | •            | PA System Panel   | NA    | NA  | NA    |  |  |
|    | •            | Battery backup  | NA NA | NA  | NA    |  |  |
|    | •            | Building Floor Plans                                      |       | NA  | NA    |  |  |
| 20 | Specia       | Fire Protection Systems for ion of special Risks, if any: | NA    | 147 |       |  |  |

The fire protection systems provided in the building were checked and found functional at the time of inspection.

258 ADO MN 64 07 2025 Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules, the NOC vide letter no F6/DFS/MS/School/WZ/2022/761 dated 15/07/2022, renewal under the rule 35 of the Delhi Fire Service rules 2010 is recommended.

Q40120(W12)

Signature of the Inspecting Officer Sarabjeet Singh ADO (MN)

Directa My 11 100/m

Sio, E. T is put up for your kind

persued s Signahunps;

11129111