GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2025/ School/WZ/ 271

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Kanya Vidyalaya (ID- 1208090) located at Inderlok, Delhi-110035 comprised of 03 Blocks (One Block- Ground plus three upper floors) & Two Blocks (Ground plus First floor) were issued FSC by this department vide letter No F6/DFS/MS/School/WZ/2022/46 dated 14.01.2022 & F6/DFS/MS/School/WZ/2021/914 dated 01.11.2021. The premises was re-inspected by the officer concerned of this department on 11.03.2025 in the presence of Sh. Dinesh Singh Rawat (Estate Manager), and observed that all the fire prevention and fire safety arrangements as provided in the premises found in good working condition. The premises have deemed complied with fire prevention & fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premise is fit for occupancy Group B Educational with effect from .. 20. 93 2025 for a period of three years, in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40, subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 20 03 2025 at New Delhi, by

Copy to: -

1. The Director, Education, Government of NCT of Delhi. Old Sect. Delhi-110054.

2. The Principal, Govt. Sarvodaya Kanya Vidyalaya (ID- 1208090) located at Inderlok, Delhi-110035.

Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

5. This certificate cannot be treated in any case for regularizations of unauthorized construction.

6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

8. The electric meter and electrical panel under the staircases of (G+1) blocks have to be removed or been segregated within a time period of three months from the date of issuance of this fire safety certificate. Failing to do so the Fire safety Certificate will be null and void.

INSPECTION REPORT

1. Name & address of the building: Govt. Sarvodaya Kanya Vidyalaya (ID-1208090) located at Inderlok

Delhi- 110035.

2. Type of Occupancy : Educational

3. Building Comprised of : 03 Blocks= One Block- (Ground plus Three Upper Floors)

Two Blocks- (Ground and First Floor)

4. Type of Case : Renewal

5. Details of Previous NOC : (G+3) Block- F6/DFS/MS/School/WZ/2022/46 Dated- 14/01/2022 &

(G+1) Blocks- F6/DFS/MS/School/WZ/2021/914 Dated- 01/11/2021

6. Fire Safety directives letter No : NBC Part IV & DOE Circular Dated 01/03/2011

7. Date of inspection : 11/03/2025

8. Name of Inspecting Officer : R.K.Sinha, ADO (BW)

9. Name and designation of officers

From the building side : Sh. Dinesh Singh Rawat (Estate Manager)

O. Year of Construction : (G+1) Blocks- 1998 & (G+3) Block- 2020-21

_	1. Applicant's letter No. : Minimum Standards on fire	NBC/BBL/ DOE	88 & 13089 dated 03/03/2025 Provided at site	Remarks		
S.	prevention and fire safety U/R 33	NBC/BBL/ BOE	1 Tovided at 5115	MR/NMR		
No.	Access to building					
1.	Road width	6 m	Provided	MR		
	Gate width	4.5 m	Provided	MR		
	Width of internal road	NA	NA	NA		
2.	Number, Width, Type & Arrange	167.000.00 E	W II	5		
	a. Number of staircases					
	Upper Floors	(G+3) Block- 04, (G+1) Blocks -01 in each block	Provided	MR		
	Basements	NA	NA	NA		
	b. Width of staircases	100				
	Upper Floor	1.50 m each	Provided	MR		
		NA	NA	NA		
54	Basements Continue	635.5				
	c. Protection of exits	NA	NA	NA		
	Fire check door	NA NA	NA	NA		
	Pressurization	(G+1) Blocks- NF		MR		
	d. No. of continuous staircases to terrace	(G+3) Block- 02	(G+3) Block- Provided	i		
	e. Width of Corridor	1.50 m	Provided	MR		
1.00	f. Door Size	(G+3) Block-1.20 m & (G+1) Blocks-1 m	& Provided	MR		
3.	Compartmentation					
J.,	Fire check door	NA	NA	NA		
	The second of th	NA	NA	NA		
	Sealing of electrical shafts	NA	NA	NA		
	Fire Rating of shaft door	NA NA	NA	NA		
	Water Curtain	NA NA	NA	NA		
	Fire Dampers	IVA	NA NA			
4.	Smoke Management System		N/A	NA		
	Basements	NA	NA			
.*	Upper floors	Required	Naturally Ventilated	MR		
5.	Fire Extinguishers			100		
J.	Total numbers	45 Nos.	Provided	MR		
	Types	ABC/ Co2 Type	Provided	MR		
	IS marking	Required	Provided	MR		
6	First-Aid Hose Reels	Aid Hose Reels Required in (G+3) Block				
6.	Total numbers on each floor	03	Provided	MR		
	Length of hose reel hose	30 m	Provided	ovided MR		
	Nozzle diameter	5 mm	Provided	MR		
	Automatic fire detection and alarm	zate diameter				
7	Type of detectors	NA NA	NA	NA		
	70.70	NA NA	NA	NA		
	 Location of Main Panel 	a./	1373	* 14 *		

	N
N	+60

PA

1		10			NIA.
-	 Location of Repeater Panel 	NA	NA -		NA F
	 Alternate source of power 	NA	NA		INA
		NA	00	V	NA
-	Hooters' Location	199	NA		NA
	OEFA	NA	NA		,NA
P	Public Address System NA NA				
A	utomatic Sprinkler System		NA		NA
-	Basement	NA	NA NA		NA
	Ground Floor	NA			NA
	 Sprinkler above false ceiling 	NA NA			1
I	Internal Hydrants				
	Size of riser/down-comer NA NA			NA NA	
	 Number of hydrants per floor 	NA	NA		NA
	Hose Box	NA	NA		
	Yard Hydrants	1, II <u>UU</u>	571		NA
	 Total number of hydrants 	NA	NA NA		NA
	Hose Box	NA	NA		e IVA
.]	Pumping Arrangements				
, j	Ground Level		274		. NA
	Discharge of main Pump	NA	NA NA		NA
	➤ Head of Main pump	NA	7.04%		NEOROS
+	> Number of main pumps	NA	NA		NA
-	> Jockey Pump out put	NA	NA		- NA
-	> Jockey pump head	NA	NA	1	NA
+	> Standby Pump out put	NA	NA	2	NA
+	> Standby Pump Head	NA	NA		NA
	Auto Starting/Manual	NA NA	NA		NA
	> Pump House Access	NA	. NA		NA
	Required in (G+3) Block				
	Terrace level			~ 1	MR
	Discharge of pump	450 lpm	2 × 450 lpm Provided		MR
		40 m	Provid	ied	14114
	➤ Head of the pump	D	Provided		- MR
	> Power Supply	Required Provided Required Provided			MR
	> Auto Starting of pump		in (G+3) Block	-	garan ana
14.	Captive Water Storage for fire fighti	0	NA NA		NA
	 Underground tank capacity 	NA	N/		NA
	> Draw-off connection	NA	N/		NA
	> Fire service inlet	NA	N/	11.7	NA
	> Access to tank	NA			MR
	Overhead Tank capacity	10,000 ltrs	Prov		MR
		Required Provided		lucu	WIIN
15.	Exit Signage.				
Sant S	Provision of Lifts.		Decide 1 De		
15. 16.	Provision of Lifts.	NA NA	NA NA		NA
Sant S	Provision of Lifts. • Pressurization of Lift Shaft	NA NA			NA NA
Sant S	Provision of Lifts. • Pressurization of Lift Shaft • Pressurization of Lift lobby	NA	NA NA NA		
Sant S	Provision of Lifts. • Pressurization of Lift Shaft • Pressurization of Lift lobby • Communication In lift Car	NA NA	NA NA		NA NA
Sant S	Provision of Lifts. • Pressurization of Lift Shaft • Pressurization of Lift lobby • Communication In lift Car • Fireman's Grounding Switch	NA NA NA	NA NA NA		NA NA NA
Sant S	Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	NA NA NA NA	NA NA NA NA		NA NA NA NA
Sant S	Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch	NA NA NA	NA NA NA		NA NA NA
16.	Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage	NA NA NA NA	NA NA NA NA		NA NA NA NA
16.	Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area.	NA NA NA NA	NA NA NA NA		NA NA NA NA
16.	Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area	NA NA NA NA	NA NA NA NA		NA NA NA NA NA
17.	Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location	NA NA NA NA NA	NA NA NA NA NA		NA NA NA NA NA
16.	Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area	NA NA NA NA NA	NA NA NA NA NA		NA NA NA NA NA

7	/ 337	10-21			
	Flo	w Switch Panel	NA	NA	NA
$\langle \ \rangle$	• PA	System Panel	NA	NA	NA
>	• Ba	ttery backup	NA	NA	NA
l .	• Bu	lding Floor Plans	NA	NA	NA
20.		e Protection System for of special Risks, if any:	Required	ABC type fire extinguisher near electrical panel	MR

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: Electrical panel and electric meter found installed under the staircases of (G+1) Blocks

which have to be removed or been segregated.

Keeping in view of deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, it is recommended to renew the Fire Safety Certificate issued vide letter no. F6/DFS/MS/School/WZ/2022/46 dated 14/01/2022 & F6/DF\$/MS/School/WZ/2021/914 dated 01/11/2021 merged into one FSC under rule 37 of the Delhi Fire Service Rules, 2010.

> Signature of Inspecting Officer Name: Rajeev Kumar Sinha Designation: ADO/B.W.

Ly cholo