

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTER: DELHI FIRE SERVICE: NEW DELHI- 110001**



No. F6/DFS/MS/School/WZ/2025/ 288

Dated: 26/03/2025

-23414000

## FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Kanya Vidyalaya (School Id-1617005) Located at Ranhaula, New Delhi-110041, comprised of 02 blocks of Ground + 03 Upper Floors only, owned/occupied by the Govt. Sarvodaya Kanya Vidyalaya (School Id-1617005), was issued Fire Safety Certificate by this department Vide Letter No. F6/DFS/MS/WZ/2021/996 dated 07/12/2021. The said premises was re-inspected by the officer concerned of this department on 10/03/2025 in the presence of Sh. Vijay Kumar Pandey (Estate Manager) and found that the premises/building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the premises/building is fit for occupancy class "Educational Building" Group B with effect from 26/03/2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010 printed below.

Issued on .. 26/03/2025 at New Delhi by.

Copy to: -

1. The Director, Directorate of Education, GNCT of Delhi, Old Secretariat Delhi – 110054.

2. The Principal, Govt. Sarvodaya Kanya Vidyalaya, ID-1617005, Ranhaula, New Delhi-110041.

## Conditions for the validity of fire safety certificate:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its

## INSPECTION REPORT

1. Name and address of the building: Govt. Sarvodaya Kanya Vidyalaya (ID-1617005) located at Ranhaula, Delhi-110041

2. Type of Occupancy

: Educational,

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/WZ/2021/996 dated 07/12/2021

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 10/03/2025

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Vijay Kumar Pandey (Estate Manager)

9. Year of Construction

: 2020

10. Applicant's letter No.

: email dated 24/02/2025

This school building is comprised of 02 blocks - G+03 Upper Floors.

S No	Minimum standards on fire prevention and fire safety U/R 33	NBC (Part-IV) Requirements	Provided at site	Remarks MR/NMR		
1.	Access of building					
	Road width	06 m	Provided	MR		
	Gate width	4.5 m	Provided	MR		
1	<ul> <li>Width of internal road</li> </ul>	NA	NA	NA		
2.	Number, width, Type & Arrangements of exits					
	a. Number of staircases		DI 1 E 02	MR		
	Upper floors	02 nos. in each block	Block E – 03 Block F - 02	MIK		
	Basements	NA	NA	NA		
	b. Width of staircases	leaster of	N NAC IN N			
	Upper floors	1.5 m in each block	Provided	MR		
	Basements	NA	NA	NA		
	c. Protection of exits					
	Fire check door	NA	NA	NA		
	Pressurization	NA	NA	NA		
	d. No of continuous	02 nos. in each	Block E - 03	MR		
	staircase to terrace	block	Block F - 02			
	e. Width Of Corridor	1.5 m	Provided	MR		
Ш	f. Door Size	1.2 m	Provided	MR		
1	Compartmentation					
+	Fire check door	NA	NA	NA		
	<ul> <li>Sealing of electrical shafts</li> </ul>	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	<ul> <li>Fire Dampers</li> </ul>	NA	NA	NA		
4.	Smoke managements System			X - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		
+	Basements	NA	NA	NA		
	Upper floors	NA .	NA	NA		

-	ч	12

. T	Fire Extinguishers	A Trible		6
-	Total numbers	40 nos.	98 nos.	) (D
	• Types	ABC & CO <sub>2</sub>	Provided Provided	MR MR
	IS marking	ISI marked	Provided	MR
	First – Aid Hose Reels	TOT HILLIACO	riovided	MIK
-	Total numbers on each floor	Block E - 02	Block E - 03	MR
	Total numbers on each floor	Block F - 01	Block F - 01	MIK
	Length of hose reel hose	30 m	Provided	MR
	Nozzle diameter	5 mm	Provided	MR
7.	Automatic fire detection and alarming		110 /1000	IVIIX
•	Type of detectors	NA	NA	NA
	Location of Main Panel	NA	NA	NA
	Location of Repeater Panel	NA	NA	NA
	Alternate source of power	NA	NA	NA
	Hooters' Location	NA	NA	NA
•		NA	NA	NA
3.	MOEFA Public Address System	NA	NA NA	NA
9.		11/21	141	1423
10.	Automatic Sprinkler System	NA	NA	NA
	Basements     Hange Floor	NA	NA	NA
	Upper Floor     Sprinkler shows false ceiling	NA	NA NA	NA
1 1	Sprinkler above false ceiling  Internal Hydrants:    Internal Hydrants:		ratio Attack	
11.	Internal Hydrants:  • Size of riser/down- comer	NA	NA	NA
	The state of the s	NA NA	NA NA	NA
	Number of hydrants per floor     Haza Boy	NA	NA NA	NA
10	Hose Box  Variable Handson to	P. St. School	PV-STID.	
12.	Yard Hydrants	NA	NA	NA.
	Total number of hydrants	NA NA	NA NA	NA
10	Hose Box  Paragraphy  Among among a	13/2	weeter to	
13.	Pumping Arrangements:		K ving age 11	6.7
	Ground Level  Discharge of main nump	NA	NA	NA
	Discharge of main pump	NA NA	NA NA	NA
	<ul><li>Head of main pump</li><li>Number of main pumps</li></ul>	NA	NA	NA
		NA	NA	NA
		NA NA	NA	NA
	<ul><li>Jockey pump head</li><li>Standby Pump out put</li></ul>	NA NA	NA	NA
	Standby Pump Head	NA NA	NA	NA
	> Auto Staring/Manual	NA NA	NA	NA
	stopping	147.		
	> Pump House Access	NA a	NA	NA
	Terrace level	o tu dal		
	> Discharge of pump	450 lpm in	Provided	MR
		each block	EXTENSION IN	
	> Head of the pump	40 m	Provided	MR
	> Power supply	Required	Provided	MR
	> Auto starting of pump	Required	Provided	MR
14.				3,4200
17.	Under ground tank capacity	NA	NA	NA
	> Draw off connection	NA	NA	NA
	> Fire service inlet	NA	NA	NA
	> Access to tank	NA	NA	NA
	Overhead Tank capacity	10,000 ltrs in	Provided	MR
	Overnous rain capacity	each block		
15	Exit Signage	Required	Provided	MR
16.		Provided in	E-Block only	
10.	> Pressurization of Lift Shaft	NA	NA	NA
	> Pressurization of Lift Shart > Pressurization of lift lobby	NA	NA	NA
	Communication in lift Car	Required	Provided	MR
	Fireman's Grounding Switch		Provided	MR

_	▶ Lift Signage	NA	NA	NA	
13	Standby power supply	NA	NA	NA	
11.	Refuge Area	* - *			
18.	> Total area	NA	NA	. NA	
	> Location	NA	NA	NA	
19.	Fire control room				
17.	> Detector system panel	NA	NA	NA	
	> Flow Switch Panel	NA	NA	NA	
	> PA System Panel	NA	NA	NA	
	> Battery backup	ŇA	NA	NA	
- 1	> Building Floor Plans	NA NA	NA	NA	
			NA	NA	
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA	na were checke		

Fire protection systems provided in the building were checked and found functional at the time of inspection. Shortcomings issued vide letter no. F6/DFS/MS/WZ/2024/799 dated 03/12/2024 found rectified.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no. F6/DFS/MS/WZ/2021/996 dated 07/12/2021 renewal under rule 35 of the Delhi Fire Service Rule 2010, is recommended.

Accordingly, DFA is prepared &put up for approval please.

OCTO (WZ)

ADO (JWP)

F-F. lattu is put-up for your mondine by

(1) It I 

FUT 03/25

AND (MP)