GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001**

No. F.6/DFS/MS/Resi./SZ/2025/657

Dated: |5|12|2025

FIRE SAFETY CERTIFICATE

Certified that the Residential Blocks No. 21(01 No.) at GPRA Type-III, Kidwai Nagar (East) New Delhi-110023 all comprises of (03 Tier Basement + Ground + 14 Upper floors) was earlier issued FSC by this department vide letter No. F.6/DFS/MS/2021/64 Dt. 25/01/2021. Now, the premises was re-inspected by the officer concerned of this department on 25/11/2025 in the presence of Sh. Jai Prakash (Project Executive/NBCC) and found that the said residential building blocks have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that all the Building Blocks as mentioned above are fit for occupancy class "Group-A (Residential)" with effect from 15 12 2025 for a period of five years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38

Dy. Chief Fire Officer Delhi Fire Service

Copy to: -

- 1. The Executive Engineer, (Bldg.), NDMC, Palika Kendra, New Delhi-110002. To kindly ensure the deviation in construction if any.
- 2. Sh. R.P. Singh GM (Engg.), Project office- Redevelopment of Kidwai Nagar (East), Aurobindo Marg, Near INA Metro Station, Kidwai Nagar (East), New Delhi-110023

Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 4. All the staff members must know the correct method of operation of firefighting system.
- 5. The trained firefighting staff should be available at the site round the clock.
- 6. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning authority.
- 7. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. This fire safety certificate may not in any way be treated as regularization of unauthorized construction, if any. Basement shall be used as per BBL concerned.
- 9. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

NHO

they do to	INSPECT	TON REPORT				
1.	Name & address of the building	Residential Blocks No. 21(01 No.) at GPRA Type-III, Kidwai Nagar (East) New Delhi- 110023				
2.	Type of occupancy		Group-A "Residential"			
3.	Building Comprised of	Blk No. 21 (03 Base. + Ground + 14 Upper floors)				
4.	Type of case	Renewal				
5.	Details of previous FSC No.	F.6/DFS/MS/2	2021/64 Dt. 25/01	/2021		
6.	Fire safety directives No	F.6/DFS/MS/I	3P/2013/01 dated	02/01/2014		
7.	Date of inspection: -	25/11/2025				
8.	Name of the inspecting officer: -	Kaushal Kisho	re, ADO (SJ)			
9.	Name & designation of officer from the building side: -	Sh. Jai Prakash (Project Executive/NBCC)				
10.	Year of construction: -	2018		CD EM/		
11	Applicant's letter No: -	Letter No. NBCC/GM/EKN-SBG R.F.M/ GPRA/DFS/2025/1329 dated 30.09.2025 received through outdoor diary No. 6623 dated 03/10/2025 Provided at Remarks				
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Old NOC Requirement	Provided at site	MR/NMR		
1.	Access to Building			MR		
	Road width	12m	12m	N/A		
	Gate width	N/A	N/A	MR		
	width of internal road	6m (two side)	6m (two side)	MK		
2.	Number, Width Type & Arrangeme	ent of Exits				
16. 11	a. Number of staircases		0.31	MR		
	Upper floors	2 Nos each	2 Nos each	MR		
	Basements	27 + 2 ramp	27 + 2 ramp	IVIIC		
	b. Width of staircase		1.42	MR		
	Upper floors	1.35m	1.43m to 1.50m			
	Basements	1.35m	1.43m to 1.50m	MR		
}	c. Protection of exits			MR		
ŀ	Fire check door	Required	Provided	IVIK		
	Pressurization	Required	Natural ventilation	MR		
	d. No. of continuous staircase to terrace	2 Nos	2 Nos	MR		
	e. Width of corridor	N/A	N/A	N/A		
	f. Door size	lm	Provided (final exit)	MR		
	Compartmentation	Deguired	Provided	MR		
	Fire check door	Required	Provided	MR		
	Sealing of electrical shafts	Required	Provided	MR		
		TO 100 100 100 100 100 100 100 100 100 10	Provided	IATIC		
	Fire rating of shaft door	Required		MD		
	 Fire rating of shaft door Water curtain (Basement) 	Required N/A	Provided N/A	MR N/A		

4.	C	A.C.			
*	Smok	e Management System			- 1 m
	•	Basements	30 ACPH	M.V. Provided	MR
	•	Upper floors	12 ACPH	Natural ventilation	MR
5,	Fire	Extinguishers			
	•	Total numbers	30 Nos.	Provided	MR
	•	Types	ABC/CO ₂ /W.C O ₂	ABC & W.CO ₂	MR
	•	ISI marking	ISI marked	Provided	MR
6.	First-	Aid Hose Reel			
	•	Total number of each floor	B1 & B2=33 each B3=31 Nos. & UF= 01 No. each	B1 & B2=33 each B3=31 Nos. & UF= 01 No. each	MR
	•	Length of hose reel hose	30m	Provided	MR
	•	Nozzle diameter	5mm	Provided	MR
7.	Autor	matic Fire Detection & Ala	Jiiiii	riovided	MK
	•	Type of detectors (Smoke)	Required	Smoke & Heat	MR
	•	Location of main panel	Required	Control Room	MR
	•	Location of repeater panel	N/A	N/A	N/A
	•	Alternate source of power	Required	Provided	MR
	•	Hooter's Location	Required	Provided	MR
8.	MOE		Required	Provided	MR
9.	Public	c Address System	Required	Provided	
10.	Autor	natic Sprinkler System		11011404	MR
	•	Basement	Required	Provided	MD
	•	Upper floors	N/A	N/A	MR
	•	Sprinkler above false ceiling	N/A	N/A	N/A N/A
11.	Intern	al Hydrants			
	•	Size of riser/down-comer	100mm	Provided	MD
	•	Number of hydrants per floor	01 No.	B1 & B2=33 each B3=31 Nos. &	MR MR
	•	Hose box	01 No.	UF= 01 No. each B1 & B2=33 each	
			01 110.	B3=31 Nos. & UF= 01 No. each	MR
2.	Yard F	lydrants		or or ivo. each	
_	•	Total number of hydrants	01 No.	01 No.	1.00
ī.	•	Hose box	01 No.	01 No.	MR
3.	Pumpir	ng Arrangement	N 14 200 20	V1 110,	MR
		ound level	Common pump ho	115/6/1	

N/72

	Discharge of main pum	(H&S) 2850 LPM	Hyd. & Sprinkler (H&S) 2850 LPM	140
		(each) Water Curtain (WC): 2 of 2280 LPM	(each) Water Curtain (WC): 2 of 2280 LPM	MR
	Head of main pump	(H&S): 90m (each) (WC): 45m (each)	(H&S): 90m (each) (WC): 45m (each)	MR
	Number of main pumps	4 Nos	4 Nos	MR
	Jockey pump out put	2 of 280 LPM	2 of 450 LPM	MR
	Jockey pump head	(H&S): 90m & 60m	(H&S): 90m & 60m	MR
	Stand by pump output	2850 LPM	2850 LPM	MR
	Stand by pump head	90m	90m	MR
	Auto starting/Manual stopping	Required	Provided	MR
_		Required	Provided	MR
	Pump House Access The second se			2.2270
	Terrace level	N/A	N/A	N/A
	Discharge of pump	N/A HEITIG	abriivN/A	N/A
	Head of pump	N/A	N/A	N/A
	Power supply	N/A	N/A	N/A
	Auto starting of pump Auto Starting of pump	27-37-48-15-15-15-15-15-15-15-15-15-15-15-15-15-		
4.	Captive Water Storage for Fire • Underground tank	2,00,000 ltr	Provided	MR
	capacity	Required	Provided	MR
	Draw-off connection	Required	Provided	MR
	Fire service inlet	Required	Provided	MR
	Access to tank Overhead tank capacity	10,000 ltr	10,000 ltr (Each Blk)	MR
		Required	Provided	MR
5.	Exit Signage.	3.54	E. I	
6.	Pressurization of lift	Required	Provided	MR
	shaft Pressurization of lift lobby	Required	Provided	MR
	Communication in lift	Required	Provided	MR
	car	Required	Provided	MR
	Fireman's switch	Required	Provided	MR
	Lift signage	Required	Provided (DG Set)	MR
7.	Stand by Power Supply	Moderne		
8.	Refuge Area	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	• Location	N/A		
),	Fire Control Room		Provided	MR
	 Detector system panel 	Required	N/A	N/A
	 Flow switch panel 	N/A	Provided	MR
	 PA system panel 	Required	Provided	MR
	Battery backup	Required	Contract Con	MR
	Building floor plan	Required	Provided ion system provided	N/A

N/73

Residential Blocks No. 21(01 No.) at GPRA Type-III, Kidwai Nagar (East) New Delhi-11002

The fire protection systems provided in the building/premises were checked, tested at random and functional at the six and a s found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and ty measures as a second the deemed compliance of the minimum standards of fire prevention and the minimum standards of the mini fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/2021/64 Dt. 25/01/2021 (Residential D). We Delhi-25/01/2021 (Residential Blocks No. 21(01 No.) at GPRA Type-III, Kidwai Nagar (East) New Delhi-110023, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for approval & signature please.

Signature of the Inspecting Officer

Name: Kaushal Kishore Designation: ADO (SJ)

hinder Singh