

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001



Dated: 20/08/2025

No. F6/DFS/MS/School/WZ/2025/ 1028

FIRE SAFETY CERTIFICATE

Certified that the GR International School, Pooth Khurd, Main Bawana Road, Delhi110039, comprised of Ground + 03 upper floors owned/ occupied by GR International
School have complied with the fire prevention and fire safety requirements in accordance with
rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of fire service
on dated 14.07.2025 in the presence of Mr. Umesh and that the building/ premise is fit for
occupancy "Group B Educational" with effect from 2008 2025 for a period of three
years, in accordance with the Rule 36 unless renewed under Rule 37 or sooner cancelled under
Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service
Rules, 2010.

Issued on 20/08/2025 at New Delhi by

(Virendra Singh)
Chief Fire Officer
Delhi Fire Service

Copy to:

- 1. The Principal, GR International School, Pooth Khurd, Main Bawana Road, Delhi-110039.
- 2. The Director of Education, GNCT of Delhi Old Secretariat, Delhi-110054 Conditions for validity of Fire Safety Certificate;
- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/ http://www.delhi.gov.in/wps/wcm/connect/doit_fire/FIRE/Home/Forms

1			N 18				
(1	, , , , , , , , , , , , , , , , , , ,		INSPEC	CTION REPORT			
1.	Name &	address of the building GR International School, Pooth Khurd, Main Bawana Road, Del					
2.	Type of	Occupancy	110039		en entre		
3.	Compris	occupancy ed of building	Educat				
111985	Type of	900		1 + 03 upper floors			
5.	Details o	f Previous NOC	New Case (Ground + 03 upper floors) F.6/DFS/MS/2022/School/WZ/122 dated 07.02.2022 perv				
			NOC 02 blocks, ground + 01 upper floors				
7. Date of inspection 14				NBC Part-IV			
			14.07.2025				
Name of Inspecting Officer Name and designation of officers				ini) & D.B Mukherjee, I	OO (NW)		
	From the	building side	Mr. Un	nesh			
10	. Year of (Construction	2007 &	2015			
11	. Applicar	at's letter No.	and a contract of the contract	e-mail dated 08.07	7.2025		
5.	Minimu	m Standards on fire prev	ention	NBC Part-IV	Provided at site	Remarks	
No	and fire	safety U/R 33		Requirement		MR/NMI	
1.	Access t	o building		1			
	• F	Road width		6m	Accessible	MR	
		Gate width		4.5m	Directly accessible	MR	
5	• 7	Vidth of internal road		-NA-	-NA-	-NA-	
2.	Number	Width, Type & Arrang	ement of	Exits			
	a. Numl	er of staircases	W. Carlotte				
	i 🗨	Upper Floors		02nos.	02nos.	MR	
	s (()	Basements		-NA-	-NA-	-NA-	
	b. Widtl	of staircases			n de		
	•	Upper Floor		1.5m	1.80m & 1.85m	MR	
	•	Basements		-NA-	-NA-	-NA-	
	c. Prot	ection of exits				om(0.00). 25	
	•	Fire check door		-NA-	-NA-	-NA-	
	•	Pressurization		-NA-	-NA-	-NA-	
	d. No. o	f continuous staircases to	terrace	Required	Provided	MR	
	e. Width of Corridor			1.5m	2.40m	MR	
	f. Door	Size		-NA-	-NA-	-NA-	
3.	Compar	tmentation				150 (50)	
	a) F	ire check door		-NA-	-NA-	-NA-	
	b) S	ealing of electrical shafts		-NA-	-NA-	-NA-	
	c) F	0.1.0.1		-NA-	-NA-	-NA-	
	d) V			-NA-	-NA-	-NA-	
	e) Fire Dampers		-NA-	-NA-	-NA-		
4.	Smoke N	Management System					
-	a) Basements		-NA-	-NA-	-NA-		
	b) Upper floors		12 a/c per hour	Natural ventilation	MR		
5.	Fire Ext	inguishers					
٥.	a) T	Total numbers		27nos.	Provided	MR	
	/	Types		ABC/CO2	ABC/CO2	MR	
	c) 15	S marking		ISI marked	Yes .	MR	
<u> </u>		I Hose Reels					
6.	\ T	Total numbers on each 11001		02nos.	Provided	MR	
	a)	Length of hose reel hose		30mm	Provided	MR	

	a) Na1 !!		- 11.1				
7.	c) Nozzle diameter	5m	Provided	MI			
/•	Automatic fire detection and alarming system						
	a) Type of detectors	-NA-	-NA-	-NA-			
	b) Location of Main Panel	-NA-	-NA-	-NA-			
	c) Location of Repeater Panel	-NA-	-NA-	-NA-			
	d) Alternate source of power	-NA-	-NA-	-NA-			
8.	e) Hooters' Location MOEFA	-NA-	-NA-	-NA-			
9. 9.		-NA-	-NA-	-NA-			
10.	Public Address System	-NA-	-NA-	-NA-			
10.	Automatic Sprinkler System a) Basement		NA	N/A			
	b) Ground & Upper Floors	-NA-	-NA-	-NA-			
		-NA-		-NA-			
11.	c) Sprinkler above false ceiling Internal Hydrants	-NA-	-NA-	-NA-			
11.	a) Size of riser/down-comer	N/A	NA	N/A			
	b) Number of hydrants per floor	-NA-	-NA- -NA-	-NA-			
	c) Hose Box	-NA-	-NA-	-NA-			
12.	Yard Hydrants	-NA-	-INA-	-IVA-			
	a) Total number of hydrants	-NA-	-NA-	-NA-			
	b) Hose Box	-NA-	-NA-	-NA-			
13.	Pumping Arrangements	-IN/A-	-11/7-	= NAS			
	Ground Level						
	Discharge of main Pump	-NA-	-NA-	-NA-			
	➤ Head of Main pump	-NA-	-NA-	-NA-			
	> Number of main pumps	-NA-	-NA-	-NA-			
	➤ Jockey Pump out put	-NA-	-NA-	-NA-			
	Jockey pump head	-NA-	-NA-	-NA-			
	Standby Pump out put	-NA-	-NA-	-NA-			
	Standby Pump Head	-NA-	-NA-	-NA-			
	➤ Auto Starting/Manual Stopping	-NA-	-NA-	-NA-			
	Pump House Access	-NA-	-NA-	-NA-			
	Terrace level						
	Discharge of pump	450lpm	450lpm	MR			
	➤ Head of the pump	40m	40m	MR			
	> Power Supply	Required	Provided	MR			
F	> Auto Starting of pump	Required	Provided	MR			
1.	Captive Water Storage for fire fighting						
	Underground tank capacity	-NA-	-NA-	-NA-			
-	> Draw-off connection	-NA-	-NA-	-NA-			
	OI NEWS	-NA-	-NA-	-NA-			
	Fire service inlet	-NA-	-NA-	-NA-			
	> Access to tank	100,100,000	10,000ltr	MR			
	Overhead Tank capacity	10,000ltr	Provided	MR			
1	Exit Signage.	Required	Provided	HIIC			
-	Provision of Lifts.	N. T. C.		NT A			
. P	a tion of Lift Shaft	-NA-	-NA-	-NA-			
	a) Pressurization of Lift lobby	-NA-	-NA-	-NA-			
	b) Pressurization of Lift lobby	-NA-	-NA-	-NA-			
	c) Communication In lift Car	-NA-	-NA-	-NA-			
	d) Fireman's Grounding Switch	-NA-	-NA-	-NA-			
	e) Lift Signage	114.4					

17.	Standby	power supply	-NA-	-NA-	-NA-		
18.	Control of the Contro	ge Area.					
			-NA-	-NA-	-NA-		
	/	otal Area	-NA-	-NA-	-NA-		
	b) I	ocation	-1424				
19.	Fire Control Room		-NA-	-NA-	-NA-		
	a) I	etector System Panel	1977/4/102	-NA-	-NA-		
		low Switch Panel	-NA-	-NA-	-NA-		
		A System Panel	-NA-	-NA-	-NA-		
	- 20	attery backup	-NA-		-NA-		
		Building Floor Plans	-NA-		-NA-		
20.	Special	Fire Protection System for on of special Risks, if any:	-NA-	-NA-			

Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in NBC Part-4, and removal of shortcomings issued vide letter no. 569 dated 03.07, 2025, under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the inspecting Office

Name: - D.B Mukherjee Designation:- DOAW

Signature of the Inspecting Officer Name: - Ajay Kumar Sharma Designation:- ADO/Rohini

DCFO/ 376-NIO