GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI- 110001**

No. F.6/DFS/MS/GH/2025/SZ/ 159

Dated: 25/03/2025

FIRE SAFETY CERTIFICATE

Certified that the M/s. Grand Godwin Guest House at 8502/41, Katra Rai Ji, Arakashan Road, Pahar Ganj, New Delhi, comprised of ground plus four upper floors using ground floor (03 guest rooms, reception, lobby & office), 1st floor to 3rd floor (09 guest rooms at each floor) & 4th floor not in use (Affidavit submitted) (total 30 guest rooms only), was issued FSC by this department vide letter No. F.6/DFS/MS/GH/NDZ/2022/187 dated 06.04.2022. The premises was re-inspected by the officer concerned of this department on dated 17.03.2025 in the presence of Mr. Vinod Sareen, and found that the guest house have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy class "Residential" (Guest house) (30 guest rooms up-to 3rd floor) w.e.f. 25 03 2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on 25/03/2025 at New Delhi.

tul Garg) Director ire Service

Copy to: -

1 The Commissioner, MCD, Delhi: to ensure the occupancy as detailed above and deviation, if any.

2 Online application Id 2025030102613 dated 10.03.2025.

Conditions for the validity of fire safety certificate: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 6. The certificate may not be treated in any case for the regularization of the unauthorized
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to

N31

INSPECTION REPORT

1. Name & address of the building

: M/s. Grand Godwin Guest House at 8502/41, Arakashan

2. Building is comprised of Road, Pahar Ganj, New Delhi.

: G+4 upper floors (total 30 guest rooms), ground floor (03 guest rooms, reception, lobby & office), 1st to 3nd floor (09 guest rooms at each floor), 4th floor not in use (as per affidavit)

3. Type of Occupancy

: Residential (Guest House)

4. Type of Case

: Renewal

5. Details of Previous FSC letter

: F.6/DFS/MS/GH/NDZ/2022/187 dated 06.04.2022

6. Fire Safety direction letter No

: N/A

7. Date of Inspection

: 17.03.2025

8. Name of the Inspecting officers

: ADO R.K. Yadav (JKP)

9. Name and designation of officer

: Mr. Vinod Sareen

from the building side

10. Year of construction

: 1990

11 Applicant's letter No

: ID No. 2025030102613 dated 10.03.2025

Sr. No.	Minimum Standards on Fire Prevention and Fire Safety U/R33		Requirement/ Existing fire safety arrangements	Provided at Site	Remarks MR/NMR		
1	Access to Building.						
	Road with	idth	N/A	09m	N/A		
	Gate wie		N/A	N/A	N/A		
		f internal road	N/A	N/A	N/A		
2	Number, Width, Type and Arrangement of Exits.						
10	a. Number of St	taircases					
	Upper fl	oor	01 Nos.	01 Nos.	MR		
	Basemer		N/A	N/A	N/A		
	B. Width of Staircases						
	Upper fl	The state of the s	0.80 m	1.30 m	MR		
	Basemer	response a contract of the con	N/A	N/A	N/A		
	c. Protection of	Exits					
	• Fire chec		N/A	N/A	N/A		
	Pressuriz		N/A	N/A	N/A		
		uous Staircases to	N/A	N/A	N/A		
	e. Width of Corridor		N/A	N/A	N/A		
	f. Door Size		1.0 m	1.0 m	MR		
3	Compartmentation.						
	Fire chec	k door	N/A	N/A	N/A		
	Sealing of	of electrical shafts	N/A	N/A	N/A		
		g of shaft door	N/A	N/A	N/A		
	Water cu	we go to the second to	N/A	N/A	N/A		
	Fire dam	pers	N/A	N/A	N/A		
4	Smoke Management System.						
	Basemen	t	N/A	N/A	N/A		
	Upper flo	oor	12 ACPH	Natural/Exhaust fan	MR		
5.	Fire Extinguishers.						
	Total nur	mbers	22 nos.	Provided	MR		
	• Types		ABC /CO ₂	Provided	MR		
,	IS marking	ng	ISI marked	Provided	MR		

N32

06	First-Aid-Hose Reels.						
_	Total numbers on each floor	01 No	Decrided	1.00			
	Length of hose reel hose	30 m	Provided Provided	MR			
	Nozzle diameter	05 mm	Provided	MR			
0=				MR			
07	Automatic Fire Detection, CO detect						
	 CO Type of detectors 	Required	Provided	MR			
	 Location of main panel 	Required	Provided at GF	MR			
	 Location of repeater panel 	N/A	N/A	N/A			
	 Alternate source of power 	Required	Provided	MR			
	Hooter's location	Required	G. Floor	MR			
08	MOEFA	Required	Provided	MR			
09	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.						
	Basement & Stilt	N/A	N/A	N/A			
	upper floor	N/A	Provided	N/A N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
		1071	IVA	10721			
11	Internal Hydrants						
	size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose box	N/A	N/A	N/A			
12	Yard Hydrants.	- 1					
	Total number of hydrants	N/A	N/A	N/A			
	Hose box	N/A	N/A	N/A			
13	Pumping Arrangements.		<u> </u>				
13	➤ Ground Level						
	Discharge of main pump						
	Head of main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby pump out put	N/A	N/A	N/A			
	Standby pump head	N/A	N/A	N/A			
	Auto starting /manual	N/A	N/A	N/A			
	stopping	N/A	N/A	N/A			
	Pump house access						
	> Terrace Level	160 7 77 7	460 1 20 1				
	Discharge of pump	450 LPM	450 LPM	MR			
	Head of the pump	40 m	40 m	MR			
	Power supply Auto Starting of pump	Required Required	Provided Provided	MR MR			
1.4							
14	Captive Water Storage for Fire Fighti	12000					
	Underground tank capacity	N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A			
	• Fire service inlet	N/A	N/A	N/A			
	Access to tank	N/A	N/A	N/A			
-	Overhead Tank capacity	5,000 ltrs	5,000 ltrs	MR			
15	Exit Signage.	Required	Provided	MR			
			= 45				

M

27

1		on of Lifts.				
70	-	Pressurization of Lift Shaft	N/A	N/A	N/A	
		Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage	N/A	N/A	N/A	
	- 10		Required	Provided	MR	
	11/2		Required	Provided	MR	
17			Required	Provided	MR	
	Standb	power supply	Required	Provided	MR	
8	Refuge Area.					
	180	otal area	N/A	N/A	N/A	
		ocation	N/A	N/A	N/A	
19	Fire Control Room					
	Detecto	etector system panel	N/A	N/A	N/A	
	• 1	low switch panel	N/A	N/A	N/A	
		A system panel	N/A	N/A	N/A	
		Battery backup	N/A	N/A	N/A	
	• E	Building Floor Plans	N/A	N/A	N/A	
	Special	Fire Protection systems for on of special Risks, if any:	N/A	N/A	N/A	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F.6/DFS/MS/GH/NDZ/2022/187 dated 06.04.2022, renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note: - As per affidavit submitted by the guest house management (placed at C- 118) the guest house building comprised of ground & four upper floors, using ground floor (03 guest rooms, reception, lobby & office), 1st floor to 3rd floor (09 guest rooms at each floor (total 30 guest rooms) & 4th floor not in use (Affidavit submitted) and not using any floor above third floor.

Signature of Inspecting Off

Name: - R.K. Yadav

Designation: - ADO (JKP)

DO (SWX

19/212

yers (moz)

C.F.O / My

Dineeta My 70/x

gry X (vol)