## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE** NEW DELHI-110 001.

No.F.6/DFS/MS/School/2025/SZ/ 337

Dated: 03 | 04 | 2025

## FIRE SAFETY CERTIFICATE

Certified that the Guru Harkrishan Public School located at Tilak Nagar, New Delhi-110018, comprised of basement (closed), ground floor plus two upper floors but school running at ground and first floor only (A Gurdwara Sahib situated at 2nd floor) located at Tilak Nagar, New Delhi-110018, owned/occupied by Guru Harkrishan Public School was issued FSC by this department vide letter No. F.6/DFS/MS/School/2021/SZ/688 dated 02.09.2021. The School building was re-inspected by the officer concerned of this department on dated 11.03.2025 in the presence of Sh. Kulvinder Kaur (Principal) and found that the School have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class "Educational Building" w.e.f. 6.3 04 2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed as below.

Issued on 03 04 2025 at New Delhi by.

Delhi Fire Service

Copy to: -

- 1. The Executive Engineer (Bldg.), MCD, Civic Centre, New Delhi: for information regarding use of basement.
- 2. Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054.
- 3. The Principal, Guru Harkrishan Public School located at Tilak Nagar, New Delhi-110018.

## Conditions for the validity of fire safety certificate: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws. Presently basement is closed.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

## INSPECTION REPORT

Name & address of the building 1.

2. Building is comprised of Guru Harkrishan Public School, Tilak Nagar, New Delhi-110018

Basement (Closed), ground plus two upper floors but school running at ground & first floor only (A Gurdwara Sahib on 2nd floor)

3. Type of Occupancy

Educational

4. Type of Case

Renewal

5. Details of Previous NOC

F.6/DFS/MS/School/2021/SZ/688 dated 02.09.2021

6. Fire Safety direction letter No

N/A

7. Date of Inspection 11.03.2025

Name of the Inspecting Officers: 8.

ADO R.K. YADAV

9. Name of the designation of Officer

from the building side

Sh. Kulvinder Kaur (Principal)

10. Year of Construction

Before 2010

Applicant's letter No

S. No.	Minimum Standards on fire prevention and fire safety requirements U/R 33	Requirement	Provided at Site	Remarks MR/NMR		
1	Access to building					
	Road width	6 m	12 m	MR		
	Gate width	4.5 m	05 m	MR		
	Width of internal road	N.A.	N.A.	N.A.		
2	Number, Width, Type and Arrangement	of Exits		m11.00		
	a. Number of Staircases	n 🛋 Ans. Par	04	MR		
	Upper Floor	04 no.	04 no.	Basement is closed		
	Basement	N.A.	N.A.	& not in use		
	B. Width of Staircases	,	1.25 m (04 no's)	MR, being old		
	Upper Floor	Old Case	1.25 III (04 IIO 5)	case		
	Basement	N.A.	N.A.	Basement is close & not in use		
	c. Protection of exits			- 6		
	Fire check door	N.A.	N.A.	N.A.		
	Pressurization	N.A.	N.A.	N.A.		
	e. No. of continuous staircases to terrace	02 no.	02 no.	MR		
	g. Width of Corridor	1.50 m	2.10 m	MR		
	h. Door Size	1.0 m	1.12 m	MR		
3	Compartmentation.					
	Fire check door	N.A.	N.A.	N.A.		
	Sealing of electrical shafts	N.A.	N.A.	N.A.		
	Fire rating of shaft door	N.A.	N.A.	N.A.		
	Water curtain	N.A.	N.A.	N.A.		
	Fire Dampers	N.A.	N.A.	N.A.		
4	Smoke Management System.					
	Basement	Required	Exhaust Fans provided	N.A.		
	Upper floor	Required	Natural Ventilation	MR		

M9

Fire Extinguisher		2	
Total numbers			MR
D Mark Seas (Section)		the second secon	MR
1.7.7			MR
10 marking	ISI marked	ISI marked	
First-aid-Hose Reels.			MR
Total numbers of each floor	00 No	Provided	MR
		30 m	MR
Nozzle diameter	5 mm	5 mm	MAX
Automatic fire detection and alarming sy		V	
		N.A.	N.A.
. I POTATO C. J.		N.A.	N.A.
		N.A.	N.A.
		N.A.	N.A.
	75302 a	N.A.	N.A.
Hooters		N.A.	N.A.
MOEFA	40.00	Provided	MR
Public address System.	N.A.		
Automatic Sprinkler System.	8	Drovided	MR
			N.A.
upper floor			N.A.
sprinkler above false ceiling	N.A.	A.W	1
		3	MR
and the second s	N.A.		MR
size of riser/down-comer	N.A.	125 6000 6000	MR
	N.A.	01 no	IVIIX
11/2/12/04/PAZ = 21/A	N.A.	01 no	MR
		01 no	MR
	NΑ	N.A.	N.A.
Ground Level		N.A.	N.A.
Discharge of main Pump		N.A.	N.A.
	The state of the s	N.A.	N.A.
	English and	N.A.	N.A.
		N.A.	N.A.
		N.A.	N.A.
		N.A.	N.A.
	2.000400	N.A.	N.A.
> Pump House Access	N.A.	N.A.	N.A.
The second secon			
	Old case	450 lpm & 180 lpm	MR
	40 m	40 m	MR
7 70 70 70 70 70 70 70 70 70 70 70 70 70	Required	Provided	MR
Auto Starting of pump	Required	Provided	MR
Captive Water Storage for Fire Fighting.			
Underground tank capacity	N.A.	N.A.	N.A.
Draw-off connection	N.A.		12000000000
Fire service inlet	N.A.	TO STANKING TO THE STANKING THE STANKING TO THE STANKING THE STA	N.A.
Access to tank	N.A.	THE PARTY OF THE P	N.A.
Overhead Tank capacity	Old Case		N.A.
Exit Signage.	10-200 Sec. 1980	0 F. 1956	MR, old cas
Lat organge.	Required	Provided	MR
	Total numbers types IS marking  First-aid-Hose Reels.  Total numbers of each floor Length of hose reel hose Nozzle diameter  Automatic fire detection and alarming sy. Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters  MOEFA  Public address System.  Automatic Sprinkler System.  basement upper floor sprinkler above false ceiling  Internal Hydrants  size of riser/down-comer Number of hydrants per floor Hose Box  Yard Hydrants.  Total number of hydrants Hose Box  Pumping Arrangements.  Ground Level Discharge of main Pump Head of Main Pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump out put Standby pump Head Auto Starting /Manual stopping Pump Head of the Pump Power supply Auto Starting of pump  Captive Water Storage for Fire Fighting.  Underground tank capacity Draw-off connection Fire service inlet Access to tank	Total numbers types IS marking IS marking First-aid-Hose Reels.  Total numbers of each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming system.  Type of detectors Location of main panel Location of repeater panel Alternate source of power Hooters  MOEFA Public address System.  Automatic Sprinkler System.  basement upper floor sprinkler above false ceiling Internal Hydrants  size of riser/down-comer Number of hydrants per floor Hose Box  Yard Hydrants.  Total number of hydrants Hose Box Pumping Arrangements.  Ground Level Discharge of main Pump Head of Main Pump NAA. Jockey pump out put Standby pump out put Standby pump Head Auto Starting /Manual stopping Pump House Access Terrace Level Discharge of pump Head of the Pump Head of the Pump Power supply Head of the Pump Power supply Head of the Pump Power supply Auto Starting of pump  Captive Water Storage for Fire Fighting.  Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity N.A. Old Case	Total numbers lypes   Smarking

400					
16	Provis on of Lifts.				
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.	
	Pressurization of Lift lobby	N.A.	N.A.	N.A.	
	Communication in lift car	N.A.	N.A.	N.A.	
	Firemen's grounding switch	N.A.	N.A.	N.A.	
	Lift Signage	N.A.	N.A.	N.A.	
17	Standby power supply	N.A.	N.A.	N.A.	
18	Refuge Area.				
	Total area	N.A.	N.A.	N.A.	
	Location	N.A.	N.A.	N.A.	
19	Fire Control Room				
	Detector system panel	N.A.	N.A.	N.A.	
	Flow switch panel	N.A.	N.A.	N.A.	
	PA system panel	N.A.	N.A.	N.A.	
	Batter backup	N.A.	N.A.	N.A.	
	Building Floor Plans	N.A.	N.A.	N.A.	
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: - As per undertaking submitted by the principal of school (placed at C-56) that the basement of the school building having two rooms which will be sold shortly and not using rooms for any purpose. Classrooms are running only ground and first floor. A Gurdwara Sahib situated on the second floor, which has been an integral part of institution for a long time.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter number F.6/DFS/MS/School/2021/SZ/688 dated 02.09.2021, renewal under rule 37, of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer Name- R.K. Yadav

Designation- A.D.O (JKP)

DO(8W)

24/3/25

27 lon from

Dinector/

Har John