

SOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001**



No F 6 / DFS / MS /EH/ 2025 /WZ/ 346

Dated

FIRE SAFETY CERTIFICATE

Certified that M/s Haldiram Products Pvt. Ltd. located at 01, Raj Nagar Enclave, Pitampura, Delhi-110034 is running at Upper Ground Floor & First Floor in a building comprised of Basement, Stilt, Upper Ground floor plus three Upper Floors have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 20.09.2025 in the presence of Ms. Ruby (Manager) and found that the building/ premises is fit for occupancy "Assembly" (Group D) Sweet Shop at Upper Ground floor & Restaurant at First Floor with effect from 06/10/2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010 printed below.

Issued on ... 06. 110.120.25. at New Delhi by

(M.K. Chattonadhyay) Dy. Chief Fire Officer

Copy to:-

1. The Commissioner, MCD, Delhi:- to ensure the occupancy as detailed above and deviation if any.

2. The Owner/ Occupier, M/s Haldiram Products Pvt. Ltd. located at 01, Raj Nagar Enclave, Pitampura, Delhi-110034.

MCD Portal ID No. 2025090813264.

Conditions for the validity of Fire Safety Certificate:

1. Fire Safety Certificate is valid for Upper Ground Floor & First Floor only.

2. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.

3. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

4. The trained fire fighting staff should be available round the clock.

5. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.

6. This certificate cannot be treated in any case for regularizations of unauthorized

construction.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate through MCD portal (https://www.mcdonline.nic.in) along with a copy of this Certificate, six months prior to its expiry".

8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on

www.dfs.delhigovt.nic.in

9. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

10. The basement shall be used strictly as per building bye laws.

Name & address of the building: M/s Haldiram Products Pvt. Ltd. located at 01, Raj Nagar Enclave, Type of Occupancy

Building Comprised of : Assembly (Sweet Shop at Upper Ground floor & Restaurant at 1st Floor) Type of Case : Basement, Stilt, Upper Ground plus Three upper floors.

5. Details of Previous NOC

6. Fire Safety directives letter No Nil 7. Date of inspection Nil

8. Name of Inspecting Officer 20/09/2025 R.K.Sinha, ADO (BW)

9. Name and designation of officers

From the building side 10. Year of Construction Ms. Ruby (Manager)

| S. | Minimum | Standards on fire | NPC/ Upper | No. 2025090813264 dated 08/ | 09/2025 | | | | | |
|-----|---|-------------------------|--------------------------|-----------------------------|--|--|--|--|--|--|
| No. | prevention and fire safety U/D 22 | | NBC/ UBBL Requirement | Provided at site | Remarks | | | | | |
| 1. | 1100035 10 | Duilding | -sequirement | | MR/NMR | | | | | |
| | Road widt | | 6 m | Provided | 1.75 | | | | | |
| | Gate width | | NA | Directly Accessible | MR NA | | | | | |
| 2. | Width of it | nternal road | 311 | NA NA | NA NA | | | | | |
| 4. | Number, | Width, Type & Arrangem | ent of Exits | IVA | NA NA | | | | | |
| | a. Number of staircases | | | | | | | | | |
| | Unner Floers | | | | | | | | | |
| | Basements | | 02 | Provided | MR | | | | | |
| | | | NA | NA | NA | | | | | |
| | b. Width of staircases Upper Floor 2 × 1.5 m Provided NO | | | | | | | | | |
| | Basements | r | 2 × 1.5 m | Provided | MR | | | | | |
| | | · · · | NA | NA | NA | | | | | |
| | c. Protection of exits Fire check door Required Provided | | | | | | | | | |
| | | | Required | Provided | MR | | | | | |
| | Pressurizati | | NA | NA | NA | | | | | |
| | d. No. of c terrace | ontinuous staircases to | 02 | Provided | MR | | | | | |
| | e. Width of | Corridor | NA | | A. 10 A. 50 A. | | | | | |
| | f. Door Siz | | 2 × 1.5 m | NA Provided | NA MR | | | | | |
| 3. | Compartmentation | | | | | | | | | |
| | Fire check d | oor | D 1 | | | | | | | |
| | | | Required | Provided | MR | | | | | |
| | | ectrical shafts | Required | Provided | MR | | | | | |
| | Fire Rating of Water Curtai | | NA | NA | NA | | | | | |
| | Fire Dampers | | NA | NA | NA | | | | | |
| 1. | | | NA | NA | NA | | | | | |
| | Smoke Management System | | | | | | | | | |
| | Basements | | NA | NA | NA | | | | | |
| | Upper Ground | floor | Required | Provided | NA MR | | | | | |
| | Fire Extinguishers | | | | | | | | | |
| | Total numbers | | | | | | | | | |
| | Types | | 06 Nos. | Provided | MR | | | | | |
| | IS marking | | ABC/Co2 Type | Provided | MR | | | | | |
| | First-Aid Hos | Reels | Required | Provided | MR | | | | | |
| | Total numbers on each g | | | | | | | | | |
| | Length of hose | reel hose | 01 | Provided | MR | | | | | |
| | Nozzle diamete | r | 30 m | Provided | MR | | | | | |
| | Automatic fire detection and | | 5 mm | Provided | | | | | | |
| 7 | Type of detectors Wik | | | | | | | | | |
| | ocation of Ma | | NA | Smoke/ Heat | 214 | | | | | |
| ī | Ocation of D | n ranel | NA | G.F. | NA | | | | | |
| A | ocation of Rep | eater Panel | NA | | NA | | | | | |
| H | Alternate source looters' Location | or power | NA | NA NA | NA | | | | | |
| N | IOEFA |)11 | NA | NA NA | NA | | | | | |
| P | ublic Address | Crust | Required | NA NA | NA | | | | | |
| 1. | - Audress | System | NA | Provided | MR | | | | | |
| | | | | NA | NA | | | | | |

| | | | ٠ |
|--------|---|-----|---|
| . 1 | | • | • |
| \sim | * | - 1 | , |
| ,- | | | |

| Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants Hose Box | NA NA NA 100 mm 01 01 | NA Provided NA Provided | NA NA NA | | | | | |
|--|---|---|--|--|--|--|--|--|
| Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants Hose Box | 100 mm 01 01 | NA Provided | NA | | | | | |
| Internal Hydrants Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants Hose Box | 100 mm 01 01 | Provided | | | | | | |
| Size of riser/down-comer Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants Hose Box | 01 | | NA | | | | | |
| Number of hydrants per floor Hose Box Yard Hydrants Total number of hydrants Hose Box | 01 | | | | | | | |
| Hose Box Yard Hydrants Total number of hydrants Hose Box | 01 | | | | | | | |
| Yard Hydrants Total number of hydrants Hose Box | | Provided | MR | | | | | |
| Total number of hydrants Hose Box | | Provided | MR | | | | | |
| Hose Box | | | MR | | | | | |
| | NA | NA | N. | | | | | |
| | NA | NA | NA NA | | | | | |
| . Pumping Arrangements Ground Level | | | | | | | | |
| Discharge of main B | | | | | | | | |
| | NA NA | NA | NA | | | | | |
| Head of Main pump | NA | NA | NA | | | | | |
| Number of main pumps | NA | NA | NA | | | | | |
| Jockey Pump out put | NA | NA | NA | | | | | |
| | NA | NA | NA | | | | | |
| | NA | NA | NA | | | | | |
| | NA | NA | NA | | | | | |
| Auto Starting/Manual Stopping | | NA | NA | | | | | |
| Pump House Access | NA | NA | NA | | | | | |
| Terrace level | | | | | | | | |
| Discharge of pump | 450 lpm | Provided | MR | | | | | |
| Head of the pump | 40 m | Provided | MR | | | | | |
| Power Supply | Required | Provided | MR | | | | | |
| Auto Starting of pump | Required | Provided | MR | | | | | |
| Captive Water Storage for fire fighting | | | | | | | | |
| Underground tank capacity | NA | NA | NA | | | | | |
| | NA | NA | NA | | | | | |
| | NA | NA | NA | | | | | |
| | NA | NA | NA | | | | | |
| AND DESCRIPTION OF THE PROPERTY OF THE PROPERT | 20,000 ltrs | 20,000 ltrs | MR | | | | | |
| Exit Signage. | Required | Provided | MR | | | | | |
| Provision of Lifts. | | | | | | | | |
| Pressurization of Lift Shaft | NA | NA | NA | | | | | |
| The state of the s | | NA | NA | | | | | |
| | | Provided | MR | | | | | |
| | | Provided | MR | | | | | |
| | | | MR | | | | | |
| | | | MR | | | | | |
| | Kequited | . 151 100 | | | | | | |
| L NA | | | | | | | | |
| Total Area | NA NA | NA NA | NA NA | | | | | |
| | NA L | NA | | | | | | |
| | | | | | | | | |
| Detector System Panel | NA | NA | NA | | | | | |
| Flow Switch Panel | NA | NA NA | NA NA | | | | | |
| PA System Panel | NA | | NA NA | | | | | |
| Battery backup | | | NA NA | | | | | |
| | Jockey Pump out put Jockey pump head Standby Pump out put Standby Pump Head Auto Starting/Manual Stopping Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Auto Starting of pump Captive Water Storage for fire figh Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift lobby Communication In lift Car Fireman's Grounding Switch Lift Signage Standby power supply Refuge Area. Total Area Location Fire Control Room Detector System Panel PA System Panel | Jockey Pump out put Jockey pump head NA Standby Pump out put Standby Pump out put NA Auto Starting/Manual Stopping NA Pump House Access Terrace level Discharge of pump Head of the pump Power Supply Required Auto Starting of pump Required Captive Water Storage for fire fighting Underground tank capacity NA Draw-off connection NA Signage. Provision of Lift Shaft NA Pressurization of Lift Shaft NA Pressurization of Lift Iobby Communication In lift Car Fireman's Grounding Switch Required Refuge Area. I total Area Location Detector System Panel PA System Panel Battery backup NA | Jockey Pump out put Jockey pump head NA NA Standby Pump out put NA NA Standby Pump out put NA NA NA NA Auto Starting/Manual Stopping NA NA NA NA Pump House Access NA NA NA NA NA Pump House Access NA | | | | | |

N-5 cial Fire Protection System for protection of special Risks, if any: NA NA NA The fire protection systems provided in the building were tested, checked and found functional at the time of inspection. Keeping in view of satisfactory compliance of the minimum standards of fire prevention and fire safety measures as required under rules it is recommended to grant Fire Safety Certificate under Rule 35 of the Delhi Fire Service Rules, 2010. Signature of Inspecting Officer Name: Rajeev Kumar Sinha Designation: ADO/B.W. MSCLY placeded