

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/EH/SZ/2025/591

Dated: 0.4/.1.1/2025

FIRE SAFETY CERTIFICATE

Certified that the M/S Haldiram Marketing Pvt. Ltd. located at Shop No. 1509. Bhishmpita Marg, Wazir Nagar, Delhi-110003 in a building comprised of basement, Ground + 03 upper floors but Restaurant is running at ground floor, first floor & second floor only. The premises was inspected by officer concerned of this department on 30/10/2025 in the presence of Mr. Rahul Aggarwal (Manager) and found that the restaurant premises has complied with the fire prevention and fire safety measures as requirements in accordance with Rule 33 of Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Assembly Building Group "D", Restaurant at ground floor, first floor & second floor only with effect from for period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 04/11/25 at New Delhi by.

DY. CHIEF FIRE OFFICER

DELHI FIRE SERVICE

Copy to:-

1. The Commissioner MCD, Civic Center New Delhi- to kindly ensure the occupancy and deviation if any

2. The Manager, M/S Haldiram Mareting Pvt. ltd located at Shop No. 1509. Bhishmpita Marg, Wazir Nagar, Delhi-110003

MCD ID No. 2025101414182

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority. Mezzanine floor shall be used only for storage purpose no seating shall be allowed.

5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry". 9. Any flammable material for interior decoration is strictly prohibited.

10. This FSC is valid only for restaurant at ground, 1st & 2nd floor only.

INSPECTION REPORT

1. Name & address of the building M/S Haldiram Mareting Pvt. ltd

Shop No. 1509. Bhishmpita Marg, Wazir

Nagar, Delhi-110003

Type of occupancy:-Assembly Building Group-D,

Restaurant at ground, first &2nd floor only,

3. Type of case:-

New case

4. Details of previous FSC:-

Nil

5. Fire safety directives No .-

N/A

6. Date of inspection:-

30/10/2025

7. Name of the inspecting officer:-

Deepak Kumar, ADO (Tahirpur)

8. Name & designation of officer

2005

From the building side:-

Mr. Rahul Aggarwal, Manager

9. Year of construction:-10. Applicant's letter No:-

2025101414182 dated 24/10/2025

The building is comprised of Basement/lower ground, Ground + 03 upper floors but restaurant is running ground, 1st & 2nd floor only. Basement/lower ground & 3rd floor (office) is not a part

\$.No.	urant and it is for other use as per be Minimum Standards on fire Prevention and fire safety U/R 33	Requirements as per UBBL/NBC Part IV	Provided at site	Remarks MR/NMR
1.	Access to Building	z dre i v	- A	
	1) Road width	06 mtr	15 mtr.	
	2) Gate width	N/A	N/A	MR
20	3)Width of internal road	N/A	N = 41	N/A
2.	Number, Width Type & Arr	angement of E	N/A	N/A
	A. Number of staircases	angement of Ex	its	
a	1. Upper floors	02 nos.	02	
	2. Basements	N/A	02 nos.	MR
	B. Width of staircase	IVA	N/A	N/A
	1. Upper floors	1.5 mtr	1.5	
	2. Basements	N/A	1.5 mtr	MR
	C. Protection of exits	IVA	N/A	N/A
	1. Fire check door	N/A	D 11	
	2. Pressurization	N/A	Provided	N/A
	D. No. of continuous		N/A	N/A
	staircase to terrace	02 nos.	02 nos.	MR
	E. Width of corridor	NI/A	I Service	
	F. Door size	N/A	N/A	N/A
3,	Compartmentation	1.5 mtr	1.5 mtr	MR
	1) Fire check door			
		Required at kitchen	Provided	MR
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door 4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	
	Smoke M.	N/A	N/A	N/A
	Smoke Management System 1) Basement	(4))		N/A
		N/A	N/A	NT/A
	2) Upper floors	12 a/c per hour	Natural	N/A MR

5.	Fire Extinguishers				
	1) Total numbers	06 Nos.	10 Nos.	MR	
	2) Types	ABC & CO2			
	3) ISI marking	Required	Provided	MR	
6.	First-Aid Hose Reel				
	1) Total number of each floor	01	01	MR	
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR	
	3) Nozzle diameter	05 mm	05 mm	MR	
7.	Automatic Fire Detection & Alarming System				
	1) Type of detectors	N/A	Provided	N/A	
411	2) Location of main panel	N/A	Gr. Floor	N/A	
	3) Location of repeater panel	N/A	N/A	N/A	
	4) Alternate source of power	N/A	Provided	N/A	
	5) Hooter's Location	N/A	Provided	N/A	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	N/A	N/A	N/A	
10.	Automatic Sprinkler System		IN/A	IN/A	
10.	1) Basement	N/A	N/A	N/A	
		N/A	Provided Provided	N/A N/A	
	Upper floors Sprinkler above false	N/A	N/A	N/A	
		IN/A	IN/A	14/74	
11	ceiling				
11.	Internal Hydrants 1) Size of riser/down-comer	100mm	100mm	MR	
		01	01	MR	
	2) Number of hydrants per	01	OI .	T. I.C.	
*	floor	01	01	MR	
	3) Hose box	101	101		
12.	Yard Hydrants 1) Total number of hydrants	N/A	N/A	N/A	
		N/A	N/A	N/A	
	2) Hose box	IVIZI	23/22		
13.	Pumping Arrangement	N/A	N/A	N/A	
	1) Ground level	N/A	N/A	N/A	
	a) Discharge of main	IN/A	1022		
	pump	N/A	N/A	N/A	
	b) Head of main pump	N/A N/A	N/A	N/A	
	c) Number of main	IN/A	A 31 A 30		
	pump	N/A	N/A	N/A	
	d) Jockey pump out put	N/A N/A	N/A	N/A	
	e) Jockey pump head	N/A	N/A	N/A	
	f) Stand by pump	14/17		17/4	
	output head	N/A	N/A	N/A	
œ	g) Stand by pump head	N/A	N/A	N/A	
	h) Auto starting/Manual	*****			
	stopping			MR	
1	2) Terrace level	450 LPM	450 lpm x 02	MR	
E	a) Discharge of pump	40 mtr.	40 mtr.	MR	
	b) Head of pump	Required	Provided	MR	
	c) Power supply d) Auto starting of	Required	Provided	TV - 1116175	
		0.5			
	Captive Water Storage for Fi	re Fighting			

	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
. 80	 d) Over head tank capacity 	20,000 lit.	20,000 lit.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	 a) Pressurization of lift shaft 	N/A	N/A	N/A
	 b) Pressurization of lift lobby 	N/A	N/A	N/A
	 c) Communication in lift car 	N/A	Provided	N/A
	d) Fireman's switch	N/A	Provided	N/A
	e) Lift signage	N/A	Provided	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	27//
	a) Detector system panel	N/A		N/A
		IN/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
		- 1/2 %	IV/A	N/A
	e) Building floor plan	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any:			N/A
	Risk, if any	N/A		

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on . fire prevention and fire safety required under the rules, if agreed, the Fire Safety Certificate under rule 35 of Delhi Fire Service Rules-2010, is recommended to

Signature of the Inspecting Officer

:- Deepak Kumar

Designation :- ADO (Tahirpur)