## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUATERS: DELHI FIRE SERVICE: NEW DELHI-110001

No. F.6/DFS/MS/EH/2025/SZ/3 69

Dated: 28/10/2025

## FIRE SAFETY CERTIFICATE

Certified that the Haldiram (A unit of Haldiram Ethnic Foods Pvt. Ltd.), Shop No. C9/14, Krishna Nagar, Shahdara, Delhi - 51, comprised of Basement (Storage), Ground, 1st, 2nd & 3rd floor but restaurant is running only in Ground (restaurant), 1st (restaurant) with Basement (Storage) owned / occupied by Haldiram Ethnic Foods Pvt. Ltd., was issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/EH/2022/NDZ/198 dated 06/07/2022. The premise was re-inspected by the officer concerned of this department on 12/10/2025 in the presence of Mr. Atul Singh (Manager) and found that the said building(restaurant)/premises is fit for occupancy class "Group D(Assembly Building)" with effect from 28/10/2025 with valid upto 31/03/2028 in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on <u>28 / /0 /2025</u> at New Delhi by

(Dr. S. K. Tomar)
Dy. Chief Fire Officer
Delhi Fire Service

Copy to: -

- The Commissioner, Municipal Corporation of Delhi, Dr. SPM Civic Center, Minto Road, New Delhi–110002 (w.r.t. online application No. 2025100113895 dated 01/10/2025).
- 2. Sh. Ashish Agarwal, Haldiram (A unit of Haldiram Ethnic Foods Pvt. Ltd.), Shop No. C9/14, Krishna Nagar, Shahdara, Delhi 51.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangement provided therein shall be maintained in good working conditions at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of fire-fighting system.
- 4. Basement shall be used strictly in accordance with the BBL.
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this certificate, prior to its expiry.
- 8. Fire Safety Certificate is valid for Ground (restaurant), 1st (restaurant) with Basement (Storage) only

	INSPECTIO	ON REPORT		
	Name & address of the building			ic Foods Put
	Name & address of the building	Ltd.), Shop Shahdara, De	unit of Haldiram Ethn No. C9/14, Krisl elhi - 51	hna Nagar,
2.	Type of Occupancy	Assembly (Gr		200
3.	Building Comprised of	Restaurant running on Ground and First floors with basement (storage)		
4.	Type of Case	Renewal		
5.	Details of previous NOC	F6/DFS/MS/E	EH/2022/NDZ/198 dated	1 06/07/2022
6.	Fire Safety directives letter No	Nil		
7.	Date of inspection	12/10/2025		
8.	Name of the Inspecting Officers	Kaushal Kish	ore (ADO SJ)	
	Name and designation of officers from the building side	Sh. Atul Singh (Manager)		
10.	4.47. Marie Carlotta (1970)	2011	d.	
11	Applicant's letter No.	Application 01/10/2025	No. 2025100113	895 dated
S.	Minimum Standards on fire prevention and fire safety U/R 33	BBL /NBC Requirem ent	Provided at site	Remarks MR/NMR
1	Access to building			MR
	Road width	06 mtr	On main road	
	Gate width	N/A	On main road	N/A
	Width of internal road	N/A	N/A	N/A
2		of Exits		
	a. Number of staircases		02	MR
	Upper Floors	02	02	MR
	Basements	01	UI	IVIX
	b. Width of staircases	1.50	1.50	MR
14	<ul> <li>Upper Floors</li> </ul>	1.50m	1.50m	MR
	Basements	1.50m	1.50m	IVIX
	c. Protection of exits			
	Fire check door     Pressurization	Required in basement	Provided	MR
		NA	NA	NA
	d. No of continuous staircase to terrace	e NA	NA	NA
1	e. Width of Corridor	NA	NA	NA
-	f. Door Size	1.5m	1.5m	MR
-	3 Compartmentation.			
	<ul><li>Fire check door</li><li>Sealing of electrical shafts</li></ul>	Required in basement	Provided	MR
	Fire Rating of shaft door     Water Curtain	Required	Provided	MR
(1)	Fire Dampers	NA	NA	NA
		NA	NA	NA
	200 00000000000000000000000000000000000	NA	NA NA	NA
	4 Smoke Management System.	D		
	<ul><li>Basements</li><li>Upper floors</li></ul>	Required Required	Provided Provided	MR
	E Partie de la Par	Required	Provided	MR
	5 Fire Extinguishers  • Total numbers	06 nos.	06Nos	MR
	Total Halloots		001103	IVIIC

	N) b	181					
		marked					
6	First-Aid Hose Reels.						
	Total numbers on each floor	01	01				
		2222		N			
	<ul> <li>Length of hose reel hose</li> </ul>	30m	30m	M			
	Nozzle diameter	5mm	5mm	M			
7	Automatic fire detection and alarming system.						
	Type of detectors	N/A	N/A	1			
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	l l			
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	. N			
	<ul> <li>Alternate source of power</li> </ul>	N/A	N/A	N			
	<ul> <li>Hooters' Location</li> </ul>	N/A	N/A				
8	MOEFA	Require	ed Provided	N			
9	Public Address System.	N/A	N/A	N.			
10	Automatic Sprinkler System.	10					
	Basement	N/A (are	a N/A	N/			
	Upper Floor	less than		14/			
100	Sprinkler above false ceiling	200m <sup>2</sup> )					
		N/A	N/A	N/			
		N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	150mm	150mm	MI			
	Number of hydrants per floor	1	1	MF			
•	Hose Box	1	1	MF			
12	Yard Hydrants.		1	1000000			
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.	-					
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	➤ Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	> Jockey pump head	N/A	N/A	N/A			
	> Standby Pump out put	N/A	N/A	N/A			
	> Standby Pump Head	N/A	N/A	N/A			
	➤ Auto Starting/ Manual	N/A	N/A	N/A			
	stopping	N/A	N/A	N/A			
	Pump House Access			CC William			
	<ul> <li>Terrace level</li> <li>Discharge of pump</li> </ul>	450LPM	900LPM (Electrical)	MR			
	Discharge of pump		900 LPM (Diesel)	1			
	➤ Head of the pump	403.477	180 LPM (Jockey)	MR			
- 1	Power Supply	40MH Required	40MH Required	MR			
	Auto Starting of pump	Required	Required	MR			
		<u> </u>	Required	IVIIC			
4	Captive Water Storage for fire-fightin	g. N/A	N/A	N/A			
	Underground tank capacity	N/A	N/A	N/A			
	> Draw-off connection	N/A	N/A	N/A			
	> Fire service inlet		N/A	N/A			
	> Access to tank	N/A	25,000 ltrs	MR			
	<ul> <li>Overhead Tank capacity</li> </ul>	20,000 ltrs	23,000 108	IVIIC			
	2		Provided	MR			
5 1	Exit Signage.	Required	1 TOVICCO				

N)	7
• • • /	

	N/ /						
16	Provision of Lifts.	W					
+	Pressurization of Lift Shaft	N/A	N/A	N/A			
-	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication In lift Car	N/A	N/A	N/A			
-	Fireman's Grounding Switch	N/A	N/A	N/A			
	Lift Signage	N/A	N/A	N/A			
7	Standby power supply	Required	Provided	MR			
8	Refuge Area.						
	> Total Area	NA	NA	NA			
	> Location	NA	NA	NA			
19	Fire Control Room						
	Detector System Panel	NA	NA	NA			
5	Flow Switch Panel	NA	NA	NA			
	PA System Panel	NA	NA	NA			
-	Battery backup	NA	NA	NA			
	Building Floor Plans	NA	NA	NA			
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA	NA	NA			

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view of the substantial compliance of the minimum standard on fire prevention & fire safety measures as required under the rules, issuance of fire safety certificate, under rule 35 of Delhi Fire Service Rules 2010 is recommended.

> Signature of the Inspecting Officer Kaushal Kishore ADO (SJ)