

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No.F6/DFS/MS/GH/SZ/2025/527

Dated:

FIRE SAFETY CERTIFICATE

Certified that the M/s Hotel City Inn situated at F-119, Jeewan Park, Uttam Nagar, New Delhi -59, building comprised of Basement + Stilt + Upper Ground + 03 upper floors: Basement -Vacant, Upper Ground to 3rd floor- 07 guest rooms each, owned & occupied by Hotel City Inn has complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by officer concerned of Delhi Fire Service on 09.10.2025 in the presence of Mr. Atul Sharma (Caretaker) and found that the premises/building is fit for occupancy of "Residential Sub Division-A-1" for total 28 guest rooms with 56 beds (Upper Ground to 3rd floor- 07 guest rooms each) with effect from .. 23 10 2.25 and valid upto 31.03.2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to conditions under Rule 38 of Delhi Fire service Rules, 2010 printed below.

Issued on 23 10 2025 at New Delhi by

Dy. Chief Fire Officer Delhi Fire Service

Reference: elt.mcdonline application no. 2025100113873.

1. The Commissioner, MCD, Dr. S.P.M. Civic Centre, Minto Road, New Delhi-110002:- To ensure the occupancy as detailed above.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The means of escape shall be kept unobstructed/unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub Rule (I) of Rule 37] along with a copy of this Certificate, six month prior to its expiry. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

	INSPI	ECTION REPOR	т			
	Name & address of the building					
	address of the building		ity Inn situated at F			
2	Building is comprised of		Park, Uttam Nagar, New Delhi -59.			
	bunding is comprised of		Basement +Stilt + Upper Ground + 03 upp			
		floors:-	floors:-			
		Basement – Vacant at the time of inspection Stilt - Parking Upper Ground floor – 07 guest rooms 1stfloor - 07 guest rooms 2ndfloor - 07 guest rooms 3rdfloor - 07 guest rooms				
3	Type of occupancy	Residential Sul				
2	Type of case	New Case				
5	Details of previous FSC	Nil				
, ,	Fire safety directive letter no.		UBBL/NBC-2016			
		09.10.2025				
1	Date of inspection		Shukla, ADO (L.N)			
3	Name of the inspecting officers					
9	Name of the designation of officer	Mr. Atul Sharm	ia (Caretaker)			
- 1	from the building side					
10	Year of construction	2025		1113873		
11	Applicant's letter no.		pplication no. 2025100	Remark		
S.No	Minimum Standards on fire	Requirements	Provided at Site	MR/		
	Prevention and fire safety	as per UBBL-		NMR		
	requirements U/R 33	NBC-2016		111122		
1	Access To Building:	Tco	6.0 m	MR		
	Road width	6.0 m	NA	NA		
	Gate width	NA	NA NA	NA		
- 5	Width of internal road	NA				
2	Number, Width, Type and Arrangement of Exits:					
	A Number of staircases	02 nos.	02 nos.	MR		
	a Upper floor	02 nos.	02 nos.	MR		
	b Basement	02 11001				
	B Width of staircases	1.50 m each	Provided	MR		
	a Upper floors) m		
	b Basement	1.50 m each	Provided	MR		
	C Protection of exits: (Re	quired as per claus	se 7.31. point no. x of	MR		
	a Fire check door	Required	Provided	NA		
	b Pressurization	NA	NA Provided	MR		
	D No. of continuous staircases	2 nos.	Flovided			
	to terrace	1.80 m	Provided	MR		
	E Width of corridor	1.0 mtrs.	Provided	MR		
	F Door size	1.0 mus.				
3	Compartmentation:	NA	NA	NA		
	A Fire check door	NA NA	NA	NA		
	B Sealing of electrical shafts	NA NA	NA	NA		
	C Fire rating of shaft door	NA NA	NA	NA		
	D Water curtain	NA	NA	NA		
		4305				
	E Fire dampers		T	MR		
4	Smoke Management System:	Required	Exhaust Fans			
4	Smoke Management System: A Basement	Required Required	Exhaust Fans Exhaust Fans	MR		
	Smoke Management System: A Basement B Upper floor					
	Smoke Management System: A Basement B Upper floor Fire Extinguisher:					
5.	Smoke Management System: A Basement B Upper floor	Required	Exhaust Fans	MR		

1

6	Fir	st-Aid-Hose Reels:	01	01 no.	MR		
	A	Total numbers of each floor	01 no.	30 m	MR		
	В	Length of hose reel hose	30 m	5 mm	MR		
	C	Nozzle diameter	5 mm		01/120/100		
7	Automatic Fire Detection And Alarming System: (Required as per Clause						
	7.31.viii, UBBL 2016 (Amendment dated 27.03.2019).						
	A	Type of detectors	CO detectors	Provided	MR		
	В	Location of main panel	At Ground	NA	NA		
	C	Location of repeater panel	NA NA	NA	NA		
	D	Alternate source of power Hooters	Audible in entire	Provided	MR		
	E	Hooters	building		incompanies.		
8	MC	DEFA:	NA	Provided	NA		
9	Pul	blic Address System:	NA	NA	NA		
10	Automatic Sprinkler System:						
	A	Basement	Required	Provided	MR		
	В	Upper floor	NA	Provided	NA		
	C	Sprinkler above false ceiling	NA	NA	NA		
11		ernal Hydrants:	15197-19		a stance of the factor		
11	A	size of riser/down-comer	NA	100 mm	NA		
	B	Number of hydrants per floor	NA	01 no.	NA		
	C	Hose box	NA	01 no.	NA		
12	- 65		IVA	01 110.	INA		
12	-	rd Hydrants:	l N/A	I NIA	Tar.		
	A	Total number of hydrants	NA	NA	NA		
12	В	Hose box	NA	NA	NA		
13	_	nping Arrangements:					
	A	Ground level					
	a)	Discharge of main pump	NA	NA	NA		
	b)	Head of main pump	NA	NA	NA		
	c)	Number of main pumps	NA	NA	NA		
	d)	Jockey pump out put	NA	NA	NA		
	e)	Jockey pump head	NA	NA	NA		
	f)	Standby pump out put	NA	NA	NA		
	g)	Standby pump head	NA	NA	NA		
	h)	Auto starting /manual	NA	NA	NA		
		stopping		2000	11/21		
	i)	Pump house access	NA	NA	NA		
	В	Terrace level	18	*			
	a)	Discharge of pump	900 LPM	Provided	MR		
	b)	Head of the pump	40 mtrs.	Provided	MR		
	c)	Power supply	Required	Provided	MR		
	d)	Auto starting of pump	Required	Provided	MR		
14	Captive Water Storage For Fire Fighting:						
	A	Underground tank capacity	NA	NA	NA		
	В	Draw-off connection	NA NA	NA NA	NA NA		
	C	Fire service inlet	NA	NA NA	NA NA		
	D	Access to tank	NA	NA NA	NA		
	E	Overhead tank capacity	10,000 ltrs	24,000 ltrs	MR		
15		t Signage:	Required	Provided	MR		
16	Provision of Lifts:						
	A	Pressurization of lift shaft	NA	NA	NA		
	В	Pressurization of lift lobby	NA	NA	NA		
	C	Communication in lift car	NA	NA	NA		
À	D	Firemen's grounding switch	NA	NA	NA		
14.9	E	Lift signage	NA	NA	NA		
17	Sta	ndby Power Supply:	Required	Provided	MR		

18	Refuge Area:					
	A	Total area	NA	NA	NA NA	
	В	Location	NA	NA	NA	
19	Fire Control Room:					
	A	Detector system panel	NA	NA	NA	
	В	Flow switch panel	NA	NA	NA	
	C	Pa system panel	NA	NA	NA	
	D	Battery backup	NA	NA	NA	
	E	Building floor plans	NA	NA	NA	
20	Sp	Special Fire Protection Systems For Protection of Special Risks, If Any:		NA	NA	

LEGENDS:-Meeting Requirement (MR), Not Meeting Requirement (NMR), Not Applicable (NA), Provided but Not Functional (PNF), Not Provided (NP).

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspections.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety measures as required under the Rules, it is recommended to grant Fire Safety Certificate under Rules 35 of Delhi Fire Service Rules 2010

Signature of the Inspecting Officer
Name Rajesh Kumar Shukla
Designation ADO (L.N)

Finohal Diversity

A.K. MALIK

A.K. MALIK