## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI – 110001

F.6/DFS/MS/GH/2025/ 206

Dated: 16/04/2025

## **FIRE SAFETY CERTIFICATE**

Certified that M/s HOTEL SOUTHGATE located at C-18, Green Park Extension, New Delhi-110016 in a building comprised of Basement, Ground Floor (Reception & Office) 1<sup>st</sup> Floor- 08 G/Rooms, 2<sup>nd</sup> Floor- 08 G/Rooms & 3<sup>rd</sup> Floor- 08 G/Rooms Total 24 Guest rooms owner/occupied by South Gate Resorts and Hotels Pvt Ltd, was earlier issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/GH/2022/SZ/365 dated 01-08-2022. Now, the premise was re-inspected by the officer concerned of this department on 05/04/2025 in the presence of Manager and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential & Lodging", Group-A" ground floor – reception & office, 1<sup>st</sup> to 3<sup>rd</sup> floor (08 guest rooms each floor) total 24 Guest Rooms up to third floor only, with effect from the date of issue 16/04/2025 for a period of Three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 16 04 205 at New Delhi by

(Atul Garg) DIRECTOR Delhi Fire Service

Copy to: -

- 1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy as detailed above and deviation in construction if any.
- 2. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi. ID no. 2025010200035 dated 02.01.2025.
- 3. M/s HOTEL SOUTHGATE located at C-18, Green Park Extension, New Delhi-110016.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times. This FSC is valid for guest house ground to third floor only.
- 2. Any loss of life or property due to nonfunctional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. The compliance with regards to electrical installation, structural stability, set back area, occupancy and any deviation in construction etc. shall be verified from authority concerned.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The means of escape such as staircase, exits, corridor, etc shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. Basement shall be used strictly as per BBL concerned.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 10. Any flammable material for interior decoration is prohibited.

		ON REPORT					
/	Name & Address of the Building	M/s Hotel So	M/s Hotel SOUTHGATE (South Gate Resorts				
1	Name & Table	1	and Hotels Pvt Ltd, at C-18, Green Park				
		Extension, New Delhi–110016.  Residential, "Group-A" (Guest House) Gr Rec. &					
	00						
2	Type of Occupancy	office, 1st to third floor (08 room at ea					
-				at each floor ) -			
		24 guest room					
3	Building Comprised of	Basement, Ground + 3 upper floors.					
4	Type of Case	Renewal					
5	Details of Previous NOC		F.6/DFS/MS/GH/2022/SZ/365 dated 01-08-2022				
6	Fire Safety Directives Letter No	Nil					
7	Date of Inspection	05-04-2025					
8	Name of the Inspecting Officers	Sh. Ravinder Singh, ADO					
9	Name & Designation of Officers	Manager	Manager				
	from the building side						
10	Year of construction	2008	2008				
11	Applicant letter No.	MHA Portal ID	2025031803918 date	d 18-03-2025			
S. No.	Minimum standards on Fire Prevention	Requirements	Provided at Site	Remarks			
	and Fire Safety U/R 33			MR/NMR			
1	Access to Building.		T 5 11 1	MR			
	Road width	6 mtr	Provided				
	Gate width	Required	Accessible from roa				
	Width of internal road	-NA-	-NA-	-NA-			
2	Number, width, type & arrangement of exits.						
	a) Number of Staircase						
	> Upper floors.	01 No	Provided	MR			
	> Basement floor.	02 Nos	Provided	MR			
	b) Width of Staircase						
	> Upper floors	1.25 mtr	1.25 mtr	MR (old case)			
	Basement floor	1.25 mtr	1.25m & 0.80m	MR (old case)			
	c) Protection of exits						
	Fire check door as per clause 7.31	Required	Provided	MR			
	in UBBL- 2016 ➤ Pressurization	-NA-	-NA-	-NA-			
·		01 No	Provided	) AD			
	<ul><li>d) No. of continuous staircase to terrace</li><li>e) Width of corridor</li></ul>	-NA-	-NA-	MR -NA-			
	f) Door size	1m	1m (final exit)	MR			
3	Compartmentation.		(mar onte)	IVIIC			
	Fire check door.	-NA-	-NA-	-NA-			
	Sealing of electrical shafts.	-NA-	-NA-	-NA-			
	Fire rating of shaft door.	-NA-	-NA-	-NA-			
	Water curtain     Fire demands	-NA-	-NA-	-NA-			
4	• Fire dampers.	-NA-	-NA-	-NA-			
-	Smoke Management system.  • Basement	As per clause 7.3	31 in UBBL 2016				
	Upper floors	12 ACPH	Exhaust fan provided	MR			
5	Fire Extinguishers.	12 ACPH	Provided	MR			
3	Total numbers			TVIIC			
	Types	1.	12 Nos	MR			
	ISI Marking	ISI marked	ABC & W.CO <sub>2</sub>	MR			
6	First Aid Hose Reels.		Provided	MR			
	Total numbers on each floor.			IVIIC			
	on outil Hoor.	Hose-reels	01 No	MR			
			30m	MR			
				TATE			

		7- 1		
	<ul> <li>Length of hose-reel hose.</li> </ul>			
	Nozzle Diameter		5mm	MR
7	Automatic fire detection & alarming system.	As per clause 7.31 in UBBL 2016		
•	<ul> <li>Type of detectors</li> </ul>	Co/detector	Provided	) Am
•.	<ul> <li>Location of Main Panel</li> </ul>	Required	Ground floor	MR
	<ul> <li>Location of Repeater Panel</li> </ul>	-NA-	-NA-	MR
	<ul> <li>Alternate source of power</li> </ul>	Required	Battery backur	-NA-
	Hooter's location	Required	Each floor	- Tranc
8	MOEFA	Required	Provided	MR
9	Public Address System	Required	Provided	MR
10	Automatic Sprinkler System			MR
	Basement	Required	Provided	MR
	• Upper floors	-NA-	-NA-	-NA-
11	Sprinkler above false ceiling	-NA-	-NA-	1
11	Internal Hydrants.			-NA-
	Size of Riser/Down-comer	100 mm	Provided	MR
	Number of Hydrant per floor	One	Provided	MR
12	Hose box.	One	Provided	MR
12	Yard Hydrants.			IVIK
	Total number of hydrants.	-NA-	-NA-	-NA-
13	Hose box.	-NA-	-NA-	-NA-
13	Pumping arrangements.			1111
	• Ground Level			
	Discharge of main pump.	-NA-	-NA-	-NA-
	Head of main pump.	-NA-	-NA-	-NA-
	<ul><li>Number of main pumps.</li><li>Jockey Pump output.</li></ul>	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	Standby Pump head.	-NA-	-NA-	-NA-
	➤ Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
,	➤ Pump house access.	-NA-	-NA-	-NA-
	Terrace Level	-NA-	-NA-	-NA-
	Discharge of pump.	450 I D) 4		
	> Head of pump.	450 LPM	Provided	MR (old case)
	> Power supply.	35m	Provided	MR
	➤ Auto starting of pump.	Required Required	Provided	MR
14	Captive water storage for fire fighting.	Required	Provided	MR
	Underground tank capacity.	-NA-	10,000 Ltr	-NA-
	Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	Access to tank.	-NA-	-NA-	-NA-
	Overhead tank capacity.	5,000 Ltr	Provided	MR (old case)
15	Exit Signage.	Required	Provided	MR
16	Provision of Lifts.			
	Pressurization of lift shaft.	-NA-	-NA-	-NA-
	Pressurization of lift lobby.	-NA-	-NA-	-NA-
	• Communication in lift car.	Required	Provided	MR
	• Fireman's switch.	Required	Provided	MR
17	Lift signage.  Standby Power Supply	Required	Provided	MR
18	Refuge Area	Required	Provided	MR
	Total area	-NA-	-NA-	-NA-
	• Location	-NA-	-NA-	-NA-
		-11/A*	-INA-	-IVA-

MUS Fire Control Room. Detector system panel. Flow switch panel. -NA--NA--NA-PA system panel. -NA--NA--NA-Battery backup. -NA--NA--NA-Building floor plan. -NA--NA--NA-Special Fire Protection System for the -NA--NA-Required ABC type fire extinguishers Protection of special Risk, if any. -NAprovided near elec. panel MR The fire protection systems provided in the building were randomly tested, checked and found The fire protection systems provided in the fire protection. Basement is being used for storage purpose photo enclosed and In view of the deemed compliance of the minimum standards of fire prevention and fire In view of the declined complete the rules, if agreed, we may renew the FSC issued vide letter No. F.6/DFS/MS/GH/2022/SZ/365 dated 01-08-2022, under rule 35(6) of the Delhi Fire Service Rules Signature of the Inspecting Officer

> Name :- Ravinder Singh Designation :- ADO (CC)

Dot spuggeste

adh — Muler olyps

CFO (MOS)

41 pors

Dêneeta

mu

Ascepane) en pertubler ken peruera

Synalus glean

15/1125

Dreet Mall

U bloode)