



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110 001**

No. F.6/DFS/MS/GH/2025/NDZ/ 468

Dated: 06 08 2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Jaggi Palace Guest House located at T-2347, Ashok Nagar, Faiz Road, Karol Bagh, New Delhi, comprised of Basement, Ground floor (Reception + 04 guest room + lobby) & 1st floor to 3rd floor (05 guest rooms at each floor) Total 19 guest rooms was earlier granted FSC by this department vide letter no. F.6/DFS/MS/GH/2022/NDZ/235 dated 20/05/2022. The premises was reinspected by the officer concerned of this department on 29/07/2025 in the presence of Sh. Suraj Singh, Manager and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class "Residential" Sub- Division-A-1, Ground floor (Reception + 04 guest room + lobby) & 1st floor to 3rd floor (05 guest rooms at each floor) Total 19 guest rooms up to third floor only with effect from 06/08/2025 up to valid 31/03/2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Q, CHIEF FIRE OFFICER

To,

1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy a detailed above.

2. Sh. Paramjeet Singh, M/s Jaggi Palace Guest House located at T-2347, Ashok Nagar, Faiz Road, Karol Bagh, New Delhi MCD online ID 2025070811131

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.

6. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building

:M/s Jaggi Palace Guest House,

T-2347, Ashok Nagar, Faiz Road, Karol Bagh

New Delhi

2. Type of Occupancy

:Residential, Sub Division-A-1 (Guest House)

3. Building is comprised of

:Basement, Ground + 03 upper floors

Ground floor (Reception + 04 guest room + lobby) & 1st floor to 3rd floor (05 guest rooms at each floor) Total 19 guest rooms

4. Type of Case

:Renewal

5. Details of Previous NOC letter

:F.6/DFS/MS/GH/2022/NDZ/235 dated 20/05/2022

6. Fire Safety directive letter No

: Nil

7. Date of Inspection

: 29/07/2025

8. Name of the Inspecting officers

:ADO (Shd.) Deepak Kumar

9. Name and designation of Officer

from the building side

: Sh. Suraj Singh (Manager)

10. Year of Construction

: 2008

11. Applicant's letter No

:2025070811131 dated 08/07/2025

sr. No.	Minimum Standards on fire prevention and fire safety U/R33	Requirement/ Existing Fire Safety arrangements	Provided at Site	Remarks MR/NMR			
1	Access to building.						
	Road width	06 mtr	12 mtr.	MR			
	 Gate width 	N/A	N/A	N/A			
	 Width of internal road 	N/A	N/A	N/A			
)2	Number, Width, Type and Arrangement of Exits.						
-	a. Number of Staircases						
	 Upper Floor 	01 no.	01 no.	MR			
	 Basement 	01 n s .	01 no.	MR			
	B. Width of Staircases	14	C1110 .	IVIIX			
	Upper Floor	1.25 mtr	1.25 mtr	MR			
-	Basement	1.25 mtr	1.25 mtr	MR			
	c. Protection of exits						
	Fire check door	N/A	N/A	N/A			
	 Pressurization 	N/A	N/A	N/A			
	d. No. of continuous staircases to terrace e. Width of Corridor	01 no.	01 nos.	MR			
	e. Width of Corridor	N/A	N/A	N/A			
	f. Door Size	01 no.	01 nos.	MR			
03	Compartmentation.						
	Fire check door	N/A	N/A				
	Sealing of electrical shafts	N/A	N/A	N/A			
	Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A N/A			
04	Smoke Management System.						
	Basement	12 a/c per hour	Exhaust fan	MR			
	Upper floor	12 a/c per hour	Natural/Exhaust fan	MR			
05.	Fire Extinguishers.						
	Total numbers	10 nos.	10 nos.	MR			
	• types	ABC/CO ₂	ABC/CO ₂	MR			
£.	IS marking	Required	Provided	MR			

2.

11/24.

06		04 No	01 No	MR			
	Total numbers on each floor	01 No.	30 mtr.	MR			
	Length of hose reel hose	30 mtr.	05 mm	MR			
07	Nozzle diameter Automatic fire detection and planning systematics	05 mm	00 11				
"	Automatic fire detection and alarming system.						
	Type of detectors CO	Required	Provided	MR			
	Location of main panel	Ground floor	Provided	N/A			
	Location of repeater panel	N/A	N/A Provided	MR			
	Alternate source of power	Required		MR			
	Hooter's location	Required	Provided	MR			
80	MOEFA	Required	Provided	MR			
09	Public address System.	Required	Provided	IVII			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	upper floor	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level	N/A	N/A	N/A			
_	Discharge of main Pump	N/A	N/A	N/A			
	> Head of Main Pump	N/A	N/A	N/A			
	> Number of main pumps	N/A	N/A	N/A			
	> Jockey pump out put	N/A	- N/A	N/A			
	> Jockey pump head	N/A	N/A	N/A			
	> Standby pump out put	N/A	N/A	N/A			
	> Standby pump Head	N/A	N/A	N/A			
	Auto Starting /Manual stopping	N/A	N/A	N/A			
	> Pump House Access	N/A	N/A	N/A			
	Terrace Level						
	Discharge of pump	450 Lpm.	450 Lpm.	MR			
	> Head of the Pump	40mtr.	40mtr.	MR			
	> Power supply	Required	Provided	MR			
	Auto Starting of pump	Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.			NVA			
	 Underground tank capacity 	N/A	N/A	N/A			
	Draw-off connection	N/A	N/A	N/A N/A			
	> Fire service inlet	N/A	N/A	N/A N/A			
	> Access to tank	N/A	N/A	MR			
	Overhead Tank capacity	5,000 ltrs.	5,000 ltrs.	MR			
15		Required	Provided	IVIT			
16	Provision of Lifts.						
	Pressurization of Lift Shaft	N/A	N/A	N/A			
		N/A	N/A	N/A			
	Pressurization of Lift lobby	N/A	N/A	N/A			
	Communication in lift car	N/A	N/A	N/A			
	 Firemen's grounding switch 	N/A	N/A	N/			
	Lift Signage						

17	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
_	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
		N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel	1	N/A	N/A		
	Battery backup	N/A	3,512.5	N/A		
	Building Floor Plans	N/A	N/A			
20	Special Fire Protection systems for protection of special Risks, if any:	N/A		N/A		

The fire protection systems provided in the building were tested/checked and found

functional at the time of inspection. Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the rule the FSC issued vide letter no. F.6/DFS/MS/GH/2022/NDZ/235 dated 20/05/2022, renewal under rule 35 of the Delhi Fire Service Rules 2010, is recommended.

Signature of the Inspecting Officer

: Deepak Kumar Name Designation : ADO (Shd)

Principal Director

Mscell