GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE

No.F.6/DFS/MS/EH/2025/SZ/230 NEW DELHI-110001

FIRE SAFETY CERTIFICATE

Certified that the Eating House in the Name & Style M/s Kaleva Foods situated at GF & FF, Kh. No 354, Sant Nagar, Shakur basti, Rani Bagh, Pitampura, Delhi 110034 comprised of Ground & One upper floor was issued Fire Safety Certificate by this department vide letter no. F.6/DFS/MS/EH/WZ/2022/264 dated 16/09/2022. The restaurant premise was re-inspected by the officer concerned of this department on 06/06/2025 in the presence of Mr. Sukesh of the restaurant and found that the said premise have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class D "Assembly Building" Restaurant at Ground & First floor only) and validity upto 31/03/2028 in accordance with rule 36/ unless renewed under rule 37 or sooner cancelled under Rule 40 and subject compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 20

Issued on ____1/_ 0 6/2025 at New Delhi by

DELHI FIRE SERVICE

Copy to: -

1. The Addl. Commissioner of Police, Lic/Branch, 1st Floor PS Defence Colony, New Delhi 110049 (Ref. MCD Portal No. 2025050107685 dated 10/05/2025)

Conditions for the validity of Fire Safety Certificate: -

1. All the means of escape/entry/exit shall be kept free from any obstruction.

2. All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

5. This fire safety certificate may not in any way be treated as regularization (Clause UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of 2.8 of

UBBL-2016), if any.

"The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

	J	11	O	
٠1			100	

1	Name & Address of the Building	M/s Kaleva Foods situated at GF & FF Kh. No 354				
2	Type of Occupancy	Delhi 110034				
3	Building Comprised of	Restaurant at G	round and First Floor or	nly		
4		Ground & First Floor only				
5	Type of Case	Renewal				
	Details of Previous NOC	F.6/DFS/MS/EH/WZ/2022/264 dated 16/09/2022				
6	Fire Safety Directives Letter No	Nil				
7	Date of Inspection	06/06/2025				
8	Name of the Inspecting Officers	ADO (BCP)				
9	Name & Designation of Officers from the building side	Mr. Sukesh				
10	Year of construction	2000				
11	Applicant letter No.	MCD Portal No. 2025050107685 dated 10/05/2025				
S. No.	Minimum standards on Fire Prevention and Fire Safety U/R 33			Remarks MR/NMR		
1	Access to Building.		er dy U. løte	MR		
17	Road width	Required	Provided	MR		
	Gate width	4.50 mtr	Provided	N/A		
	Width of internal road	N/A	N/A	N/A		
2	Number, width, type & arrangement of ex	its.	Bys I promoter in			
	a) Number of Staircase	.gam atan	le sy osite ty l	MR		
	> Upper floors.	02 Nos	03 Nos	N/A		
	> Basement floor.	N/A	N/A	1077		
	b) Width of Staircase	rangelikal la Kawada	1 50 & 0 00m	MR		
	> Upper floors	1.50 mtr each	2m, 1.50m & 0.99m N/A	N/A		
	> Basement floor	N/A	N/A			
	c) Protection of exits	nthous lumbin	N/A	N/A		
	> Fire check door	N/A		· N/A		
	> Pressurization	N/A	03 No	MR		
	d) No. of continuous staircase to terrace	Required	N/A	N/A		
	e) Width of corridor	N/A (100 100 100 100 100 100 100 100 100 10	2.10m & 1.55m	MR		
	f) Door size	2 x 1.50 mtr	2.10m & 1.55m			
3	Compartmentation.	N/A	N/A	N/A		
1164	Fire check door.	N/A	ngana N/A	N/A		
	Sealing of electrical shafts.	N/A	N/A	N/A		
	Fire rating of shaft door.	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	• Fire dampers.		Title Land	5		
4	Smoke Management system.	30 ACPH	N/A	N/A		
	Basement	12 ACPH	Natural Ventilation	MR		
	• Upper floors	12 ACI II	. manu Tonniauon	IVIK		
5	Fire Extinguishers.	08 Nos	10 Nos) M		
	Total numbers	ABC/CO ₂		MR		
	• Types	ISI marked	ABC- & CO ₂ - Provided	MR		
	ISI Marking ISI Marking	151 marked	Flovided	MR		
6	First Aid Hose Reels. Total numbers on each floor.	One	Provided			
	Length of hose-reel hose.	30m	Provided	MR		
	Nozzle Diameter	5mm	Provided	· MR		
7	Automatic fire detection & alarming system		Danivor	MR		

•	Type of detectors		आज़ाई	का महोत्स
•	Location of Main Panel	N/A		ाहात्स्र ।
•	Location of Repeater Panel	N/A	N/A	N/A
•	Alternate source of power	N/A	N/A	N/A
	Hooter's location	N/A	N/A	N/A
8 MOE		N/A	N/A	N/A
	c Address System	Required	N/A	N/A
10 Auto	natic Sprinkler System	N/A	Provided	MR
	Basement	N/A	N/A	N/A
	Ground G	21/4	Z 1 10 10 10 10 10 10 10 10 10 10 10 10 1	IVA
	Ground floor.	N/A	N/A	N/A
11 Inter	Sprinkler above false ceiling	N/A	N/A	N/A
	Juliants.	N/A	N/A	N/A
	Size of Riser/Down-comer	Day 1		IVA
a, th.	Number of Hydrant per floor Hose box.	Required	100 mm	1/10
12 Yard	Hydrants.	Required Required	One	MR
NE T		voduned	One	MR MR
the Co	Total number of hydrants. Hose box.	MIA		IVIK
13 Pum	Hose Dox.	N/A	N/A	NIA
- 411	oing arrangements.	N/A	N/A	N/A
-	Ground Level	A religion		N/A
	Discharge of main	medius 5	RETURNATION OF THE	
100	ricad of main nume	N/A	N/A	77/4
	Number of main pumps.	N/A	N/A	N/A
ii- li	Jockey Pump output.	N/A	N/A	N/A
7.2	Jockey Pump head. Standby Pump output.	N/A	N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting/Manual Stopping.	N/A	N/A	N/A
	Pump house access.	N/A	. N/A	N/A
	200033.	N/A	N/A	N/A
Mill	Terrace Level	N/A	N/A	N/A
	Discharge of pump	Ethiop and Spending	browning in the s	N/A
187	Head of pump	450 LPM	450 LPM	D .
	Power supply	40 m	Provided	MR
4 17* 1 X	Auto starting of pump.	Required	Provided	MR
14 Capt	ve water storage for fire fighting.	Required	Provided	MR
•	Underground tank capacity.	alightens:	riovided	MR
	Draw-off connection.	N/A	N/A	
2	Fire Service Inlet.	N/A		N/A
-	Access to tank	N/A	N/A	N/A
•	Overhead tank capacity.	N/A	N/A	N/A
15 Exit S	ignage.	20,000 Ltrs	N/A	N/A
16 Provi	sion of Lifts.	Required	20,000 ltr	MR
2.1001		quired	Provided	MR
1 2	Pressurization of lift shaft.	N/A	22	ul
	Pressurization of lift lobby	N/A N/A	N/A	N/A
<u>.</u>	Communication in lift car	N/A	N/A	N/A
	Fireman's switch	N/A	N/A	N/A
17 Stand	Lift signage.	N/A	N/A	N/A
~tatili	by Power Supply	Required	N/A	N/A
Kefug	e Area	rodaned	Provided	MR
•	Total area			
	Location	N/A	N/A	N/A
		N/A	N/A	N/A

				7	
19	Fire	Control Room.	~/\2	आज़	ादी _{का}
		Detector system panel			गदी _{का} मृत महोत्सर
		Flow switch panel	N/A		
		PA system panel	N/A	N/A	N/A
		Battery backup.	N/A	N/A	N/A
		Building floor plan	N/A	N/A	N/A
20 S	Spe	Special Fire Protection System for the Protection of special Risk, if any.	N/A	N/A	N/A
	Pro			N/A	N/A
		or special Risk, if any.	N/A	N/A	N/A

The Fire protection systems provided in the premises were test checked at random and Keening in views of the premise were test checked at random and

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no rules, 2010 is recommended.

Keeping in view of the deemed compliance of the minimum standard on fire prevention rules, as required under the rules, the FSC issued vide letter no rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer
Name: Sh. Rajesh Kumar

Design: ADO (BCP)

``

DCFO(WZ)

1916

Deted alb last

Dineston Dineston

to opporoved, F.T. let

for I gone Syratux &

Uplade)

ie puli

11/4/201