

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001



No. F6/DFS/MS/School/WZ/2025/1192

Dated:-

25/09/2025

## **FIRE SAFETY CERTIFICATE**

Certified that the Late Smt. Kaushalya Devi Memorial Educational Society (The Richwood School), located at Block-B, Meera Bagh, Paschim Vihar, Delhi-110063, comprised of basement, stilt, ground + 02 upper floor, owned/occupied by Late Smt. Kaushalya Devi Memorial Educational Society (The Richwood School), have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and verified by the officer concerned of Fire Service on 09/09/2025 in the presence of Sh. Rajesh Vij (Chairman) and that the building/premises is fit for occupancy class "Educational Building" Group B with effect from 25 09 2025 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 25 109 25 at New Delhi by

Virendra Singh
Chief Fire Officer

Copy to:-

- 1. The Deputy Director, Delhi Municipal Corporation, Civic Centre, Minto Road, Delhi-110002.
- 2. The Principal, Late Smt. Kaushalya Devi Memorial Educational Society (The Richwood School), B-Block, Meera Bagh, Paschim Vihar, Delhi-110063.

Conditions for validity of fire safety certificate:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

- 5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.
- 6. All comments / directions of licensing Department shall always be permitted and followed.
- 7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.
- 9. The basement shall be used as per BBL.

## INSPECTION REPORT

1. Name and address of the building: Late Smt. Kaushalya Devi Memorial Educational

Society (The Richwood School), located at Block-B, Meera Bagh, Paschim Vihar, Delhi-110063

2. Type of Occupancy

: Educational

3. Type of Case

: New

4. Details of previous NOC

: Nil

5. Fire Safety directives Letter No.

: F.6/DFS/MS/BP/2015/School/327 dated 18/12/2015

6. Date of inspection

: 09/09/2025

7. Name of the Inspecting Officer

: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Rajesh Vij (Chairman)

9. Year of Construction

: 2024-25

10. Applicant's letter No.

: nil dated 20/08/2025

The building is comprised of basement, stilt, ground plus two upper floors only.

S No	Minimum standards on fire prevention and fire safety U/R 33	Requirements as per directive letter issued dated 18/12/2015  Provided at site		Remarks MR/NMR		
1.	Access of building					
	<ul> <li>Road width</li> </ul>	06 m 9.1 m		MR		
	<ul> <li>Gate width</li> </ul>	4.5 m	4.5 m	MR		
	<ul> <li>Width of internal road</li> </ul>	NA	A NA			
2.	Number, width, Type & Arrangements of exits					
	<ul> <li>a. Number of staircases</li> </ul>					
	<ul> <li>Upper floors</li> </ul>	02 nos.	Provided	MR		
- 1	<ul> <li>Basements</li> </ul>	NA	NA	NA		
- 1	<ul> <li>b. Width of staircases</li> </ul>					
	<ul> <li>Upper floors</li> </ul>	1.5 m each	Provided	MR		
-	<ul> <li>Basements</li> </ul>	NA	NA	NA		
- 1	<ul> <li>c. Protection of exits</li> </ul>			241		
- 1	<ul> <li>Fire check door</li> </ul>	NA	NA	NA		
1	<ul> <li>Pressurization</li> </ul>	NA	NA	NA		
	d. No of continuous staircase to terrace	02 nos.	Provided	MR		
	e. Width Of Corridor	1.5 m	Provided	MR		
	f. Door Size	1.2 m	Provided	MR		
3.	Compartmentation					
J	Fire check door	Required	Provided	MR		
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	Provided	MR		
	<ul> <li>Fire Rating of shaft door</li> </ul>	, NA	NA	NA		
	<ul> <li>Water Curtain</li> </ul>	NA	NA	NA		
1 1	<ul> <li>Fire Dampers</li> </ul>	NA	NA	NA		
4.	Smoke managements System					
	<ul> <li>Basements</li> </ul>	Required	Provided	MR		
	Upper floors	Required	Natural Ventilatio	n MR		

		-
	•	
	J ~	
-		_

h-3					20:
	Fire Extinguishers	12	Provide		1 /6
	Total numbers	12 nos. ABC & CO <sub>2</sub>	Provide	1411	
	• Types	ISI marked	Provid		
	IS marking	151 marked	110110	- IVI	K
5.	First – Aid Hose Reels  Total numbers on each floor	01 nos.	Provid	ed N	IR I
- 1		30 m	Provid		1R
	Length of hose reel hose	5 mm	Provid		AR
	Nozzle diameter  Automatic fire detection and alarming	Control Contro			
7.	Automatic fire detection and alarming	NA	N/	1	NA
1	<ul><li>Type of detectors</li><li>Location of Main Panel</li></ul>	NA	N/	1	NA
	Location of Repeater Panel	NA	N/	1	NA
	Alternate source of power	NA	N.		NA
	Hooters' Location	NA	N	A	NA
		NA	N	Λ	NA
8.	MOEFA	Required	Prov	rided	MR
9.	Public Address System				
10.	Automatic Sprinkler System  Basements	Required		vided	MR
		NA		NA	NA
	Upper Floor	NA	1	NA	NA
	Sprinkler above false ceiling				
11.	Internal Hydrants:	NA		NA	NA .
	Size of riser/down-comer	214		NA	NA
	Number of hydrants per floor	NA		NA	NA
	Hose Box				
12.	Yard Hydrants	NA		NA	NA
	<ul> <li>Total number of hydrants</li> </ul>	NA NA		NA	NA
	Hose Box	INA			
13.	Pumping Arrangements:	1			
	Ground Level	NIA		NA	NA
	<ul> <li>Discharge of main pump</li> </ul>	NA		NA NA	NA
	Head of main pump	NA		NA NA	NA
	> Number of main pumps	NA		NA NA	NA
	Jockey pump out put	NA			NA
	> Jockey pump head	NA		NA	NA NA
	> Standby Pump out put	NA		NA	
	Standby Pump Head	NA		NA	NA NA
	> Auto Staring/Manual	NA		NA	NA
	stopping	7			
	> Pump House Access	NA		NA	- NA
	Terrace level				
	Discharge of pump	1620 lpr	• •	rovided	MR
	> Head of the pump	40 m	P	rovided	MR
		Require		rovided	MR
	<ul><li>Power supply</li><li>Auto starting of pump</li></ul>	Require	<u> </u>	rovided	MR
			<u>, u</u>		
14	. Captive water Storage for fire figh	iting:		NA	NA NA
	<ul> <li>Under ground tank capacit</li> </ul>	y NA		NA	NA
	> Draw off connection	NA			NA NA
4	> Fire service inlet	NA		NA	
	STATE	NA	Δ	NA	NA
	Access to tank		178	Provided	MR
-	Access to tank  Overhead Tank capacity	25,000	ltrs.		
	<ul> <li>Overhead Tank capacity</li> </ul>	The second secon		Provided	MR
15	Overhead Tank capacity     Exit Signage	25,000 Requ			MR
15	<ul> <li>Overhead Tank capacity</li> <li>Exit Signage</li> <li>Provision of Lifts</li> </ul>	Requ	ired	Provided	MR
	<ul> <li>Overhead Tank capacity</li> <li>Exit Signage</li> <li>Provision of Lifts</li> <li>Pressurization of Lift Sha</li> </ul>	Requi	ired A	Provided NA	NA NA
	<ul> <li>Overhead Tank capacity</li> <li>Exit Signage</li> <li>Provision of Lifts</li> <li>Pressurization of Lift Sha</li> <li>Pressurization of lift lobb</li> </ul>	Requirement of the second of t	A A	Provided  NA  NA	NA NA
	<ul> <li>Overhead Tank capacity</li> <li>Exit Signage</li> <li>Provision of Lifts</li> <li>Pressurization of Lift Sha</li> <li>Pressurization of lift lobb</li> <li>Communication in lift Ca</li> </ul>	Requirement of the second of t	A A A	NA NA NA	NA NA NA
	<ul> <li>Overhead Tank capacity</li> <li>Exit Signage</li> <li>Provision of Lifts</li> <li>Pressurization of Lift Sha</li> <li>Pressurization of lift lobb</li> <li>Communication in lift Ca</li> </ul>	Requirement of the second of t	A A	NA NA NA Provided	NA NA NA MR
	<ul> <li>Overhead Tank capacity</li> <li>Exit Signage</li> <li>Provision of Lifts</li> <li>Pressurization of Lift Sha</li> <li>Pressurization of lift lobb</li> <li>Communication in lift Ca</li> </ul>	Required No. 10	A A A	NA NA NA	NA NA NA MR
	<ul> <li>Overhead Tank capacity</li> <li>Exit Signage</li> <li>Provision of Lifts</li> <li>Pressurization of Lift Sha</li> <li>Pressurization of lift lobb</li> <li>Communication in lift Ca</li> <li>Fireman's Grounding Sw</li> </ul>	Requirements of the second sec	A A A A uired	NA NA NA Provided	NA NA NA MR

8.	Refuge Area	NA	NA	NA
	> Total area	NA NA	NA	NA
	> Location	y*****		
19.	Fire control room	NA	NA	NA
	> Detector system panel	NA	NA	NA
	> Flow Switch Panel	NA	NA	NA
	> PA System Panel	NA	NA	NA
	> Battery backup	NA	NA	NA
	> Building Floor Plans	NA	NA	NA
20.	Special Fire Protection Systems for Protection of special Risks, if any;			

Fire protection systems provided in the building were checked and found working at the time of inspection.

Keeping in view substantial compliance of the minimum standards of fire prevention and fire safety requirements under the rules, grant of Fire safety Certificate is recommended under rule 35 of the Delhi Fire service Rules 2010 under the DFS Act 2007.

Accordingly, DFA is prepared & put up for approval please.

Aman Kumar Lathar ADO (JWP)

F.F. letter is mutufo for openature bl.