GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE **NEW DELHI- 110001**

No. F.6/DFS/MS/GH/2025/SZ/57

Dated: 29/01/2025

FIRE SAFETY CERTIFICATE

Certified that the M/s La-Vista Guest House at Plot No. 937, Street No. 3, Naiwalan, Karol Bagh, New Delhi, comprised of, basement (vacant), ground floor (reception, lobby & office), 1st floor to 3rd floor (05 guest rooms at each floor) (total 15 guest rooms only), was issued FSC by this department vide letter No. F.6/DFS/MS/NDZ/2019/2030 dated 22.10.2019. The premises was re-inspected by the officer concerned of this department on dated 20.01.2025 in the presence of Sh. Rachit Gupta (Director) and found that the guest house have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi fire service Rules 2010 and that the building/premises is fit for occupancy, class "Residential" (Guest house) (15 guest rooms only upto 3rd floor only) w.e.f 29 01 2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on 29/01/2025 at New Delhi.

Delki Fire

Copy to: -

1 The Commissioner, MCD, Delhi: to ensure the occupancy as detailed above and deviation,

2 Online application Id 2025010600204 dated 08.01.2025.

The Executive Engineer (Bldg.), MCD, Civic Centre, New Delhi.

: - for information regarding use of basement.

Conditions for the validity of fire safety certificate: -

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.

3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

4. The trained staff should be available round the clock.

5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

6. The certificate may not be treated in any case for the regularization of the unauthorized

construction, if any.

7. Basement shall be used as per the building bye laws and use of the basement will only be allowed after permission from MCD. Presently basement is vacant.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building

: Lavista Guest House at 937, Street No. 3, Naiwalan, Karol Bagh,

New Delhi.

2. Building is comprised of

: B, G+3 upper floors (total 15 guest rooms), Ground (Reception, lobby & office), 1st floor to 3rd floor (05 guest rooms at each floor)

3. Type of Occupancy

: Residential (Guest House)

4. Type of Case

: Renewal

5. Details of Previous FSC letter

: F.6/DFS/MS/NDZ/2019/2030 dated 22.10.2019

6. Fire Safety direction letter No

: N/A

7. Date of Inspection

: 20.01.2025

8. Name of the Inspecting officers

: ADO R.K. Yadav (JKP)

9. Name and designation of officer

from the building side

: Sh. Rachit Gupta (Director)

10. Year of construction

2010

11 Applicant's letter No

ID No. 2025010600204 dated 08.01.2025

Sr. No.		num Standards on Fire ntion and Fire Safety U/R33	Requirement	Provided at Site	Remarks MR/NMR		
1	Acces	s to Building.		g-said to			
75	•	Road width	N/A	06 m	N/A		
	•	Gate width	N/A	N/A	N/A		
	•	Width of internal road	N/A	N/A	N/A		
2	Numb	oer, Width, Type and Arrang	ement of Exits.	TANK TO S			
	a. Number of Staircases						
		Upper floor	01 Nos.	01 Nos.	100		
	•	Basement	01 Nos.		MR		
	B. Wi	dth of Staircases	01 1403,	01 Nos.	MR		
		Upper floor	0.80 m, old case	1.23 to 1.28 m	MR		
	•	Basement	0.80 m, old case	1.28 m	MR		
	c. Pro	tection of Exits					
	•	Fire check door	N/A	N/A	N/A		
	•	Pressurization	N/A	N/A	N/A		
	d. No. Terrac	of Continuous Staircases to e	01	01	MR		
	e. Wic	th of Corridor	N/A	2.20, 2.05 m	N/A		
	f. Doo	r Size	1.0 n	0.89 × 2.08 m	MR, old		
3	Compartmentation.						
	•	Fire check door	N/A	N/A	N/A		
	•	Sealing of electrical shafts	N/A	N/A	N/A		
	•	Fire rating of shaft door	N/A	N/A	N/A		
		Water curtain	N/A	N/A	N/A		
	•	Fire dampers	N/A	N/A	N/A		
4	Smoke Management System.						
		Basement	30 ACPH	Exhaust fan	MR		
	10.2	Upper floor	12 ACPH	Natural Ventilation	MR		
5.	Fire Extinguishers.						
	25/105/25 (1997)	Mario de Caractería de Caracte	12 ====	Provided	MR		
		Total numbers	12 nos.	Provided	MR		
	•	Types	ABC /CO ₂ ISI marked	Provided	MR		
Vic	•	IS marking	151 Harkeu	Tiovided	IVIIX		

N	12
---	----

	Total Ald Harry Davids					
06	First-Aid-Hose Reels. The description of the Provided Provided Provided Provided			MR		
	Total numbers on each floor	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR		
	Nozzle diameter	05 mm				
0.5	Automatic Fire Detection, CO detect					
07		Required	110110	MR		
	CO Type of detectors	Ground floor	Provided	MR		
	 Location of main panel 	N/A	N/A	N/A		
	 Location of repeater panel 	Required	Provided	MR		
	 Alternate source of power 	N/A	N/A	N/A		
	Hooter's location		Provided	MR		
08	MOEFA	Required	Provided	MR		
09	Public Address System.	Required				
10	Automatic Sprinkler System.	and all the	9 (4.4	MR		
	Basement & Stilt	Required	Provided	N/A		
		N/A	N/A	N/A N/A		
	upper floorsprinkler above false ceiling	N/A	N/A	IV/A		
11	Internal Hydrants		Shinane			
11		27/4	N/A	N/A		
	size of riser/down-comer	N/A	N/A	N/A		
	 Number of hydrants per floor 	N/A	N/A	N/A		
	Hose box	N/A				
12	Yard Hydrants.					
	Total number of hydrants	N/A	N/A	N/A		
	Total number of hydrants Hose box	N/A	N/A	N/A		
13	Pumping Arrangements.					
	> Ground Level					
	Discharge of main pump			NIA		
	Head of main pump	N/A	N/A	N/A		
	Number of main pumps	N/A	N/A	N/A		
	Jockey pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby pump out put	N/A	N/A	N/A		
	Standby pump head	N/A	N/A	N/A		
	Auto starting /manual	N/A	N/A	N/A		
	stopping	N/A	N/A	N/A		
	Pump house access Terrace Level			F		
	6 (MSS0)MSS0(SEVER)	450 LPM	450 LPM	MR		
	Discharge of pump	40 m	40 m	MR		
	Head of the pump	Required	Provided	MR		
	Power supply Auto Starting of pump	Required	Provided	MR		
4	Captive Water Storage for Fire Fighti			Digital Constitution		
	Underground tank capacity	N/A	N/A	N/A		
	Draw-off connection	N/A	N/A	N/A		
	Fire service inlet	N/A	N/A	N/A		
	Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	5,000 ltrs	5,000 ltrs	MR, old		
			1	case		
5	Exit Signage.	Required	Provided	MR		

10	Pressurization of Lift Shaft	N/A	N/A	N/A		
	 Pressurization of Lift lobby Communication in lift car Firemen's grounding switch 	- N/A	N/A	N/A		
		N/A	N/A	N/A		
		N/A	N/A	N/A		
	• Lift Signage	N/A	N/A	N/A		
,	Standby power supply	Required	Provided	MR		
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
0	Special Fire Protection systems for	N/A	N/A	N/A		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: - The building is comprised of Basement (vacant), ground floor (reception, lobby & office), 1st, 2nd, & 3rd floor each having 05 guest rooms respectively (total 15 guest rooms only).

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F.6/DFS/MS/NDZ/2019/2030 dated 22.10.2019, renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Signature of Inspecting Officer

Name: - R.K. Yadav Designation: - ADO (JKP)

DO (eb)

23/1/25

(Coloroz) - on leave

cfo

Deneter

400) W