GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI

No. F6/DFS/MS/School/WZ/2025/206

Dated: 04/03/2025

FIRE SAFETY CERTIFICATE

Certified that the Laurel High School, located at Behind IDPL CHBS Society, Pitampura Village, New Delhi-110034., comprised of Ground plus Three Upper Floors, owned/occupier by Millennium Child Education Society (Regd), 129 Harsh Vihar, Pitampura, Delhi-110034, was issued FSC vide letter No F6/DFS/MS/School/WZ/2022/235 dated 07/03/2022. The premises was re - inspected by the officer concerned by this department on 20/02/2025 in the presence of Sh. Amit Kumar and observed that all the fire prevention & fire safety arrangements provided in the premises found in good working condition. That the building/premises have deemed complied with fire prevention and fire safety requirements in accordance with DOE 3298-3398 dated 01/03/2011/NBC Part-IV and the building/ premises is fit for occupancy class "Educational" (Group –B) with effect from ON 2015... for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the condition under rule 38 of the Delhi Fire Service Rules, 2010. Condition mentioned below 1

Issued on ... 04/03/2025 at New Delhi.

Copy to:

1. Director of Education, GNCT of NCT of Delhi, Old Secretariat, Delhi 110054.

2. The Principal, Laurel High School, located at Behind IDPL CHBS Society, Pitampura Village, New Delhi-110034. Email ID-laurelhigh2@gmail.com.

Conditions for the validity of FSC:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. All the means of escapes/exits shall not be locked/blocked at any time for safe evacuation of the occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

PERC

	1	INSPECTION REPORT				
1.	Nam	e & address of the building	Laurel High School, located at Behind IDPL CHBS Soc			
			Titampura VIII	CLIDS SOCIE		
2.	Туре	of Occupancy	Educational			
3.	Type	of Case	Renewal			
4.	Deta	ls of previous NOC	F6/DFS/MS/School/WZ/2022/235 dated 07/03/2022.			
5.	Fire	Safety directives letter No	DOE 3298-3398 dated 01/03/2011/NBC Part-IV			
6.		of inspection	20/02/2025			
7.	Nam	e of the Inspecting Officers	Sarabjeet Singh ADO (MN)			
8.		and designation of officers	Sh. Amit Kumar			
18		the building side				
9.	Year	of Construction	2007 (As per previous Inspection Report dated 24/02/2023			
10.		icant's letter No.	Email dated 18/02/2025.			
The		chool building is comprised of				
S.	16	Minimum Standards on fire	As per Rule	120 6	Provided at site	Remarks
No.	_	vention and fire safety U/R 33	DFS Rule	2010	1	MR/NMF
1	Acc	ess to building			oregon and the	
12/3		Road width	06 mts	Directly	accessible from road	MR
		Gate width	05 mts		Provided	MR
	1	Width of internal road	NA	51	NA	NA
2	Nui	nber, Width, Type & Arrangen	nent of Exits			
	a. N	umber of staircases				1,335
	- 1	Upper Floors	02		Provided	MR
		Basements	NA NA		NA	NA
	b. V	lidth of staircases		din	And her	
		Upper Floors	1.50 mts	each	Provided	MR
		Basements	NA		NA	NA
	c. P	rotection of exits	العال أن	(P' -	. 4 4 7	
		Fire check door	NA		NA	NA
		Pressurization	NA	ELECTION OF	NA	NA
		o. of continuous staircases to terrac			02 Provided	MR
		'idth of Corridor	1.5 m		1.78 mts	MR
		oor Size	1.0 m	its	Old case	MR(old cas
3	Con	partmentation.	- 4			
	•	Fire check door	NA		NA	NA
	•	Sealing of electrical shafts	NA		NA	NA
	•	Fire Rating of shaft door	NA NA	0	NA	NA
	•	Water Curtain	NA		NA	- NA
	•	Fire Dampers	NA		NA	NA NA
4	Smo	ke Management System.			Name of the last o	
	•	Basements	NA		NA	NA
	•	Upper floors	NA		NA	NA
5	Fire	Extinguishers				
	•	Total numbers	07 no	s.	Provided	MR
		Types			Provided	
			CO ₂ , ABC t	ype		MR
	•	IS marking	ISI marked	- 1	Provided	MR
	First-	-Aid Hose Reels.			2011	100
		Total numbers on each floor	01	1	Provided	
	1				ASSE	MR
	1	Length of hose reel hose	30 mt		Provided	MR
	•	Nozzle diameter	05 mm	n	Provided	MR
- 1					334200000000000000000000000000000000000	IVIL

	A	a evetem			
	Automatic fire detection and alarming system. NA NA NA				
	Type of detectors Location of Main Panel	NA	NA	NA	
	55 154	NA	NA	NA	
	Location of Repeater Panel	NA	NA	NA	
	Alternate source of power	NA	NA	NA	
8	Hooters' Location MOEFA	Required	Provided	MR	
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
10	SERVICE CONTROL OF STREET	NA	NA	NA	
	Basement	NA	NA	NA	
	Upper Floor Carinkles above false seiling	NA	NA	NA	
	Sprinkler above false ceiling				
11	Internal Hydrants	100 mm	Provided	MR	
	Size of riser/down-comer	01	01	MR	
	Number of hydrants per floor	01	01	MR	
- 4	Hose Box	. 01	*		
12	Yard Hydrants.		NA	NA	
	 Total number of hydrants 	NA	V decrees a second control of	NA	
	Hose Box	NA	NA		
13	Pumping Arrangements.				
	Ground Level			NIA	
	Discharge of main Pump	NA	NA	NA NA	
	➤ Head of Main pump	NA	NA		
	> Number of main pumps	NA	NA	NA NA	
	> Jockey Pump out put	NA	NA	NA NA	
	> Jockey pump head	NA	NA	NA NA	
	> Standby Pump out put	NA	NA	NA NA	
	> Standby Pump Head	NA	NA	NA NA	
	> Auto Starting/ Manual stopping	NA	NA		
	> Pump House Access	NA	NA	NA	
	• Terrace level		ادار بيونون	MD	
	> Discharge of pump	02 x 450 LPM	Provided	MR MR	
	> Head of the pump	40 LPM each	Provided	MR	
	> Power Supply	Required	Provided	The state of the s	
	Auto Starting of pump	Required	Provided	MR	
14	Captive Water Storage for fire fighting	ng.	CONT.		
	Underground tank capacity	NA	NA	NA	
	> Draw-off connection	NA	NA	NA	
	> Fire service inlet	NA	NA	NA	
	Access to tank	NA	NA	NA	
	Overhead Tank capacity	5,000 lts	5,000 lts	MR	
5	Exit Signage.	Required	Provided	MR	
	Provision of Lifts.		Not Applicable		
_	THE STATE OF A LINES.	the state of the s	NA	NA	
6	Provision of Lift Shaft	NA			
6	Pressurization of Lift Shaft	NA NA	NA	NA	
6	Pressurization of Lift Shaft Pressurization of Lift lobby		a set services to the second	NA MR	
16	Pressurization of Lift Shaft	NA	NA	20,2428.1	



17	Standby power supply	MIS				
1,	AND THE PROPERTY OF THE PROPER	NA	NA	NA		
18	Refuge Area.					
	Total Area	NA	NA	NA		
	Location	NA	NA	NA NA		
19	Fire Control Room					
	Detector System Panel	NA	NA	NA		
	Flow Switch Panel	NA	NA	NA		
	PA System Panel	NA	NA	NA		
	Battery backup	NA	NA	NA		
	Building Floor Plans	NA	NA	NA		
20	Special Fire Protection Systems for Protection of special Risks, if any:	NA	NA	NA		

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules, the NOC vide letter no F6/DFS/MS/School/WZ/2022/235 dated 07/03/2022, renewal under DOE 3298-3398 dated 01/03/2011/NBC Part-IV is recommended.

1450 MA

Quepolisiz)

Signature of the Inspecting Officer Sarabjeet Singh ADO (MN)

24,24.043.ALW

- July your

Directally 120

ofm

Sir, F. T is put up for

your

Kigd

personal &

Signatur

, please

64/3/200

Directly Mant