## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/SZ/2025/ 356

Dated: 19/05/2025

## FIRE SAFETY CERTIFICATE

Issued on 19/05/2025 at New Delhi by

Delhi Fire Service

Tel: 011-23414000g

## Copy to:-

- 1. The Commissioner, MCD:- to kindly ensure the occupancy as detailed above & deviation, if any.
- The Joint Commissioner of Police (Licensing), 1<sup>st</sup> Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2025042507175 dated 25.04.2025.
- The Licensee, M/s LIV INN Guest House (A Unit of Castle Square Pvt. Ltd.) at E 14, Naraina Vihar, Delhi - 110028.

## Conditions for the validity of fire safety certificate

- No occupancy used above third floor and basement used for incidental storage purpose only shall be strictly adhered by Owner/occupier.
- All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.

|     |                                |  |               | INSPECT                                 | TION REPORT  |   |                       |  |
|-----|--------------------------------|--|---------------|---|--|---|-----------------------|--|
| 1   | Name & address of the building |  |               |   | M/s LIV INN Guest House (A Unit of Castle<br>Square Pvt. Ltd.) located at E 14, Naraina<br>Vihar, Delhi - 110028.  |   |                       |  |
| 2   | В                              | uildin   | g i           | s comprised of                          | (Basement + Ground + 03 upper floors)  Basement - (incidental storage)  Ground floor - (reception)  1 <sup>st</sup> floor - (06 guest rooms)  2 <sup>nd</sup> floor - (06 guest rooms)  3 <sup>rd</sup> floor - (06 guest rooms) |   |                       |  |
|     |                                |  |               |   |  |   |                       |  |
| 3   | Type of occupancy              |  |               |   | Residential  |   |                       |  |
| 4   | Type of case                   |  |               | case                                    | Renewal  |   |                       |  |
|     |                                | Details of previous FSC  |               |   | F6/DFS/MS/G  | F6/DFS/MS/GH/SZ/2022/333 dated 07.07.2022 |                       |  |
| 6   |                                | Fire safety direction letter no.   |               |   | Nil  |   |                       |  |
| 7   | _                              | Date of inspection   |               |   | 10.05.2025   |   |                       |  |
| 8   | _                              |  | _             | the inspecting officers                 | ADO (SPM)  |   |                       |  |
| 9   | 1                              | Name of the designation of officer from the building side                        |               |   |  |   |                       |  |
| 10  |                                | Year   | of            | construction                            | 2010   |   |                       |  |
| 11  |                                | Appl   | ica           | nt's letter no.                         | MCD portal ID No. 2025042507175 dated  |   |                       |  |
|     |                                | A.F.   |               |   | 25.04.2025   |   |                       |  |
| S.N | No                             | o Minimum Standards on fire<br>Prevention and fire safety<br>requirements U/R 33 |               |   | Requirements<br>as per FSC<br>dt. 07.07.2022   | Site                                      | Remarks<br>MR/<br>NMR |  |
| 1   |                                | Access To Building:  |               |   |  |   |                       |  |
|     |                                | Road width   |               | Old case                                | 18 m   | MR  |                       |  |
|     |                                | Gate width   |               |   | NA   | Directly<br>accessible from<br>road       | NA                    |  |
|     |                                | Wic  | lth           | of internal road                        | NA   | NA  | NA                    |  |
| 2   |                                |  |               | er, Width, Type and Arra                | angement of Exit   | s:  |                       |  |
|     |                                | A  |               | umber of staircases                     |  |   |                       |  |
|     |                                |  | a             | Upper floor                             | 01 no.   | 01 no.                                    | MR (being old case)   |  |
|     |                                |  | Ь             | Basement                                | 02 nos.  | 02 nos.                                   | MR                    |  |
|     |                                | В  | _             | idth of staircases                      | 011  | 1.07                                      | 200                   |  |
|     |                                |  | $\overline{}$ | Upper floor<br>Basement                 | Old case   | 1.27 m<br>1.27 m & 1.16 m                 | MR<br>MR              |  |
|     |                                | C  | _             | rotection of exits                      | Old case   | 1.27 III & 1.10 III                       | IVER                  |  |
|     |                                |  | _             | Fire check door                         | NA   | NA  | NA                    |  |
|     |                                |  | _             | Pressurization                          | NA NA  | NA NA                                     | NA                    |  |
|     |                                | D  | 1             | No. of continuous staircases<br>terrace |  | 01 no.                                    | MR                    |  |
|     |                                | E  |               | Width of corridor                       | Old case   | 1.15 m                                    | MR (being old case)   |  |
|     | 3                              | F  |               | Door size                               | Old case   | 80 cms x 202 cms                          | MR (being old case)   |  |
| F   | _                              | A  |               | Fire check door                         | NA   | NA  | NA                    |  |
|     |                                | B  | -             | Sealing of electrical shafts            | Required   | Sealed                                    | MR                    |  |
|     |                                | C  |               | Fire rating of shaft door               | NA   | NA  | NA                    |  |
|     |                                | D  | _             | Water curtain                           | NA NA  | NA NA                                     | NA                    |  |
|     |                                | E  | -             | Fire dampers                            | NA   | NA NA                                     | NA                    |  |
|     | 4                              |  |               | ke Management System:                   | - mtri disina  |   |                       |  |
|     |                                | A  | T             | Upper floors                            | 12 ACPH  | Natural/Ventilation & exhaust fans        | MR                    |  |
|     |                                | В  |               | Basements                               | 12 ACPH  | Exhaust fans                              | MR                    |  |

| _  | Fire Extinguisher:  A Total numbers 02 nos. each Provided MR |                                       |                       |                         |              |  |  |  |
|----|--|---------------------------------------|-----------------------|-------------------------|--------------|--|--|--|
|    | A  | Total numbers                         | 02 nos. each<br>floor |                         |              |  |  |  |
| +  | В  | Types                                 | CO <sub>2</sub> & ABC | Provided                | MR           |  |  |  |
| t  | C  | ISI marking                           | Required              | Provided                | MR           |  |  |  |
|    | First-Aid-Hose Reels:  |                                       |                       |                         |              |  |  |  |
| -  | A  | Total numbers of each floor           | 01 no.                | Provided                | MR           |  |  |  |
|    | В  | Length of hose reel hose              | 30 m                  | 30 m                    | MR           |  |  |  |
|    | C  | Nozzle diameter                       | 05 mm                 | 05 mm                   | MR           |  |  |  |
| 7  |  | omatic Fire Detection And A           |                       | :                       |              |  |  |  |
|    | A  | Type of detectors                     | Carbon<br>Monoxide    | Provided                | MR           |  |  |  |
|    | В -  | Location of main panel                | Required              | Provided near reception | MR           |  |  |  |
|    | C  | Location of repeater panel            | NA                    | NA                      | NA           |  |  |  |
|    | D  | Alternate source of power             | Required              | Provided                | MR           |  |  |  |
|    | E  | Hooters                               | Required              | Provided                | MR           |  |  |  |
| 8  |  | DEFA:                                 | Required              | Provided                | MR           |  |  |  |
| 9  |  | blic Address System:                  | Required              | Provided                | MR           |  |  |  |
| 10 | _  | tomatic Sprinkler System:             |                       |                         |              |  |  |  |
|    | A  | Basement                              | Required              | Provided                | MR           |  |  |  |
|    | В  | Upper floor                           | NA                    | NA                      | NA           |  |  |  |
|    | C  | Sprinkler above false ceiling         | NA                    | NA                      | NA           |  |  |  |
| 11 |  |                                       |                       |                         |              |  |  |  |
|    | A  | size of riser/down-comer              | NA                    | NA                      | NA           |  |  |  |
|    | В  | Number of hydrants per floor          | NA                    | NA                      | NA           |  |  |  |
| 7. | C  | Hose box                              | NA                    | NA                      | NA           |  |  |  |
| 12 | Y  | ard Hydrants:                         |                       |                         |              |  |  |  |
|    | A  | Total number of hydrants              | NA                    | NA                      | NA           |  |  |  |
|    | В  | Hose box                              | NA                    | NA                      | NA           |  |  |  |
| 13 | P  | umping Arrangements:                  |                       |                         |              |  |  |  |
|    | A Ground level   |                                       |                       |                         |              |  |  |  |
| 1  | a)   | Discharge of main pump                | NA                    | NA                      | NA           |  |  |  |
|    | b)   | Head of main pump                     | NA                    | NA                      | NA           |  |  |  |
|    | c)   | Number of main pumps                  | NA                    | NA                      | NA           |  |  |  |
|    | d)   | Jockey pump out put                   | NA                    | NA                      | NA           |  |  |  |
|    | e)   |                                       | NA                    | NA                      | NA           |  |  |  |
|    | f)   |                                       | NA                    | NA                      | NA NA        |  |  |  |
|    | g  |                                       | NA                    | NA                      | NA           |  |  |  |
|    | h  | stopping                              | NA                    | NA                      | NA           |  |  |  |
|    | <u>i)</u>  |                                       | NA                    | NA                      | NA           |  |  |  |
|    | P  |                                       |                       |                         |              |  |  |  |
|    | a  | - 製物                                  | 450 LPM               | 450 LPM                 | MR (ol case) |  |  |  |
|    | _  | Head of the pump                      | 40 m                  | 40 m                    | MR           |  |  |  |
|    | -  | i) Power supply Auto starting of pump | Required              | Provided                | MR           |  |  |  |
| L  | -11  | Auto starting of pump                 | Required              | Provided                | MR           |  |  |  |
|    |  |                                       |                       | 84                      |              |  |  |  |

| 14 | Ca                  | ptive Water Storage For Fire                         |             | al because  | 1574                |  |  |  |
|----|---------------------|--|-------------|-------------|---------------------|--|--|--|
|    | A                   | Underground tank capacity                            | NA          | NA          | NA                  |  |  |  |
|    | В                   | Draw-off connection                                  | NA          | NA          | NA                  |  |  |  |
|    | C                   | Fire service inlet                                   | NA          | NA          | NA                  |  |  |  |
|    | D                   | Access to tank                                       | NA          | NA          | NA                  |  |  |  |
|    | E                   | Overhead tank capacity                               | 5,000 ltrs. | 5,000 ltrs. | MR (being old case) |  |  |  |
| 15 | Ex                  | it Signage:  | Required    | Provided    | MR                  |  |  |  |
| 16 | Provision of Lifts: |  |             |             |                     |  |  |  |
| _  | A                   | Pressurization of lift shaft                         | NA          | NA          | NA                  |  |  |  |
|    | В                   | Pressurization of lift lobby                         | NA          | NA          | NA                  |  |  |  |
|    | C                   | Communication in lift car                            | Required    | Provided    | MR                  |  |  |  |
|    | D                   | Firemen's grounding switch                           | Required    | Provided    | MR                  |  |  |  |
|    | E                   | Lift signage   | Required    | Provided    | MR                  |  |  |  |
| 17 |                     | andby Power Supply:                                  | Required    | Provided    | MR                  |  |  |  |
| 18 | Refuge Area:        |  |             |             |                     |  |  |  |
|    | A                   | Total area   | NA          | NA          | NA                  |  |  |  |
|    | B                   | Location   | NA          | NA          | NA                  |  |  |  |
| 19 | Fire Control Room:  |  |             |             |                     |  |  |  |
| ., | A                   | Detector system panel                                | NA          | NA          | NA                  |  |  |  |
|    | B                   | Flow switch panel                                    | NA          | NA          | NA                  |  |  |  |
|    | C                   | Pa system panel                                      | NA          | NA          | NA                  |  |  |  |
|    | D                   | Battery backup                                       | NA          | NA ·        | NA                  |  |  |  |
|    | E                   | Building floor plans                                 | NA          | NA          | NA                  |  |  |  |
| 20 | Sp                  | pecial Fire Protection Systems lecial Risks, If Any: | NA          | NA          |                     |  |  |  |

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

The owner has submitted an affidavit on 10.05.2025 stating not to use any floor above third floor for any purpose & basement used for incidental storage.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No F.6/DFS/MS/GH/SZ/2022/333 dated 07.07.2022 is recommended to be renewed from ground to 3<sup>rd</sup> floor only, under Rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name Designation

Sumit Kumar ADO (SPM)

Director (D

For Signature, Please.