## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI – 110001

No. F6/DFS/MS/GH/NDZ/2025/ 326

## Dated: 09/05 /2025

## FIRE SAFETY CERTIFICATE

Delhi Fire Service Tel: 011-23414000

## Copy to:-

- 1. The Commissioner, MCD, Delhi:- with a request to kindly ensure the occupancy as detailed above & deviation, if any.
- 2. The Joint Commissioner of Police (Licensing), 1<sup>st</sup> Floor, Police Station Defence Colony, New Delhi. w.r.to ID No. 2025042206928 dated 22.04.2025.
- 3. The Licensee, M/s Maha Laxmi Guest House at 2682/8, Chuna Mandi, Pahar Ganj, New Delhi. Conditions for the validity of fire safety certificate
- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".
- 8. Any change in the occupancy shall be intimated to this Deptt. and approval shall be obtained thereto before occupancy of the same.
- 9. The occupancy of above 3<sup>rd</sup> floor not allowed as per clause 7.31 in UBBL-2016.

		INSPE	CTION REPORT				
1	Nam	e & address of the building					
1		-	Chune M	xmi Guest House	at 2682/8		
•	Build	ding is comprised of			elhi		
2		2 7-1002 01	Chuna Mandi, Pahar Ganj, New Delhi.  (Ground + 04 upper floors)				
9.1			Ground floor -	(recention   01 or			
			room)	Ground floor – (reception + 01 office + 01 gues room)			
			1st floor to ard a				
			floor)	1 <sup>st</sup> floor to 3 <sup>rd</sup> floor - (04 guest rooms at each floor)			
			11001)				
			4" floor- (not in use as per affidants to				
3	Type	e of occupancy	4th floor- (not in use as per affidavit dated 05.05.2025)				
1	Type	e of case	Residential, Sub Division-A-1				
5		ils of previous FSC	Kenewal				
5	Fire	safety direction letter no.	F6/DFS/MS/GH/NDZ/2022/226 dated 13.05.2022				
7	Date	of inspection	IVII				
8	Nam	e of the inspection	03.05.2025				
9	Nam	e of the inspecting officers		Suman Kumar, ADO			
	Name of the designation of		Mr. Rajan Kumar (Manager)				
10	officer from the building side			( 8)			
10 11		r of construction	2002				
11	Applicant's letter no.		MCD Portal ID No. 2025042206928 dated				
C N			22.04.2025				
S.No	Minimum Standards on fire		Requirement/	Provided at Site	Remarks		
	Prevention and fire safety		Existing fire		MR/		
	req	uirements U/R 33	safety		NMR		
1	Access To Building:						
	Road width		NA	3.60 m	NA		
	Gat	e width	NA				
		dth of internal road	NA	NA NA	NA NA		
2		mber, Width, Type and Arra		INA	INA .		
	A	Number of staircases	Engement of Exits.		1		
		a Upper floor	01 no.	01 no.	MR		
		b Basement	NA	NA			
	В	Width of staircases	INA	INA	NA		
	<b>D</b>	a Upper floor	0.80 mtm	1.15	\		
		b Basement	0.80 mtr.	1.15 mtr.	MR		
	C	Protection of exits	INA	NA	NA		
		a Fire check door	NA	NA			
		b Pressurization		NA	NA		
-	D	No. of continuous	NA NA	NA	NA		
		staircases to terrace	INA.	NA	NA		
	E	Width of corridor	NA	NA	214		
	F	Door size	1.0 mtr.	10. 10.00	NA		
3	_	mpartmentation:	1.0 mu.	1.06 mtr.	MR		
	A	Fire check door	NA	NA	1		
	B	Sealing of electrical shafts	NA NA	NA NA	NA		
	C	Fire rating of shaft door	NA	NA NA	NA		
	-	Water curtain	NA NA	NA NA	NA		
	D				NA		
	D E	Fire dampers	NA	NIA	374		
4	E	Fire dampers oke Management System:	NA	NA	NA		
4	E	Fire dampers oke Management System: Upper floors	NA 12 ACPH	NA Natural/ exhaust fans	NA MR		

5.	Fire	Extinguisher:		10 nos.	10 nos.	MR		
	A	Total numbers		CO <sub>2</sub> & ABC	Provided	MR		
	В	Types		Required	Provided	MR		
	C	ISI marking						
6	Firs	t-Aid-Hose Reels:	ch	01 no.	01 no.	MR		
-	A	Total numbers of	CII					
		floor Length of hose reel l	hose	30 m	30 m	MR		
	В	4		05 mm	05 mm	MR		
	C	Nozzle diameter	Alar	ming System:				
7	Auto	Nozzle diameter  matic Fire Detection And  Type of detectors (C	0	Required	Provided	MR		
_	A	Type of detectors (			Provided	MR		
		type) Location of main par	nel	Required	NA	NA NA		
	В	Location of repeater		NA	INA.	1		
	C	1		Required	Provided	MR		
	D	Alternate source of p	ower	Required	Provided	MR		
	E	Hooters		NA	NA	NA		
3	MOE	FA:	-1	Required	Provided	MR		
	Dublic	Address System:		Required				
0	Auton	natic Sprinkler System:		NA	NA	NA		
	A	Basement		6	NA	NA		
	B	Upper floor		NA	NA	NA		
		Sprinkler above false		NA	INA			
	C	ceiling						
i	Intern	al Hydrants:		- T A	NA	NA		
_	A	size of riser/down-con-		NA	NA NA	NA		
	B	Number of hydrants pe	er	NA	1471			
	Б	floor		NA	NA	NA		
	C	Hose box		INA				
	Yard H	lydrants:			NA	NA		
$\dashv$	A	Total number of hydrar		NA	NA .	NA		
-	B	Hose box	1	NA	NA .			
+			•					
-+	Pumping Arrangements:  A Ground level NA							
_	<u>A</u>	Discharge of main pun	np ]	NA	NA	NA		
_	a)	Head of main pump	1	VA	NA	NA		
_	b)			NA	NA	NA		
_	c)	Number of main pump		NA	NA	NA		
(	d)	Jockey pump out put			NA	NA		
	e)	Jockey pump head		NA NA	NA	NA		
f		Standby pump out put			NA	NA		
g	g)	Standby pump head		JA	NA NA	NA		
h	)	Auto starting /manual	L	JA	147 2			
_		stopping	N	ΙA	NA	NA		
<u>i)</u>		Pump house access	11		. 1			
В		Terrace level	1 2	OS I DM	225 LPM	MR		
a)		Discharge of pump		25 LPM 0 m	30 m	MR		
b)		Head of the pump			Provided	MR		
c)		Power supply		equired		MR		
d)		Auto starting of pump	R	equired	Provided	TATT		

14	Ca	Captive water Storage For Fire Fighting:						
1	A	Underground tank capacity	NA	N				
	В	Draw-off connection	NA	NA	NA			
	C	Fire service inlet	NA	NA	NA			
	D	Access to tank	NA	NA	NA			
	E	Overhead tank capacity	2,500 ltrs.	NA	NA			
15	Ex	it Signage:	Required	2,500 ltrs.	MR			
16	Pr	ovision of Lifts:	required	Provided	MR			
	A	Pressurization of lift shaft	NA					
	B	Pressurization of lift lobby	NA NA	NA	NA			
	C	Communication in lift car	NA	NA	NA			
	D	Firemen's grounding switch	NA NA	NA	NA			
	E	Lift signage		NA	NA			
17	Standby Power Sunal			NA	NA			
18	Refuge Area: Required			Provided	MR			
	A Total area							
	В	Location	NA	NA	NA			
19	Fi	e Control Room:	NA	NA	NA			
	A	Detector system panel		*				
	В	Flow switch panel	NA	NA	NA			
	C	Pa system panel	NA	NA	NA			
	D	Battery backup	NA	NA	NA			
	E	Building floor plans	NA	NA	NA			
20	_	ecial Fire Protection Sand	NA	NA	NA			
	Sp	ecial Fire Protection Systems For ecial Risks, If Any:	NA	NA				
	The C							

The fire protection systems provided in the building were tested, checked at random and found functional at the time of inspection.

Shortcomings communicated vide letter No.F.6/DFS/MS/GH/2025/SZ/185 dated 21/04/2025 has been rectified.

Keeping in view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the Rules, the FSC issued vide letter No F6/DFS/MS/GH/NDZ/2022/226 dated 13.05.2022 is recommended to be renewed upto 3<sup>rd</sup> floor only, under Rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer
Name Suman Kumar

Designation ADO

65125

phito (was

06/05/25

- I my

7 57 20

And/sign Kr