GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001**



F6/DFS/MS/EH/NDZ/2025/217

Dated: 02 06 2025

FIRE SAFETY CERTIFICATE

Certified that the Mayur's Urban Spice, Located at B-1, Kh. No. 136, Old Plot No. 74 and 75, Chajjupur, Main 100 Futta Road, Shahadara, Delhi-110032, restaurant is running at ground floor only in a building is comprised of basement, ground plus 03 Upper Floors owned/occupied by Mayurs this department Vide Letter No. Urban Spice, was issued Fire Safety Certificate by F6/DFS/MS/2022/EH/NDZ/22 dated 01/02/2022. The said premise was re-inspected by the officer concerned of this department on 27/05/2025 in the presence of Sh. Tarun Gupta (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with the rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Assembly Building" Group D (Restaurant at ground floor only) with effect from 2006 2025 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed below.

Issued on .0.2.10.6.12.25 at New Delhi by.

Chief Fire Officer

Copy to: -

1. The Commissioner, Municipal Corporation of Delhi, Civic Centre, Minto Road, New Delhi-110002 :- in r/o online application id. 2025043007608 dated 03/05/2025

2. The Joint Commissioner of Police (Lic), 1st Floor, Licensing Unit, Police Station, Defence Colony,

3. The Authorized Signatory, Mayur's Urban Spice, B-1, Kh. No. 136, Old Plot No. 74 and 75, Chajjupur, Main 100 Futta Road, Shahadara, Delhi-110032.

Conditions for the validity of fire safety certificate :-

1. This FSC is valid for restaurant area's ground floor only.

2. All the means of escape shall be kept free of all type of obstruction all the time.

3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

4. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional if fire safety measures, management shall be responsible.

5. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

6. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

7. All comments / directions of licensing Department shall always be permitted and followed.

8. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

9. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

4-13

1. Name & address of the building : M/s Mayurs Urban Spice, located at B-1, Kh.

No. 136, Old Plot No. 74 and 75, Chajjupur, Main 100 Futta Road, Shahadara, Delhi-110032

2. Type of Occupancy Assembly "Control Pull Road, Shahadara, Delhi-11

3. Type of Case : Assembly, "Group-D" : Renewal

4. Details of previous NOC : F6/DFS/MS/2022/EH/NDZ/22 dated 01/02/2022

5. Fire Safety directives Letter No. : N/A

6. Date of inspection : 27/05/2025

7. Name of the Inspecting Officer : Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side : Sh. Tarun Gupta (Manager)

9. Year of Construction : 2020

10. Applicant's letter no. : 2025043007608 dated 03/05/2025

The building is comprised of basement, ground plus 03 upper floors but restaurant is

running at ground floor only.

| | running at ground floor only. | | | | |
|---------|---|-------------------------------|------------------|-------------------|--|
| S No | Minimum standards on fire prevention and fire safety U/R 33 | NBC (Part-IV) Requirements | Provided at site | Remarks MR/NMR | |
| 1. | Access of building | | | | |
| | Road width | 09 m | 30 m | MR | |
| | Gate width | NA | NA | NA | |
| | Width of internal road | NA | NA | NA | |
| 2. | Number, width, Type & Arrangements of exits | | | | |
| | a. Number of staircases | | 27.4 | NIA | |
| | Upper floors | NA | NA | NA | |
| | Basements | NA | NA | NA | |
| | b. Width of staircases | | 27.4 | NIA | |
| | Upper floors | NA | NA | NA | |
| | Basements | NA | NA | NA | |
| 1 | c. Protection of exits | | | | |
| | Fire check door | NA | NA | NA | |
| | Pressurization | NA | NA | NA | |
| | d. No of continuous staircase to terrace | NA | 01 | NA | |
| | e. Width Of Corridor | NA | NA | NA | |
| | f. Door Size | 02 m & 1.50 m | 02 m each | MR | |
| | g. Number of Door | 02 nos. | Provided | MR | |
| 3. | Compartmentation | 02 11001 | | | |
| 3. | Fire check door | NA | NA | NA | |
| | Sealing of electrical shafts | NA | NA | NA | |
| | Fire Rating of shaft door | NA | NA | NA | |
| 4 | Water Curtain | NA | NA | NA | |
| | Fire Dampers | NA | NA | NA | |
| 4. | Smoke managements System | | | | |
| | Basements | NA | NA | NA | |
| | Upper floors | NA | NA | NA | |
| | | G DA | | | |

| | | ١. | |
|---|---|----|---|
| - | 1 | 11 | л |
| | | 1. | |

| 5. | Fire Extinguishers | 06 Nos. | Provided | MR |
|----------|--|------------------------|----------------------|----------|
| | Total numbers | ABC & CO ₂ | Provided | MR |
| | • Types | ISI Marked | Provided | MR |
| | IS marking | 101 Ividinos | | |
| 6. | First – Aid Hose Reels | 01 | Provided | MR |
| | Total numbers on each | 01 | | |
| | floor | 30 m | Provided | MR |
| | Length of hose reel hose | 5 mm | Provided | MR |
| | Nozzle diameter | | Tiovided | IVIIC |
| 7. | Automatic fire detection and alarm | ning system | NA | NA |
| | Type of detectors | NA | NA NA | NA NA |
| | Location of Main Panel | NA | | |
| | Location of Repeater Pane. | 1 NA | NA | NA |
| | Alternate source of power | NA | NA | NA |
| | Hooters' Location | NA | NA | NA |
| 3. | MOEFA | Required | Provided | MR |
|).). | Public Address System | NA | NA | NA |
| 0. | Automatic Sprinkler System | + | | |
| ı U. | Basements | NA | NA | NA |
| | BasementsGround Floor | NA | NA | NA |
| | | NIA | NA | NA |
| | Sprinkler above false ceilir | 16 | | |
| 1. | Internal Hydrants: | 100 mm | Provided | MR |
| | • Size of riser/down-comer | 01 | Provided | MR |
| | Number of hydrants per | 01 | 110114 | |
| | floor | 01 | Provided | MR |
| | Hose Box | 01 | Tiovided | |
| 12. | Yard Hydrants | NA | NA | NA |
| | Total number of hydrants | NA | NA NA | NA |
| | Hose Box | NA | INA | 1471 |
| 13. | Pumping Arrangements: | | | |
| | Ground Level | 274 | NA | NA |
| | Discharge of main pump | NA | | NA NA |
| | Head of main pump | NA | NA NA | NA NA |
| | Number of main pumps | NA | | NA NA |
| | Jockey pump out put | NA | NA NA | NA NA |
| | Jockey pump head | NA | | NA NA |
| | Standby Pump out put | NA | NA | NA NA |
| | Standby Pump Head | NA | NA | NA NA |
| | > Auto Staring/Manual | NA | NA | INA. |
| | stopping | | NIA | NA |
| | > Pump House Access | NA NA | NA | INA |
| | Terrace level | 4501 | Durwided | MR |
| | > Discharge of pump | 450 lpm | Provided Provided | MR |
| | > Head of the pump | 40 m | Provided | MR |
| | > Power supply | Required | Provided | MR |
| | > Auto starting of pump | Required | Provided | IVIIC |
| 14. | Captive water Storage for firefigh | ting: | NA | NA |
| | Underground tank capacity | y NA | NA NA | NA NA |
| | Draw off connection | NA | NA NA | NA NA |
| | > Fire service inlet | NA Required | Provided | MR |
| | Access to tank | Required | Provided | MR |
| | Overhead Tank capacity | 20,000 ltrs. Required | Provided | MR |
| 15 | | Required | Tiovided | + ····· |
| 16 | | t NA | NA | NA |
| | > Pressurization of Lift Shafe | | NA NA | NA |
| | Pressurization of lift lobbyCommunication in lift Car | | NA NA | NA |
| | Fireman's Grounding | NA NA | NA NA | NA |
| | Switch | 141 | | 9 |
| | ➤ Lift Signage | NA | NA | NA |
| | | | | |
| 1 | 7. Standby power supply | Required | Provided | MR |

416

| area | | , | |
|---------------------------------|----|----|----|
| ation | NA | NA | NA |
| | NA | NA | NA |
| ol room | | | |
| etector system panel | | | |
| low Switch Panel | NA | NA | NA |
| A System Panel | NA | NA | NA |
| Battery backup | NA | ÑA | ŇA |
| Building Floor Plans | NA | NA | NA |
| I Fire Protection Systems for | NA | NA | NA |
| ction of special Risks, if any; | NA | ŇÁ | ŃA |

The fire protection systems provided in the building were checked and found ctional at the time of inspection. Shortcomings issued vide letter no. /DFS/MS/EH/NDZ/2024/555 dated 16/12/2024 found rectified.

In view of the deemed compliance of minimum standards of fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no. F6/DFS/MS/2022/EH/NDZ/22 dated 01/02/2022 renewal under rule 37 of the Delhi Fire Service Rule 2010, is recommended.

Accordingly FT is prepared & put up for approval please.

Aman Kumar La ADO (JWP)

by GO (NYZY)

2.F.D | | | 2000

ms cell

18 180 Nordel