GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F.6/DFS/MS/Hospital/2025/SZ/275

FIRE SAFETY CERTIFICATE

Certified that the **Mother & Child Block**, Masjid Moth, AIIMS, Complex, New Delhi–110029, comprised of Three tier Basement, Ground + 08 upper floors & service floor between 2nd & 3rd Floor, owned/occupied by All India Institute of Medical Sciences, was issued Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/Hospital/2021/SZ/145 dated 24/02/2021. The premise was re-visited by the officer concerned of this department on 17/05/2025 in the presence of Sh. Pardeep Kumar Executive (Electrical) and found that the said premises have deemed complied with fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the said building/premises is fit for occupancy class "Institutional, Group—C" (Hospital) with effect from 29/05/2025 for a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS Rules, 2010.

Issued on 29 /05 /2025 at New Delhi by

(ATUL GARG) DIRECTOR Ph. 011-23414000

Dated: 29/65/2025

Copy to: -

 Col. Digvijay Singh, Chief Security Officer, Administrative Block, AIIMS Complex, New Delhi–110029

Conditions for the validity of Fire Safety Certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- All the fire safety arrangement provided therein shall be maintained in good working conditions at all time as seen during inspection. Any loss of life property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. Basement shall be used strictly in accordance with Building Bye-Laws.
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this certificate, prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in

11-19

| 1 | Name 9 4 11 | ON REPORT | | 1 ATT 10 | |
|-----|-------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|-------------------|--|
| | Name & Address of the Building | Mother & Child Block, Masjid Moth, AIIMS, Complex, New Delhi-110029 | | | |
| 2 | Type of Occupancy | Institutional Building "Group -C" (Hospital) | | | |
| 3 | Building Comprised of | Three tier Basement, Ground + 08 upper floors & service floor between 2 nd & 3 rd Floor which i approved in the drawings Renewal | | | |
| 4 | Type of Case | | | | |
| 5 | Details of Previous NOC | | ital/2021/SZ/145 dated 2 | 24/02/2021 | |
| 6 | Fire safety directives letter No | F6/DFS/MS/Hospital/2021/SZ/145 dated 24/02/2021 F6/DFS/MS/BP/2013/206 dated 23/07/2013 | | | |
| 7 | Date of Inspection | 17/05/2025 | | | |
| 8 | Name of the Inspecting Officers | | | | |
| 9 | Name & Designation of Officers from the building side | ADO (SJ) Sh. Pardeep Kumar, Executive (Electrical) | | | |
| 10 | Year of construction | 2019-20 | | | |
| 11 | Applicant letter No. | Through e-mail | dated 17/04/2025 | | |
| S. | Minimum standards on Fire | Requirement | Provided at Site | Remarks MR/NMR | |
| No. | Prevention and Fire Safety U/R 33 | Old NOC | | MINIMI | |
| 1 | Access to Building. | 20 | Provided | MR | |
| | Road width | 20 mtr | Provided | MR | |
| | Gate width | 6 mtr | Provided | MR | |
| | Width of internal road | 6 mtr | Flovided | IVIIC | |
| 2 | Number, width, type and arrangeme | ents of exits. | | | |
| | a. Number of Staircase | 0631 | 06 Nos | MR | |
| | > Upper floors | 06 Nos | 08 Nos | MR | |
| | > Basement floor | 08 Nos | U8 NOS | IVIK | |
| | b. Width of Staircase | 02 mtr | 2m x 6nos | MR | |
| | > Upper floors | 2m & 1.50m | 2m x 7 & 1.50m x 1 | MR | |
| | > Basement floor c. Protection of exits | 211 60 1.5 011 | 211 X / C 1.5011 X 1 | MIC | |
| | > Fire check door | Required | Provided | MR | |
| | > Pressurization | Required | Provided | MR | |
| | d. No. of continuous staircase to terrace | 05 Nos | 06 Nos | MR | |
| | e. Width of corridor | 2.40m | 2.40m | MR | |
| | f. Door size | 2 mtr | 2 mtr | MR | |
| 3 | Compartmentation. | | | | |
| 3 | Fire check door. | Required | Provided | MR | |
| | Sealing of electrical shafts. | Required | Provided | MR | |
| | Fire rating of shaft door. | Required Required | Provided | MR | |
| | Water curtain | Required | Provided Provided | MR | |
| | • Fire dampers. | required | Tiovided | MR | |
| 4. | Smoke Management system. | Required | Provided | MR | |
| _ | Basement Upper floors | Required | Provided | MR | |
| | Fire Extinguishers. | • | | IVIK | |
| 5. | Total numbers | 16 Per Floor 200 Nos | | MR | |
| | Types | ABC/CO ₂ /W.CO ₂ | Provided | MR | |
| | ISI Marking | ISI marked | Provided | MR | |
| - | First Aid Hose Reels. | | | IVIK | |
| 6. | Total numbers on each floor. | Hose Reels | B3, B2=09, B1=08 & Upper Floors=06nos | MR | |
| | Length of hose-reel hose. | | 30m | MR | |
| | Nozzle Diameter | | 5mm | MR | |



N-17

| | Automatic Fire Detection and Alarm | Smoke & Heat | Smoke & Heat | MR |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| | Type of detectors | Ground Floor | Provided | MR |
| 1 | Location of Main Panel | Required | Provided | MR |
| | Location of Repeater Panel | Required | Provided | MR |
| | Alternate source of power | All Areas Required | Provided Provided Provided | MR MR MR |
| | Hooter's location | | | |
| 8. | MOEFA | | | |
| | Public Address System | Required | | |
| 0. | Automatic Sprinkler System | | 2/8 |) (D |
| | Basement | Required | Provided | MR |
| | Upper floors | Required | Provided | MR |
| | Sprinkler above false ceiling | Required | Provided | MR |
| | Internal Hydrants. | | | |
| 11. | | 150 mm | Provided | MR |
| 1 | Size of Riser / Down-comer | B3, B2=09, B1=08 | B3, B2=09, B1=08 & | MR |
| | Number of Hydrant per floor | & UFs=06nos | Upper Floors=06nos | MD |
| | Hose box. | B3, B2=09, B1=08 & UFs=06nos | B3, B2=09, B1=08 & Upper Floors=06nos | MR |
| 12. | Yard Hydrants. | | | |
| N. PATEL | Total number of hydrants. | 08 Nos | Provided | MR |
| | Hose box. | 08 Nos | Provided | MR |
| 13. | Pumping arrangements. | Common fire-j | lighting pumps for Mo liatrics and Service Bl | other & ock |
| | Ground Level | Chita, Ger | inities with periods | |
| | • Ground Level ➤ Discharge of main pump. | Hyd=2850 LPM | Hyd=2850 LPM | MR |
| | Discharge of main pump. | Sprk=2850 LPM W/C=4500 LPM | Sprk=2850 LPM W/C=4500 LPM | 18000000 |
| | Head of main pump. | 85m | Provided | MR |
| | Number of main pumps. | Two | Provided | MR |
| | Jockey Pump output. | 2 x 280 LPM | Provided | MR |
| | Jockey Pump head. | 85m | Provided | MR |
| | Standby Pump output. | 2850 LPM | Provided | MR |
| | Standby Pump head. | 85m | Provided | MR |
| | Auto Starting/Manual Stopping | Required | Provided | MR |
| | Pump House Access | Required | Provided | MR |
| | Terrace Level | | | |
| | Discharge of pump. | -NA- | 450 LPM | -NA- |
| | > Head of pump. | -NA- | 40m | |
| | | | | -NA |
| | Power supply. | -NA- | 77700000 | -NA |
| | Power supply.Auto starting of pump. | | Provided Provided | - |
| 14. | | -NA- -NA- Common pump | Provided Provided house & UGWST for M | -NA -NA Iother & |
| 14. | Auto starting of pump. Captive water storage for firefighting. | -NA- -NA- Common pump Child, Ge | Provided Provided house & UGWST for Meriatrics and Service Blo | -NA -NA Aother & ock |
| 14. | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. | -NANA- Common pump Child, Ge 2,00,000 Ltr | Provided Provided house & UGWST for Meriatrics and Service Black Provided | -NA -NA Aother & ock MR |
| 14. | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required | Provided Provided house & UGWST for Mariatrics and Service Blace Provided Provided | -NANA- Mother & Ock MR MR |
| 14. | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required | Provided Provided house & UGWST for Meriatrics and Service Blace Provided Provided Provided Provided | -NA -NA Aother & ock MR MR |
| 14. | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. Fire Service Inlet. Access to tank. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required Required | Provided Provided house & UGWST for Meriatrics and Service Blace Provided Provided Provided Provided Provided Provided | -NA -NA Mother & ock MR MR MR |
| 14. | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. Fire Service Inlet. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required Required 20,000 Ltr | Provided Provided house & UGWST for Mariatrics and Service Blace Provided Provided Provided Provided Provided Provided Provided | -NA -NA Mother & ock MR MR MR MR |
| | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required Required | Provided Provided house & UGWST for Meriatrics and Service Blace Provided Provided Provided Provided Provided Provided | -NA -NA Mother & ock MR MR MR MR |
| 15. | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required Required 20,000 Ltr Required | Provided Provided house & UGWST for Meriatrics and Service Blace Provided Provided Provided Provided Provided Provided Provided Provided | -NANANA- Mother & ock MR MR MR MR MR |
| 15. | Auto starting of pump. Captive water storage for firefighting. Underground tank capacity. Draw-off connection. Fire Service Inlet. Access to tank. Overhead tank capacity. Exit Signage. Provision of Lifts. Pressurization of lift shaft. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required 20,000 Ltr Required 20,000 Ltr Required | Provided Provided house & UGWST for Mariatrics and Service Blace Provided | -NANA- Mother & ock MR MR MR MR MR MR |
| 15. | ➤ Auto starting of pump. Captive water storage for firefighting. • Underground tank capacity. ➤ Draw-off connection. ➤ Fire Service Inlet. ➤ Access to tank. • Overhead tank capacity. Exit Signage. Provision of Lifts. • Pressurization of lift shaft. • Pressurization of lift lobby. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required 20,000 Ltr Required 20,000 Ltr Required | Provided | -NANA- Mother & ock MR MR MR MR MR MR MR |
| 15. | ➤ Auto starting of pump. Captive water storage for firefighting. • Underground tank capacity. ➤ Draw-off connection. ➤ Fire Service Inlet. ➤ Access to tank. • Overhead tank capacity. Exit Signage. Provision of Lifts. • Pressurization of lift shaft. • Pressurization of lift lobby. • Communication in lift car. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required 20,000 Ltr Required 20,000 Ltr Required Required Required | Provided | -NANANA- Mother & ock MR MR MR MR MR MR MR |
| 15. | ➤ Auto starting of pump. Captive water storage for firefighting. • Underground tank capacity. ➤ Draw-off connection. ➤ Fire Service Inlet. ➤ Access to tank. • Overhead tank capacity. Exit Signage. Provision of Lifts. • Pressurization of lift shaft. • Pressurization of lift lobby. • Communication in lift car. • Fireman's switch. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required 20,000 Ltr Required 20,000 Ltr Required Required Required Required Required Required Required Required | Provided | -NA -NA Mother & Ock MR MR MR MR MR MR MR MR |
| 15. | ➤ Auto starting of pump. Captive water storage for firefighting. • Underground tank capacity. ➤ Draw-off connection. ➤ Fire Service Inlet. ➤ Access to tank. • Overhead tank capacity. Exit Signage. Provision of Lifts. • Pressurization of lift shaft. • Pressurization of lift lobby. • Communication in lift car. • Fireman's switch. • Lift signage. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required 20,000 Ltr Required | Provided | -NANA- Aother & ock MR MR MR MR MR MR MR MR MR |
| 15. 16. | ➤ Auto starting of pump. Captive water storage for firefighting. • Underground tank capacity. ➤ Draw-off connection. ➤ Fire Service Inlet. ➤ Access to tank. • Overhead tank capacity. Exit Signage. Provision of Lifts. • Pressurization of lift shaft. • Pressurization of lift lobby. • Communication in lift car. • Fireman's switch. • Lift signage. Standby Power Supply | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required 20,000 Ltr Required 20,000 Ltr Required Required Required Required Required Required Required Required | Provided | -NANA- Mother & Ock MR MR |
| 15. 16. | ➤ Auto starting of pump. Captive water storage for firefighting. • Underground tank capacity. ➤ Draw-off connection. ➤ Fire Service Inlet. ➤ Access to tank. • Overhead tank capacity. Exit Signage. Provision of Lifts. • Pressurization of lift shaft. • Pressurization of lift lobby. • Communication in lift car. • Fireman's switch. • Lift signage. | -NANA- Common pump Child, Ge 2,00,000 Ltr Required Required 20,000 Ltr Required | Provided | -NANA- Aother & ock MR MR MR MR MR MR MR MR MR |



| 19. | Fire Control Room. | | | |
|-----|------------------------------------------------------------------------|----------|----------------------------------------------------------------|----|
| | Detector system panel. | Required | Provided | MR |
| | Flow switch panel. PA system panel. Battery backup | Required | Provided | MR |
| | | Required | Provided | MR |
| | | Required | Provided | MR |
| | Building floor plan | Required | Provided | MR |
| 20. | Special Fire Protection System for Protection of special Risk, if any. | Required | Provided CO ₂ flooding system in electric panels | MR |

The fire protection systems provided in the premises/building were checked, tested at random and found functional at the time of inspection. The shortcomings issued vide letter No. F.6/DFS/MS/SZ/2024/75 dated 23/02/2024 found complied.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules, the fire safety certificate issued vide letter No. F6/DFS/MS/Hospital/2021/SZ/145 dated 24/02/2021, renewal under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly, DFA is put up for perusal/approval & signature please.

Signature of the Inspecting Officer

Name: Santosh Kumar Designation: ADO (SJ)

DO (St) Muler m/5/ps

Director 1/1 223 311 200

ix Italy

FI wor is postup for your

mouth Myshs