GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

FS/MS/GH/NDZ/2025/ 425

Dated: 20 | 6 | 2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Mountain Bliss, located at 8496, Plot no. H-48, Arakashan Road, Pahar Ganj, New Delhi-110055, is comprised of Stilt + ground floor + 03 upper floors only, owned/occupied by M/s Mountain Bliss have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of this department on 13/06/2025 in the presence of Sh. Prayag Shukla and building/Premises is fit for occupancy "Residential Building" Group A for guest house, ground to 3rd floor (05 guest rooms at each floor) Total 20 guest rooms only with effect from 2 6 2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules 2010 printed below.

Issued on 20 6 2025 at New Delhi by

011-23414000

Copy to:-

1. The Commissioner, Municipal Corporation of Delhi, Civic Centre, Minto Road, New Delhi 110002 :- in r/o computer id no. 2025050808131 dated 21/05/2025

2. The Joint Commissioner of Police, Licensing unit, 1st Floor, Police Station, Defence Colony, New

3. The Authorized Signatory, M/s Mountain Bliss, 8496 Plot No. H-48, Arakashan Road, Pahar Ganj, New Delhi-110055.

Conditions for validity of Fire Safety Certification:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse

rendering non-functional if fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupation, electric installation etc. may be got verified from the concerned authorities.

5. The Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction / unauthorized use of land if any.

6. All comments / directions of licensing Department shall always be permitted and followed.

7. The owner /occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

8. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in 'Form J' (sub Rule (1) of Rule 37) along with copy of the certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building: M/s Mountain Bliss, located at 8496 Plot no. H-48,

Arakashan Road, Pahar Ganj, Delhi-110055

2. Type of Occupancy : Residential, Group A-1, the building is comprised

of stilt, ground plus 03 upper floors only, stilt (parking), ground to 3rd floor (05 guest rooms

at each floor) Total 20 guest rooms only

3. Type of Case

: New Case

Details of previous NOC

: Nil

5. Fire Safety directives Letter No.: Nil

6. Date of inspection

: 13/06/2025

7. Name of the Inspecting Officer: Aman Kumar Lathar, ADO (JWP)

8. Name and designation of Officer

from the building side

: Sh. Prayag Shukla

9. Year of Construction

: 2025

10. Applicant's online application no.: 2025050808131 dated 21/05/2025

| S No | Minimum standards on fire prevention and fire safety U/R 33 | UBBL/NBC Requirements | Provided at site | Remarks MR/NMR | | | |
|---------|--|--------------------------|------------------|-------------------|--|--|--|
| ١. | Access of building | | | | | | |
| | Road width | Required | Provided | MR | | | |
| | Gate width | Required | Provided | MR | | | |
| | Width of internal road | NA | NA | NA | | | |
| 1. | Number, width, Type & Arrangements of exits | | | | | | |
| | a. Number of staircases | | | | | | |
| 5 | Upper floors | 02 nos. | Provided | MR | | | |
| | Basements | NA | NA | NA | | | |
| | b. Width of staircases | | | | | | |
| | Upper floors | 1.5 m each | 1.5 m x 2 | MR | | | |
| | Basements | NA | NA | NA | | | |
| | c. Protection of exits | | a la casa di s | | | | |
| | Fire check door | NA | NA | NA | | | |
| | Pressurization | NA | NA | NA | | | |
| | d. No of continuous staircase to terrace | 02 nos. | Provided | MR | | | |
| | e. Width Of Corridor | 1.8 m | Provided | MR | | | |
| | f. Door Size | NA | NA | NA | | | |
| 3. | Compartmentation | | | INA | | | |
| | Fire check door | NA | NA | NIA | | | |
| | Sealing of electrical shafts Fire Poting of the 0.1. | NA | NA | NA NA | | | |
| | Fire Rating of shaft door Water Curtain | | | | | | |
| | Fire Dampers | NA | NA | NA | | | |
| | The Dampers | NA | NA | NA | | | |
| 4. | Smoke managements System | NA | NA | NA | | | |
| | Basements | NTA. | | - 11. | | | |
| | Upper floors | NA Possi 1 | NA | NA | | | |
| 5. | Fire Extinguishers | Required | Natural /exhaus | st MR | | | |
| | Total numbers | 00 | | 1411 | | | |
| | • Types | 08 nos. | Provided | MD | | | |
| | ISI marking | ABC & CO ₂ | Provided | MR | | | |
| | A | Required | Provided | MR | | | |
| | Mi | | riovided | MR | | | |

| | | NIL | | | | |
|-----|--|----------------|------------|---------------|----------|--|
| 5, | First - Aid Hose Reels | | | | | |
| | Total numbers on each | floor | 01 | Provided | MR | |
| - 1 | Length of hose reel ho | se _ | 30 m | Provided | MR | |
| | Nozzle diameter | | 05 mm | Provided | MR | |
| , | Automatic fire detection and alarming system | | | | | |
| | Type of detectors | | CO type | Provided | MR | |
| | Location of Main Pane | 550 | Required | Provided | MR | |
| | Location of Repeater I | | NA | NA | NA | |
| | Alternate source of po | wer | Required | Provided | MR | |
| - | Hooters' Location | | Required | Provided | MR | |
| | MOEFA | | NA | NA NA | NA | |
| | Public Address System | | NA | NA | NA | |
| 0. | Automatic Sprinkler System Basements NA NA NA | | | | | |
| | Basements | - | NA NA | NA NA | NA NA | |
| | Upper Floor Caribba and Floor and Floor | | NA | NA NA | NA | |
| , | Sprinkler above false Internal Hydrants: | ceiting | IIA | | 1.1.4 | |
| 1. | Internal Hydrants: • Size of riser/down- co | mer | NA | NA | NA | |
| | Number of hydrants p | | | | | |
| | Hose Box | Ci HOOI | NA | NA NA | NA NA | |
| | | | NA | NA | INA | |
| 2. | Yard Hydrants | | NIA | NA | NA | |
| | Total number of hydra | ınts | NA NA | NA NA | NA NA | |
| _ | Hose Box | | INA | IVA | 1171 | |
| 3. | Pumping Arrangements: | | | | | |
| | Ground Level | | NA | NA | NA | |
| | Discharge of main pur | mp | NA | NA | NA | |
| | Head of main pump Number of main pump | 08 | NA | NA | NA | |
| | > Jockey pump out put | P ³ | NA | NA | NA | |
| | > Jockey pump head | | NA | NA | NA | |
| | Standby Pump out pu | | NA | NA | NA | |
| | ➤ Standby Pump Head | | NA | NA | NA | |
| | ➤ Auto Staring/Manual | | NA | NA | NA | |
| | stopping | - | | | | |
| | Pump House Access | | NA | NA | NA | |
| | Terrace level | | | | MD | |
| | Discharge of pump | - | 450 lpm | Provided | MR MR | |
| | > Head of the pump | | 40 m | Provided | MR | |
| | > Power supply | | Required | Provided | MR | |
| | > Auto starting of pump | | Required | Provided | IVIK | |
| 4. | Captive water Storage for fire | nghting: | NA | NA | NA | |
| | Underground tank car | acity _ | NA NA | NA NA | NA | |
| | > Draw off connection | - | NA NA | NA NA | NA | |
| | Fire service inlet | - | NA NA | NA NA | NA | |
| | Access to tank | ity - | 5,000 ltrs | Provided | MR | |
| 20 | Overhead Tank capac | ity | Required | Provided | MR | |
| 5 | Exit Signage | | Manag | 0 MARK VICTOR | | |
| 6. | Provision of Lifts | 01 0 | NIA | NA | NA | |
| | > Pressurization of Lift | Shaft | NA NA | NA NA | NA | |
| | > Pressurization of lift l | obby | NA NA | NA NA | NA | |
| | Communication in lif | Curitah | NA NA | NA NA | NA | |
| | > Fireman's Grounding | Switch | NA NA | NA NA | NA | |
| | ➤ Lift Signage | | Required | Provided | MR | |
| 7. | Standby power supply | | Required | 1101100 | | |
| 8. | Refuge Area | | *** | NA | NA | |
| | > Total area | | NA | NA NA | NA | |
| | > Location | | NA NA | NA. | - 1.0 | |

| 200 | > Detector system panel | NA | NA | NA |
|-----|--|----|----|----------|
| | Flow Switch Panel PA System Panel Battery backup Building Floor Plans | NA | NA | NA NA |
| | | NA | NA | NA |
| | | NA | NA | NA |
| | | NA | NA | NA |
|). | Special Fire Protection Systems for Protection of special Risks, if any; | NA | NA | NA |

The fire protection systems provided in the building were checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety requirements under the rules, grant of Fire Safety Certificate is recommended under rule 35 of the Delhi Fire Service Rules, 2010 under the DFS Act 2007.

Accordingly DFA is prepared & put up for your approval please.

Aman Kumar Lathar ADO (JWP)

F.F. letter is pout up for your signalure M.