

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001



No. F6/DFS/MS/School/2025/WZ/515

Dated: 22/0

FIRE SAFETY CERTIFICATE

Certified that the Murti Devi Public School, D-23, Inder Enclave, Phase-II, Mubarak Pur Road, Village Nithari, Delhi-86 comprised of Ground + 02 upper floors has already been issued FSC by this department vide letter No.F.6/DFS/MS//2022/WZ/829 dated 02.08.2022. The premises was re-inspected by the officer concerned of this department on 09.04.2025 in the presence of Mrs. Suman (Teacher) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Educational 'Group B' with effect from 22/04/2025 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subjected to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 22 04 2025 at New Delhi by

DIRECTOR Ph; 011-23414000

Copy to :-

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sect. Delhi 54.
- 2. The Principal, Murti Devi Public School, D-23, Inder Enclave, Phase-II, Mubarak Pur Road, Village Nithari, Delhi-86

Conditions for the validity of fire safety certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Fire+Safety+Acts+and+Rules/http://www.delhi.gov.in/wps/wcm/connect/doit fire/FIRE/Home/Forms

INSPECTION REPORT

1. Name & address of the building: Murti Devi Public School, D-23, Inder Enclave, Phase-II,

Mubarak Pur Road, Village Nithari, Delhi-86.

2. Type of Occupancy

: Educational

3. Type of Case

: Renewal (Ground + 02 upper floors)

4. Details of Previous NOC

: F.6/DFS/MS//2022/WZ/829 dated 02.08.2022.

5. Fire Safety directives letter No

: NBC Part-IV

6. Date of inspection

: 09.04.2025

7. Name of Inspecting Officer

: A.K.Sharma ADO(Rohini)

8. Name and designation of officers From the building side

: Mrs. Suman (Teacher)

9. Year of Construction

: 2009 & 2012

10. S. No.	Applicant's letter No. : Online e-ma Minimum Standards on fire prevention and fire safety U/R 33	NBC Part-IV Requirement	Provided at site	Remarks MR/NMR	
	Access to building			MR	
•	Road width	Accessible	Accessible		
	Gate width	Accessible	4.5m	MR	
	Width of internal road	-NA-	-NA-	-NA-	
2.	Number, Width, Type & Arrangement of l	Exits			
۷.	a. Number of staircases		00	MR	
	Upper Floors	01nos.	02nos.	-NA-	
	Basements	-NA-	-NA-	-NA-	
	AND CASE SERVICE			3.00	
	b. Width of staircases	1.5m	1.52 & 1.53m	MR	
	Upper Floor	-NA-	-NA-	-NA-	
	Basements	-11/1-			
	c. Protection of exits	-NA-	-NA-	-NA-	
	Fire check door	1 - 2X	-NA-	-NA-	
	Pressurization	-NA-	-NA-	-NA-	
	d. No. of continuous staircases to terrace	-NA-	-NA-	-NA-	
	e. Width of Corridor		1.5m Double door	MR	
	f. Door Size	1.5m Double door 1.0m	1.5m Double door	2,5-2	
	a towartation				
3.	Compartmentation	-NA-	-NA-	-NA-	
	Fire check door	-NA-	-NA-	-NA-	
	Sealing of electrical shafts Sealing of electrical shafts The shaft door The shaft doo	-NA-	-NA-	-NA-	
	Fire Rating of shaft door	#C0250255	-NA-	-NA-	
	Water Curtain	-NA-	-NA-	-NA-	
	Fire Dampers	-NA-	-1121		
4.	Smoke Management System	374	-NA-	-NA-	
	Basements	-NA-		MR	
	Upper floors	12 a/c per hour	Natural ventilated	IVIIC	
5.	Fire Extinguishers 08nos 12nos.				
<u>.</u>	Total numbers	08nos.	ABC-12	MR MR	
	• Types	ABC/CO2	Yes	MR	
	IS marking	ISI marked	1 65	1722	
6.	First-Aid Hose Reels	7	Provided	MR	
	 Total numbers on each floor 	01nos.	Provided	MR	
	 Length of hose reel hose 	30mm	Provided	MR	
	Nozzle diameter	5m	Flovided	IVIIC	
7.	Automotic fire detection and alarming system				
1	Type of detectors	-INA		-NA-	
	 Location of Main Panel 	-NA-	-NA-	-NA-	
	Location of Repeater Panel	-NA-	-NA-	-NA-	
	Alternate source of power	-NA-	-NA-	-INA	

N)26

	• Hootom' I			2 4			
•	Hooters' Location MOEFA	-NA-	-NA-	-NA-			
	Public Address System	-NA-	-NA-	-NA-			
0.	Automatic Sprinkler System	-NA-	-NA-	-NA-			
	Basement						
	Ground & Upper Floors	-NA-	-NA-	-NA-			
	Sprinkler above false ceiling	-NA-	-NA-	-NA-			
l1.	Internal Hydrants	-NA-	-NA-	-NA-			
	Size of riser/down-comer	-NA-	274				
	Number of hydrants per floor	-NA-	-NA-	-NA-			
	Hose Box	-NA-	-NA-	-NA-			
12.	Yard Hydrants	-NA-	-NA-	-NA-			
	Total number of hydrants	-NA-	-NA-	-NA-			
	Hose Box	-NA-	-NA-	-NA-			
13.	Pumping Arrangements	141	TAA	-NA-			
	Ground Level			T			
	Discharge of main Pump	-NA-	-NA-	-NA-			
	➤ Head of Main pump	-NA-	-NA-	-NA-			
	> Number of main pumps	-NA-	-NA-	-NA-			
	> Jockey Pump out put	-NA-	-NA-	-NA-			
	> Jockey pump head	-NA-	-NA-	-NA-			
	Standby Pump out put	-NA-	-NA-	-NA-			
	Standby Pump Head	-NA-	-NA-	-NA-			
	> Auto Starting/Manual Stopping	-NA-	-NA-	-NA-			
	> Pump House Access						
		-NA-	-NA-	-NA-			
	 Terrace level Discharge of pump 	4501	4501) (D			
	> Head of the pump	450lpm 40m	450lpm 40m	MR MR			
	> Power Supply	Required	Provided	MR			
	➤ Auto Starting of pump	Required	Provided	MR			
14.	Captive Water Storage for fire fighting	Roquirou	Tiovidou	.,			
	Underground tank capacity	-NA-	-NA-	-NA-			
	> Draw-off connection	-NA-	-NA-	-NA-			
	Fire service inlet	-NA-	-NA-	-NA-			
	> Access to tank	-NA-	-NA-	-NA-			
	Overhead Tank capacity	10,000ltr	10,000ltr	MR			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.		,				
	SEAR AND SEAR OF SERVICE SERVI	NTA T	NIA	-NA-			
	Pressurization of Lift Shaft	-NA-	-NA-	-NA-			
	Pressurization of Lift lobby Communication In lift Car	-NA-	-NA-	-NA-			
	Communication in lift Car Fireman's Grounding Switch		-NA-	-NA-			
	Lift Signage	-NA-		L 934-5			
17		-NA-	-NA-	-NA-			
17.	Standby power supply	-NA-	-NA-	-NA-			
18.	Refuge Area.						
	Total AreaLocation	-NA-	-NA-	-NA-			
19.	Fire Control Room	-NA-	-NA-	-NA-			
19.		NT4 T	NY 4				
	 Detector System Panel Flow Switch Panel 	-NA-	-NA-	-NA-			
	PA System Panel	-NA-	-NA-	-NA-			
	Battery backup	-NA-	-NA-	-NA-			
	June	-11/1-	-11/2-	-11/7-			

Special Fire Protection System for NA -NA--NA-Protection of special Risks, if any: Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection. Keeping in view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures required stipulated in Director of Education Circular, the FSC issued vide letter no. F.\$/DFS/MS/2022/WZ/829 dated 02.08.2022 is recommended for renewal under rule 37 of the Delhi Fire Service rules 2010. Signature of the Inspecting Officer Ajay Kumar Sharma Name Designation ADO(Rohini) DO (NW) DCF0/1387-NW