

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE **NEW DELHI-110001**

F.6/DFS/MS/GH/2025/SZ/ 148 No.

Dated: 20./.03./2025

FIRE SAFETY CERTIFICATE

Certified that the Lodging House in the Name & Style of M/s Muskan Lodge Guest House located at 1367, Haveli Hisamuddin, Punjab Phatak, Ballimaran, Delhi 110006 comprised of Ground plus two upper floors, Ground floor (Commercial use), 1st Floor (01 Dormitory with 06 beds) & 2nd Floor (03 Guest Rooms) was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/GH/NDZ/2021/486 dated 28/10/2021. The premise was re-inspected by the officer concerned of this department on 11/03/2025 in the presence of Md. Samse and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential, Group-A" (01 dormitory with 06 Beds & 03 Guest Rooms) with effect from and validity upto 31/03/2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

<u>03</u>/2025 at New Delhi by

Copy to: -

1. The Commissioner, MCD, Civic Centre New Delhi, to ensure the occupancy as detailed above and deviation (if any).

2. The Addl. Commissioner of Police (Lic.), 1st Floor, P.S. Defence Colony, New Delhi-110049 (Ref. MCD Portal 2025022102233 dated 21/02/2025)

Conditions for the validity of Fire Safety Certificate: -

All the means of escape/entry/exit shall be kept free from any obstruction.

All the fire safety arrangement provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life property due to nonfunctional fire safety measures shall be at the responsibility of the management.

3. All the staff members must know the correct method of operation of fire fighting

system.

- 4. The owner/occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization (Clause 2.8 of UBBL-2016) of unauthorized construction or Alteration (Clause 1.4.3 of UBBL-2016), if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry."

M/20



	INCDECTO	ONIBRE	-1.1.6	न महात्सव		
1	Name & Address of the Building M/s Muskan Lodge located at 1367, Punjal					
2		Phatak Balliman	odge located at 1	367, Punja		
3	Type of Occupancy	Phatak, Ballimaran, Delhi 06 Residential, "Group-A" (Guest House)				
	Building Comprised of	Ground + 02 upper floors 8-t-11-t-				
4	Type of Case	Ground + 02 upper floors &toilets at terrace Renewal				
5	Details of Previous NOC					
6	Fire Safety Directives Letter No	F6/DFS/MS/GH/NDZ/2021/486 dated 28/10/2021				
7	Date of Inspection	Nil				
8	Name of the Inspecting Officers	11/03/2025				
9	Name & Designation of Officers	ADO (BCP)				
	from the building side	Md. Samse Kumar				
10	Year of construction	1000				
11	Applicant letter No.	1989				
S. No.	Minimum standards on Fire Prevention	MCD Portal 2025022102233 dated 21/02/2025				
	and Fire Safety U/R 33	Old NOC	Provided at Site	Remarks		
1	Access to Building.	requirements		MR/NMR		
	Road width	NA '1				
	Gate width	-NA- special area		Old case		
	Width of internal road	-NA-	-NA-	-NA-		
2	Number, width, type & arrangement of exits.	-NA-	-NA-	-NA-		
	a) Number of Staircase					
	> Upper floors.	01.37				
	Basement floor.	01 No	Provided	MR		
		-NA-	-NA-	-NA-		
	b) Width of Staircase		trill ett. bret			
	> Upper floors	0.80 mtr	0.81 to 0.90 mtr	MR		
	> Basement floor	-NA-	-NA-	-NA-		
	c) Protection of exits		malroyd a			
	> Fire check door	-NA-	-NA-	-NA-		
1	▶ Pressurization	-NA-	-NA-	-NA-		
	d) No. of continuous staircase to terrace	01	01	MR		
	e) Width of corridor	-NA-	-NA-	-NA-		
	n Door size	1.0 mtr	1.0 m	MR		
3	Compartmentation.			17224		
	Fire check door.	-NA-	-NA-	-NA-		
	Sealing of electrical shafts.	-NA-	-NA-	-NA-		
	Fire rating of shaft door.	-NA-	-NA-	-NA-		
	Water curtain	-NA-	-NA-	-NA-		
	Fire dampers.	-NA-	-NA-	-NA-		
4	Smoke Management system.	As per clause 7.31 of UBBL 2016				
-	Basement	12 ACPH Exhaust fan Provided MR				
	Upper floors	-NA-	-NA-	-NA-		
		7117	TIA	-11/1		
5	Fire Extinguishers.	06 Nos	Provided	MR		
	Total numbers	ABC / CO2	ABC & CO2	MR		
	Types			MR		
	ISI Marking	ISI marked	Provided	IVIK		
6	First Aid Hose Reels.	NIA I	Provided	-NA-		
	Total numbers on each floor.	NA 30 mtr	Provided	-NA-		
	Length of hose-reel hose.	30 mtr 5 mm	Provided	-NA-		
	Nozzle Diameter			-IN/1-		
7	Automatic fire detection & alarming system. • Type of detectors	As per clause 7.31 o	Provided	MR		



N/21

	14121		आज़ादी _ज अमृत महोत्स	
	Location of Main Panel	Required	Provided	MR
	Location of Repeater Panel	-NA-	-NA-	-NA-
	Alternate source of power	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
_		-NA-	-NA-	-NA-
8	MOEFA Public Address System	-NA-	-NA-	-NA-
9	Automatic Sprinkler System			374
10	Basement	-NA-	-NA-	-NA-
	The state of the s	-NA-	-NA-	-NA-
	Upper floors. Sprinkler above false ceiling	-NA-	-NA-	-NA-
11	Internal Hydrants. • Size of Riser/Down-comer	-NA-	-NA-	-NA-
		-NA-	-NA-	-NA-
	Number of Hydrant per floor	-NA-	-NA-	-NA-
	Hose box.	1		
12	Yard Hydrants.	-NA-	-NA-	-NA-
	Total number of hydrants.	-NA-	-NA-	-NA-
	Hose box.	-11//		
13	Pumping arrangements.			
	Ground Level	-NA-	-NA-	-NA-
	Discharge of main pump.	-NA-	-NA-	-NA-
	➤ Head of main pump.	-NA-	-NA-	-NA-
	Number of main pumps.	=NA=	=NA=	=NA=
	Jockey Pump output.	-NA-	-NA-	-NA-
	> Jockey Pump head.	-NA-	-NA-	-NA-
	Standby Pump output.	-NA-	-NA-	-NA-
	> Standby Pump head.	-NA-	-NA-	-NA-
	> Auto Starting/Manual Stopping.	-NA-	-NA-	-NA-
	> Pump house access.	-NA-	die gallala.	
	Terrace Level	-NA-	225 LPM	-NA-
	Discharge of pump.	-NA-	30 m	-NA-
	➤ Head of pump.	-NA-	Provided	-NA-
	> Power supply.	-NA-	Provided	-NA-
	> Auto starting of pump.	-INA-		
14	Captive water storage for fire fighting.	-NA-	NA	-NA-
	 Inderground tank capacity. 	10.0% ///	-NA-	-NA-
	> Draw-off connection.	-NA-	-NA-	-NA-
	Fire Service Inlet.	-NA-	-NA-	-NA-
	> Access to tank.	-NA-	500 ltrs	NA
	Overhead tank capacity.	NA	Provided	MR
10	Exit Signage.	Required	rrovided	ATTAC
15	Provision of Lifts.		-NA-	-NA-
16	Pressurization of lift shaft.	-NA-	-NA-	-NA-
-	Pressurization of lift lobby.	-NA-		-NA-
	Communication in lift car.	-NA-	-NA-	-NA-
	• Fireman's switch	-NA-		-NA-
	The second secon	-NA-	-NA-	MR
	Lift signage. Continue Power Supply	Required	Provided	IVIN
17	Standby Power Supply			-NA-
18	Refuge Area	-NA-	-NA-	The second
	Total area	-NA-	-NA-	-NA-
	Location			1
19	Fire Control Room.	-NA-	-NA-	-NA-
	Detector system panel. Flow switch panel.	-NA-	-NA-	-NA-
				-NA-



-NA--NA-PA system panel. -NA-Battery backup. -NA--NA-Building floor plan. -NA-Special Fire Protection System for the Protection of special Risk, if any.

The fire protection system provided in the building were randomly checked and found

functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standard on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter no F6/DFS/MS/GH/NDZ/2021/486 dated 28/10/2021, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

 Λ ccordingly, DF Λ is put up for approval and signature please.

Signature of the Inspecting Officer Name: Sh. Rajesh Kumar Design: ADO (BCP)

A approved F.1. Letter is proposed your synature of Dinectal