



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110 001**

No. F.6/DFS/MS/School/2025/NDZ/ 686

Dated: 21/05/2025

FIRE SAFETY CERTIFICATE

Certified that Nav Bal Vikas Vidyalaya located at 3A, New Govind Pura Ram Mandir, Street, Delhi-110051 comprised of ground plus three upper floors but school is running ground plus two upper floor (3rd floor has sealed by the owner),owned/occupied by NAV Bal Vikas Vidyalaya was issued FSC vide letter No. F.6/MS/DFS/06/1508 dated 06/07/2006. The school building was reinspected by the officer concerned of this department on dated 05/05/2025 in the presence of Mr. Vishal (Manager) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with Circular No. 262-362 dated 17/01/2025 issued by the Director of Education and that the building/premisesis fit for occupancy class 'Educational (Group-B)'(Ground to 2nd floor only) with effect from ...21..05. 2025 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 & also conditions printed below.

Issued on 21/05/2025 at New Delhi by

To:-

The Manger,

Nav Bal Vikas Vidyalaya at 3A, New Govind Pura Ram Mandir Street, Delhi-110051.

Copy to:

The Dy. Director of Education, MCD

Udyog Sadan, Plot No. 419, FIE, Patparganj Ind. Area, Delhi- 110092

Conditions for the validity of Fire Safety Certificate

1. FSC is valid for ground to 2nd upper floor only. 3rd floor sealed may not be used for any purpose failing should be treated null and void.

2. All the means of escape shall be kept free of all type of obstruction all the time.

- 3. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 4. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 5. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 6. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry. 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of

		INSPECTION RI	EPORT				
1	. Name & address of the building						
1 1	 Name & address of the building : Nav Bal Vikas Vidyalaya, 3A, New Govind Pura, Ram Mandir, Street Delhi-1100. 						
2.	. Building is comprised of	SA, New Goving	1 Pura, Ram Mandir, Succi	running ground			
2.	. Building is comprised of	: Ground plus thre	e upper floor but school is only (3 rd floor sealed by the	owner)			
3.	. Type of Occupancy	: Educational	only (3 Hoof sealed by the	Owner			
4.		 : Renewal : F6/MS/DFS/2006/1508 Dated 06/07/2006 : Circular No. 262-362 dated 17/01/2005 					
	-71						
5.	Details of French 1100 feller						
6.							
7.	Contractive Contractive Programmes	: 05/05/2025					
8.	Name of the Inspecting officers	: ADO (Shd.) Deepak Kumar					
9.	9. Name and designation of Officer						
	from the building side	: Mr. Vishal					
10	O. Year of Construction	: 2000 (GF) & 2005 (1 st & 2 nd floor)					
11	. Applicant's letter No	: mail ID nbpsdp21@gmaul.com dated 17/03/2025					
			7 11 1 4 6 4 5	Remarks			
Sr.	Minimum Standards on fire	Circular	Provided at Site	MR/NMR			
No	prevention and fire safety U/R33	Requirement		Morning			
01	Access to building.						
	Road width	06 mtr.	06 mtr	MR			
	Road widthGate width	N/A	N/A	N/A			
	Gate widthWidth of internal road	N/A	N/A	N/A			
2	Number, Width, Type and Arrangen		1772	1 =			
		ment of Latts.					
	a. Number of Staircases		00) (D			
1	 Upper Floor 	01 nos.	02 nos.	MR			
	Basement	N/A	N/A	N/A			
	B. Width of Staircases						
	• Upper Floor	1.50 mtr	01 mtr & 1.10 mtr	MR old case			
	• Basement	N/A	N/A	N/A			
1 '	c. Protection of exits			*			
	• Fire check door	N/A	N/A	N/A			
	• Pressurization	N/A	N/A	N/A			
(d. No. of continuous staircases		- "-	11/21			
	to terrace	01 nos.	01 nos.	N/A			
	Wild CO	1.50 mtr.					
	e. Width of Corridor		1.50 mtr.	MR			
_	f. Door Size Compartmentation.	01 mtr.	01 mtr.	MR			
-				,			
	 Fire check door 	N/A	N/A	N/A			
	 Sealing of electrical shafts 	N/A	N/A	N/A			
	 Fire rating of shaft door 			13/7			
	Water curtain	N/A	N/A	N/A			
	 Fire Dampers 	N/A	N/A	N/A			
4 5	Smoke Management System.	N/A	N/A	N/A			
				TUR			
	Basement Unner G	N/A	· N/A	277			
5.	• Upper floor Fire Extinguishers.	N/A	N/A	N/A			
				N/A			
	• Total numbers	06 nos.	0.6				
	• Types	ABC/CO ₂	06 nos.	MR			
	 IS marking 	ISI marked	ABC /CO ₂	MR			
		(8)	ISI marked	MR			

	First-aid-Hose Reels.	01 nos.	01 nos.	MR
)	Total numbers on each floor	30 mtr	30 mtr	MR
	Length of hose reel hose	05 mm	05 mm	MR
	Nozzle diameter			
l.	Automatic fire detection and alarming system.		N/A	N/A
	Type of detectors	N/A	N/A	N/A
	Location of main panel	N/A	N/A	N/A
	Location of repeater panel	N/A	N/A	N/A
	Alternate source of power	N/A		N/A
	Hooter's location	N/A	N/A	N/A
3	MOEFA	N/A	N/A	N/A
)	Public address System.	N/A	N/A	IVA
	Automatic Sprinkler System.			
	Basement	N/A	N/A	N/A
		N/A	N/A	N/A
	upper floorsprinkler above false ceiling	N/A	N/A	N/A
	Internal Hydrants	11/12		
	size of riser/down-comer	N/A	N/A	N/A
		N/A	N/A	N/A
	Number of hydrants per floorHose Box	N/A	N/A	N/A
2	Yard Hydrants.	N/A	14/11	1 11/11
	•	NI/A	N/A	N/A
	Total number of hydrantsHose Box	N/A	N/A N/A	N/A
} .	Pumping Arrangements.	N/A	N/A	IN/A
	> Ground Level	57/		T
		N/A	N/A	N/A
	Discharge of main PumpHead of Main Pump	N/A	N/A	N/A
	Number of main pumps	N/A	N/A	N/A
	Jockey pump out put	N/A	N/A	N/A
	Jockey pump head	N/A	N/A	N/A
	Standby pump out put	N/A	N/A	N/A
	Standby pump out put Standby pump Head	N/A	N/A	N/A
		N/A	N/A	N/A
	 Auto Starting /Manual stopping Pump House Access 	N/A	N/A	N/A
	> Terrace Level	N/A	N/A	N/A
	Discharge of pump	N/A	NI/A	77/1
	Head of the Pump	N/A	N/A	N/A
	Power supply	N/A	N/A	N/A
1.4	Auto Starting of pump	N/A	N/A N/A	N/A
14	Captive Water Storage for Fire Fighting.		IVA	N/A
	Underground tank canacity	N/A	N/A	
	Braw-Off Connection	N/A	N/A	N/A
	Fire service inlet Access to tank	N/A	N/A	N/A
	• Overhead Taul	N/A	N/A	N/A N/A
15	- Take Signage	2,500 ltr	2,500 ltr	MR
16	Provision of Lifts.	Required	Provided	MR
1	Pressurization of Lift Shaft			
	Pressurization of Links	N/A	N/A	N/A
		N/A	N/A	
-1	Firemen's grounding switch Lift Signage	N/A	N/A	N/A N/A
		N/A N/A	N/A	N/A N/A
	* · · · · · · · · · · · · · · · · · · ·		N/A	N/A



17	Standby power supply	27//		
18	Refuge Area.	N/A	N/A	N/A
	Total area			
9	• Location	N/A	N/A	N/A
1	Fire Control Room	N/A	N/A	N/A
	Detector system panel Flow switch	N/A	N/A	27/4
	Flow switch panel PA system panel	N/A	N/A	N/A N/A
	Battery backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
	Special Fire Protection systems for	N/A	N/A	N/A
	protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the rule the FSC issued vide letter No. F6/MS/DFS/2006/1508 Dated 06/07/2006 renewal under rule 35 of the Delhi Fire Service Rule, 2010 is recommended.

Signature of the Inspecting Officer

Name

:- Deepak Kumar

Designation

:- A.D.O (Shd)

DO(ED)

06/8/2025

Jy cto (NOT)

26/05/25

7 51 P

Déneeter My

ADO/SZA

Sir, P.T. la

is for up for

you king signature

Jept 16/05/202

Diseron