

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

**NEW DELHI- 110001** 

No. F.6/DFS/MS/School/2025/SZ/ 1083

Dated: 02/08/2025

## FIRE SAFETY CERTIFICATE

Certified that the New Ring Midways Public School at E-109-0113, Nanhey Park, Uttam Nagar, New Delhi- 110059, comprised of ground floor plus two upper floors, owned/occupied by New Ring Midways Public School, was issued Fire Safety Certificate by this department vide letter No. F6/DFS/MS/School/2018/SZ/232 dated 09.02.2018. The school building was re-inspected by the officer concerned of this department on dated 18.08.2025 in the presence of Sh. Mahesh (Principal) of the school, and found that the school building have complied the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises (ground plus two upper floors) is fit for occupancy class "Educational Building" w.e.f. Delia for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule-38 of the Delhi Fire Service Rules, 2010 printed as below.

Issued on 02/09/25— at New Delhi by.

(Virendra Singh) Chief Fire Officer

Copy to: -

1. The Director of Education, Govt. of NCT of Delhi, Old Secretariat, New Delhi-110054

2. The Manager, New Ring Midways Public School at E-109-0113, Nanhey Park, Uttam Nagar, New Delhi- 110059.

## Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape shall be kept unlocked and unobstructed for unhindered evacuation of occupants in case of emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

## INSPECTION REPORT

1. Name & address of the building

New Ring Midways Public School at E-109, Nanhey Park,

Uttam Nagar, New Delhi-110059

2. Building is comprised of

Two Blocks Old block having G+2 upper floors & New

Block having G+3 upper floors.

3. Type of Occupancy

'Educational Building' (School running at Old block only)

4. Type of Case

5. Details of Previous FSC letter

F6/DFS/MS/School/2018/SZ/232 dated 09/02/2018

6. Fire Safety direction letter No

N/A

:

7. Date of Inspection

8. Name of the Inspecting officers

18.08.2025 .

9. Name and designation of Officer:

ADO R.K. Yadav

From the building side

10. Year of Construction

Sh. Mahesh (Manager) Old Block Before 2010 & New Block 2020 :

11. Applicant's letter No

NRPMS/2025 dated 04.08.2025

No.	Minimum Standards on fire prevention and fire safety U/R33	Requirement	Provided at Site	Remarks MR/NMR		
1.	Access to building					
	Road width	06 m.	Provided	MR		
	Gate width	4.5 m	Direct accessible from road	N/A		
	<ul> <li>Width of internal road</li> </ul>	N/A	N/A	N/A		
2.	Number, Width, Type and Arrangement of Exits					
	a. Number of Staircases					
	Upper Floor	02 Nos.	2 Nos.	MR		
	Basement	N/A	N/A	N/A		
	B. Width of Staircases			1471		
	Upper Floor	1.5 & 0.75 m in Old Blk	1.25 m each in old blk	MR		
	Basement	N/A	N/A	N/A		
	c. Protection of exits					
	Fire check door	N/A	N/A	N/A		
	Pressurization	N/A	N/A	N/A		
	d. No. of continuous staircases to	02 Nos.	Provided	MR		
	terrace e. Width of Corridor	1.5 M	Provided	MR		
	f. Door Size	1.0 m	1.0 m	MR		
3.	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	Sealing of electrical shafts	N/A	N/A	N/A		
	Fire rating of shaft door	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
١.	Smoke Management System.					
	Basement	N/A	N/A	N/A		
	Upper floor	Required	Natural Ventilation	MR		
	Fire Extinguishers					
-	Total numbers	15 nos.	Provided	MR		
		ABC /CO <sub>2</sub>	ABC /CO <sub>2</sub>	MR		
	Types     IS marking	IS I marked	ISI marked	MR		

Total numbers of each floor   Length of hose reel hose   Nozzle diameter   0.5 mm   Provided   MR	6	First-aid-Hose Reels			1		
• Length of hose red hose   Nozzle diameter   O5 mm   Provided   MR	2720	Total numbers of each floor	01 No	Provided	MR		
Nozzle diameter			30 m	Provided	MR		
Type of detectors			05 mm	Provided	MR		
Type of detectors	7						
Location of main panel   Location of main panel   Location of repeater panel   N/A   N/		Type of detectors	N/A	N/A	N/A		
Location of repeater panel   N/A				N/A	N/A		
• Alternate source of power   N/A		The first of the f	N/A	N/A	N/A		
Hooter's location			N/A	N/A	N/A		
No.			N/A	N/A	N/A		
10	8	MOEFA	N/A	N/A	N/A		
Basement   N/A   N/A   N/A   N/A     • upper floor   N/A   N/A   N/A   N/A   N/A     • sprinkler above false ceiling   N/A   N/A   N/A   N/A     • sprinkler above false ceiling   N/A   N/A   N/A   N/A     • size of riser/down-comer   N/A   N/A   N/A   N/A     • Number of hydrants per floor   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A    12	9	Public address System.	N/A	Provided	N/A		
• upper floor   N/A   N/A   N/A   N/A     • sprinkler above false ceiling   N/A   N/A   N/A   N/A     • sprinkler above false ceiling   N/A   N/A   N/A   N/A     • size of riser/down-comer   N/A   N/A   N/A   N/A   N/A     • Number of hydrants per floor   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     12 Yard Hydrants.     • Total number of hydrants   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     • Discharge of main Pump   N/A   N/A   N/A   N/A     • Discharge of main Pump   N/A   N/A   N/A   N/A     • Head of Main Pump   N/A   N/A   N/A   N/A     • Dockey pump out put   N/A   N/A   N/A   N/A     • Jockey pump out put   N/A   N/A   N/A   N/A     • Standby pump out put   N/A   N/A   N/A   N/A     • Standby pump Head   N/A   N/A   N/A   N/A     • Standby pump Head   N/A   N/A   N/A   N/A     • Auto Starting /Manual   N/A   N/A   N/A   N/A     • Pump House Access   N/A   N/A   N/A   N/A     • Pump House Access   N/A   N/A   N/A     • Power supply   Required   Provided   MR     • Discharge of pump   450 LPM   450 LPM   MR     • Power supply   Required   Provided   MR     • Underground tank capacity   N/A   N/A   N/A   N/A     • Draw-off connection   N/A   N/A   N/A     • Paw-off connection   N/A   N/A   N/A     • Preverse vice inlet   N/A   N/A   N/A     • Preverse vice inlet   N/A   N/A   N/A     • Overhead Tank capacity   10,000 ttr   Provided   MR    15 Exit Signage.   Required   Provided   MR	10	Automatic Sprinkler System.					
• upper floor   N/A   N/A   N/A   N/A     • sprinkler above false ceiling   N/A   N/A   N/A   N/A     • sprinkler above false ceiling   N/A   N/A   N/A   N/A     • linternal Hydrants     • size of riser/down-comer   N/A   N/A   N/A   N/A     • Number of hydrants per floor   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     • Discharge of main Pump   N/A   N/A   N/A   N/A     • Discharge of main Pump   N/A   N/A   N/A   N/A     • Head of Main Pump   N/A   N/A   N/A   N/A     • Jockey pump out put   N/A   N/A   N/A   N/A     • Jockey pump bead   N/A   N/A   N/A   N/A     • Standby pump out put   N/A   N/A   N/A   N/A     • Standby pump Head   N/A   N/A   N/A   N/A     • Auto Starting /Manual   N/A   N/A   N/A   N/A     • Pump House Access   N/A   N/A   N/A   N/A     • Pump House Access   N/A   N/A   N/A     • Pump House Access   N/A   N/A   N/A     • Power supply   Required   Provided   MR     • Discharge of pump   450 LPM   450 LPM   MR     • Power supply   Required   Provided   MR     • Underground tank capacity   N/A   N/A   N/A   N/A     • Draw-off connection   N/A   N/A   N/A   N/A     • Parve-cervice inlet   N/A   N/A   N/A   N/A     • Prever service inlet   N/A   N/A   N/A   N/A     • Overhead Tank capacity   10,000 ltr   Provided   MR    15 Exit Signage.   Required   Provided   MR		Basement	N/A	N/A	N/A		
• sprinkler above false ceiling   N/A   N/A   N/A     • size of riser/down-comer   N/A   N/A   N/A     • Number of hydrants per floor   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A     • Total number of hydrants   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A     • Discharge of main Pump   N/A   N/A   N/A     • Number of main pump   N/A   N/A   N/A     • Number of main pump   N/A   N/A   N/A     • Number of main pump   N/A   N/A   N/A     • Jockey pump out put   N/A   N/A   N/A     • Jockey pump out put   N/A   N/A   N/A     • Standby pump pead   N/A   N/A   N/A   N/A     • Standby pump Head   N/A   N/A   N/A     • Auto Starting /Manual   N/A   N/A   N/A     • Auto Starting /Manual   N/A   N/A   N/A     • Pump House Access   N/A   N/A   N/A     • Discharge of pump   450 LPM   450 LPM   MR     • Head of the Pump   40 M   40 m   MR     • Power supply   Required   Provided   MR     • Auto Starting of pump   Required   Provided   MR     • Auto Starting of pump   Required   Provided   MR     • Draw-off connection   N/A   N/A   N/A     • Draw-off connection   N/A   N/A   N/A     • Pire service inlet   N/A   N/A   N/A     • Pire service inlet   N/A   N/A   N/A     • Overhead Tank capacity   10,000 tr   Provided   MR    15 Exit Signage.   Required   Provided   MR			250 W. W. C. Z.				
Internal Hydrants							
• size of riser/down-comer   N/A   N/A   N/A     • Number of hydrants per floor   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     • Hose Box   N/A   N/A   N/A   N/A     • Ground Level	11						
Number of hydrants per floor   N/A   N/A   N/A   N/A     Hose Box   N/A   N/A   N/A   N/A     12   Yard Hydrants.     Total number of hydrants   N/A   N/A   N/A   N/A     Hose Box   N/A   N/A   N/A   N/A     Hose Box   N/A   N/A   N/A   N/A     Total number of hydrants   N/A   N/A   N/A   N/A     Hose Box   N/A   N/A   N/A   N/A     Discharge of main Pump   N/A   N/A   N/A   N/A     Head of Main Pump   N/A   N/A   N/A   N/A   N/A     Number of main pumps   N/A   N/A   N/A   N/A     Jockey pump out put   N/A   N/A   N/A   N/A     Jockey pump head   N/A   N/A   N/A   N/A     Standby pump out put   N/A   N/A   N/A   N/A     Standby pump Head   N/A   N/A   N/A   N/A     Standby pump Head   N/A   N/A   N/A   N/A     Auto Starting /Manual   N/A   N/A   N/A   N/A     Pump House Access   N/A   N/A   N/A   N/A     Pump House Access   N/A   N/A   N/A     Head of the Pump   40 M   40 m   MR     Power supply   Required   Provided   MR     Auto Starting of pump   Required   Provided   MR     Auto Starting of Fire Fighting.     Underground tank capacity   N/A   N/A   N/A     Prire service inlet   N/A   N/A   N/A     Provided   MR     Exit Signage.   Required   Provided   MR     Exit Signage.   Required   Provided   MR	11						
Hose Box				LAUDING ON	700000000000000000000000000000000000000		
12				400 500 000	NET 1989 V 1978		
• Total number of hydrants         N/A         N/A         N/A           • Hose Box         N/A         N/A         N/A           13 Pumping Arrangements.         • Ground Level         - Discharge of main Pump         N/A         N/A           • Discharge of main Pump         N/A         N/A         N/A         N/A           • Head of Main Pump         N/A         N/A         N/A         N/A           • Number of main pumps         N/A         N/A         N/A         N/A           • Number of main pumps         N/A         N/A         N/A         N/A           • Jockey pump out put         N/A         N/A         N/A         N/A           • Jockey pump head         N/A         N/A         N/A         N/A           • Standby pump out put         N/A         N/A         N/A         N/A           • Standby pump lead         N/A         N/A         N/A         N/A         N/A           • Standby pump lead         N/A         N/A         N/A         N/A         N/A         N/A           • Pump House Access         N/A         N/A         N/A         N/A         N/A         N/A           • Pump House Access         N/A         N/A         N/A		Hose Box	N/A	N/A	N/A		
• Hose Box         N/A         N/A         N/A           13         Pumping Arrangements.         • Ground Level	12	Yard Hydrants.					
Hose Box   N/A   N/A   N/A   N/A		Total number of hydrants	N/A	N/A	N/A		
Ground Level      Discharge of main Pump     N/A     Head of Main Pump     N/A			N/A	N/A	N/A		
Discharge of main Pump       N/A       N/A       N/A         Head of Main Pump       N/A       N/A       N/A         Number of main pumps       N/A       N/A       N/A         N/A       N/A       N/A       N/A       N/A	13						
Discharge of main Pump       N/A       N/A       N/A         Head of Main Pump       N/A       N/A       N/A         Number of main pumps       N/A       N/A       N/A         N/A       N/A       N/A       N/A       N/A							
New Head of Main Pump       N/A       N/A       N/A         Number of main pumps       N/A       N/A       N/A         Number of main pumps       N/A       N/A       N/A         Nockey pump out put       N/A       N/A       N/A         Nockey pump head       N/A       N/A       N/A         Nockey pump head       N/A       N/A       N/A         Nockey pump bead       N/A       N/A       N/A         N/A       N/A       N/A       N/A         N/A <td></td> <td>The state of the s</td> <td>N/A</td> <td>NI/A</td> <td>NI/A</td>		The state of the s	N/A	NI/A	NI/A		
Number of main pumps       N/A       N/A       N/A         Jockey pump out put       N/A       N/A       N/A         Jockey pump head       N/A       N/A       N/A         Standby pump out put       N/A       N/A       N/A         N/A       N/A       N/A       N/A							
▶ Jockey pump out put       N/A       N/A       N/A         ▶ Jockey pump head       N/A       N/A       N/A         ▶ Standby pump out put       N/A       N/A       N/A         ▶ Standby pump Head       N/A       N/A       N/A         ▶ Auto Starting /Manual stopping       N/A       N/A       N/A         ▶ Pump House Access       N/A       N/A       N/A         ▶ Pump House Access       N/A       N/A       N/A         ▶ Discharge of pump       450 LPM       450 LPM       MR         ▶ Head of the Pump       40 M       40 m       MR         ▶ Power supply       Required       Provided       MR         14 Captive Water Storage for Fire Fighting.       N/A       N/A       N/A         ■ Underground tank capacity       N/A       N/A       N/A         ▶ Draw-off connection       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A         ▶ Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR					100000000000000000000000000000000000000		
▶ Jockey pump head       N/A       N/A       N/A         ▶ Standby pump out put       N/A       N/A       N/A         ▶ Standby pump Head       N/A       N/A       N/A         ▶ Auto Starting /Manual stopping       N/A       N/A       N/A         ▶ Pump House Access       N/A       N/A       N/A         ▶ Pump House Access       N/A       N/A       N/A         ▶ Discharge of pump       450 LPM       450 LPM       MR         ▶ Head of the Pump       40 M       40 m       MR         ▶ Power supply       Required       Provided       MR         ▶ Auto Starting of pump       Required       Provided       MR         14 Captive Water Storage for Fire Fighting.       V/A       N/A       N/A         ▶ Draw-off connection       N/A       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A       N/A         ▶ Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR				TAN SALVANDAS			
▶ Standby pump out put       N/A       N/A       N/A         ▶ Standby pump Head       N/A       N/A       N/A         ▶ Auto Starting /Manual stopping       N/A       N/A       N/A         ▶ Pump House Access       N/A       N/A       N/A         ▶ Discharge of pump       450 LPM       MR         ▶ Head of the Pump       40 M       40 m       MR         ▶ Power supply       Required       Provided       MR         ▶ Auto Starting of pump       Required       Provided       MR         14 Captive Water Storage for Fire Fighting.       V/A       N/A       N/A         ▶ Draw-off connection       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A         ▶ Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR				CONTRACTO:			
▶ Standby pump Head       N/A       N/A       N/A         ▶ Auto Starting /Manual stopping       N/A       N/A       N/A         ▶ Pump House Access       N/A       N/A       N/A         ▶ Discharge of pump       450 LPM       MR         ▶ Head of the Pump       40 M       40 m       MR         ▶ Power supply       Required       Provided       MR         ▶ Auto Starting of pump       Required       Provided       MR         14 Captive Water Storage for Fire Fighting.       V/A       N/A       N/A         ▶ Underground tank capacity       N/A       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR			ANY SQUARES				
NAUTO Starting /Manual stopping       N/A       N/A       N/A         Pump House Access       N/A       N/A       N/A         Pict Ferrace Level       N/A       MR         Patternal Level       MR       MR         Pedal of the Pump       450 LPM       MR         Power supply       Required       Provided       MR         Power supply       Required       Provided       MR         Power supply       Required       Provided       MR         Provided       MR       N/A       N/A       N/A         Provided       N/A       N/A       N/A       N/A       N/A         Provided       MR       N/A       N/A <t< td=""><td></td><td></td><td>THESE STATES</td><td>TANK AND AND AND AND AND AND AND AND AND AND</td></t<>				THESE STATES	TANK AND		
stopping  Pump House Access N/A  Terrace Level  Discharge of pump 450 LPM 450 LPM MR  Head of the Pump 40 M Fower supply Required Provided MR  Auto Starting of pump Required Provided MR  Captive Water Storage for Fire Fighting.  Underground tank capacity N/A Draw-off connection N/A Fire service inlet N/A				3000 A 20			
▶ Pump House Access       N/A       N/A       N/A         • Terrace Level       N/A       N/A       N/A         ▶ Discharge of pump       450 LPM       MR         ▶ Head of the Pump       40 M       40 m       MR         ▶ Power supply       Required       Provided       MR         ▶ Auto Starting of pump       Required       Provided       MR         14 Captive Water Storage for Fire Fighting.       N/A       N/A       N/A         • Underground tank capacity       N/A       N/A       N/A         ▶ Draw-off connection       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR			N/A	N/A	N/A		
<ul> <li>Terrace Level</li> <li>Discharge of pump</li> <li>Head of the Pump</li> <li>Power supply</li> <li>Required</li> <li>Provided</li> <li>MR</li> <li>Auto Starting of pump</li> <li>Required</li> <li>Provided</li> <li>MR</li> <li>Captive Water Storage for Fire Fighting.</li> <li>Underground tank capacity</li> <li>Draw-off connection</li> <li>N/A</li> <li>Fire service inlet</li> <li>N/A</li> <li>N/A</li> <li>Access to tank</li> <li>Overhead Tank capacity</li> <li>Required</li> <li>Provided</li> <li>MR</li> </ul>			N/A	N/A	N/A		
▶ Head of the Pump       40 M       40 m       MR         ▶ Power supply       Required       Provided       MR         ▶ Auto Starting of pump       Required       Provided       MR         14 Captive Water Storage for Fire Fighting.       V/A       N/A       N/A         ● Underground tank capacity       N/A       N/A       N/A         ▶ Draw-off connection       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR				1071	IVA		
▶ Head of the Pump       40 M       40 m       MR         ▶ Power supply       Required       Provided       MR         ▶ Auto Starting of pump       Required       Provided       MR         14 Captive Water Storage for Fire Fighting.       V/A       N/A       N/A         ● Underground tank capacity       N/A       N/A       N/A         ▶ Draw-off connection       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR			450 LPM	450 I PM	MD		
Power supply       Required       Provided       MR         Auto Starting of pump       Required       Provided       MR         14       Captive Water Storage for Fire Fighting.       V/A       N/A       N/A         • Underground tank capacity       N/A       N/A       N/A         • Draw-off connection       N/A       N/A       N/A         • Fire service inlet       N/A       N/A       N/A         • Access to tank       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15       Exit Signage.       Required       Provided       MR					1		
Auto Starting of pump       Required       Provided       MR         14       Captive Water Storage for Fire Fighting. <ul> <li>Underground tank capacity</li> <li>N/A</li> <li>Draw-off connection</li> <li>N/A</li> <li>Fire service inlet</li> <li>N/A</li> <li>N/A</li> <li>Access to tank</li> <li>N/A</li> <li>Overhead Tank capacity</li> </ul> N/A     N/A         15       Exit Signage.       Required       Provided       MR				With DOOR STATE			
14 Captive Water Storage for Fire Fighting.   • Underground tank capacity N/A N/A N/A   Draw-off connection N/A N/A N/A  Fire service inlet N/A N/A N/A  Access to tank N/A N/A N/A  • Overhead Tank capacity 10,000 ltr Provided MR  15 Exit Signage. Required Provided MR							
<ul> <li>Underground tank capacity</li> <li>N/A</li> <li>Draw-off connection</li> <li>N/A</li> <li>Fire service inlet</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>Access to tank</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>N/A</li> <li>Provided</li> <li>MR</li> </ul> 15 Exit Signage. <ul> <li>Required</li> <li>Provided</li> <li>MR</li> </ul>	14	Captive Water Storage for Fire Fightin	I IVIIC				
Draw-off connection       N/A       N/A       N/A         ▶ Fire service inlet       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR		- Hadamada I. I. V. Nila					
Fire service inlet       N/A       N/A       N/A         ▶ Access to tank       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR		Draw-off connection		W/9X80350			
➤ Access to tank       N/A       N/A       N/A         • Overhead Tank capacity       10,000 ltr       Provided       MR         15 Exit Signage.       Required       Provided       MR			The Control of the Co				
Overhead Tank capacity 10,000 ltr Provided MR      Exit Signage. Required Provided MR							
15 Exit Signage. Required Provided MR				The state of the s			
Tovided IVIK	15						
		Dait Signage.	Required	Provided	MR		

1 -

16	Provisi	on of Lifts.				
	•	Pressurization of Lift Shaft	N/A	N/A	N/A	
	•	Pressurization of Lift lobby	N/A	1 2500502ttr/f2:		
	•	Communication in lift car	N/A	N/A N/A	N/A	
	•	Firemen's grounding switch	N/A	N/A N/A	N/A	
	•	Lift Signage	N/A	N/A	N/A N/A	
17	Stand	y power supply	N/A	N/A	N/A	
18	Refuge Area.					
	•	Total area	N/A	N/A	N/A	
	•	Location	N/A	N/A	N/A	
19	Fire Control Room					
	•	Detector system panel	N/A	N/A	N/A	
	•	Flow switch panel	N/A	N/A	N/A	
	•	PA system panel	N/A	N/A	N/A	
	•	Battery backup	N/A	N/A	N/A	
	•	Building Floor Plans	N/A	N/A	N/A	
20	Specia	Fire Protection systems for tion of special Risks, if any:	N/A	N/A	N/A	

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Note: - As per Affidavit submitted by the school management (placed at C-) that the school compound comprises two separate buildings. Old block comprised of ground plus two upper floors and New Block comprised of ground plus three upper floors but school running at Old Block (G+2 upper floors) only. The New Block building (G+3 upper floors) is not being used for any educational activity, nor has it ever been used for such purposes and not be used for educational purpose in the future either.

In view of the deemed compliance of the minimum standards of fire prevention and fire measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/School/2018/SZ/232 dated 09/02/2018 is recommended to be renewed under rule 37, of the Delhi Fire Service Rules, 2010.

Signature of Inspecting Officer

Name: - R.K. Yadav

Designation: - ADO (JKP)

DO (South West