

## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001



No F6/DFS/MS/2025/WZ/Metro/ 537

Dated: 11 10 2025

## FIRE SAFETY CERTIFICATE

Certified that the North Pitampura Metro Station of Line-8 (Extn.) Phase-IV, comprised of (Basement – Pump rooms,) Ground Level + Concourse + Platform Level was inspected by the officer concerned of this department on 09/10/2025 in the presence of Mr. Ajay Bhati (Manager Electrical) and found that the said premises have complied with the fire prevention and fire safety requirements in accordance with Rule 33 of the Delhi Fire Service Rules, 2010 and that the premise is fit for occupancy class 'Assembly (Metro Station)' with effect from 11/10/2025 for a period of 03 (Three) years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on \_\_\_\_\_ at New Delhi by

DY. CHIEF FIRE OFFICER

Copy to:-

 Sh. Shailendra Kumar (Additional General Manager/E&M/RC-1, Metro Bhawan, 13, Fire Brigade Lane, New Delhi 110001.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management/occupier.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Fire+Safety+Acts+and+Rules/http://www.delhi.gov.in/wps/wcm/connect/doit\_fire/FIRE/Home/Forms

9. DMRC shall ensure compliance of clause 4.4.2.4.1 (h) of NBC part-IV/2016, and provide sufficient louvers for smoke ventilation if façade/glazing is provided at concourse or platform level within two months as undertaking given by DMRC.

any

5				<u> </u>			
Y	-		INSPE	CTION REPORT			
1.	Name & address of the building North		n Pitam Pura Metro Station of Line-8 (Extn.) Phase-IV				
2.	Type of O		Assem	bly Building			
3.	Type of Ca	Type of Case New O		Case (Basement -Pur	mp rooms) Ground Leve	l + Concour	
4.	Details of	Previous NOC	-NA-	ili Level)			
5.		directives letter No		S/MS/BP/2022/68	dated 21.02.2022.		
6.	O MORE REPORTED			6/DFS/MS/BP/2022/68 dated 21.02.2022. /10/2025 . A. K. Sharma ADO (WP)			
7.		specting Officer					
8.	B. Name and designation of officers From the building side  Mr. A			Ajay Bhati (Manager Electrical)			
9.		nstruction	2025				
1,5/10	). Applicant	12/10/10/2		o.6348 dated 23/09/2	2025		
S.		Standards on fire prev		Requirement as	Provided at site	Remarks MR/NMR	
No		afety U/R 33		per GL, NBC/BBL		MR/NWR	
1.	Access to	building				100	
- •		ad width		9.5m	Provided	MR	
	12.54	nte width		-NA-	-NA-	-NA-	
	4550	idth of internal road		-NA-	-NA-	-NA-	
2.	1000	TO AND THE RESERVE AND THE PARTY OF THE PART	ment of	Exits			
2.	Number, Width, Type & Arrangement of a. Number of staircases			.()			
			Gr. to Concourse-02		MR		
	Upper Floors			Platform-Concourse-	0.4	MR MR	
	Basements		Gr. to pump room	01nos.	IVIIX		
	b. Width of staircases				2 (	MR	
	Upper Floor			Gr. to Concourse-2n Platform-Concourse-2	2m 2.6m	MR	
	Basements		Gr. to pump room 1.25m	- 1.25m	MR		
	c. Protec	ction of exits					
		Fire check door	e constitue	Required	Provided	MR	
	•	Pressurization	N.	-NA-	-NA-	-NA-	
	d. No. of	continuous staircases to	terrace	-NA-	-NA-	-NA-	
	e. Width of Corridor		W <sup>4</sup>	-NA-	-NA-	-NA-	
	f. Door Size		02mtr	2mtr	MR		
3.	Comparti						
	a) Fire check door		. 4	Required	Provided	MR	
	b) Sea	aling of electrical shafts		Required	Provided	MR	
	c) Fire Rating of shaft door			-NA-	-NA-	-NA-	
	d) Water Curtain			-NA-	-NA-	-NA-	
	e) Fire Dampers		-NA-	-NA-	-NA-		
4.	Smoke Management System						
	a) Basements		12 a/c per hour	Provided	MR		
	b) Up	per floors		12 a/c per hour	Natural ventilated	MR	
5.	Fire Extinguishers						
	a) Total numbers		12nos.	Provided	MR		
	b) Types			ABC/CO2	ABC/CO2	MR	
	c) IS marking			ISI marked	Yes	MR	
6.	First-Aid	Hose Reels			103	IVIIX	

	a) T-+-1						
	a) Total numbers on each floor	Concourse l	evel-03   Concourse lev	vel-03 // M			
	1	Platform leve	el-06   Platform lev	vel-06 // M			
	b) Length of hose reel hose	30mm	Provide	d // MF			
	c) Nozzle diameter	5m	Provided				
7.	Automatic fire detection and alarming system						
MIN	a) Type of detectors	Heat/Smok	ce Provided	MR			
	b) Location of Main Panel	Concourse		MR			
		Concourse		MR			
	c) Location of Repeater Panel	Battery & DG s	B. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	MR			
	d) Alternate source of power	Required	Provided	MR			
	e) Hooters' Location	Required	Provided	MR			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	Required					
10.		-NA-	-NA-	-NA-			
	a) Basement	-NA-	-NA-	-NA-			
	b) Ground & Upper Floors	-NA-	Only in escalator	-NA			
	<ul> <li>c) Sprinkler above false ceiling</li> </ul>	-11/1-		MR			
11.	Internal Hydrants	100mm	Provided	1,77.5			
	a) Size of riser/down-comer	On road level- Concourse level-4	Provided	MR			
	b) Number of hydrants per floor	Platform level-03 each side		MR			
		As above	As above				
	c) Hose Box		22 - 21	MR			
12.	Yard Hydrants	02nos.	02nos. · 02nos.	MR			
	a) Total number of hydrants	02nos.	UZHOS.				
	b) Hose Box						
13.	Pumping Arrangements  • Ground Level		1620lpm	MR			
	Discharge of main Pump	1620lpm	70m	MR			
	▶ Head of Main pump	70m 01nos.	01nos.	MR			
	Number of main pumps	180lpm	180lpm	MR			
	Jockey Pump out put	70m	70m	MR MR			
	> Jockey pump head	1620lpm	1620lpm	MR			
	<ul><li>Standby Pump out put</li><li>Standby Pump Head</li></ul>	70m	70m	MR			
	Standby Pump Head  Auto Starting/Manual Stopping	Required	Provided				
	> Pump House Access	Required	Provided	MR			
	Terrace level						
	> Discharge of pump	-NA-	-NA-	-NA-			
	➤ Head of the pump	-NA-	-NA-	-NA-			
	> Power Supply	Required	Provided	MR			
	> Auto Starting of pump	Required	Provided	MR			
14.	Captive Water Storage for fire fighting						
	Underground tank capacity	50,000ltr	50,000ltr	MR			
	> Draw-off connection	Required	Provided	MR			
	➤ Fire service inlet	Required	Provided				
-		14070000000	Trovided	MR			
	> Access to tank	Required	Dearth				
	> Access to tank	Required	Provided	MR			
5. 1	> Access to tank	Required -NA- Required	Provided -NA- Provided				

\*

_	N12	_

100	Provision of Lifts.	112 -				
	Pressurization of Lift Shaft					
	Pressurization of Lift Jobby	-NA-	-NA-	-NA-		
	Communication In lift Car	-NA-	-NA-	-NA-		
	Fireman's Grounding Switch	Required	Provided	MR		
	Lift Signage	Required	Provided	MR		
17.	Standby power supply	Required	Provided	MR		
18.	Refuge Area.	Required	300K VA	MR		
	➤ Total Area					
	Location	-NA-	-NA-	-NA-		
19.	Fire Control Room	-N <b>∧</b> -	-NA-	-ΝΛ-		
	Detector System Panel	-ΝΛ-	-NA-	-NA-		
	Flow Switch Panel	-ΝΛ-	-NA-	-NA-		
	PA System Panel	-ΝΛ-	-ΝΛ-	-NA-		
	Battery backup	-NA-	-NA-	-NA-		
	Building Floor Plans	-ΝΛ-	-NA-	-NA-		
20.	Special Fire Protection System for Protection of special Risks, if any:	-ΝΛ-	-ΝΛ-	-NA-		

Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended for Grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010 subject to following condition.

Note DMRC shall ensure compliance of clause 4.4.2.4.1 (h) of NBC part-IV/2016, and provide sufficient louvers for smoke ventilation if façade/glazing is provided at concourse or platform level within two months as undertaking given by DMRC.

Signature of the Inspecting Officer Name: - A. K. Sharma

Designation ADO(WP)

DO/W

ogliola

ne char

Dy. Cro to

10/10/26

Dy. CFO (WA)

LIND S

(ADD (NOP)

Perusal and signature pass

LIV Sugar