



GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE **NEW DELHI- 110 001**

No. F.6/DFS/MS/GH/2025/NDZ/ 472

Dated:

14/08/2025

FIRE SAFETY CERTIFICATE

Certified that the M/s Orient Palace Dx Guest House located at 3984, Gali Kaseruwalan, Pahar Ganj, New Delhi, comprised of Ground floor (Reception) & 1st floor to 3rd floor (04 guest rooms at each floor) Total 12 guest roomsowned/occupied M/s Orient Palace Dx Guest House was earlier granted FSC by this department vide letter no. F.6/DFS/MS/GH/2022/NDZ/334 dated 07/07/2022. The premises was re-inspected by the officer concerned of this department on 30/07/2025 in the presence of Sh. Vijay Kumarand found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy Class"Residential"Sub- Division-A-1, Ground floor (Reception) & 1st floor to 3rd floor (04 guest rooms at each floor), total 12 guest rooms only up to third floorwith effect from 1408 2025 up to valid 31/03/2028 in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under Rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 14 08 2025 at New Delhi by

(VIRENDRA SINGH) CHIEF FIRE OFFICER

To,

- 1. The Commissioner, MCD, Civic Centre, New Delhi: to ensure the occupancy a detailed above.
- 2. Sh. Vijay Kumar, M/s Orient Palace Dx Guest House located at 3984, Gali Kaseruwalan, Pahar

MCD online ID 2025071011191

Conditions for the validity of Fire Safety Certificate

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All the fire fighting equipment shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized

6. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

11/29

1. Name & address of the building

: M/s Orient Palace Dx Guest House located at

3984, Gali Kaseruwalan, Pahar Ganj, New Delhi

2. Type of Occupancy

:Residential, Sub Division-A-1 (Guest House)

3. Building is comprised of

: Ground + 03 upper floors,

Ground floor (Reception), 1st floor to 3rd floor (04 guest rooms at each floor), Total 12 guest rooms

4. Type of Case

:Renewal

5. Details of Previous NOC letter

:F.6/DFS/MS/GH/2022/NDZ/334 dated 07/07/2022

6. Fire Safety directive letter No

: Nil

7. Date of Inspection

: 30/07/2025

8. Name of the Inspecting officers

: Deepak Kumar, ADO (Shd.)

9. Name and designation of Officer

from the building side

: Sh. Vijay Kumar

10. Year of Construction

: 2001

11. Applicant's letter No

2025071011191 dated 10/07/2025

01	Road width Gate width Width of internal road Number, Width, Type and Arranger Number of Staircases Upper Floor Basement B. Width of Staircases Upper Floor	N/A N/A N/A ment of Exits. 01 nos. N/A 80 cms.	04 mtr. N/A N/A 01 nos. N/A	MR N/A N/A			
02	 Road width Gate width Width of internal road Number, Width, Type and Arranger a. Number of Staircases Upper Floor Basement B. Width of Staircases Upper Floor Upper Floor Upper Floor Upper Floor Upper Floor 	N/A N/A ment of Exits. 01 nos. N/A	N/A N/A	N/A N/A			
02	Gate width Width of internal road Number, Width, Type and Arranger a. Number of Staircases Upper Floor Basement B. Width of Staircases Upper Floor	N/A N/A ment of Exits. 01 nos. N/A	N/A 01 nos.	N/A MR			
02	Width of internal road Number, Width, Type and Arranger a. Number of Staircases	N/A ment of Exits. 01 nos. N/A	01 nos.	MR			
02	Number, Width, Type and Arranger a. Number of Staircases • Upper Floor • Basement B. Width of Staircases • Upper Floor	01 nos. N/A	25-74-107-107-107-107-107-107-107-107-107-107				
	a. Number of Staircases	01 nos. N/A	25-74-107-107-107-107-107-107-107-107-107-107				
	 Upper Floor Basement Width of Staircases Upper Floor 	N/A	25-74-107-107-107-107-107-107-107-107-107-107				
	Basement B. Width of Staircases Upper Floor		N/A	I N/A			
	B. Width of Staircases	80 cms					
			1.10 mtr.	MR			
		ASS S0	A CONTRACT CASE AND CA	N/A			
	 Basement 	N/A	N/A	IVA			
	c. Protection of exits	N/A	N/A	N/A			
ı	Fire check door	N/A	N/A	N/A			
	 Pressurization d. No. of continuous staircases 	01 no.	01 nos.	MR			
	to terrace e. Width of Corridor	N/A	N/A	N/A			
	f. Door Size	01 mtr.	01 mtr.	MR			
03	Compartmentation.						
	Fire check door	N/A	N/A	N/A			
	a w f t tital shaffa	N/A	N/A	N/A			
	Sealing of electrical shalls Fire rating of shaft door	N/A	N/A	N/A			
	Water curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
04	Smoke Management System.						
-	Basement	12 a/c per hour	N/A	N/A			
	Upper floor	12 a/c per hour	Natural	MR			
05.	Fire Extinguishers.						
	Total numbers	10 nos.	10 nos.	MR			
	• types	ABC/CO ₂	ABC/CO ₂	MR			
	ISI marking	Required	Provided	MR			

17/30

		12120					
06	First-aid-Hose Reels.						
	Total numbers on each floor	01 No.	01 No.	MF			
	 Length of hose reel hose 	30 mtr.	30 mtr.	MF			
	Nozzle diameter	05 mm	05 mm	MF			
07	Automatic fire detection and alarming syst		00 111111				
	Type of detectors CO	Required	Provided	MR			
	Location of main panel	Ground floor	Provided	MR			
	Location of repeater panel	N/A	N/A	N/A			
	Alternate source of power	Required	Provided	MR			
	Hooter's location	Each floor	Provided	MR			
08	MOEFA	Required	Provided	MR			
09	Public address System.	Nequired	Fiovided	IVII			
10	Automatic Sprinkler System.						
	Basement	N/A	N/A	N/A			
	upper floor	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A N/A	N/A	N/A			
11	Internal Hydrants	IN/A	IN/A	IN/A			
170	size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floor	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.						
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.						
	Ground Level	N/A	N/A	N/A			
	Discharge of main Pump	N/A	N/A	N/A			
	➢ Head of Main Pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	Standby pump out put	N/A	N/A	N/A			
	Standby pump Head	N/A	N/A	N/A N/A			
	Auto Starting /Manual stopping	N/A	N/A N/A	N/A			
	> Pump House Access	N/A	N/A	IN/A			
	Terrace Level	180 Lpm.	180 Lpm.	MR			
	> Discharge of pump	40mtr.	40mtr.	MR			
	> Head of the Pump	Required	Provided	MR			
	 Power supply Auto Starting of pump 	Required	Provided	MR			
14	Captive Water Storage for Fire Fighting.	P	NIA	N/A			
2000	 Underground tank capacity 	N/A	N/A	N/A			
>	Draw-off connection	N/A	N/A	N/A			
	> Fire service inlet	N/A	N/A N/A	N/A			
	> Access to tank	N/A	2,500 ltrs.	MR			
	Overhead Tank capacity	2,500 ltrs.	Provided	MR			
15	Exit Signage.	Required	FIUVICEG	1			
16	Provision of Lifts.	1 10	NI/A	N/A			
	Pressurization of Lift Shaft	N/A	N/A	N/A			
	Bassization of Lift lobby	N/A	N/A	N/A			
	ainsting in lift car	N/A	N/A	N/A N/A			
		N/A	N/A	N/A			
	Firemen's grounding switch	N/A	N/A	1 11//1			

a) - (iii

	er supply	Required	Provided	MR
7_	Standby power supply			
8	Refuge Area.	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	Location	•		
	Fire Control Room	21/4	N/A	N/A
9	File Communication panel	N/A	N/A	N/A
	Detector system panel	N/A	N/A	N/A
	Flow switch parier	N/A		N/A
	PA system paner	N/A	N/A	N/A
	n Hank hackup	N/A	N/A	N/A
	Building Floor Flatte Building Floor Flatte	-		
20	for projection of the		ere tested/check	

The fire protection systems provided in the building were tested/checked and found

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the Rules. The FSC issued vide letter No. functional at the time of inspection. F.6/DFS/MS/GH/2022/NDZ/334 dated 07/07/2022 renewal under rule 37 of the Delhi Fire Service Rule, 2010 is recommended.

Signature of the Inspecting Officer : - Deepak Kumar Designation : - A.D.O (Shd)